



Great North Road Solar and Biodiversity Park

Environmental Statement

Volume 4 – Technical Appendices

Technical Appendix A14.1 – Transport Statement

Document reference – EN010162/APP/6.4.14.1A

Revision number 2

January 2026

Infrastructure Planning (Applications: Prescribed Forms and Procedure) Regulations 2009, APFP Regulation 5(2)(q)

Contents

A14.1.1 Introduction	4
A14.1.1.1 Background.....	4
A14.1.1.2 The Site and Surrounding Area	4
A14.1.1.3 The Commission.....	4
A14.1.1.4 Purpose of this Report	5
A14.1.1.5 Scoping Discussions.....	5
A14.1.1.6 Report Structure	5
A14.1.2 Site Vision	7
A14.1.2.1 Introduction	7
A14.1.2.2 Sustainable Vision	7
A14.1.3 Policy Context	8
A14.1.3.1 Introduction	8
A14.1.3.2 National Planning Policy	8
A14.1.3.2.1 National Policy Statement for Energy (NPS EN-1)	8
A14.1.3.2.2 National Policy Statement for Renewable Energy Infrastructure (NPS EN-3).....	9
A14.1.3.2.3 National Policy Statement for Electricity Networks Infrastructure (NPS EN-5).....	9
A14.1.3.2.4 National Planning Policy Framework (NPPF, 2024)	9
A14.1.3.2.5 National Planning Practice Guidance.....	11
A14.1.3.2.6 The Strategic Road Network and the Delivery of Sustainable Development, DfT Circular 01/2022.....	12
A14.1.3.3 Local Planning Policy.....	12
A14.1.3.3.1 Nottinghamshire Local Transport Plan 2011-2026	12
A14.1.3.3.2 Newark & Sherwood Local Development Framework Core Strategy & Allocations (Adopted March 2019)	12
A14.1.3.4 Summary	13
A14.1.4 Site Baseline and Accessibility Audit	13
A14.1.4.1 Introduction	13
A14.1.4.2 Study Area	13
A14.1.4.3 Walking	13
A14.1.4.3.1 Sutton-On-Trent	14
A14.1.4.3.2 Carlton-on-Trent.....	14
A14.1.4.3.3 Caunton.....	14
A14.1.4.3.4 Kelham	14
A14.1.4.3.5 Maplebeck.....	14
A14.1.4.3.6 Summary	15
A14.1.4.4 Cycling	15
A14.1.4.5 Horse Riding	15

A14.1.4.6	Bus Travel.....	16
A14.1.4.7	Train Travel.....	17
A14.1.4.8	Description of Road Network	17
A14.1.4.9	Personal Injury Collisions (PIC) Review	19
A14.1.4.10	Summary	21
A14.1.5	The Development	21
A14.1.5.1	Introduction	21
A14.1.5.2	Development Description.....	21
A14.1.5.3	Rochdale Envelope.....	22
A14.1.5.4	Routes Hierarchy	22
A14.1.5.5	Site Access Arrangements	24
A14.1.5.6	Passing Places	28
A14.1.6	Trip Generation and Distribution.....	31
A14.1.6.1	Introduction	31
A14.1.6.2	Construction Phases.....	31
A14.1.6.3	Trip Generation.....	32
A14.1.7	Impact Assessment	36
A14.1.7.1	Introduction	36
A14.1.7.2	Construction Phase	37
A14.1.7.3	Operational Phase	40
A14.1.7.4	Abnormal Loads.....	41
A14.1.7.5	Summary	42
A14.1.8	Summary.....	43
A14.1.9	Appendix A – Figures	
A14.1.10	Appendix B – Collision Data	
A14.1.11	Appendix C – Traffic Data	
A14.1.12	Appendix D – Site access drawings	
A14.1.13	Appendix E – Passing place drawings	
A14.1.14	Appendix F – Trip Generation Calculations	
A14.1.15	Appendix G – Abnormal Load Reports	

A14.1.1 INTRODUCTION

A14.1.1.1 BACKGROUND

- 1 Elements Green Trent Ltd (“the Applicant”) is bringing forward a Development Consent Order (DCO) application for the proposed development of the Great North Road (GNR) Solar and Biodiversity Park (“the Development”).
- 2 This Technical Appendix (TA) presents the Transport Statement and has been prepared as part of an Environmental Statement for a solar PV (the Development) located on land located to the northwest of Newark, in the Newark and Sherwood district, Nottinghamshire, East Midlands, which comprise the Order Limits.

A14.1.1.2 THE SITE AND SURROUNDING AREA

- 3 The Order Limits are shown on ES Figure 5.1 [EN010162/APP/6.3.5.1] as being to the west of the A1, north of the A617, east of Eakring, and south of Egmanton, to the north and north-west of Staythorpe.
- 4 The Development essentially consists of discrete land parcels proposed to be occupied by solar PV panels and connected by cable route areas. The eastern side of the Development runs from the north of North Muskham to Egmanton in the north. The western side of the Development runs north-west from National Grid Staythorpe Power Substation and then splits at Maplebeck, with spurs running to Eakring in the north-west and Kneesall to the north-northeast, then connecting with the eastern side of the Development.

A14.1.1.3 THE COMMISSION

- 5 SYSTRA Ltd has been commissioned to provide highways and transport advice in relation to the Development, including the preparation of this Transport Statement to accompany the application. A Transport Chapter (14 [EN010162/APP/6.2.14]) within the ES has also been prepared, as well as an outline Travel Plan (oTP) (ES Technical Appendix (TA) A14.2 [EN010162/APP/6.4.14.2]) and outline Construction Traffic Management Plan (oCTMP) (which is ES TA A5.2 [EN010162/APP/6.4.5.2]).
- 6 Transport Statements report the overall transport strategy to maximise accessibility for non-car modes of transport but also assess the traffic impact of the proposals based on an assessment of conditions on the highway network. Traffic and movement assessments for ES present the impact of traffic and movement on people and the environment.
- 7 Solar farms of over 50 MW comprise a ‘Nationally Significant Infrastructure Project (NSIP) under Section 14(1)(a) and 15(2) of the Planning Act 2008 (‘the Act’) and require a Development Consent Order to allow permission for the Development to be constructed and operated.
- 8 The DCO submission is being made following the completion of extensive surveys, assessments, design iterations and consultation processes.

A14.1.1.4 PURPOSE OF THIS REPORT

- 9 This report is the Transport Statement (TS) for the Development. The report has been commissioned to help understand and analyse the effects of the Development from a transport perspective and to inform the proposals.
- 10 The purpose of the TS is to provide a systematic review and robust assessment of the transport impacts of the Development and identify any mitigation measures that could be implemented if necessary to alleviate the Development impact, both within the Order Limits and externally. The mitigation may include improvements to the travel planning, accessibility and safety for all modes of travel, including construction traffic and may also include some physical infrastructure improvements.

A14.1.1.5 SCOPING DISCUSSIONS

- 11 During the production of the DCO documents, SYSTRA has engaged in discussions with Nottinghamshire County Council (NCC) and National Highways through its pre-application advice process. The Development was presented to both parties with the general scope of assessment agreed in principle. The scope also reflects comments received by other consultees and the public as part of the consultation feedback on the Preliminary Environmental Impact Report.

A14.1.1.6 REPORT STRUCTURE

- 12 Following this introductory section, the remainder of this TS is structured as follows:
 - A14.1.2: Site Vision
 - A14.1.3: Policy Context
 - A14.1.4: Baseline and Accessibility Audit
 - A14.1.5: Proposed Development
 - A14.1.6: Trip Generation and Distribution
 - A14.1.7: Impact Assessment
 - A14.1.8: Summary
- 13 This TS is supported by the following Figures in Appendix A:
 - A14.1.1 – Order Limits
 - A14.1.2 – Nearby Residential Settlements
 - A14.1.3 – Cycle Routes
 - A14.1.4 – Bus services
 - A14.1.5 – Roads in Study Area
 - A14.1.6 – Personal Injury Collision Locations
 - A14.1.7 – Site Access Locations
 - A14.1.8 – Traffic Survey Locations
 - A14.1.9 – Passing Place Locations
 - A14.1.10 – Land Parcel Site Access Assignment
 - A14.1.11 – Link Identification Plan
 - A14.1.12 – Abnormal Load Routes



A14.1.2 SITE VISION

A14.1.2.1 INTRODUCTION

- 14 This Section details the transport vision for the Development, including sustainable transport access, local workforce proximity and how the location of the Development is beneficial with regard to reducing residual car trips and would not create a significant constraint to the delivery of any planned improvements to the transport network.
- 15 Both within the Development and beyond its boundaries, successful development depends upon a movement network that ensures connections are sustainable for non-motorised users.

A14.1.2.2 SUSTAINABLE VISION

- 16 Beyond the construction phase of the Development, the level of operational traffic to and from the Development will be low and therefore the principles of sustainable development in the updated DfT Circular 01/2022 guidance will not apply, however it is noted that the Development has a role in achieving zero emission transport through its construction phase.
- 17 The Development occupies a large area across multiple land parcels, but its proximity to good standard A-class roads, including the A1 and wider Strategic Road Network (SRN) can be maximised for deliveries for infrastructure and will help construction phase traffic route to the Order Limits efficiently.
- 18 The construction hours outlined later in this report mean that the Development is likely to generate minimal operational traffic in the peak hours. Where HGV movements will be necessary during the construction phase of the site, appropriate scheduling outside of the peak hours has an important role to play in achieving a net zero maintenance in construction emissions by 2040.
- 19 The Transport Decarbonisation Plan¹ and the Future of Freight Plan² also recognise that local planning and highway authorities need help when planning for sustainable transport and developing innovative policies to reduce car dependency, and thus the locality of the Development to the SRN in particular is key to achieving this objective.
- 20 In the context of creating sustainable development, the Development would fit into this criterion, as the sole purpose of the Development is to create renewable energy.

¹ Department for Transport (updated 2023). Transport decarbonisation plan. Available at: <https://www.gov.uk/government/publications/transport-decarbonisation-plan>

² Department for Transport (published 2022). Future of freight plan. Available at: <https://www.gov.uk/government/publications/future-of-freight-plan>

A14.1.3 POLICY CONTEXT

A14.1.3.1 INTRODUCTION

- 21 Before considering the Development, it is important to examine the context of the Development and how this relates to relevant transport planning policies and guidelines. This section of the report sets out these elements, providing an overall spatial and planning context for the Development proposal in relation to transport.
- 22 A planning system which places greater emphasis on the link between transport and land use planning policies has also been adopted to encourage transport decisions at a local level that are compatible with environmental and community goals and best reflect local circumstances and requirements.

A14.1.3.2 NATIONAL PLANNING POLICY

- 23 Consultation drafts of the National Policy Statements (NPSs) have been issued (April 2025) in response to changing climate change policy, however, the content of these with respect to this Chapter is materially unchanged from the adopted versions, and hence the adopted versions are referred to below.

A14.1.3.2.1 National Policy Statement for Energy (NPS EN-1)

- 24 The NPS for Energy (EN-1)³ was published in 2023 and provides the basis for decisions regarding nationally significant energy infrastructure. Section 5.14 outlines the planning policy for traffic and transport, including guidance on undertaking relevant parts of the EIA. The most relevant paragraphs for transport are 5.14.5 to 5.14.10 which are set out as follows:
 - Paragraph 5.14.5 states that if a project is likely to have significant transport implications, a transport appraisal should be included with the ES;
 - Paragraph 5.14.6 states that Applicants should consult with National Highways and Highways Authorities as appropriate on the assessment and mitigation to inform the application to be submitted;
 - Paragraph 5.14.7 states that a Travel Plan should be prepared to include demand management measures to mitigate transport impacts;
 - Paragraph 5.14.8 states that the assessment should consider any possible disruption to services and infrastructure (such as road, rail and airports);
 - Paragraph 5.14.9 states that if additional transport infrastructure is needed or proposed, it should always include good quality walking, wheeling and cycle routes, and associated facilities (changing/storage etc.) needed to enhance active transport provision; and
 - Paragraph 5.14.10 states that where additional transport infrastructure is proposed, this should be discussed with the relevant network

³ DESNZ (2023). Overarching National Policy Statement for energy (EN-1). <https://www.gov.uk/government/publications/overarching-national-policy-statement-for-energy-en-1> [accessed on 20/11/2024].

providers (in terms of the possibility of co-funding by Government for any third-party benefits).

A14.1.3.2.2 National Policy Statement for Renewable Energy Infrastructure (NPS EN-3)

25 The NPS for Renewable Energy Infrastructure (EN-3)⁴ was published in 2023 and sets out the policies relating to electricity generation from renewable sources of energy, for consideration in conjunction with NPS EN-1. The 2023 version of this document includes solar photovoltaic generation impacts within Section 2.10. The most relevant paragraphs are set out as follows:

- Paragraph 2.10.123, which discusses the importance of assessing various potential routes to the site for the delivery of materials and components during the construction period;
- Paragraph 2.10.124, which sets out that where there is uncertainty in delivery routes, worst-case assumptions should be made;
- Paragraph 2.10.125, which states that any road or bridge modifications required for a development should be set out in the ES; and
- Paragraph 2.10.126, which states that where a cumulative impact is likely because multiple energy infrastructure developments are proposing to use a common port and/or access route and pass through the same towns and villages, applicants should include a cumulative transport assessment as part of the ES.

A14.1.3.2.3 National Policy Statement for Electricity Networks Infrastructure (NPS EN-5)

26 The NPS for Electricity Networks Infrastructure (EN-5)⁵ was published in 2023 and is a legal document that outlines the government's policy for electricity networks infrastructure projects in the UK. It provides a framework for decision-making on these projects, particularly for those that are considered Nationally Significant Infrastructure Projects.

A14.1.3.2.4 National Planning Policy Framework (NPPF, 2024)

- 27 The Government's National Planning Policy Framework (NPPF)⁶ was originally published in March 2012 and most recently revised in December 2024, outlining the Government's planning policies and how they are expected to be applied.
- 28 The most relevant paragraphs in the context of transport are set out below.
- 29 Paragraph 109 states that "*Transport issues should be considered from the earliest stages of plan-making and development proposals, using a vision-*

⁴ DESNZ (2023). National Policy Statement for renewable energy infrastructure (EN-3). <https://www.gov.uk/government/publications/national-policy-statement-for-renewable-energy-infrastructure-en-3> [accessed on 20/11/2024].

⁵ <https://www.gov.uk/government/publications/national-policy-statement-for-electricity-networks-infrastructure-en-5> [accessed on 12/06/2025].

⁶ Ministry of Housing, Communities and Local Government (updated 2024). National Planning Policy Framework. available at: <https://assets.publishing.service.gov.uk/media/675abd214cbda57cacd3476e/NPPF-December-2024.pdf>

led approach to identify transport solutions that deliver well-designed, sustainable and popular places. This should involve:

- 30 *a) making transport considerations an important part of early engagement with local communities;*
- 31 *b) ensuring patterns of movement, streets, parking and other transport considerations are integral to the design of schemes, and contribute to making high quality places;*
- 32 *c) understanding and addressing the potential impacts of development on transport networks;*
- 33 *d) realising opportunities from existing or proposed transport infrastructure, and changing transport technology and usage – for example in relation to the scale, location or density of development that can be accommodated;*
- 34 *e) identifying and pursuing opportunities to promote walking, cycling and public transport use; and*
- 35 *f) identifying, assessing and taking into account the environmental impacts of traffic and transport infrastructure – including appropriate opportunities for avoiding and mitigating any adverse effects, and for net environmental gains”.*
- 36 Paragraph 115 outlines the key considerations when assessing sites to be allocated for development in plans or specific development applications. It notes that the following should be ensured:
 - 37 *“a) sustainable transport modes are prioritised taking account of the vision for the site, the type of development and its location;*
 - 38 *b) safe and suitable access to the site can be achieved for all users;*
 - 39 *c) the design of streets, parking areas, other transport elements and the content of associated standards reflects current national guidance, including the National Design Guide and the National Model Design Code; and*
 - 40 *d) any significant impacts from the development on the transport network (in terms of capacity and congestion), or on highway safety, can be cost effectively mitigated to an acceptable degree through a vision-led approach.”*
- 41 Within this context, paragraph 117 states that applications for development should:
 - Give priority first to pedestrian and cycle movements and then, as far as possible, facilitate access to high quality public transport;
 - Address the needs of people with disabilities and reduced mobility in relation to all modes of transport;
 - Create places that are safe, secure, and attractive, which minimise the scope for conflicts between pedestrians, cyclists, and vehicles;
 - Allow for the efficient delivery of goods, and access by service and emergency vehicles; and
 - Be designed to enable charging of plug-in and other ultra-low emission vehicles in safe, accessible, and convenient locations.

- 42 As outlined in Paragraph 118, all developments that generate significant amounts of movement should be required to provide a Travel Plan, and the application should be supported by a Transport Statement or Transport Assessment so that the likely impacts of the proposal can be assessed.

A14.1.3.2.5 National Planning Practice Guidance

- 43 The Government’s Planning Practice Guidance; Travel Plans, Transport Assessments and Transport Statements in Decision Making (2014)⁷ provides advice on when Transport Assessments and Transport Statements are required, and what they should contain. The most relevant paragraphs are set out below:
- Paragraph 002 states that Travel Plans, Transport Assessments and Transport Statements are all ways of assessing and mitigating the negative transport impacts of development in order to promote sustainable development. They are required for all developments which generate significant amounts of movements;
 - Paragraphs 004 and 005 state that Transport Assessments and Transport Statements primarily focus on evaluating the potential transport impacts of a development proposal and may propose mitigation measures to promote sustainable development and in order to avoid unacceptable or “severe” impacts where necessary;
 - Paragraph 006 states that Transport Assessments and Transport Statements support national planning policy and can positively contribute to encouraging sustainable travel, reducing traffic generation and detrimental impacts, reducing carbon emissions and climate impacts, creating accessible, connected and inclusive communities, improving health outcomes and quality of life, improving road safety and reducing the need for new development to increase existing road capacity of provide new roads;
 - Paragraph 007 states that Transport Assessments and Transport Statements should be established at an early stage and tailored to local circumstances, as well as proportionate to the size and scope of the proposed development. In addition, they should be brought forward through collaborative ongoing working between the local planning authority/ transport authority, transport operators, rail network operators, as well as National Highways where there may be implications for the strategic road network and other relevant bodies; and
 - Paragraphs 013 to 015 provide further details of when Transport Assessments and Transport Statements are required, how the need and scope should be established and what information should be included.

⁷ Ministry of Housing, Communities and Local Government (2014). Travel Plans, Transport Assessments and Statements. Available at: [<https://www.gov.uk/guidance/travel-plans-transport-assessments-and-statements>] [accessed on 09/05/2025].

A14.1.3.2.6 The Strategic Road Network and the Delivery of Sustainable Development, DfT Circular 01/2022

- 44 The Strategic Road Network and the Delivery of Sustainable Development⁸ published by DfT is a document that sets out how Highways England (now “National Highways”) will interact with stakeholders and interested parties to maintain a fully functional Strategic Road Network (SRN), in regard to economic and sustainable growth.
- 45 The document provides ample guidance on how the SRN should be assessed when accompanying planning applications which may affect the SRN.
- 46 The document details that development proposals are likely to be accepted if the volume of traffic it is to generate are within the available capacity of the network, or if they do not increase the demand for a specific link or junction.

A14.1.3.3 LOCAL PLANNING POLICY

A14.1.3.3.1 Nottinghamshire Local Transport Plan 2011-2026

- 47 This policy document is the third Local Transport Plan (LTP3)⁹ to be produced by Nottinghamshire County Council and replaces the second Local Transport Plans for Greater Nottingham (which was produced jointly with the city of Nottingham) and for North Nottinghamshire. LTP3 details the transport strategy for the whole of the county of Nottinghamshire for the fifteen-year period 1 April 2011 to 31 March 2026.
- 48 The LTP3 transport goals are to:
- Provide a reliable, resilient transport system which supports a thriving economy and growth whilst encouraging sustainable and healthy travel;
 - Improve access to key services, particularly enabling employment and training opportunities, and
 - Minimise the impacts of transport on people’s lives, maximise opportunities to improve the environment and help tackle carbon emissions.

A14.1.3.3.2 Newark & Sherwood Local Development Framework Core Strategy & Allocations (Adopted March 2019)

- 49 The Newark & Sherwood Local Development Framework Core Strategy & Allocations¹⁰ is a vision for the area and strategic objectives for Newark and Sherwood District Council is proposed to guide development to 2033.
- 50 The transport vision for the area includes the following objectives:
- Access will be improved; key transport improvements will have been secured and non-car use encouraged.

⁸ Department for Transport and National Highways (updated 2022). Strategic road network and the delivery of sustainable development available at: <https://www.gov.uk/government/publications/strategic-road-network-and-the-delivery-of-sustainable-development>

⁹ Nottinghamshire County Council (2011). Nottinghamshire Local Transport Plan available at: <https://www.nottinghamshire.gov.uk/policy-library/39018/nottinghamshire-local-transport-plan-2011-2026>

¹⁰ Newark and Sherwood District Council (2019). Local Development Framework available at: <https://www.newark-sherwooddc.gov.uk/ldf/>

- Development will be environmentally sound, energy and water efficient, minimise waste, and maximise opportunities for appropriate renewable energy, helping to reduce the impact of climate change.
- To retain and improve accessibility for all, to employment, services, community, leisure and cultural activities, through:
 - The integration of development and transport provision, ensuring that most new development will be located where it is accessible to use services and facilities by a range of means of transport;
 - The retention and upgrading of existing infrastructure, services and facilities relating to transport and communications; and
 - Encouraging the increased use of public transport, walking and cycling.

A14.1.3.4 SUMMARY

- 51 In summary, there are a number of integrated land use and transport planning policies and policy guidance documents that support and underpin the Development.

A14.1.4 SITE BASELINE AND ACCESSIBILITY AUDIT

A14.1.4.1 INTRODUCTION

- 52 This section provides a general overview of the existing transport conditions in the Study Area, including a description of the local highway network. A review of the road safety history is also considered in this chapter.

A14.1.4.2 STUDY AREA

- 53 The study area has been identified to cover the extent of the surrounding road network to be used by construction related vehicles travelling to and from the Development.
- 54 Figure 14.1 provides a map of the Study Area along with names of key roads which represent the Study Area.

A14.1.4.3 WALKING

- 55 Almost all journeys include an element of walking therefore pedestrian facilities should not be considered in isolation. Walking offers the connection between cycling, public transport and highway transport to destinations.
- 56 Due to the rural nature of the Order Limits, there are limited footway provisions alongside the roads in the area, these are however described in this section. In addition, an overview of the pedestrian facilities in the villages surrounding the Order Limits are also detailed below to give context to the availability of the immediate wider area.
- 57 To provide context to the locations, some of the main residential villages are identified in Figure A14.1.2 within Appendix A.

A14.1.4.3.1 Sutton-On-Trent

- 58 The B1164 which passes Sutton-on-Trent to the west offers very limited provisions for pedestrians, with only a narrow footway (less than 1 m) provided along the eastern side of the road, with no separation from traffic or streetlighting.
- 59 Within Sutton-On-Trent village itself, there is a mix of pedestrian facilities, primarily concentrated in the centre of the village. There are footways along the main thoroughfares and near key areas such as the village hall, shops, and the school. The availability of designated crossing locations is limited. Street lighting is adequate in the village centre but becomes sparse towards the residential streets.

A14.1.4.3.2 Carlton-on-Trent

- 60 The B1164 which passes Carlton-on-Trent to the west has no footways between its junction with Ferry Lane and the A1. From the Ferry Lane junction both northwards and to the west, there is limited availability with only a narrow footway (less than 1 m) provided on one side of the road. Both of these sections include a bus stop.
- 61 Street lighting is generally limited to areas near the A1 and some key junctions. The village has basic signage present to assist with wayfinding.

A14.1.4.3.3 Caunton

- 62 There are no footways on the A616 (Link 4) as it passes Caunton and as such, no pedestrian movements along this arterial route are expected.
- 63 Within Caunton, footways are primarily located along the main road and in the village centre, with few extending into residential streets. The quality of pedestrian footways varies within the village, with some areas being narrow or having uneven surfaces. Street lighting is not extensive, with most present near the village centre.

A14.1.4.3.4 Kelham

- 64 As the A617 passes through Kelham from the east, there is a footway along the northern side which reduces in width as it leaves the village to the west. A short section of footway is introduced on the southern side of the road in the vicinity of Broadgate Lane and Home Farm Close.
- 65 Pedestrian crossing opportunities on the A617 are limited. Street lighting is present along the A617 which enhances pedestrian safety. Signage through the village is adequate, with some traffic calming measures near the main local amenities.

A14.1.4.3.5 Maplebeck

- 66 Maplebeck is a small village with minimal pedestrian facilities. Footways are present along the Hollows and Church Lane, which are the two main residential streets in Maplebeck. Street lighting and signage is sparse and limited to a few key areas. The roads through the village are narrow and have no road markings, reflecting the low traffic volume.

- 67 Maplebeck Road bypasses the village to the north. This road has centreline markings but has grass verges and offers no footway provision or street lighting.

A14.1.4.3.6 Summary

- 68 Overall, there are very limited pedestrian facilities alongside the routes being used for construction traffic. Those that are present are typically characterised by being relatively narrow and with limited or no separation from traffic.
- 69 Within the villages, provisions are generally sufficient and suitable to meet local demand and need.

A14.1.4.4 CYCLING

- 70 Cycling provides the means to undertake numerous short-distance journeys typically under five kilometres, either as a standalone mode or in conjunction with other forms. Cycling levels are influenced by the condition of the routes, the volume of traffic and the availability of secure cycle storage at the destination.
- 71 Within the Study Area, cycling occurs on the local roads but dedicated cycling infrastructure is limited.
- 72 Designated cycle route availability in the area is generally limited. There are however two National Cycle Routes (NCR) that pass close to the Study Area – NCR 645 terminates at Southwell, approximately 2.4 km south of Hockerton and NCR 64 runs from Newark in a north-east direction. From Newark town centre, access is also provided to the Southwell Loop on the regional cycle route, which travels through South Muskham, North Muskham and Norwell, and continues to Southwell. The route passes through Egmanton and Tuxford where it intersects with National Cycle Route 647.
- 73 Across the Study Area cyclists often share the road with general traffic, although cycling trips along A class roads with high volumes of traffic and fast-moving vehicles are likely to be limited.
- 74 Elsewhere, the rural local roads provide quieter and safer alternatives for cycling although they lack dedicated cycle infrastructure. The lower traffic volumes however make the rural roads a more attractive proposition compared to the 'A' roads.
- 75 In summary, although the Study Area does not have an extensive network of dedicated cycling infrastructure, cyclists may be present on less busy roads and routes away from heavy and fast-moving traffic.
- 76 The formally recognised cycle routes that pass through, or within close proximity, to the Order Limits are indicated on Figure A14.1.3.

A14.1.4.5 HORSE RIDING

- 77 Formal equestrian routes in the Study Area exist but are relatively limited, although equestrian facilities such as stables, liveries and grazing areas are noted as being near Caunton and Bathley, and Averham Park Farm.
- 78 Whilst there is unlikely to be many horse-riding journeys on A and B class roads, except where a bridleway crosses them, on minor roads, horse riding

may be more regular. Indeed, it is noted that looking at rights of way in isolation understates the equestrian access resource as it may be possible to link up public rights of way using minor roads and other access resources.

A14.1.4.6 BUS TRAVEL

- 79 The bus is generally considered a viable mode of travel over short and medium distances although some routes and services with limited stops make longer distances viable.
- 80 Kersall Road bus stop is located to the north of Kersall on the A616, where the service 733 operates. The 733 bus operates two services per day and serves the nearby villages of Norwell and Moorhouse.
- 81 Newark Castle train station bus stop is located to the south of the A46/A616/A617/B6326 roundabout in Newark-on-Trent, approximately 4 km from the proposed Work no. 5a, BESS, and Work no. 5b, 400 kV Compound. Seven bus services operate from this stop; the services 28, 29, 37, 38, 300, X22 and the X37.
- 82 A pair of bus stops are located on the A617 at Hockerton, near the junction with Caunton Road. Bus service 964 operates from these stops.
- 83 Table A14.1.1 summarises bus services locally and these are also presented on Figure A14.1.4. The figure demonstrates the routes and services within the area, with several routes overlapping on the same roads.

Table A14.1.1. Bus Services

Bus Number	Service	Frequency
28	Mansfield Bus Station-Farndon Long Lane	8 services per day
29	Mansfield Bus Station-Newark Bus Station	4 services per day
37	Retford-Newark	Hourly between 9am and 6pm
40	Tuxford – South Muskham	1 service per day
300	Lowdham to Newark	2 services per day
X22	Sutton on Trent- Grantham	1 service per day
X37	Tuxford-Newark (southbound)	1 service per day
339	North Muskham - Tuxford	4 services per day
733	Kneesall - Tuxford	2 Services per day

- 84 Bus services in rural villages are typically less frequent compared to urban areas, with some routes operating only a few times per day, especially outside of peak hours. The primary function of the bus services is to connect these rural communities with Newark-on-Trent, which serves as a local hub for shopping, healthcare, and other services.
- 85 In addition to the scheduled services in Table A14.1.1 it is also noted that Nottsbus On Demand services operate in the area and do not follow a fixed

timetable but instead operate on a flexible, on demand basis, allowing users to travel between bus stops and designated points with the travel zone, where there are currently no local bus routes.

- 86 Bus stops in these villages are usually basic, often consisting of a simple pole with a timetable, and occasionally a shelter. Due to the rural nature of these villages, the infrastructure is generally minimal.
- 87 In summary, while public transport services operate in the area, they are limited and infrequent.

A14.1.4.7 TRAIN TRAVEL

- 88 The nearest station to the Development is Newark Castle train station, which operates regular services to destinations such as Nottingham, Leicester, Lincoln and Grimsby.
- 89 Newark Northgate station is situated slightly further away and operates regular services to destinations that include London, Doncaster and York.

A14.1.4.8 DESCRIPTION OF ROAD NETWORK

- 90 The road network within and around the Order Limits are described below and are shown in the wider context on Figure A14.1.5.

A14.1.4.8.1 A1

- 91 The A1 is a major trunk road that is operated and maintained by National Highways. As it passes the Order Limits to the east, the A1 operates as a dual carriageway, with two lanes in each direction. Within proximity to the Order Limits there are junctions at Tuxford, Carlton-on-Trent, Cromwell, North Muskham and Newark-on-Trent:
- Tuxford – for southbound traffic, an off-slip and on-slip are available at Tuxford. For northbound traffic on the A1, an off slip is provided, but access to the A1 northbound cannot be achieved at Tuxford.
 - Carlton-On-Trent – both northbound and southbound slip roads are available at the grade-separated junction at Carlton-on-Trent.
 - Cromwell – to the north of Cromwell a southbound off-slip and on-slip is available for southbound traffic, which provides access to an HGV parking area or continued southbound journeys into Cromwell. A short distance further south, another southbound off-slip and on-slip provision is available via a grade-separated junction. For northbound traffic an off-slip is provided to the south of the village and another to the north of the village, from where a northbound on-slip is also available.
 - North Muskham – to the north of North Muskham, at-grade junctions provide for both southbound and northbound movements. Approximately 700 metres further south, the A1 continues over a grade-separated roundabout beneath, which accommodates all movements.
 - Newark-on-Trent – to the north of Newark-on-Trent, a grade-separated junction for all movements provides access to the A46, A17 and the B6166.

A14.1.4.8.1.2 A617

- 92 The A617 runs in an east-west direction to the south of the Order Limits. The A617 is a single carriageway road which is in good condition and is characterised by bends and typically has a speed limit of 50 mph which reduces to 30 mph through the villages of Kelham, Hockerton and Kirklington. As it passes through the villages, some sections have a footway and street lighting, outside of these areas the road is typically unlit with only soft verges on either side of the road.

A14.1.4.8.1.3 A616

- 93 The A616 is a single carriageway road that runs in a north westerly direction, connecting Newark-On-Trent with Ollerton and is a single carriageway road. The road is to a generally good standard and has centre line and road edge markings with soft verges and no street lighting. As the road passes Little Carlton and through Kneesall there is localised active frontage and footways are present.

A14.1.4.8.1.4 A614

- 94 The A614 runs in a north-south direction to the west of the Order Limits from the north of Nottingham directly to Apleyhead Interchange, a major junction on the A1. The A614 is a single carriageway road with a national speed limit northwards from its junction with the A616 near Ollerton and 50 mph to the south, with a good road surface.

A14.1.4.8.1.5 B6325

- 95 The B6325 runs between North Muskham and South Muskham, north of Newark-on-Trent, and it is also referred to as Great North Road. The road starts at a large grade-separated roundabout with full access to the A1 just outside of North Muskham and, after bridging the East Coast Main Line railway, continues to the South Muskham bypass. The road ends on the west side of South Muskham at a mini-roundabout junction with the A616.
- The road is single carriageway and subject to the national speed limit at its northern end, which reduces to 30 mph as it enters South Muskham. The road surface in reasonable condition and has centreline and road edge markings.

A14.1.4.8.1.6 Carlton Lane

- 96 Carlton Lane runs from north to south between Ossington Road and Main Street in Norwell. The road is relatively narrow with soft verges on both sides and has no pedestrian facilities.

A14.1.4.8.1.7 Ossington Road

- 97 Ossington Road runs from east to west, providing a connection between Carlton-on-Trent, Ossington and Kneesall. The road is a single carriageway subject to the national speed limit as it approaches Ossington from the east, before reducing to 30 mph as it approaches the village. The road has grass verges and no pedestrian facilities on its section subject to the national speed limit, but a narrow footway is available as it enters the village.

A14.1.4.8.1.8 Kersall Road

- 98 Kersall Road runs from north to south between Ossington Road and the A616. It provides a connection between Kneesall and Ossington. The road is a single carriageway with centre line road markings, subject to the national speed limit, with soft verges and no pedestrian facilities on either side of the carriageway.

A14.1.4.8.1.9 Maplebeck Road / Newark Road

- 99 Maplebeck Road runs in the northwestern direction providing a connection between Caunton and Eakring, where it is then referred to as Newark Road. The road is a single carriageway with centre line road markings and is subject to the national speed limit. It has no street lighting and has soft verges, with no pedestrian facilities on either side of the carriageway.

A14.1.4.8.1.10 Caunton Road

- 100 Caunton Road runs from north to south between the A616 and the A617. It provides a connection between Caunton and Hockerton. The road is a single carriageway subject to the national speed limit, with no pedestrian facilities provided on either side of the carriageway.

A14.1.4.8.1.11 Ossington Lane

- 101 The road is a rural, single carriageway with a width suitable to allow two-way traffic for cars. It links the B1164 at Sutton-on-Trent with the village of Ossington via Ossington Road. There is no street lighting or road markings along this link and each side of the road is abutted by soft verge with no pedestrian facilities.

A14.1.4.8.1.12 Moorhouse Road

- 102 Moorhouse Road serves local traffic and runs northwards from the village of Moorhouse, linking onto Weston Road. The road is single carriageway and subject to the national speed limit, with soft verges. No street lighting is present and there are no pedestrian facilities.

A14.1.4.8.1.13 Weston Road

- 103 Weston Road connects the B1164 in the east with the village of Egmanon in the west via a bridge over the A1. The road has no street lighting or pedestrian facilities, with soft verges on either side of the road. The road is of sufficient width for two-way car traffic.

A14.1.4.8.1.14 Staythorpe Road

- 104 Staythorpe Road connects the towns of Staythorpe and Rolleston to the A617 and runs in a north – south direction. It has centre line markings and operates at a 50mph speed limit except at the built-up areas where the speed limit reduces to 30mph.

A14.1.4.9 PERSONAL INJURY COLLISIONS (PIC) REVIEW

- 105 A review of personal injury collision (PIC) data has been undertaken for all construction phase traffic routes shown on Figure A14.1.5 in Appendix A. The review of the collision records has been undertaken to identify patterns of collision types that may be attributed to issues arising from the existing

road design or layout and identify any trends that could be exacerbated by Development-related traffic.

106 Data was obtained from Nottingham County Council for the most recent full 3-year period, 01 January 2022 to 31 December 2024, which allows consideration of comparable post-COVID19 data. PICs are classified as 'slight', 'serious' and 'fatal' depending on the severity of the injuries sustained. Table 14.1.2 provides a total summary for the Study Area and Figure 14.1.6 presents their location.

Table 14.1.2: PIC Severity Summary

Year	Severity			Total
	Slight	Serious	Fatal	
2022	18	6	0	24
2023	17	4	1	22
2024	17	9	1	27
Total	52	19	2	73

107 The presentation of collision locations shown in Figure A14.1.6 in Appendix A and clearly shows that the majority of collisions in the Study Area have occurred along the A617 and A46 and to a lesser degree, the A616. The data does not present any other particular trend in collisions.

108 It is noted that a fatality was reported on Moorhouse Road. The collision occurred on the morning of Sunday 29 December 2024 and involved a car and pedal cycle that were both travelling in the same direction. The weather was reported as being fine but the road surface wet.

109 Another fatal collision is also reported on the A617, which occurred on the morning of Tuesday 11 July 2023. The collision involved two cars.

110 The largest number of collisions observed was along the A617 with 15 slight collisions, seven serious and one fatal collision recorded during this period. Six slight collisions and six serious collisions were recorded along the A616 during this period. There were 10 slight collisions recorded at the A614/A46/Great North Road junction, while eight slight collisions and one serious collision were reported at the A1/A46/A17 junction.

111 During consultation, members of the public have raised comment on the perceived safety concerns of construction traffic using the Weston Road junction with the B1164 Great North Road with issued associated with the visibility of turning vehicles at this junction. A closer examination of this junction shows that there have been zero injury-related collisions at this junction within the study period. To provide a greater insight to the junction safety record, data for the past 25 years, from 1999 to 2023 inclusive has been reviewed. This shows that in the past 25 years, there have been a total of four collisions recorded, including a single vehicle accident in July 2008 resulting in slight injury. The other collisions at this junction occurred were all two vehicle collisions, including a serious collision in 1999, a slight

injury collision in 2001 and a slightly injury collision in 2013. The recorded collision history at this junction does not present a concern. It should be noted that the construction vehicles using this junction will predominantly be HGVs, with drivers having an elevated view of oncoming traffic and similarly, the larger vehicle heights will make their presence more conspicuous for approaching vehicles.

A14.1.4.10 SUMMARY

- 112 An accessibility audit has been undertaken, including a review of the local highway network, sustainable transport accessibility by public transport, and walking and cycling accessibility. The review indicates that the Development site is well served by the strategic and local road network whilst sustainable transport accessibility is reasonable given the relatively rural location of the Order Limits.
- 113 Having reviewed the collision data provided for the study period, the above analysis shows that the majority of collisions in the Study Area have occurred along the A617 and A46 which are already designed for higher volumes of traffic and greater speeds. Elsewhere on the network, there is insufficient collisions to draw any trends in collision cause.

A14.1.5 THE DEVELOPMENT

A14.1.5.1 INTRODUCTION

- 114 This Section presents an overview of the Development proposals, including the site access arrangements, staff numbers and shift patterns associated with the construction phase of the Development.

A14.1.5.2 DEVELOPMENT DESCRIPTION

- 115 The Development would be located to the northwest of Newark, in the Newark and Sherwood district of Nottinghamshire, East Midlands. The Development would be within an area bound by the Order Limits. The Order Limits are to the west of the A1, north of the A617, east of Eakring, and south of Egmanton, to the north and northwest of Staythorpe.
- 116 The Development is described by ES Chapter 5, Development Description, [EN010162/APP/6.2.5], and briefly summarised here. The Development essentially consists of discrete land parcels proposed to be occupied by solar PV panels and associated infrastructure, connected by cable route areas. Up to 4 intermediate substations will be spaced around the solar areas, and a Battery Energy Storage System (BESS) and 400 kV Compound will collate the electrical energy and step up the voltage before cabling it to the National Grid Staythorpe Substation, possibly via the Consented Staythorpe BESS.
- 117 The wider area within and surrounding the Order Limits are generally composed of agricultural land, interspersed by occasional woodlands. Surrounding villages and hamlets are connected by rural roads and public rights of way.

A14.1.5.3 ROCHDALE ENVELOPE

- 118 It is important to provide development flexibility within the DCO and to allow for this, a Rochdale Envelope approach has been used, with parameters given values within ranges set out in ES Chapter 5, Development Description [EN010162/APP/6.2.5].
- 119 For transport assessment purposes, values within the parameter range (where relevant to the assessment) have been used that represent the realistic worst-case in the context of this assessment. These are outlined further in this report and their use ensures the final design of the Development as-built, will be no worse than predicted. Such parameters include the upper limits on values such as the length of access tracks and fencing, and the maximum range for the total area of solar PV modules.

A14.1.5.4 ROUTES HIERARCHY

- 120 Access to the Development has been ascertained by a methodology using a hierarchy of routes to the access locations to be used for the Works Areas shown on Figure 5.1: Works Areas [EN010162/APP/6.3.5.1] during the construction phase. These routes will be secured through the oCTMP and then the CTMP secured by a Requirement in the DCO. The oCTMP will be used as a basis for the final CTMP to be submitted for approval to NSDC in consultation with NCC and National Highways.
- 121 The overarching construction access route strategy for the Development uses a preference hierarchy of:
1. Trunk Roads;
 2. 'A' Roads;
 3. 'B' Roads; and
 4. Classified and unclassified roads.
- 122 For determining the most appropriate construction route, the land parcels within the Order Limits have been grouped into distinct areas that will each be served by a designated site access. The most appropriate route to that site access from the A1 trunk road has then been considered, whilst acknowledging that some traffic may possibly also route from the west and for assessment purposes, a sensitivity test has been undertaken on these routes assuming half of traffic could route from the west.
- 123 Using the above hierarchy as the guiding principle, the route to each site access also:
- Considers the shortest route;
 - Seeks to avoid sensitive areas so far as possible, such as schools and villages;
 - Uses roads of appropriate width and alignment; and
 - Utilises internal haul roads where available and convenient.
- 124 When it is not viable to achieve the above, additional mitigation measures will be implemented and these are discussed in the Outline CTMP (ES TA A5.2 [EN010162/APP/6.4.5.2]).

- 125 The route hierarchy above has been adopted to ensure that construction traffic avoids sensitive receptors in nearby towns, villages and hamlets as far as practicable. There are also other wider key benefits, including:
- **Traffic Management:** the SRN and A-roads are designed to handle higher volumes of traffic, including HGVs, and by directing construction traffic to these roads, congestion on smaller localised roads is minimised, ensuring a smoother traffic flow;
 - **Safety:** A-roads are designed with better safety features, such as wider lanes, clearer signage and more frequent maintenance. This reduces the risk of collisions involving construction vehicles;
 - **Efficiency:** Using A-roads for construction routes can significantly reduce travel time. These roads often have higher speed limits and fewer restrictions, allowing for quicker and more predictable transportation of materials and equipment; and
 - **Economic Benefits:** Efficient transportation routes reduce fuel consumption and vehicle wear and tear, minimising road damage and the need for repairs.
- 126 The routing principles enhance traffic management between private motor vehicles and construction traffic, and maximise safety, efficiency and economic benefits of the Development. The Figure A14.1.5 in Appendix A presents the construction traffic routes that will be utilised whilst constructing the Development. Construction phase contractors will be expected to plan their route in advance to ensure the most appropriate route to arrive via the A1. Abnormal load routes are considered separately.
- 127 Due to the layout and scale of the Development, it is dissected by several public roads and as such, numerous site access locations are required from these roads. Site access locations have been carefully selected to ensure they are appropriately located in relation to visibility and overall suitability. Where appropriate, preference has been to use already established access locations, which will be upgraded as required to meet design requirements.
- 128 Where appropriate, any unsurfaced access tracks that run through the Development would be utilised in preference to the installation of new access tracks, to minimise land disturbance and environmental effects.
- 129 Internal construction haul routes will be used to facilitate movement between fields and minimise traffic impact on the local road network. Two noteworthy examples of the use of these tracks to alleviate traffic impact during construction are:
- Near Ossington – an internal construction track will route from Ossington Road to the east of the village and traverse within the Order Limits to the north and then west to meet Moorhouse Road. As a result, HGV construction related traffic will not pass through the village of Ossington.
 - Near Maplebeck - an internal construction track will route from Maplebeck Road to the east of the village and traverse within the Order Limits to the south and then west to provide access to solar areas to the south and west of Maplebeck. As a result, HGV construction related traffic will not pass through the village of Maplebeck.

- 130 Access to the majority of the solar arrays during operation will be via grassed tracks. The intermediate substations would require accesses to be constructed of tarmac. Access to construction compounds would be made of compacted stone that can readily be taken up and the land reinstated following completion of the construction stage.
- 131 Figure A14.1.5 presents the construction traffic routes that are to be utilised whilst constructing the Development.

A14.1.5.5 SITE ACCESS ARRANGEMENTS

- 132 Detailed consideration has been given to site access arrangements for the developable solar areas, cable route, compounds and BESS area to ensure that they are appropriate to meet the needs of the Development, whilst also giving due consideration to operational safety, environmental impact and minimising disruption to other road users.
- 133 When defining site access arrangements, the utilisation of existing accesses have been prioritised when seeking suitable locations into the site from the public highway. Where existing accesses cannot be utilised, or if no existing access is conveniently located to access the areas, new accesses have been proposed. An overview of the site access locations can be seen in Figure 14.1.7 (NE, NW, SE and SW), presenting the location of the existing (to be upgraded) and new accesses proposed.
- 134 The site accesses have been separated into three categories, these being:
- Primary Access – these accesses form the main access into the site from the public highway. They will typically serve a site compound area. They have been designed to accommodate the turning movements of all sizes of vehicle, including HGV, and will operate under free-flow conditions;
 - Secondary Access – the function of these accesses is to supplement the primary access and will typically facilitate cross-over movements of the public highway between land parcels of solar development on either side. Traffic egress movements out of these locations will operate under the supervision of a banksman during the construction phase. They have typically been designed to accommodate the turning movements of Cars and LGVs and only the cross-over movements of HGVs; and
 - AIL Access – in addition to their function of performing as a primary access, an over-run provision is included to accommodate the turning movement of the AIL vehicle transporting the cable drum to site. All AIL movements will be undertaken under appropriate supervision measures.
- 135 A total of 43 access locations are proposed, of which 24 are existing access locations, many of which will require upgrading to ensure they have appropriate visibility, geometry and surfacing. There are 19 new access locations proposed, which have been located to best suit the development needs, visibility and limit environmental/ecological impact, i.e., reduce the need to remove hedgerow, trees and general vegetation.
- 136 Site access locations have sought to be located on minor roads; however, this has not been viable in 3 locations, with 2 accesses being located on the

A616 and 1 access on the A617. All 3 of these access locations are existing field accesses that are currently used by agricultural vehicles.

- 137 All access locations will be retained for continued use during the operational phase. A summary of each primary access is listed in Table A14.1.3 which sets out a brief rationale for their location and whether they are existing/upgraded, or new. Access locations are shown in Figure A14.1.7.
- 138 The implementation of new access junctions is essential for ensuring materials can be delivered to the Development site safely and efficiently. A detailed exercise has been undertaken to find suitable locations for the new access points involving site visits and a review of the existing roads from which access will be taken. Suitable access junction locations were then selected based on the ability to achieve an appropriate geometric layout and to achieve visibility splay standards.
- 139 In the assessment of visibility splays at each access location, a robust methodology is adopted that integrates data collection, established standards, and professional judgement to ensure accurate evaluations. This approach ensured that all assessments were consistent with best practices and applicable guidance.

Table A14.1.3: Primary Access Locations

Access ID	Location	Description
PA1	A617 – 100 m east of Main Road junction	An existing hard surfaced field access to be upgraded and used to access BESS site.
PA2	Caunton Road – approx. mid-length of road	An existing hard surfaced site access of the public road onto private access and then into field via new access to the south.
PA3	Caunton Road – approx. mid-length of road	A new site access to be formed at location of gap in hedgerow to gain access to land to the west.
PA4	Maplebeck Road – 2 km west of A616 junction	An existing hard surfaced field access to be upgraded to gain access to land to the south.
PA5	Newark Road – 590 m east of Sandy Lane Public Footpath	A new site access to be formed to gain access land to the south.
PA6	Newark Road – 720 m east of Sandy Lane Public Footpath	A new site access to be formed to gain access to land to the south.
PA7	A616 – 1.08 km south-east of Kersall Road	An existing hard surfaced field access to be upgraded to gain access to land to the west.

Access ID	Location	Description
PA8	A616 – 1.03 km south-east of Kersall Road	An existing hard surfaced field access to be upgraded to gain access to land to the east.
PA9	Kersall Road - 240 m north-east of A616 junction	An existing hard surfaced field access to be upgraded to gain access to land to the south.
PA10	Kersall Road - 375 m south of Ossington Road junction	An existing soft standing field access to be upgraded to gain access to land to the west.
PA11	Ossington Road - 500 m north of Main Street junction	A new site access to be formed across grassed soft verge to gain access to land to the west.
PA12	Moorhouse Road – 150 m south of Hagg Lane.	An existing hard surfaced field access to be upgraded to gain access to land to the east.
PA13	Ossington Lane – 250 m west of Brimblebeck Lane.	An existing field access to be upgraded to gain access to land to the west and onwards.
PA14	Ossington Road – 1.95 km west of Carlton Lane	A new site access to be formed to gain access to land to the north.
PA15	Ossington Road – 1.4 km west of Carlton Lane	An existing hard surfaced access track to be upgraded to gain access to land to the south
PA16	Ossington Road – 1.35 km west of Carlton Lane	A new site access to be formed to gain access to land to the north.
PA17	Carlton Lane – 300 m south of Ossington Road junction.	A new site access to be formed to gain access to land to the west.
PA18	Staythorpe Road – 395 m east of Pingley Lane	An existing hard surfaced access to be used in its current form to gain access to the cable route to the north.
PA19	Staythorpe Road – 190 m east of Pingley Lane	An existing field access to be used with localised removal or hedgerow. Approval for use by HGV received as part of planning application 24/01261/FULM.

- 140 The visibility requirements for the primary site accesses are related to the stopping sight distance (SSD). The SSD is the distance within which drivers need to be able to see ahead and stop from a given speed. For existing roads, the 85th percentile speed is used to determine the SSD.
- 141 A third-party survey company were appointed to undertake traffic volume and speed surveys in the proximity of the proposed new site access locations. The traffic surveys were undertaken using Automatic Traffic Count (ATC) loops, which collected continuous data for a 7-day period on the following neutral dates that are considered representative of typical conditions:
- 17 April to 23 April 2024;
 - 25 February to 03 March 2025; and
 - 14 March to 20 March 2025
- 142 Figure A14.1.7 shows a location plan of the ATC loops. All traffic survey data collected was shared with NCC and full set of data is provided in Appendix C.
- 143 The SSD is calculated from the speed of the vehicle, the time required for a driver to identify a hazard and then begin to brake (the perception–reaction time), and the vehicle’s rate of deceleration.
- 144 The basic formula for calculating safe stopping distance (in metres) is:

$$SSD = vt + \frac{v^2}{2d}$$

where:

v = speed (m/s)

t = driver perception reaction time (seconds)

d = deceleration (m/s²)

- 145 This formula is used in the Design Manual for Roads and Bridges (DMRB)¹¹, Manual for Streets (MfS)¹² and the Highway Code¹³ to calculate stopping distances. All of these documents assume different values for the driver perception reaction time (t), and the deceleration (d).
- 146 To inform interpretation of the SSDs, it is relevant to note some of the summary findings of reviewed research into SSD undertaken during the production of the Manual for Streets (2007). This research into SSD found that:
- The desirable minimum SSDs used in the Design Manual for Roads and Bridges are based on a driver perception–reaction time of 2 seconds and a deceleration rate of 2.45 m/s² (equivalent to 0.25g

¹¹ National Highways (2020). Design Manual for Roads and Bridges. Available at: <https://www.standardsforhighways.co.uk/dmrb> [accessed on 09/05/2025].

¹² Department for Transport (2007). Manual for Streets. Available at: https://assets.publishing.service.gov.uk/government/uploads/system/uploads/attachment_data/file/341513/pdfmanforstreets.pdf

¹³ Department for Transport (2025). The Highway Code. Available at: <https://www.gov.uk/guidance/the-highway-code>

where g is acceleration due to gravity (9.81 m/s^2). Drivers are normally able to stop much more quickly than this in response to an emergency;

- The stopping distances given in the Highway Code assume a driver reaction time of 0.67 seconds, and a deceleration rate of 6.57 m/s;
 - While it is not appropriate to design street geometry based on braking in an emergency, there is scope for using lower SSDs; and
 - Research shows that the 90th percentile reaction time for drivers confronted with a side-road hazard in a driving simulator is 0.9 seconds.
- 147 Carriageway surfaces are normally able to develop a skidding resistance of at least 0.45 g in wet weather conditions. Deceleration rates of 0.25 g (assumed value adopted in DMRB) are more typically associated with snow-covered roads.
- 148 While it is not appropriate to design road geometry based on braking in an emergency, the DMRB values are clearly based on conservative values. It is the DMRB standards that have been used to inform the visibility requirements for the proposed site accesses.
- 149 A set of site access drawings are provided in Appendix D, which note the recorded 85th percentile speed and corresponding visibility splay. All land required to deliver the site accesses are contained within the Order Limits.
- 150 It will also be necessary for vehicles to access land identified for mitigation. Access to these areas will continue to be gained as per their current arrangements. Traffic volumes and frequency of trips to this land is expected to be not greater than current baseline levels.

A14.1.5.6 PASSING PLACES

- 151 Due to the rural location of the Order Limits and many of the roads to be used for construction being of a width not sufficient for two vehicles to pass comfortably, it is proposed for passing places to be constructed along several sections of the construction traffic route to enable the safe passing of two vehicles. The selection of passing place locations along the access routes has been informed by several practical considerations to ensure road safety and efficiency. The primary method in this process has been undertaking of swept path analysis and site visits. The swept path analytical tool allows the simulation of vehicle movements along the route, enables pinch-points to be identified and ensures that the passing places are strategically positioned, so as to limit areas of vehicle conflict and facilitate continued two-way traffic flow.
- 152 Forward visibility is another factor in the placement of passing places, ensuring that drivers have clear sightlines to these areas is important for safety. An assessment of forward visibility has informed the location of inter-visible passing places and thereby reducing the likelihood of vehicles meeting on a section unsuitable for two vehicles to pass. It must however be noted that the study area is rural, and routes frequently used by large, slow moving agricultural vehicles and as such, these instances are already occurring to some degree, although these movements typically result in vehicle over-run of the verges.

- 153 Wherever possible, the utilisation of existing passing places or areas suitable for vehicles to wait for a short period have been assumed. This minimises environmental disruption and maximises the use of already established locations, which is more efficient. Use of these existing locations assists with continuity and familiarity for regular road users, further promoting safety and ease of use.
- 154 In instances where existing passing places and/or areas are insufficient, new places have been strategically proposed. The locations of these new passing places have been informed by the availability of roadside verge, allowing for the expansion of the road width whilst reducing the removal of vegetation. In some instances, where verge space is limited or reduced, the creation of passing places have been established by localised widening on both sides of the road to create a 'bulb' effect.
- 155 It was recognised that the addition of passing places would be required for some route sections in order to facilitate two-way working on these routes. Consideration of passing places has been guided by the HS2 Rural Road Design Criteria. They are proposed along the following sections of road, with a commentary of their location, spacing/visibility and rationale provided:

A14.1.5.6.1 Weston Road (4No passing places on 800m section)

- 156 Whilst this road is of sufficient width for two cars to pass, there is no centreline markings and the presence of HGV traffic along this road could potentially lead to localised verge over-run. Traffic surveys indicate that although a low volume (7 AADT), HGVs currently use this road.
- 157 The road has excellent forward visibility, with a clear line of sight available between the B1164 and the first bend in the road (a distance of approximately 380m).
- 158 Between its junction with the B1164 and the first passing place (PP24) there is a distance of 90m, with the next passing place (PP23) located a further 240m shortly before a bend in the road.
- 159 The next passing place (PP22) is located a distance of 70m on the other side of the bend, from where clear forward visibility is available to the bridge over the A1 where the road widens slightly on its approach.
- 160 On the eastern side of the bridge over the A1, there is clear forward visibility to the Moorhouse Road junction. A passing place is provided at the mid-distance between the Moorhouse Road junction and the bridge over the A1, approximately 50m in each direction.

A14.1.5.6.2 Moorhouse Road (4No passing places on 1km section)

- 161 Whilst the width of this road accommodates two passing cars, there are no centreline markings, and it is considered relatively narrow. In its current form, it is not considered sufficient to accommodate HGV traffic without localised verge over-run. Traffic surveys indicate that although at a low volume (2 AADT), HGVs currently use this road.
- 162 The road has good forward visibility, with a clear line of sight between the Weston Road junction and the first bend in the road (a distance of approximately 550m).

- 163 Between its junction with Weston Road and the first passing place (PP20) is a distance of approximately 20m, with the next passing place (PP19) located a further 240m, followed by the next passing place (PP18) located another 175m south before a slight bend in the road.
- 164 Continuing southward after the bend, there is again good forward visibility. There is a distance of 175m between PP18 and the next passing place (PP17), with the site access (PA12) then located a further 230m.

A14.1.5.6.1.3 Ossington Lane (4No passing places on 1.25km section)

- 165 Whilst the width of this road accommodates two passing cars, there are no centreline markings and it is considered relatively narrow. In its current form it is not considered sufficient to accommodate HGV traffic without localised verge over-run. One HGV was recorded using the road during the traffic surveys and just 390 other vehicles per day.
- 166 The road has good forward visibility, with a good line of sight available between the B1164 junction and the first passing place (PP28) located a distance of 120m away.
- 167 Between PP28 and the next passing place (PP27) is a distance of 200m with good forward visibility between the two before the road passes over the A1.
- 168 Between passing places PP27 and PP26, there is a distance of 280m as the road passes over the A1.
- 169 At distance of approximately 230m west of passing place P26, the road bulbs slightly with hardstanding on each side in the vicinity of Brimblebeck Lane. Passing place PP25 is proposed a 130m west, before the site access which is located a further 100m.

A14.1.5.6.1.4 Ossington Road (1No passing place on 2.25km section)

- 170 This road currently accommodates two lanes of traffic, separated by centre line markings. HGVs currently use this road, and 82 HGVs were noted from the traffic survey.
- 171 Whilst the road currently accommodates HGVs, as the road continues westward towards site access PA14 the road has no centre line. To ease the confidence of passing vehicles in this area, one passing place is proposed (PP29).

A14.1.5.6.1.5 Carlton Lane (1No passing place on 290m section)

- 172 The width of Carlton Lane is not sufficiently wide enough for two vehicles to comfortably pass. There is clear intervisibility between the junction with Ossington Lane and the site access (PA17) located approximately 300m south. A passing place is provided at mid-length between the site access and the junction with Ossington Road.

A14.1.5.6.1.6 Maplebeck Road / Newark Road (15No passing places on 6.75km section)

- 173 This road accommodates two-way traffic and has centre line markings separating traffic flows. HGVs currently use this road, and 14 HGVs were noted from the traffic survey.
- 174 Noting the existing ability of the road to accommodate HGV traffic yet acknowledging the temporary increase in frequency due to the construction

phase of the Development, the approach here is to provide passing places along this section of road to increase the confidence of vehicles to pass an HGV.

- 175 As the road is currently two lanes and the intention to provide increase confidence of exiting occurrences, intervisibility between passing places is unnecessary. The distance between proposed passing places along this route range from 100m to 600m. Passing places have been located along the route in positions informed by professional judgement, with consideration given to appropriate opportunities with limited vegetation removal requirements.
- 176 Whilst informal and not confirming to any design criteria, a number of hard surfaced accesses abut the road at the eastern end of the route and will likely already perform a function of easing two-way movements when larger vehicles pass.
- 177 It should be noted that the Order Limits extend along the key routes to the Development from the main road and includes the full width of the adopted highway – road and verge. As such, if through liaison with the Local Highway Authority in agreeing the Detailed CTMP it is found necessary for additional passing places to be created, there is the ability to deliver these within the Order Limits.

A14.1.5.6.1.7 Retention and Reinstatement

- 178 Through continued liaison with the Local Highway Authority, the long-term status of the installed passing places will be established on a location-by-location basis. This will inform decisions on whether the passing places will be removed, and the verge reinstated or retained thereafter for community benefit. It is proposed that the passing places installed on sections of road that comfortably operate two-way traffic be retained through the operational and decommissioning period and the others be reinstated. Specifically, it is proposed that only the passing places on Weston Road, Moorhouse Road and Ossington Lane be retained.

A14.1.5.6.1.8 Location Summary and Outline Designs

- 179 Figure A14.1.9 shows the proposed location of passing places with their outline designs included in Appendix E, which also includes the swept path analysis that informed part of the initial route analysis. It should be noted the passing place references and drawing numbers may not run consecutively, this is due to varies design iterations adding and removing places, and the original references retained for continuity between versions.

A14.1.6 TRIP GENERATION AND DISTRIBUTION

A14.1.6.1 INTRODUCTION

- 180 This section sets out the trip generation for the Development and the distribution of these trips onto the highway network.

A14.1.6.2 CONSTRUCTION PHASES

- 181 The construction of the Development is anticipated to take approximately 24 months. The associated traffic flows and 'worst case' will vary over that time

as different elements and phases of the Development are constructed, possibly simultaneously, or at least with a degree of overlap. It should be noted that although 5 phases are presented in the outline construction programme, this is a spatial separation, but not necessarily temporal, with phases 1 and 3 being concurrent and 2, 4 and 5 being concurrent. This is equivalent, therefore, to two temporal phases with two or three construction teams operating concurrently.

182 For assessment purposes and as a worst-case scenario, it is assumed that the Development will be constructed with the two southern phases being built concurrently, followed by the two northern phases.

A14.1.6.3 TRIP GENERATION

183 The construction of the Development will involve a phased approach to manage the traffic generated during the construction period effectively. This phased approach ensures that the impact on the local highway network is minimised and that construction activities are carried out efficiently.

184 To inform the assessment of the construction phase, the most intense phase for traffic generation, a series of trip generation calculations have been undertaken using details contained in ES Chapter 5, Development Description [EN010162/APP/6.2.5]. The inputs and assumptions used in the trip generation calculation are presented in Table A14.1.4.

Table A14.1.4: Calculation Inputs and Assumptions

Item	Value
Total area of solar PV modules	550 ha
Total length of access tracks (Tarmac)	3 km
Total length of access tracks (Stone)	50 km
Area of compound areas	2 ha each
Total length of fencing	145 km
Site accesses to construct	41 No.
Construction vehicles required per access	5 HGV
Solar modules size range	3 sqm
Solar modules per container	620 No.
Frames per module factor	0.1
Storage units per substation	1 each
Vehicles required per storage unit	300
Number of intermediate substations	4 No.
Number of battery containers	754
Number of passing places to construct	40 No.
Internal stone track width	4 m
Internal stone track depth	0.15 m

Item	Value
Internal tarmac track width	5 m
Internal tarmac track depth	0.02m
Density tarmac	2.3 t/m ³
Density stone	1.8 t/m ³
Truck capacity	20 t
Compound Areas	19
Length of fencing per HGV load	10 m
Number of construction workers per phase	500
% of workers travelling to site by shuttle bus	30 %
Number of workers per bus	20
Workers' car share ratio	1.3
Contingency	20%

185 The above assumptions were then used to forecast the total trip generation, which were then apportioned by total area of solar PV within each phase and activity (a shown in Table A14.1.5). Following that calculation, trips were then presented to allow identification of the worst-case month for peak construction activity.

186 With the peak construction traffic forecast for each phase, activity and element of the project, these were then apportioned in accordance with the area being served by each primary access. This then allowed the peak construction trips on each road link to be forecast.

187 The assessment considers the respective worst-case flows, which also include further layers of robustness, such as a 20% uplift in traffic forecasts to account for fluctuations in activity and uncertainty.

188 When forecasting construction worker trips, it is assumed that 30% will travel via shuttle bus and car share ratio of 1.3 is used for non-shuttle bus users. This is considered robust when compared to other similar projects that assume a 50% shuttle bus usage and 1.5 car share ratio.

189 It is important to note that the Applicant has agreed a partnership that expects to see the mounting frames constructed using only British steel and onsite manufacturing, which is estimated to result in 650 fewer HGV movements overall. In simple terms for transport, this process means that steel for the mounting frames would be delivered to the Order Limits as flat sheets rather than prefabricated frames, thereby reducing the number of vehicles required due to space-savings.

190 Appendix F provides the calculations of trip generation described above and Figure A14.1.10 identifies the areas being served by each primary site access.

- 191 Construction of the Development is anticipated to take approximately 24 months. The associated traffic flows and 'worst case' will vary over that time as different elements and phases of the site are developed and constructed, possibly simultaneously, or not least, with a degree of overlap. The peak traffic generation in the month has been identified and used for assessment purposes.
- 192 The outline construction programme below in Table A14.1.5 provides a summary of the forecast traffic generation over each month and phase (HGV, LGV and car/van). As can be seen traffic levels are expected to peak during the fourth month of each phase and shows there are two 'worst case' period months when traffic levels are expected to peak, each occurring on different parts of the network. The trip generation assessment however considers the combination of the respective worst-case flows for two phases (i.e. Phase 3 and 4).
- 193 Table A14.1.6 provides the forecast levels of two-way traffic using each site access during its peak month of use during the construction period. During other periods of the site access use during construction, traffic movements will be less.

Table A14.1.5 Monthly Construction Traffic and Programme

Construction Activity		Month																								
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	
Phase One	Site access points	8	8	8																						
	Roads and tracks		328	164	55																					
	Construction compounds			324	486																					
	Fencing and CCTV				14	27	41	42	42	42	41	27	14													
	Solar PV poles, modules, inverters and transformers				50	100	152	155	155	155	152	100	50													
	Cabling				28	56	85	87	87	87	85	56	28													
	Intermediate substation								20	20	20	20	20											20	20	
	BESS/400 kV compound								211	211	211	211	211	5	5	5	5	5	5	5	5	5	25	25	25	25
	Connection to the transmission network at the existing National Grid Staythorpe Substation																							10	10	
Mitigation/enhancement planting				2	2	2	2	2	2	2	2	2											2	2		
Phase Two	Site access points													20	20	20										
	Roads and tracks														364	182	61									
	Construction compounds															540	810									
	Fencing and CCTV																15	30	46	47	47	47	46	30	15	
	Solar PV poles, modules, inverters and transformers																55	111	168	172	172	172	168	111	55	
	Cabling																31	62	95	96	96	96	95	62	31	
	Intermediate substation																					20	20	20	20	
	Mitigation/enhancement planting																2	2	2	2	2	2	2	2	2	
Phase Three	Site access points	15	15	15																						
	Roads and tracks		334	167	56																					
	Construction compounds			324	486																					
	Fencing and CCTV				14	28	42	43	43	43	42	28	14													
	Solar PV poles, modules, inverters and transformers				51	102	155	158	158	155	102	51														
	Cabling				29	57	87	88	88	87	57	29														
	Intermediate substation								20	20	20	20	20										20	20		
	Mitigation/enhancement planting				2	2	2	2	2	2	2	2	2										2	2		
Phase Four	Site access points													23	23	23										
	Roads and tracks														616	308	103									
	Construction compounds															864	1296									
	Fencing and CCTV																26	51	78	79	79	79	78	51	26	
	Solar PV poles, modules, inverters and transformers																94	188	285	291	291	291	285	188	94	
	Cabling																31	62	95	96	96	96	95	62	31	
	Intermediate substation																					20	20	20	20	
Mitigation/enhancement planting																2	2	2	2	2	2	2	2	2		
Phase Five	Battery installation													5	5	5	5	5	10	10	10	10	10			
		23	685	1002	1272	374	566	578	829	829	817	625	441	53	1033	1947	2536	519	786	801	841	861	846	629	376	

Table A14.1.6: Primary Access Peak Traffic Usage

Access ID	Location	Peak Month Daily 2-way Flow
PA1	A617 – 100 m east of Main Road junction	211
PA2	Caunton Road – approx. mid-length of road	377
PA3	Caunton Road – approx. mid-length of road	76
PA4	Maplebeck Road – 2 km west of A616 junction	339
PA5	Newark Road – 590 m east of Sandy Lane Public Footpath	62
PA6	Newark Road – 720 m east of Sandy Lane Public Footpath	52
PA7	A616 – 1.08 km south-east of Kersall Road	133
PA8	A616 – 1.03 km south-east of Kersall Road	54
PA9	Kersall Road - 240 m north-east of A616 junction	58
PA10	Kersall Road - 375 m south of Ossington Road junction	130
PA11	Ossington Road - 500 m north of Main Street junction	107
PA12	Moorhouse Road – 150 m south of Hagg Lane.	95
PA13	Ossington Lane – 250 m west of Brimblebeck Lane.	156
PA14	Ossington Road – 1.95 km west of Carlton Lane	40
PA15	Ossington Road – 1.4 km west of Carlton Lane	50
PA16	Ossington Road – 1.35 km west of Carlton Lane	44
PA17	Carlton Lane – 300 m south of Ossington Road junction.	145
PA18	Staythorpe Road – 395 m east of Pingley Lane	20
PA19	Staythorpe Road – 190 m east of Pingley Lane	20

A14.1.7 IMPACT ASSESSMENT

A14.1.7.1 INTRODUCTION

¹⁹⁴ This section summarises the effect of the Development on the local highway network.

195 The traffic impact assessment has been informed by separating the road network into links. These links are those sections of road to be used for construction traffic, with each section being assigned a Link ID, which is given in Table A14.1.7. Assigning a Link ID allows for ease of reference and enables different sections of the same road to be considered and discussed.

A14.1.7.2 CONSTRUCTION PHASE

- 196 The construction phase of the Development is expected to last approximately 24 months. The assessment of the effects of the construction phase is based on peak construction vehicle movements.
- 197 The construction phase for the Development includes the preparation of the land and construction compounds, installing the access tracks, erection of security fencing, assembly and erection of the PV strings, installation of the inverters/transformers and the grid connection.
- 198 A Construction Traffic Management Plan (CTMP) will be implemented during the construction phase of the Proposed Development. The aim of the CTMP is to manage and minimise the effects of the construction phase on the highway network and on local residents. An outline of the CTMP is provided as ES TA A5.2 [EN010162/APP/6.4.5.2].
- 199 Core working hours are proposed to be between 07.00 and 19.00, Monday to Friday, and 07.00 and 13.00 on a Saturday (unless in exceptional circumstances where the need arises to protect plant, personnel or the environment). These core working hours will be secured through the Construction Environmental Management Plan. In addition to this, a start-up and close-down period of up to an hour before and after the core working hours is proposed, which does not include the operation of plant or machinery likely to cause a disturbance. Also, deliveries will be scheduled to avoid school drop off and collection periods and other sensitive times. Restrictions will also be made on construction vehicle movements during periods of the road network that are experiencing abnormal conditions – such as road closures on the A1 due to incident management measures.
- 200 Pedestrian and cycling activity on the rural roads will be low but still presents some risk when construction traffic is present. To mitigate this, the Outline CTMP sets out measures such as the route hierarchy and presents reduction in speed limits and signage to safely manage the passage of non-motorised users on the local network in proximity to the site accesses.
- 201 The traffic surveys identified previously provided sufficient coverage of road network locations along the proposed construction routes.
- 202 Following the completion of the Development construction phase, baseline traffic levels will likely be less than those reported in this TS due to the temporary change of use of the agricultural land and its associated farm vehicle movements. For the assessment of the construction phase, local growth factors have been applied to the base flows using factors derived from TEMPro Version 8.1, the Trip End Model Presentation Program used to access and analyse data from the National Trip End Model (NTM). The following factors have been determined from the 'Region of Newark and Sherwood: Average Day' dataset from TEMPro and used to adjust the

baseline traffic flows from 2024 to 2028, which is the assumed mid-point of the construction period:

- Trunk Road: 1.0477;
- A Road: 1.0328; and
- Minor Road: 1.0317.

²⁰³ The 2028 future baseline traffic flows are shown in Table A14.1.7 which should be read in conjunction with Link ID plan given in Figure A14.1.11.

Table A14.1.17. Construction Baseline and Future Traffic

Link	Description	2024 BASELINE AADT	
		Total Vehicles	HGV
1	A46	29,174	2,811
2	A616 Great North Road	10,076	475
3	A617 Kelham Road	15,668	731
4	A616	5,529	177
5	Caunton Road (South)	1,694	0
6	Caunton Road (North)	1,694	51
7	Maplebeck Road	675	9
8	Newark Road	1,068	14
9	Kersall Road	621	15
10	Main Street	622	8
11	Ossington Road (South)	133	0
12	Ossington Road (East)	683	82
13	Ossington Lane	390	1
14	Moorhouse Road	298	2
15	Weston Road	771	7
16	B1164 Great North Road	1,932	63
17	Carlton Lane	215	2
18	Staythorpe Road	1,925	26
19	A1 (Northbound)	25,677	4,237
20	A1 (Southbound)	25,658	4,234
21	A616 (East)	5784	164
22	A617 (West)	10,481	890

²⁰⁴ Daily construction traffic flows have been added onto 2024 base to show the change in vehicles. This is summarised in Table A14.1.8.

Table A14.1.8. 2028 Future Base with Construction Traffic

Link	Construction Traffic		2028 Plus Construction Traffic		Percentage Change
	Total Vehicles	HGV	Total Vehicles	HGV	Total Vehicles (%)
1	823906	107	30,079	2,946	3 %
2	823906	107	10,982	610	9 %
3	612	10	16,280	741	4 %
4	342374	64	5,903	218	6 %
5	179200	0	1,894	51	12 %
6	412453	53	2,147	104	27 %
7	412453	53	1,128	91	71 %
8	104114	13	1,182	35	11 %
9	171187	32	808	36	21 %
10	4044	0	667	8	7 %
11	40	0	173	0	30 %
12	257278	68	961	150	41 %
13	242264	57	654	51	66 %
14	8895	23	393	25	32 %
15	8895	23	866	31	12 %
16	242264	57	2,196	113	13 %
17	134145	36	360	38	68 %
18	250	5	2,175	33	14 %
19	453	107	26,130	4,291	2 %
20	453	107	26,111	4,288	2 %
21	453	54	6,237	218	8 %
22	453	54	10,934	944	4 %

205 This Table provides data on traffic changes associated with construction activities from a 2028 future base level. It is important to note that larger increases in traffic volume change are typically associated with a low baseline level.

206 It is worth noting that the numbers presented are total daily flows and demonstrate a maximum number over the course of a 24-hour period. Overall, the table underscores the varying degrees of traffic impact across different links, with most experiencing unnoteworthy increases on the local highway network. It is important to highlight that links reporting high

percentage increases are those that typically have a low baseline level of traffic and so more sensitive to changes in traffic volume.

- 207 With the implementation of passing places, where appropriate, the proposed construction traffic routes are suitable for use by the relatively low number of HGVs associated with the construction period. The likelihood of background traffic being delayed is low.
- 208 When considering the suitability of the site access locations, this has been undertaken with reference to DMRB CD123 – Geometric design of at-grade priority and signal-controlled junctions. Within CD123, guidance is provided on the form of junction provision on single carriageway roads based on traffic flows. Simple priority junctions are generally accepted when traffic flows on the minor arm are in the order of 300 two-way AADT. It can be seen from Table A14.1.6 that two site access locations are forecast to receive in excess of 300 two-way AADT, these being access PA2 and PA4. It should be noted however that:
- DMRB CD123 outlines that the traffic flow thresholds are approximate. The two site access points exceeding 300 two-way AADT do so by less than 80 two-way movements over the day.
 - The values provided in Table A14.1.6 are those forecast during the peak month of construction activity. Outside of this period, flows will be less.
 - Aside from the arrival and departure of the workforce, traffic using the junction will be spread relatively evenly through the day.
 - Measures within the detailed CTMP allow for greater levels of control and driver awareness of the site access.
 - It is not considered appropriate to design the site access locations with a ghost island arrangement for a temporary construction period.
- 209 The low level of daily construction vehicle movements and their occurrence outside of the road network peak periods means that there will not be a material effect on the highway network during the construction period.

A14.1.7.3 OPERATIONAL PHASE

- 210 Once solar parks are operational, they generate very few traffic movements on a day-to-day basis.
- 211 During the operational phase, there are anticipated to be around 15 vehicle trips per day across the whole site for maintenance purposes. These would typically be made by light van or 4x4 type vehicles. Whilst each construction compound will have been removed at the end of the construction phase, internal tracks and space will remain for vehicles to turn around to ensure that reversing will not occur onto the highway.
- 212 It should be noted that two Electric Vehicle charging points for site workers/visitors will be installed at each intermediate substation and the 400 kV compound.
- 213 There will be no transport operational effects associated with the installed grid connection cables as they will be located underground. Access may be required for maintenance, but this is only likely once or twice a year.
- 214 The BESS components are assumed to be replaced on average less than twice over the 40-year lifetime. Solar PV modules typically have a design life

of over 40 years and so are not expected to be replaced in bulk, with only occasional need for replacements as part of routine maintenance.

- 215 Traffic levels during the operational phase will be far fewer than those outlined and assessed for the construction phase.
- 216 As outlined previously, during the construction phase, traffic will route to the most appropriate primary access and note its arrival before then using the secondary accesses, predominately in a cross-over movement. The CTMP allows for traffic management measures to be installed as required.
- 217 During the operational phase, there may, on occasion, be a requirement for vehicles to access a solar area only served by a secondary access from the public highway. In most instances, these movements can occur under normal traffic conditions and will typically be less than the agricultural use in their current form for existing field accesses. However, the final Operational Environmental Management Plan (TA A5.5 [EN010162/APP/5.5]) will identify any locations where site-specific activities may require localised temporary traffic management measures to be agreed in advance with the Local Highway Authority – such as the use of banksmen. The temporary traffic management measures will be proportionate to the nature and duration of activity and the expected volume and type of traffic movements.

A14.1.7.4 ABNORMAL LOADS

- 218 Transporting abnormal loads to a new development is a complex but essential task that requires meticulous planning and execution. Abnormal loads for the Development will include transformers and cable drums.
- 219 To assist in the planning of abnormal loads transportation, Wynns, a specialist abnormal load transportation specialist has been engaged from an early phase of the project.
- 220 Wynns are well placed to provide specialist advice given their extensive experience, which includes other projects in the area that have used much of the same road network.
- 221 Appendix G provides a copy of the abnormal load assessments undertaken to the substation areas and confirms that it is reasonable to consider the routes to all of the proposed substation sites to be feasible in terms of heavy load AIL requirements based on historical movement requirements at heavier weights in the area.
- 222 Wynns were also commissioned to consider the viability of transporting Abnormal Indivisible Loads (AILs) to the proposed access points. The report, which is included in Appendix G, considers access in respect to AIL access for cable drums to various sites within the proposed construction corridors. The report was informed by a physical route survey and highlighted the preferred AIL access routes via the public road network and advised on their viability. Following this assessment, a Red, Amber, Green rating was assigned.
- Green – Proposed site access considered negotiable for AILs;
 - Amber – Some remedial works will be required to secure site access for AILs. Further surveys and Swept Path Assessments (SPA) to be

- undertaken to clarify requirements but access is considered feasible with additional works; and
- Red – Proposed site access not considered negotiable for AILs and alternative access point required/suggested via internal haul roads along cable route.
- 223 Only the accesses considered to be ‘Green’ have been taken forward.
- 224 Figure A14.1.12 shows the routes considered for the transportation of AILs for the substations and cable drum access.
- 225 The AILs will be delivered under Special Types General Order (STGO) Regulations and will not be limited to the nearest potential port of delivery and access is considered from the nearest known heavy load routes, the A1, A617 and A616 which have been historically used for access to Staythorpe Power Station for much larger heavy electrical plant.
- 226 The review of the routes is based on the preferred route for negotiability. There are structures belonging to authorities including Nottinghamshire County Council and Network Rail that would require confirmation of their suitability for STGO AILs prior to movement. However, no specific structural restrictions were identified and there are no weak structures (which cannot accommodate standard 44te Construction and Use traffic) on the preferred routes.
- 227 Further discussions with Nottinghamshire County Council and the police would be necessary to confirm access requirements in terms of escorting of the AILs. The AIL movements will likely take place during quieter periods on the local highway network. Therefore, the effect on the local highway network will be temporary and reduced.

A14.1.7.5 SUMMARY

- 228 The effect of the temporary changes in traffic flows on the local highway network associated with the construction phase of the scheme are not anticipated to be significant in nature, and therefore the impact on each link will not be significant in terms of road capacity and the impact on existing users.
- 229 The potential environmental effects associated with the increase in traffic level is assessed separately within the ES Chapter 14 Traffic and Transport [EN010162/APP/6.2.14]. The CTMP will be the key mitigation measure to ensure that the access strategy is followed, and the effects of construction traffic are managed and minimised (see the Outline CTMP, TA A5.2 [EN010162/APP/5.2]).

A14.1.8 SUMMARY

- 230 This report is the Transport Statement to support the development of the Great North Road (GNR) Solar and Biodiversity Park, a solar photovoltaic (PV) electricity generating facility northwest of Newark-on-Trent, Nottinghamshire.
- 231 The Transport Statement provides systematic review and assesses the transport impacts of the Development, proposing mitigation measures to alleviate any negative effects.
- 232 The report outlines the transport vision of the site in relation to sustainable transport.
- 233 The policy context includes national and local planning policies supporting sustainable development and transport. An accessibility audit reviews existing transport conditions, including walking, cycling, bus, and train travel. A commentary of the surrounding road network is also considered along with a review of recent road safety data.
- 234 The road safety review did not identify any areas where the road safety history would imply that development related traffic would exacerbate conditions. Measures are included to reduce the impact of traffic, including scheduled timing for deliveries to be outside of peak periods and passing places.
- 235 The Development includes multiple access points, using existing and new access locations. A hierarchy of construction routes has been deployed in the access strategy to minimise the traffic impact on local roads. The construction phase is expected to last 24 months, with minimal operational traffic post-construction. The impact assessment indicates that the construction traffic will not significantly affect the local highway network, and abnormal loads will be managed to minimise disruption.
- 236 Overall, the report concludes that the traffic impact of the Development is manageable and that with the proposed mitigation measures in place, it can be delivered in a safe and efficient manner that minimises disruption to the local transport network.