

Green Hill Solar Farm

EN010170

Statement of Common Ground: Environment Agency Revision C

Prepared by: Lanpro Services

Date: March 2026

Document Reference: EX6/GH8.3.5_C

Infrastructure Planning (Examination Procedure) Rules 2010



Contents

<u>1</u>	<u>Introduction</u>	<u>3</u>
1.1	Purpose of the Document	3
1.2	Parties to this Statement of Common Ground	3
1.3	Terminology and Referencing	3
1.4	Topic Referencing for All Matters	3
<u>2</u>	<u>Record of Engagement</u>	<u>4</u>
2.1	Summary of Consultation	4
<u>3</u>	<u>Matters of Discussion</u>	<u>8</u>
3.1	Overview	8
3.2	Ecology and Biodiversity	8
3.3	Hydrology, Flood Risk and Drainage	24
3.4	Ground Conditions and Contamination	57
<u>4</u>	<u>Signatories</u>	<u>75</u>
4.1	Overview	75

List of Tables

Table 1.1: Topic Referencing	3
Table 2.1: Record of Engagement	5
Table 3.1: Ecology and Biodiversity	8
Table 3.2: Hydrology, Flood Risk and Drainage	24
Table 3.3: Ground Conditions and Contamination	57



Issue Sheet

Report Prepared for: Green Hill Solar Farm

Examination Deadline 6

Statement of Common Ground: Environment Agency (Revision C)

Prepared by

Name: Lucy Antell

Job title: Flood Risk Consultant

Approved by

Name: Joshua Rigby

Job title: Manager | Water Environment

Revision	Date	Prepared by	Approved by
Original	19/11/2025	LA	JR
A	14/01/2026	CA	JC
B	26/02/2026	CA	JC
C	24/03/2026	CA	JC



1 Introduction

1.1 Purpose of the Document

1.1.1 This Statement of Common Ground (SoCG) has been prepared as part of the proposed Green Hill Solar Farm Development Consent Order (the Application) made by Green Hill Solar Farm Ltd (the Applicant) to the Secretary of State for Energy Security & Net Zero (the Secretary of State) pursuant to the Planning Act 2008 (PA 2008).

1.1.2 This SoCG does not seek to replicate information which is available elsewhere within the Application documents. All documents are available on the Planning Inspectorate’s website.

1.1.3 This SoCG has been produced to confirm to the Examining Authority (ExA) where agreement has been reached between the parties, and where agreement has not yet been reached. SoCGs are an established means in the DCO consenting process, of allowing all parties to identify and focus on specific issues that may need to be addressed during the examination.

1.2 Parties to this Statement of Common Ground

1.2.1 This SoCG has been prepared by (1) Green Hill Solar Farm Ltd. as the Applicant and (2) the Environment Agency (EA).

1.2.2 Collectively, Green Hill Solar Farm Ltd. and the Environment Agency are referred to as ‘the parties’.

1.3 Terminology and Referencing

1.3.1 In the Tables in Section 3 of this SoCG below:

- “Agreed” indicates where the issue has been resolved;
- “Not Agreed” indicates a final position; and
- “Under discussion” indicates where these points will be the subject of ongoing discussion wherever possible to resolve, or refine, the extent of disagreement between the parties.

1.4 Topic Referencing for All Matters

1.4.1 All matters agreed, under discussion and not agreed have been given unique references which relate to the topic matter. The referencing system is defined as follows:

Table 1.1: Topic Referencing

Topic	Unique Identifying Code
Ecology and Biodiversity	EB-XX
Hydrology Flood Risk and Drainage	HYD-XX
Ground Conditions and Contamination	GCC-XX



2 Record of Engagement

2.1 Summary of Consultation

2.1.1 The parties have been engaged in consultation since March 2024.

2.1.2 A non-statutory consultation took place in March to May 2024. The statutory consultation process took place between 7th November and 19th December 2024.

2.1.3 The Applicant and the Environment Agency have engaged extensively throughout the pre-application and Environmental Impact Assessment (EIA) stages of the Proposed Development. The key engagement has included statutory consultation responses, technical discussions on flood risk modelling and drainage design, and provision of supporting information to inform the Environment Agency's review.

2.1.4 The main focus of discussions has related to:

- The hydrology, flood risk and drainage assessments set out in Environmental Statement (ES) Chapter 10 **[EX6/GH6.2.10_C]** and the Flood Risk Assessment (FRA) Covering Report **[REP5-021]** and Annexes **[APP-100 to APP-108, REP5-021; REP5-027; REP5-029 and REP5-031]**.
- The scope and methodology of the Water Framework Directive (WFD) Assessment **[REP5-081]**.
- The approach to climate change allowances in the FRA and drainage strategy.
- Provision of rainfall hyetograph data and ReFH2 calculations to support verification of the 2D direct rainfall model.
- The design of bunded drainage and pollution prevention measures for Battery Energy Storage System (BESS) areas.
- Measures to manage residual flood risk, including emergency response procedures.
- Construction phase flood risk management.
- Consideration of impacts upon fish species, especially migratory fish species and impacts associated with trenching and Horizontal Directional Drilling around watercourses.
- Consideration of impacts upon aquatic invertebrates.

2.1.5 Consideration of the risks associated with historical landfill areas in proximity to the site, including their potential to cause contamination and impact controlled waters. A summary of the meetings and correspondence that has taken place between Green Hill Solar Farm Ltd and statutory consultees in relation to the Application is outlined in **Table 2.1** below.



Table 2.1: Record of Engagement

Date	Form of Correspondence	Key Topics Discussed	Key Outcomes
March–May 2024	Email correspondence (non statutory consultation)	Applicant requested EA Product 4, 5 and 6 data and sought early agreement on baseline information needs for the FRA and WFD screening, including available hydraulic models, historic flood records and climate allowance parameters.	EA acknowledged the requests and confirmed data availability to support preparation of the assessments.
November–December 2024	Statutory consultation response (Section 42)	Environment Agency provided detailed comments on ES Chapter 10, the FRA, and the WFD screening assessment, including recommendations on model verification, drainage design and pollution prevention measures.	Comments and recommendations to take forward.
December 2024–January 2025	Email correspondence	EA requested provision of rainfall hyetograph data, ReFH2 calculations and model logs to support verification of the hydraulic modelling approach.	See below.
January 2025	Statutory consultation response (Section 42)	Environment Agency provided detailed comments on fisheries legislation; mitigation measures for activities which may impact fish (such as trenching of watercourses); potential impacts on aquatic invertebrates; and characterisation of watercourses.	Comments and recommendations to take forward.
January 2025	Statutory consultation	Ground Conditions and Contamination: Environment Agency requested the	Comments actioned within GH6.2.22 Environmental Statement Chapter 22



Date	Form of Correspondence	Key Topics Discussed	Key Outcomes
	response (Section 42)	assessment of landfill risk to controlled waters, queried the requirement of cable leak protection and requested further details regarding Source Protection Zones (SPZs) and aquifers as potential receptors.	Ground Conditions and Contamination [REP1-025].
January–March 2025	Email correspondence and file submission	Applicant provided model logs, rainfall hyetograph files and ReFH2 outputs. Updated mapping datasets were submitted reflecting NaFRA2 (January 2025) and revised RoFSW outputs.	EA acknowledged receipt and confirmed the information would inform their review.
April–May 2025	Email correspondence	Ongoing review of hydraulic modelling and drainage design. EA raised clarifications on residual risk measures, construction phase arrangements and pollution prevention measures for BESS areas.	N/A
June–July 2025	Email correspondence and SoCG preparation	Parties discussed the structure of the SoCG, confirmed the topics for inclusion.	Parties agreed to record current positions pending final review.
1 st October 2025	Teams meeting	Issue raised in EA Relevant Representation [RR-1224] regarding avoidance of the coarse fish spawning period for open-cut trenching of watercourses during cable route installation.	Applicant committed to avoidance period of October – June 15 th for relevant works, or completion of habitat suitability survey work pre-commencement to establish whether spawning fish are likely present/absent. This commitment is secured in the Outline Ecological Protection



Date	Form of Correspondence	Key Topics Discussed	Key Outcomes
			Mitigation and Strategy Revision D [EX6/GH7.5_D].
19 February 2026	Teams meeting	Comments raised in response to the draft SoCG at Deadline 4 [REP4-033] .	Applicant set out the updates and deliverables that are being submitted at Deadline 5.

2.1.6 It is agreed that this is an accurate record of the key meetings and consultation undertaken between Green Hill Solar Farm Ltd and the Environment Agency in relation to the issues addressed in this SoCG.



3 Matters of Discussion

3.1 Overview

3.1.1 **Table 3.1** to **Table 3.3** below detail by topic the matters agreed, under discussion, or not agreed with the Environment Agency at the point of this document being published.

3.2 Ecology and Biodiversity

Table 3.1: Ecology and Biodiversity

	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
EB-01	Legislation	<p><u>EA Statutory Consultation Feedback</u></p> <p>The Salmon and Freshwater Fisheries Act 1975 and The Eels (England and Wales) Regulations 2009 have not been included in the list of legislation that is relevant to biodiversity. The legal responsibility on the developer pertaining to this fish specific legislation has not been considered. This infers that the impacts on fish from the construction, operation and decommissioning have not been fully considered. Both pieces of legislation should be listed as relevant in the biodiversity chapter of the ES</p>	<p>This legislation has been considered and referenced in the Environmental Statement Chapter 9 Ecology and Biodiversity [EX6/ GH6.2.9_B].</p>	<p>Noted and agree.</p>	<p>Agreed</p>



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		and submitted as part of the DCO.			
EB-02	Mitigation for fish species	<p><u>EA Statutory Consultation Feedback</u></p> <p>Fish surveys or fish habitat surveys have not been included as part of the baseline data collection. Certain construction activities may have a negative impact on notable fish populations. Particularly where open cut trenching is proposed for cable crossing of waterbodies. A qualitative fish habitat assessment (coupled with the desk-based study) should be completed where cable crossings are proposed. This will inform necessary mitigation measures. Where quantitative fish surveys have not been completed, the precautionary approach should be taken and assumed that fish species present within the catchment will be present if habitat is suitable.</p>	<p>An approach is set out whereby either open-cut trenching or trenchless techniques, such as HDD, will be used for cable crossing points. The final approach may be revised based on qualitative assessments to be completed pre-construction and outlined in the Outline Ecological Protection and Mitigation Strategy (OEPMS) [EX6/GH7.5_D]. Appropriate mitigation for fish species will be implemented in the event of open-cut trenching. This is considered appropriate and proportionate.</p>	<p>Noted and agree with this approach based on detail and mitigation in section 7.4 Rivers and Stream of the OEPMS [EX6/GH7.5_D] as well as Table 3.4 of OCEMP.</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>Mitigation measures should be stringent to control pollution and fine sediment runoff into waterbodies. Where open trench crossings are proposed, it is assumed that waterbodies that will be flumed, or coffer dammed and thus require over-pumping. It may be necessary for a fish rescue and relocation to take place and for key spawning and migration periods to be avoided. Mitigation should be included within the Outline CEMP and submitted with the DCO application. Any over-pumping should ensure that screens are fitted on inlets and outlets of pumps and that they are compliant with the Eels (England and Wales) Regulations 2009.</p>			
EB-03	Noise impacts on fish	<p><u>EA Statutory Consultation Feedback:</u></p> <p>Impacts on fish from noise associated with vibration created by HDD has not been included. Sensitive fish</p>	<p>The Environmental Statement Chapter 9 Ecology and Biodiversity [EX6/GH6.2.9_B] assesses the likely impacts of noise and vibration on fish. The Outline Ecological Protection and</p>	<p>Noted and agree precautionary way of working as per section 8 of OEPMS [EX6/GH7.5_D].</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>species associated with the River Nene could be disturbed during construction and decommissioning activities. The EIA should include an assessment on the risk of fish populations within the River Nene and other main watercourses being impacted by noise from HDD during construction. Mitigation and management of any impacts should be detailed in the Outline CEMP. Standard mitigation would be to avoid this activity during sensitive fish migration and spawning times, or drilling to a depth where any significant noise becomes negligible to fish.</p> <p>Noisy construction activities such as HDD under watercourses may disturb fish during key periods of migration and spawning. In extreme cases, noise may kill fish. According to our records, the River Nene contains European eel (Section 41 priority species NERC), brook</p>	<p>Mitigation Strategy (OEPMS) [EX6/GH7.5_D] details mitigation measures to be implemented. The impact assessments and mitigation measures proposed are considered appropriate and proportionate.</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		lamprey (<i>Lampetra planeri</i>) (Annex II Habitats Directive), bullhead (<i>Cottus gobio</i>) (Annex II Habitats Directive), spine loach (<i>Cobitis taena</i>) (Section 41 priority species NERC and Annex II Habitats Directive) and brown/sea trout (<i>Salmo trutta</i>) (Section 41 priority species NERC). It maybe that appropriate mitigation to avoid impacts on fish would be a sufficient buffer zone from water courses and/or noisy construction activities avoiding key periods of migratory and fish spawning.			
EB-04	Consultation	<u>EA Statutory Consultation Feedback:</u> Table 9.1: Summary of Consultation and Responses doesn't include the Environment Agency.	Consultation with the EA is shown in Table 9.2 of the Environmental Statement Chapter 9 Ecology and Biodiversity [EX6/GH6.2.9_B].	Noted and agree.	Agreed
EB-05	Impacts on aquatic invertebrates	<u>EA Statutory Consultation Feedback:</u> Solar farms that have wetland habitats on site or are near wetland habitats should	Studies on this matter are inconclusive, although there is some evidence to suggest that polarotactic invertebrates may be	We will endeavour to provide further comments as soon as possible following information from the Applicant confirming whether they have already	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>implement mitigation to prevent adverse impacts on aquatic invertebrates. Many species of aquatic invertebrates mistake the polarised light reflected from solar panels for open water, leading them to try and lay eggs on panels, which ultimately fail. Low-cost mitigation measures can be taken that do not impact on energy generation, such as including a pattern of roughened or painted glass or a horizontal light blocking grid so that they are no longer attractive to aquatic invertebrates.</p>	<p>attracted to panels, which reflect polarised light.</p> <p>Wetland habitats were of limited extent within the Survey Area, meaning there is limited suitable habitats for aquatic invertebrates and a notable population is considered unlikely to be present. Moreover, buffers to boundary habitats of elevated importance for aquatic invertebrates, such as the Grendon Brook, are substantial (at least 30m). Therefore, no significant adverse effects on aquatic invertebrates through polarised light are anticipated.</p> <p>Applicant Response to Consultee Position</p> <p>The Scheme retains flexibility on panel technology at this stage as per Section 4.3: Rochdale Envelope of the Environmental Statement Chapter 4: Scheme Description (Revision B) [EX6/GH6.2.4_B]. The technical specification of the panel will be chosen at detailed design stage (post-consent) in line with the</p>	<p>considered/ would be willing to consider using anti-glare/anti/reflective coatings on the solar panels.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We are satisfied that this issue has been resolved. Buffer strips will be provided around watercourses and ponds and there will be no solar panels at Green Hill BESS where the stream on site has been deemed most valuable for aquatic invertebrates.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>parameters assessed and defined in the Concept Design Parameters and Principles Document Revision C [EX6/GH7.17_C]. As detailed above, it is the position of the Applicant that no significant adverse effects on aquatic invertebrates through this impact pathway are anticipated, and therefore no additional mitigation measures (such as particular panel coatings) are considered necessary.</p>		
EB-06	Watercourse assessment	<p><u>EA Statutory Consultation Feedback:</u></p> <p>Watercourses present in some array areas (e.g. A, A1, B, C, D, & E) have been dismissed as agricultural drains, however, some appear to be spring fed natural watercourses and not artificial field drains. Lack of consideration of natural spring fed watercourses in array areas could result in morphological and ecological harm to headwater streams. Ensure that natural spring fed</p>	<p>Relevant datasets have been consulted to determine the status of watercourses across the sites, supported by ground-truthing field surveys. Evaluation of these features and enhancement measures are detailed in the Environmental Statement Chapter 9 Ecology and Biodiversity [EX6/GH6.2.9_B] which are considered appropriate and proportionate.</p> <p>Applicant Response to Consultee Position</p>	<p>Unable to locate the correct part of the document that contains the response to this point.</p> <p>However, we have located the following information: “9.9.135 The opportunity for practicable ditch and watercourse management, including vegetation clearance (for choked ditches) or planting of locally appropriate wetland marginal species will be explored through consultation with local conservation stakeholders and consultees”. This is the only response to this</p>	Matter Under Discussion



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>watercourses are correctly identified, in the proposed MoRPh surveys and BNG assessment as “other rivers and streams”, rather than “ditches”. Minor works to improve these watercourses could result in significant uplift for the project.</p>	<p>Regarding the identification and categorisation of watercourses, please refer to the Applicant’s response to EA-025 in Applicant Responses to Relevant Representations [REP1-161]. Table 9.3 of Environmental Statement Chapter 9 Ecology and Biodiversity (Revision B) [EX6/GH6.2.9_B] gives a summary of the watercourses present on the Sites. Full baseline habitat maps are given in Environmental Statement Appendix 9.2 Habitat Surveys (Revision A) [REP1-045].</p> <p>All watercourses, including ditches, streams and rivers, are protected with undeveloped buffer zones (minimum 8m) through embedded mitigation measures, as per paragraph 9.8.4 of Environmental Statement Chapter 9 Ecology and Biodiversity (Revision B) [EX6/GH6.2.9_B].</p>	<p>concern, and as such is disappointing.</p> <p>To protect natural spring fed watercourses, we would expect some commitment to establishing buffer zones around these features and associated watercourses, e.g. in BNG, minimum riparian buffer for ditch habitat is 5m from banktop. It is possible that this would be sufficient for such watercourses and springheads/wet flushes. Protecting springs and associated headwater channels would also help to prevent deterioration of any WFD waterbodies further downstream.</p> <p>Further information on the importance of headwaters can be found via this link: CaBA-Biodiversity-Pack-Headwaters.pdf</p> <p>We note the commitment to buffers, we require clarity on protection of headwaters/wet flushes/springheads -</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Applicant Response to Consultee Position</p> <p>“Wet flushes” is not a defined hydrological or regulatory category. There is no recognised spatial dataset for wet flushes and they do not constitute a separate waterbody type requiring standalone assessment.</p> <p>In respect of headwaters, these are the upstream extents of the same watercourses already identified and assessed within ES Chapter 10. The assessment considers watercourses as whole systems. Embedded mitigation applies to all watercourses irrespective of size or stream order, including buffers, avoidance of in-channel works except agreed crossings, and standard pollution prevention measures. The upper reaches are therefore already captured within the overall assessment and protection framework.</p>	<p>springs/wet flushes are not ditches/other watercourses streams, could even be classified as an area habitat unit under BNG, rather than a linear (watercourse) unit, so could come under the 20m buffer for ponds/moderate watercourses.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We have identified at least one spring within the Order limits of Area E, just north of Brook Hill Farm and one very close to the southern boundary.</p> <p>For the avoidance of doubt - “Springs and flushes are areas where water from underground – called groundwater – flows out onto the surface to create freshwater and wetland habitats.</p> <p>Springs are the locations where water bubbles out of the ground, which can then either flow into obvious stream channels or spread across the ground to</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Applicant Response to Consultee Position 24/03/2026</p> <p>Green Hill EF29 and EF30 do not include panels and are proposed areas of diverse wildflower meadow as shown on ES Figure 4.15 Landscape and Ecology Mitigation Plan E (Sheet 2) [EX6/GH6.4.4.15_C].</p> <p>Panels within Green Hill EF27 been offset from Hockerhill Farm. Based on a review of approximate markup provided by the Environment Agency and Ordnance Survey data, the panels appear to be appropriately offset from the identified spring.</p> <p>If springs were present and contributing to a wet habitat (such as a watercourse or wet grassland), these habitats would have been recorded as such during the habitat walkover surveys. These surveys were completed at various times of year between August 2023 and September 2025 across the Order Limits, and plant communities associated with wet</p>	<p>make an area of wetland that doesn't have a single channel.</p> <p>Flushes are essentially a special kind of springline wetland, where the water is flowing diffusely across the ground surface, held up by impermeable soils and rock." – Freshwater Habitats Trust [accessed 16/03/26]</p> <p>It is pleasing to see that the headwaters of the watercourses identified in Chapter 10 of the ES will be subject to the suggested buffers included in the protection framework.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>habitats would likely have been present and detectable during the survey periods. As shown in Appendix 9.2: Habitat Surveys [REP1-045], Figure 9.2.7 identifies the eastern edge of EF27 and the southern edge of EF29 as Other Rivers and Streams, which have been appropriately offset.</p>		
EB-07	<p>Impacts of Electromagnetic Fields (EMF) on migratory fish species</p>	<p>EA released a Position Statement entitled 'Impact of Electromagnetic Fields on Freshwater Fish in Inland Waters', stating that 'in the absence of conclusive evidence of no impact, we adopt the precautionary principle and require that appropriate measures are put in place by the developer, so that no detectable EMFs result from the installation of underground cables within the wetted area of an inland waterbody'.</p>	<p>The potential effects of anthropogenic EMF on ecology is an emerging and poorly researched issue, however a summary of research on this issue is provided in Environmental Statement Chapter 9 Ecology and Biodiversity [EX6/GH6.2.9_B] (paragraphs 9.9.249 – 9.9-250). A precautionary approach to mitigation has been taken, whereby all cables which cross the River Nene will be buried to a minimum depth of 5m, to maximise attenuation of electromagnetic fields and minimise the risk of any adverse impacts. This depth is far greater than typical installation depths</p>	<p>Agree with the depth of cable of 5m under the Nene is precautionary. In order to provide confidence, we would also like to know what the likely strength of magnetic field at the bed of the river is at this depth when compared to natural background levels (~50µT). Furthermore, the evidence in Chapter 9 (paragraphs 9.9.353 – 9.9.357) is poor and confusing. The statement that glass eel are unlikely to found in the Nene is flawed as glass eel are present in the lower reaches with elver migrating upstream. According to the Eel Regulations, based on historical evidence, the presence of eel</p>	<p>Matter Under Discussion - pending detailed estimation of likely strength of magnetic fields for the design specific cables being used.</p>



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>and will significantly reduce the EMF, particularly magnetic (B-field), exposures. In this way, it is anticipated that the low risk of impacts on sea trout (and other species) will be avoided and effects reduced to neutral and non-significant levels.</p> <p>Applicant Response to Consultee Position 24/03/2026</p> <p>The Applicant agrees to limit EMF levels at the riverbed to below 12 μT. The Applicant has calculated the likely worst-case voltage of the cables under the River Nene riverbed and has found this would be below the threshold. Additionally, if at the detailed design stage, the current is higher than anticipated there are design options available to achieve the agreed limit:</p> <ul style="list-style-type: none"> • Reduce cable separation distance between the cables; and/or 	<p>can only be ruled out—or considered very unlikely—when a location in the catchment is both more than 100 km from the head of tide and more than 150 m above sea level. This is not the case for the location where the cable crosses the River Nene; therefore, eel of all life stages cannot be ruled out.</p> <p>The argument in section 9.9.357 suggests that sea trout will need to pass through the cable corridor to reach their spawning grounds. Consequently, there is a potential risk that their migration could be delayed by the presence of the cable corridor. To assess this risk with greater confidence and detail, it is important to determine the likely strength of the magnetic field at the cable corridor (as a result of the cable) on the riverbed and compare it to natural background levels.</p> <p>The applicant provided some technical information in an email to the EA dated 11/02/2026. The applicant also hosted a</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<ul style="list-style-type: none"> Bury the cables deeper below the riverbed. <p>At the detailed design stage it is proposed that EMF levels will be calculated using maximum magnetic field strength for typical underground cables as reported by National Grid. These values would then be scaled to account for the worst-case current, the cable configuration and the distance between cables and receptors (in this case the riverbed).</p> <p>This commitment has been secured within the Outline Construction Environmental Management Plan [EX6/GH7.1_C] under Table 3.15.</p>	<p>meeting to discuss this issue with the EA on 19/02/2026. Feedback to the applicant as follows:</p> <p>The applicant states that the worst case magnetic field strength from the buried cables beneath the River Nene would be 14.72 μT, which they describe as “substantially lower than natural background levels.” However, this interpretation is misleading. Magnetic fields generated by the cables will not be masked by the natural geomagnetic background (approximately 50 μT); rather, they will be additional to it. Therefore, the expected magnetic field exposure in the river environment would be 14.72 μT above background levels.</p> <p>Given that Anguillid species are known to detect magnetic fields as low as 12–13 μT, there remains a precautionary concern that the applicant’s estimated worst case field strength could negatively affect</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
				<p>the migration of European eel within the River Nene. We therefore request more detailed information on the actual likely magnetic field emissions expected beneath the river for this development, including any modelling assumptions used.</p> <p>We also strongly encourage the applicant to consider design measures that would reduce the emitted magnetic field to below an acceptable threshold of 12 μT. The configuration of the cable array is particularly important in this regard, as closely paired or appropriately arranged cables can partially cancel out each other's magnetic fields.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We look forward to receiving further clarification on this matter by Deadline 6.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
EB-08	Avoidance of coarse fish spawning period where open-cut trenching is used at watercourse crossing points	EA raised in their Relevant Representation that the period of avoidance for open-cut trenching at watercourse crossing points should be extended to June 16 th (avoidance period was previously October – May inclusive) to protect spawning coarse fish which may be present.	<p>This comment was discussed in a meeting between the Applicant and the Environment Agency on 01/10/2025.</p> <p>The Applicant notes this comment, and, as agreed, will seek to either avoid open-cut trenching works on the affected watercourses during the coarse fish spawning period (15th March - 15th June inclusive), or otherwise pre-commencement survey work will be undertaken to establish whether the avoidance period is required for each relevant watercourse crossing point. This may comprise habitat suitability assessments to establish whether suitable spawning habitat is present at each crossing point, or fish surveys to determine whether fish which may spawn in the watercourse are present/likely absent.</p> <p>The Environment Agency confirmed during the meeting that features characterised as wet ditches can be scoped out of this timing restriction, as this only</p>	Noted and agree.	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>applies to permanently wet watercourses with a flow.</p> <p>The cable installation methodology to be used at each of the affected crossing points, as well as any required mitigation measures for spawning/migrating fish, would be discussed and agreed with the EA/relevant consenting body post-DCO consent, prior to work commencing. An updated version of the Outline Ecological Protection and Mitigation Strategy CONFIDENTIAL [EX6/GH7.5_D] has been submitted at Deadline 1 which outlines this approach.</p>		



3.3 Hydrology, Flood Risk and Drainage

3.3.1 Below are the matters that have been identified through consultation, grouped into Matters Agreed and Matters Under Discussion.

Table 3.2: Hydrology, Flood Risk and Drainage

	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
HYD-01	Water Framework Directive (WFD)	The Environment Agency required confirmation that the scope and methodology of the Water Framework Directive (WFD) assessment were appropriate, including consideration of hydromorphology, water quality and pollution risk, in line with WFD objectives.	<p>The WFD Assessment [REP5-081] sets out an appraisal of potential impacts on relevant waterbodies. It follows a source-pathway-receptor approach and confirms that the Proposed Development will not lead to deterioration in status or prevent achievement of Good Ecological Potential. The assessment draws on baseline data also presented in the Water Resources Assessment [REP5-081], Environmental Statement Chapter 10 Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C], and ES Appendix 10.1 Flood Risk Assessment and Drainage Strategy Report [REP5-021].</p> <p>Applicant Response to Consultee Position</p>	<p>We are satisfied with this assessment.</p> <p>Please note, the mitigation in the WFD Assessment is not identical to that captured in the OCEMP, for instance, Table 8 of the WFD Assessment in the Construction section does not mention drip trays as a way for managed fuel/oil (as an example). Please align for consistency.</p> <p>Firewater risk is not identified in the operation section of Table 8; it should be for consistency and to ensure that WFD bodies are assessed for all impacts. However, providing our other advice is followed we don't have concerns that firewater will be able to enter any WFD bodies.</p> <p>We await to see updated WFD Assessment and OCEMP when submitted.</p>	Agreed.



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>The Applicant notes the EA's comments and will seek to review the consistency of mitigation. A review and update of the management plans and commitments register will be carried out by Deadline 6 to ensure any amendments throughout the examination process are captured and consistent. This will include aligning the mitigation schedule in the WFD Assessment with the OCEMP (for example construction fuel and oil management controls) and updating the operational mitigation schedule to explicitly include firewater as a potential pathway, reflecting the embedded containment and testing approach.</p> <p>Applicant Response to Consultee Position 24/02/2026</p> <p>The mitigation schedule in the WFD Assessment [REP5-081] has been updated with the</p>	<p>Consultee Position following Applicant Response 17/03/2026</p> <p>This matter is resolved as the WFD Assessment has been updated with the relevant information as requested.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>OCEMP [EX6/GH7.1_C] for submission at Deadline 5.</p>		
HYD-02	Design	<p>The Environment Agency required that the design incorporate appropriate embedded measures to prevent contamination of surface water features, particularly from the BESS, substation and other infrastructure, consistent with the scope of ES Chapter 10.</p>	<p>Embedded pollution prevention measures include bunded drainage systems, self-actuating shut-off valves for the BESS, and firewater containment. These are detailed in Environmental Statement Chapter 10 Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C], ES Appendix 10.1 Flood Risk Assessment and Drainage Strategy Report [REP5-021] and Annex J [REP5-031] and are secured through the Outline Construction Environmental Management Plan [EX6/GH7.1_C] and DCO Requirement 11 in the Draft Development Consent Order [EX6/GH3.1_E]. Groundwater contamination risk is considered separately under ES Chapter 11: Ground Conditions [REP1-025].</p>	<p>Embedded pollution prevention measures regarding bunded drainage and measures throughout construction are suitable for this design stage of the project. We wish to be consulted on the detailed design measures secured within the CEMP, OEMP and DEMP. Please include the Environment Agency as a named consultee in DCO Requirements 13 (Construction environmental management plan), 14 (Operational environmental management plan) and 21 (Decommissioning and restoration).</p> <p>Regarding BESS drainage and firewater containment, there are a few areas where will still require further details to be included in the relevant documents. Further comments on the OBSSMP are below in reference to HYD-09.</p> <p>We await to see updated draft DCO when submitted.</p>	Agreed.



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Applicant Response to Consultee Position</p> <p>The Applicant will incorporate the proposed amendment into the next iteration of the Draft DCO, adding the Environment Agency as a named consultee in Requirements 13 (Construction Environmental Management Plan), 14 (Operational Environmental Management Plan), and 21 (Decommissioning and Restoration).</p> <p>Applicant Response to Consultee Position 24/02/2026</p> <p>The draft DCO [EX6/GH3.1_E] has been updated for submission at Deadline 5 to include the Environment Agency as a named consultee for the surface and foul water drainage.</p>	<p>Consultee Position following Applicant's Response 17/03/2026</p> <p>The matter is resolved as the Draft DCO has been updated with the relevant wording as requested.</p>	
HYD-03	Surface Water Flooding	The Applicant was required to assess the risk of surface water flooding using current Environment Agency	Surface water flood risk was assessed using the NaFRA2 dataset (January 2025) and Risk of Flooding from Surface Water (RoFSW) mapping. This	We would defer to the respective LLFA with regards to surface water drainage, but the datasets used for the baseline assessment are	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		datasets and an approach aligned with national guidance.	approach is consistent with EA guidance and is documented in in Environmental Statement Chapter 10 Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] and the ES Appendix 10.1 Flood Risk Assessment and Drainage Strategy Report [REP5-021] . The modelling confirms the site is at low risk from surface water flooding.	considered reasonable and up to date.	
HYD-04	Drainage Strategy	The Environment Agency required the drainage strategy to apply appropriate climate change uplifts in accordance with the latest allowances to demonstrate resilience of SuDS and flood mitigation.	The Environment Agency required the drainage strategy to apply appropriate climate change uplifts in accordance with the latest EA guidance to demonstrate resilience of SuDS and flood mitigation. The drainage design uses the EA upper peak rainfall allowance for the Anglian Nene catchment, applying a 40% uplift to peak rainfall intensity for the critical events, as set out in ES Chapter 10 Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] and the ES Appendix 10.1 Flood Risk Assessment and Drainage	We are satisfied that by using SuDS surface runoff can be treated sufficiently and can be used to manage surface water. However, please include the Environment Agency as a named consultee in DCO Requirement 11 for the surface and foul water drainage. EA Relevant Reps issue EA/WQ/04 is not included in the SoCG and is unresolved – please include this as an issue in this document. Our comments on foul drainage are as follows: Whilst we appreciate the updates to section 5.3.9 of the FRADS (REP5-021) and in Table 3.4 of the OOEMP	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Strategy Report [REP5-021]. This provides the basis for the site-specific drainage design in the supporting annexes.</p> <p>Applicant Response to Consultee Position</p> <p>Points relating to EA/WQ/04 and EA/WQ/07 have been included in the SOCG under matters ‘HYD-16 and HYD-17’.</p> <p>The Applicant will incorporate the proposed amendment into the next iteration of the Draft DCO, adding the Environment Agency as a named consultee Requirement 11 for the surface and foul water drainage.</p> <p>Comments on HYD-16 and HYD-17 are now below.</p> <p>Applicant Response to Consultee Position 24/02/2026</p> <p>The draft DCO [EX6/GH3.1_E] has been updated for submission at Deadline 5 to</p>	<p>(EX6/GH7.2_D), there have been no updates to Table 3.4 of the OCEMP (EX6/GH7.1_C), and there is an absence of any reference to foul water in the Decommissioning Statement (EX6/GH7.3_C). There should be consistent details provided in all three phases of the project, so we request that the OCEMP and Decommissioning Statement are updated.</p> <p>Regarding EA/WQ/07, we don’t believe this has been resolved as despite what was written in the Responses to Deadline 1 Submissions (REP2-050), Chapter 10 has not yet been updated to clarify that filtering effect is only for sediment, and not for hydrocarbons and heavy metals. Furthermore, although you have said that protections against other pollutants are secured in the OCEMP, whilst we acknowledge that there is good oil and fuel management in the OCEMP (EX6/GH7.1_C), it but doesn’t explicitly mention heavy metals. Chapter 10 and the OCEMP should be updated before EA/WQ/07 can be resolved.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			include the Environment Agency as a named consultee for the surface and foul water drainage.	<p>We await to see updated draft DCO when submitted.</p> <p>Consultee Position following Applicant's Response 17/03/2026</p> <p>The matter is resolved as the Draft DCO has been updated with the relevant wording as requested.</p>	
HYD-05	Surface Water Management	The Environment Agency required the Applicant to identify and characterise all relevant on-site and off-site watercourses and ditches to inform the FRA and surface water management.	All relevant watercourses and field drains were identified using a combination of site walkovers, LiDAR, and topographic survey data. These are described in Environmental Statement Chapter 10 Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] and documented across the ES Appendix 10.1 to 10.8 [REP5-021, REP-023 and REP-025, APP-100, APP-101, APP-102, REP5-027, APP-104, APP-105]. This information informed the surface water drainage strategy and identification of flow paths.	Noted as complete	Agreed
HYD-06	Fluvial Flood Modelling	Whether the baseline hydraulic modelling for Grendon Brook and	Fluvial flood risk to the BESS has been assessed using the updated Environment Agency	We are happy with the modelling approach undertaken for the Grendon Brook. The Applicant has	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>the River Nene, including use of 1D ISIS models and application of +45% climate change allowance, is appropriate and consistent with EA modelling standards.</p>	<p>Middle Nene and Grendon Brook Flood Modeller models together with a 2D TUFLOW direct rainfall model of the Field Drain. The Hydraulic Modelling Report submitted at Deadline 2 sets out the model geometry, hydrology, climate change allowances and sensitivity testing. The Middle Nene and Grendon Brook models simulate the 1 percent and 0.1 percent AEP events with +13 percent and +36 percent uplifts, using updated LiDAR and targeted checks on roughness, flows and bed levels. The Field Drain model applies ReFH2 rainfall with 25 percent and 35 percent uplifts paired to the river flow allowances. Results confirm the BESS remains flood free from the River Nene, that only narrow low lying margins adjacent to Grendon Brook flood in higher order events, and that fluvial risk from the Field Drain is negligible. A merged depth grid identifies the worst case across all models and confirms the BESS platform</p>	<p>provided additional detail with regards to some of the assumptions made in the modelling and has undertaken associated sensitivity testing.</p> <p>With regards to the River Nene modelling, the Applicant has undertaken additional sensitivity testing; however, the Applicant should present the mapped outputs of the sensitivity testing for the middle River Nene in relation to the Battery Energy Storage System (BESS) within the Flood Risk Assessment. This is important because the Applicant's updated hydraulic modelling for the middle River Nene shows a reduction in flood extent when compared to the existing Environment Agency hydraulic model outputs. We need to be confident that the BESS is not at flood risk from the River Nene during the design flood event.</p> <p>With regards to climate change allowances, the higher central (+13%) and upper (+36%) climate change scenarios for the 2080s epoch for the Nene management catchment have been used. These</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>meets the less than one metre flood depth resilience criterion in ES Appendix 10.11 BESS FRA [REP5-031] with no increase in flood risk elsewhere.</p> <p>Applicant Response to Consultee Position</p> <p>The Applicant will provide the mapped outputs from the Middle River Nene sensitivity testing at the BESS location within the Flood Risk Assessment material, to evidence the modelled flood extents for the design events and confirm the BESS is not at fluvial flood risk from the River Nene. This will be issued by Deadline 5 and will be presented alongside the existing BESS assessment in ES Appendix 10.11 BESS FRA [REP5-031].</p> <p>Applicant Response to Consultee Position 24/02/2026</p>	<p>are the correct fluvial climate change allowances and are compliant with policy.</p> <p>The applicant's response seems reasonable in principle; however, we await the mapped outputs from the sensitivity testing for the River Nene before this matter can be agreed.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>Sensitivity testing model outputs for the Middle Nene are now included in Green Hill Solar Farm Hydraulic Modelling Technical Note BESS (February 2026) (REP5-092). The sensitivity testing outputs for the Middle Nene where roughness is increased by 20% (Sensitivity Test 1 – ST1) shows that the BESS area is not affected by flooding. This is reasonable and no further action is considered necessary. This matter is resolved.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			The updated Hydraulic Modelling Note has been submitted at Deadline 5.		
HYD-07	Rainfall Hyetographs	Whether rainfall hyetograph data and associated ReFH2 calculations used in the 2D surface water modelling are accurate and aligned with EA requirements.	Surface water modelling of the Field Drain was undertaken in TUFLOW using direct rainfall derived from ReFH2. The Hydraulic Modelling Report submitted at Deadline 2 sets out the catchment descriptors, storm profiles and hyetographs used for the 3.3 percent, 1 percent and 0.1 percent AEP events, with 25 percent and 35 percent rainfall uplifts applied in line with current Environment Agency allowances. Hydrological checks and sensitivity testing were completed for rainfall rate, downstream boundary and roughness. The approach is consistent with ReFH2 guidance and appropriate for a small responsive catchment and provides a robust basis for assessing surface water exceedance alongside the wider FRA in ES Appendix 10.1 [REP5-021] and the BESS	<p>The use of the Revitalised Flood Hydrograph (ReFH2) approach to derive rainfall hydrographs and account for infiltration losses through the application of net rainfall is considered reasonable. The applicant should confirm that the Flood Estimation Handbook (FEH) depth duration frequency (DDF) 22 rainfall dataset has been used in their assessment as it is not clear from the updated hydraulic modelling technical note document reference 313532-REP-001 Issue 2 (document library reference REP2-052) that this is the case.</p> <p>The applicant's response is reasonable. Use of the FEH DDF22 rainfall data is up to date. This matter is agreed.</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>assessment in ES Appendix 10.11 [REP5-031].</p> <p>Applicant Response to Consultee Position</p> <p>The Applicant will confirm within the hydraulic modelling technical note that the FEH DDF22 rainfall dataset has been used to derive the ReFH2 rainfall depths and hyetographs for the Field Drain direct rainfall model. If any discrepancy is identified, the Applicant will update the hyetograph inputs and reissue the supporting calculations and outputs by Deadline 5.</p>		
HYD-08	Residual Risk and Emergency Response	Adequacy of the Applicant's assessment of residual flood risk and emergency response planning, particularly in relation to overtopping events or blocked drainage scenarios.	Residual flood risk has been assessed using the updated Middle Nene, Grendon Brook and Field Drain models documented in the Hydraulic Modelling Report [REP2-052] submitted at Deadline 2, together with the BESS assessment in ES Appendix 10.11 [REP5-031] and the wider FRA in ES Appendix	<p>Applicant Response to Consultee Position 24/02/2026</p> <p>The updated Hydraulic Modelling Note to be submitted at Deadline 5.</p> <p>Please see our comments raised in response to HYD-06 regarding the sensitivity runs for the River Nene. Additionally, please clarify why compensatory storage is not required if the BESS platforms encroach into</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>10.1 [REP5-021]. Sensitivity testing has been undertaken to represent overtopping, blockage and reduced capacity scenarios, including variations in flows, roughness, bed levels, rainfall rate, downstream boundary conditions and culvert dimensions. The merged depth grid confirms the BESS platform remains within the less than one metre flood depth resilience threshold under all sensitivity scenarios. Operational resilience, emergency access, drainage shut-off controls and response procedures are secured through the OCEMP [EX6/GH7.1_C] and OEMP [EX6/GH7.2_D]. Residual risks are therefore well understood and can be safely managed through embedded design and operational measures.</p> <p>Applicant Response to Consultee Position</p> <p>The Applicant will address the River Nene sensitivity outputs</p>	<p>areas of flood risk as highlighted in table 2 page 14 of Appendix 10.11: Flood Risk Assessment and Drainage Strategy Annex J: Green Hill BESS</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>Note that the updated FRA confirms that the BESS does not result in a loss of floodplain storage. The roughness sensitivity testing for the Middle Nene shows that the BESS is not affected by flooding. This seems reasonable and this matter is agreed.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>as set out under HYD-06. The Environment Agency's published flood extents have been superseded by site-specific hydraulic modelling, which confirms that there is no fluvial flooding from the River Nene or Grendon Brook within areas of built development at the BESS. The shallow flooding identified in Appendix 10.11 relates to pluvial exceedance from direct rainfall and local drainage pathways, not displacement of fluvial floodwater, and is managed through the drainage design which captures, conveys and contains runoff within the BESS drainage catchment, with controlled discharge and shut-off capability in the event of an incident.</p> <p>No compensatory flood storage is therefore required, as there is no loss of fluvial floodplain storage or impediment to flood flows. This resolves the concern, subject to provision of</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>the River Nene sensitivity mapping at Deadline.</p> <p>Applicant Response to Consultee Position 24/02/2026</p> <p>The updated Hydraulic Modelling Note has been submitted at Deadline 5.</p>		
HYD-09	Drainage Strategy and BESS Containment	Whether the drainage design adequately protects BESS infrastructure from flooding and prevents discharge of contaminants.	<p>The BESS will use an impermeable and isolated drainage system that provides a sealed containment arrangement during an incident, consistent with the commitments in the BESS FRA in ES Appendix 10.11 [REP5-031], the wider FRA in ES Appendix 10.1 [REP5-021] and the Outline Battery Storage Safety Management Plan [REP5-075]. The solution will follow the performance-based requirements set out in the ES and OBSSMP, which focus on impermeability, isolation of the BESS area during a fire event, and controlled release after testing. The final approach will be confirmed at detailed design,</p>	<p>There are still uncertainties with regards to BESS drainage and firewater containment. This is partly because although some information is detailed in some documents, it is not specific across all relevant documents.</p> <ul style="list-style-type: none"> • <u>Impermeable lining</u> - For example, impermeable lining is mentioned many times in the FRADS Annex J: Green Hill BESS (REP1-058) in section 3.5.3, 3.9.2 and 4.1.3. It is also included in the updated Chapter 10 in section 10.9.3 (REP1-024) and Table 3.4 of the OOEMP (REP1-134). However, there is no reference to impermeable lining in the FRADS (REP1-054) or in the OBSSMP (REP1-144). The FRADS and OBSSMP 	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>but will deliver an impermeable lined system with isolation valves and no routine connection to the wider drainage network. ES Chapter 22 Ground Conditions and Contamination [REP1-025] confirms low sensitivity receptors. On this basis, the drainage strategy will protect the BESS infrastructure from flooding and will prevent the discharge of contaminants to surface or groundwater. Together, these confirm the risk of discharge to surface or groundwater is negligible.</p> <p>Applicants Response to Consultee Position</p> <p>The Applicant confirms that the BESS drainage strategy secures containment, isolation and prevention of contaminant discharge, and that the Environment Agency's concern relates to consistency and specificity across the document suite rather than the adequacy</p>	<p>should be updated for consistency. Issues EA/WQ/01 and EA/WQ/08 raised in EA Relevant Representation are still not resolved.</p> <ul style="list-style-type: none"> • <u>Automatic valves</u> – As we commented back in our Response to first written questions (ExQ1) (REP1-185), we requested that more information should be added to the OBSSMP and the FRADS to secure a manual closing options and the method of how the valve would be triggered to close. We welcome the Applicant Responses to Deadline 1 Submissions (REP2-050) for Q8.0.9, but that information must be secured in the OBSSMP. If it is not updated, we will be raising this post-consent when we are consulted on the BSSMP. Therefore, as above, issues EA/WQ/01 and EA/WQ/08 in EA Relevant Representations are still not resolved. <p>Additionally, although FRADS Annex J: Green Hill BESS (REP1-058) has a maintenance section in Annex F,</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>of the underlying approach. The Applicant is not committing to detailed design methods at this stage, but will strengthen and align the principles that will govern detailed design and operation.</p> <p>By Deadline 5, the Applicant will update the Flood Risk Assessment and Drainage Strategy, the Outline Battery Storage Safety Management Plan and the relevant operational management text so they consistently secure: impermeable lining of the BESS drainage system; incident isolation from the wider drainage network; containment of firewater for sampling and analysis prior to any controlled release or off-site removal; and shut-off valve operation, including the trigger mechanism, manual closure or override, and an inspection, testing and maintenance regime. The updates will also explicitly secure post-incident recovery principles, including</p>	<p>there is no mention of any regular maintenance or monitoring of the shut-off valve. It should be tested at a suitable frequency to ensure it remains in good working order so that in the event of a fire it could close quickly when required. The Applicant should update the OBSSMP or FRADS to reflect this. This was previously requested in EA/WQ/09 and therefore this is not resolved.</p> <ul style="list-style-type: none"> • <u>Gravel cleaning/removal</u> – EA Relevant Representations (RR-1224) made clear that gravel substrate can get contaminated by firewater, and after a fire event could cause secondary pollution if any contaminants are re-mobilised by surface runoff. We welcome the Applicant Responses to Relevant Representations (REP1-161) for EA009 which says that there will be inspection, maintenance and replacement of contaminated subbase, but that information must be secured in the OBSSMP and OOEMP to ensure that any post-incident recovery is 	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>inspection of the drainage system and gravel subbase (where used) and, where contamination is identified, cleaning and or removal and replacement prior to recommencing operation.</p> <p>The Applicant also confirms that reuse of firefighting water from the drainage system would be exceptional, would be operator-led with appropriate testing and specialist advice, and is not an assumed firefighting tactic. Northamptonshire Fire and Rescue Service (NFRS) would be consulted as part of this onsite operational decision-making process; there must be complete confidence that there is no water contamination because this would be highly likely to damage NFRS critical firefighting equipment. Operation would not restart following an incident until the drainage system has been fully remediated and is confirmed to be functioning as intended in accordance with the DCO</p>	<p>secured. This was previously requested in EA/WQ/01, EA/WQ/03, and EA/WQ/09 but these updates to OBSSMP or OOEMP have not yet happened and therefore this is not resolved.</p> <p>In the meeting on 1st October, the Applicant verbally agreed that a detailed management plan would confirm cleaning process or removal of gravel, and that the management plan would include general maintenance and cleaning of BESS drainage, however we have not yet seen this in the documents submitted at this deadline.</p> <ul style="list-style-type: none"> • Testing of firewater and battery removal during operation also need resolving but these issues haven't been raised yet (further information provided to the Applicant on 16/12/2025) <p>We understand that the Flood Risk Assessment and Drainage Strategy, and the Outline Battery Storage Safety Management Plan will be</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>requirements. These updates will be provided by Deadline 5.</p> <p>Applicant Response to Consultee Position 24/02/2026</p> <p>The updated Flood Risk Assessment and Drainage Strategy [REP5-027, REP5-029 and REP5-031], and the Outline Battery Storage Safety [REP5-075] Management Plan have been updated for submission at Deadline 5. The applicant confirms that although we cannot commit to a design at this stage we can agree to binding principals that will be carried through to detailed design and subject to relevant consultee approvals including the Environment Agency.</p>	<p>updated at the next deadline and await to review those documents.</p> <p>We note that in the meeting on the 19th February, the Applicant stated that they were not committing to design details, but seeking to agree design principles. This is acknowledged, but the documents should still assess worst-case scenarios.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>Additional information added to Flood Risk and Drainage Strategy (5.3.9 to 5.3.13), and oBSMP (5.3.2 & 5.5.5 to 5.5.7) which resolves these queries. This matter is now agreed.</p>	
HYD-10	Construction Phase Flood Risk	Whether construction phase flood risks have been adequately assessed and mitigated, including surface water and fluvial risk to	Construction phase flood risk has been assessed in the FRA in ES Appendix 10.1 [REP5-021] and ES Chapter 10 Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] , supported by the findings of the	Noted.	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		compounds and laydown areas.	<p>Hydraulic Modelling Report submitted at Deadline 2. The identified construction compounds and laydown areas avoid Flood Zone 3 where practicable and are located outside the main areas of fluvial and surface water hazard. Where temporary works fall within areas of surface water accumulation, risk will be managed through good practice measures secured in the OCEMP [EX6/GH7.1_C], including temporary drainage control, exceedance routing, material storage protocols and contingency arrangements for high flows. ES Chapter 22 Ground Conditions and Contamination [REP1-025] confirms low sensitivity receptors and that pollution risks are controllable with standard site management. On this basis, construction phase flood risks have been adequately assessed and can be safely managed.</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
HYD-11	Watercourse Crossing Design and Permitting	Whether the approach to watercourse crossing design and environmental permitting is sufficiently developed and in line with EA expectations.	<p>All permanent and temporary watercourse crossings have been assessed, with HDD adopted where feasible to avoid instream works. Crossing locations are selected to minimise hydraulic or ecological impact, with entry/exit points located outside the floodplain. All works will be subject to Environmental Permitting Regulations and will require Flood Risk Activity Permits where relevant. Engagement with the Environment Agency on detailed design and permitting is ongoing. The design approach is consistent with CIRIA C793 and EA good practice.</p> <p>Applicant Response to Consultee Position</p> <p>Appendix 10.2 [REP5-023 and REP5-025] has been updated to acknowledge the Wilby Flood Storage Area and measures to mitigate impacts to the FSA.</p>	<p>The approach to watercourse crossings is generally acceptable. However, the submitted Crossing Schedule (document ref: EX6/GH7.18_B) shows Main River crossings HV_SP8561_004, GHF_SP8959_002, HV_SP8859_001 using open cut construction. We would expect all Main River crossings to employ HHD methodology.</p> <p>As discussed at the meeting on 19 Feb, applicant to look into these crossing points and amend Crossing Schedule as necessary.</p> <p>Disapplication</p> <p>We confirm that the Applicant's request to disapply Flood Risk Activity Permits (FRAP) under the Environmental Permitting (England and Wales) Regulations 2016 has been deemed appropriate for the proposed development. The standard Protective Provisions in favour of the Environment Agency must be included in the DCO.</p> <p>The following conditions must also be met by the Applicant for the disapplication of FRAP to be</p>	Matter Under Discussion



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Applicant Response to Consultee Position 24/03/2026</p> <p>The Applicant has updated the Crossing Schedule [EX6/GH7.18_B] to include the Wilby Flood Storage Area. The Outline Construction Environmental Management Plan [EX6/GH7.1_C] has also been updated to include a commitment to undertake a pre-commencement survey and to engage with the Environment Agency regarding the proposed crossing in this area.</p> <p>The draft DCO (Revision E) [EX6/GH3.1_E] has been updated at Deadline 6 to include the Environment Agency standard form of protective provisions.</p>	<p>acceptable to the Environment Agency:</p> <p>All Main River crossings must use Horizontal Directional Drilling (HDD) methodology.</p> <p>The Applicant doesn't seem to have made reference to the Wilby Flood Storage Area at NGR: SP8610865442. This needs to be acknowledged in relevant documents, including the Crossings Register.</p> <p>Ideally, we do not want the cable under the control structure / reservoir wall, we would also prefer if it was further upstream in the storage area, in the event we wished to do works to the reservoir embankment. The Applicant should take heed of this comment.</p> <p>We will require details that the Applicant's works do not impact Environment Agency assets.</p> <p>NB: HDD launch and exit pits should preferably be located outside the floodplain, or at least sufficiently distant from the watercourse so that</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
				<p>any future lateral movement (geomorphic change) of the watercourse does not intercept and expose cable infrastructure.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>The above comments regarding disapplication remain valid.</p> <p>We note the Protected Provisions in the draft DCO submitted at Deadline 5 have been amended. Our standard Protective Provisions have been robustly reviewed and they are fit for purpose. We will only accept amendments to them when it is necessary <u>and</u> appropriate. In the case of this project, amendments to our standard Protective Provisions are not required. We request that our standard Protective Provisions are included in the DCO.</p> <p>We provided further confirmation on our position regarding the use of our standard Protective Provisions in an email to the applicant's legal team on 17 March 2026.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
				<p>Regarding Wilby FSA reference added to Appendix 10.2, this is noted and an important addition to that document. Discussions are ongoing with the Applicant, and the EA are investigating available asset details.</p>	
HYD-12	Floodplain Storage and Compensation	Whether the potential loss of functional floodplain has been appropriately assessed and level-for-level compensation secured if necessary.	<p>Encroachment into Flood Zone 3 has been minimised through iterative design. Any unavoidable encroachment is limited in area and depth and has been assessed for impact on floodplain storage using the hydraulic model. These are reported in ES Appendix 10.1 Flood Risk Assessment and Drainage Strategy Report [REP5-021]. Where applicable, level-for-level compensatory storage will be provided in hydraulically connected areas, secured through detailed design. The development will not reduce floodplain function or increase flood risk elsewhere.</p> <p>Applicant Response to Consultee Position</p>	<p>Noted. Applicant to submit further detail confirming extent of floodplain compensation required, and how this can be delivered.</p> <p>The applicant should submit calculations to support the conclusion that the scheme results in no loss of floodplain, and no compensatory flood storage required.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We are satisfied with the submitted calculations with regards to floodplain volume impacts, and the conclusions that flood plain compensation is not required. This matter is now agreed.</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Encroachment into Flood Zone 3 has been assessed and is limited to peripheral areas of panelled development at Green Hill E and Green Hill F only, with no built form or ground raising within the functional floodplain. At these locations, potential floodplain storage displacement has been conservatively quantified using the cross sectional area of panel support piles, assumed pile density and worst case flood depth. This demonstrates a very small displaced volume which, when distributed across the receiving floodplain, results in a sub millimetre theoretical change in flood depth and no measurable effect on flood levels, extents or flow routes. This assessment is set out within Environmental Statement Appendix 10.8 Flood Risk Assessment and Drainage Strategy Annex G Green Hill E [APP-105] and Environmental Statement Appendix 10.9 Flood Risk Assessment and Drainage</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Strategy Annex H Green Hill F [APP-106].</p> <p>On this basis, level for level floodplain compensation is not considered necessary or proportionate, as there is no material loss of functional floodplain storage and no increase in flood risk elsewhere. This resolves the concern.</p> <p>Applicant Response to Consultee Position 24/02/2026</p> <p>Floodplain storage displacement calculations have already been undertaken and reported within the submitted FRA annexes, confirming that the Scheme results in no material loss of floodplain storage and that compensatory storage is not required.</p> <p>For Green Hill E, a conservative assessment of PV support pile displacement has been completed (cross-sectional area 28.65 cm², assumed 2,200 piles</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>within Flood Zones 2 and 3, worst-case flood depth 1.2 m). This results in a total displaced volume of approximately 8 m³. When distributed across the defined floodplain area of circa 27,000 m², the theoretical increase in flood depth is approximately 0.296 mm, which is negligible. These calculations are presented in FRA Annex G: Green Hill E [APP-392], Section 2.1 (paragraphs 2.1.5 to 2.1.7).</p> <p>For Green Hill F, the same conservative displacement volume (8 m³) has been tested against the defined upstream floodplain extents for Fields FF3 and FF32. When spread across the assessed floodplain areas (approximately 318,482.07 m² and 20,483.7 m² respectively), the theoretical increases in flood depth are approximately 0.000025 mm and 0.39 mm. These calculations are set out in FRA Annex H: Green Hill F [APP-393], Section 2.1 (paragraphs 2.1.6 to 2.1.9).</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>On this basis, the submitted calculations demonstrate that the Scheme does not give rise to any material loss of floodplain storage and that compensatory flood storage is not required.</p>		
HYD-13	Pollution Control in Sensitive Catchments	Whether pollution control measures are adequate in locations designated as Drinking Water Groundwater Safeguard Zones.	<p>The layout avoids locating infiltration SuDS within Drinking Water Safeguard Zones. In these areas, surface water will be collected via lined drainage systems and discharged only where appropriate risk assessments support this. Infrastructure such as the BESS and substation are located on impermeable surfacing within contained areas. No discharges to ground are proposed in sensitive zones. These measures are documented in ES Appendix 10.1 Flood Risk Assessment and Drainage Strategy Report [REP5-021] and confirmed in ES Chapter 22 Ground Conditions and Contamination [REP1-025] which reports no contaminant</p>	<p>The whole site is underlain by various Drinking Water Surface Water Safeguard Zones, and the southern extent is underlain by a Drinking Water Surface Water Protected Area, but none of the site is underlain by a Drinking Water Groundwater Safeguard Zone. Please amend the comments on the left as appropriate. We will provide comment in the next iteration of the draft SoCG.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>The applicant's response remains written in a way which does not acknowledge the whole site is underlain by Drinking Water Surface Water Safeguard Zones, but their commitment to avoid infiltration SuDS in these areas is acceptable</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>linkages or risks to groundwater quality.</p> <p>Applicant Response to Consultee Position</p> <p>The layout avoids locating infiltration SuDS within Drinking Water Surface Water Safeguard Zones and within the Drinking Water Surface Water Protected Area. In these areas, surface water will be collected via lined drainage systems and discharged only where appropriate risk assessments support this. Infrastructure such as the BESS and substation are located on impermeable surfacing within contained areas. No discharges to ground are proposed in these sensitive surface water designations. These measures are documented in ES Appendix 10.1 Flood Risk Assessment and Drainage Strategy Report [REP5-021] and confirmed in ES Chapter 22 Ground Conditions and Contamination</p>	<p>regardless of how it is worded. The other measures outlined also appear to be acceptable.</p> <p>As noted in HYD-09, the applicant must consider storage and disposal routes for contained potentially contaminated firewater, including the timescales involved and implications for continued safe site operation. Due to Drinking Water Surface Water Safeguard Zones, we might not agree for this to be discharged to ground.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>[REP1-025] which reports no contaminant linkages or risks to groundwater quality.</p>		
HYD-14	Foul Water Drainage	Whether a foul water disposal strategy should be provided in more detail.	<p>As confirmed in ES Chapter 10: Hydrology, Flood Risk and Drainage Revision A [EX6/GH6.2.10_C] and the ES Appendix 10.1 FRADS [REP5-021], there is no foul drainage network associated with the Scheme and no discharges of foul or polluted material to watercourses will occur under any circumstances.</p> <p>Welfare facilities at substations will be served by sealed septic tanks or self-contained units, to be emptied as required by tanker using a licensed waste carrier. This approach is embedded in the submitted strategy and consistent across all sites, as confirmed in the FRADS Annexes A–J [APP-098 to APP-108]. Whilst detailed sizing and emptying frequency of septic tanks will be confirmed at the design stage, the principle of sealed containment with tanker</p>	<p>Whilst we appreciate the updates to section 5.3.9 of the FRADS (REP5-021) and in Table 3.4 of the OOEMP (EX6/GH7.2_D), there have been no updates to Table 3.4 of the OCEMP (EX6/GH7.1_C), and there is an absence of any reference to foul water in the Decommissioning Statement (EX6/GH7.3_C). There should be consistent details provided in all three phases of the project, so we request that the OCEMP and Decommissioning Statement are updated.</p> <p>As discussed in the meeting on the 19th February, the use of sealed welfare vehicles is agreed in principal but we await to see updated documents at the next Deadline.</p> <p>Consultee Position following Applicant Response 17/03/2026</p>	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>removal is fixed. The draft DCO does not seek any right to connect to water company foul networks. Where discharge permits are required for temporary facilities, these will be obtained from the Environment Agency at the relevant stage. Wastewater removed by tanker will be managed in accordance with the waste management procedures set out in the OCEMP Revision B [EX6/GH7.1_C], with disposal through licensed carriers to appropriate receiving facilities.</p> <p>Applicant Response to Consultee Position</p> <p>The OCEMP [EX6/GH7.1_C] and ODS [EX6/GH7.3_C] have been updated at Deadline 5 to clarify these points.</p>	<p>The updated comments on foul water in the OCEMP and ODS are satisfactory. EA/WQ/04 is resolved.</p>	
HYD-15	Risk to Controlled Waters	<u>Whether</u> vegetation in solar panel areas will capture and take up or filter contaminants including	The Applicant notes the comments. The discussion in the ES Chapter 10: Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C]	Chapter 10 has not yet been updated to clarify that filtering effect is only for sediment, and not for hydrocarbons and heavy metals. Furthermore, although you have said that	Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>hydrocarbons and heavy metals, thus reducing potential impact to groundwater receptors.</p>	<p>recognises that the risk of hydrocarbon and heavy metal contamination from solar panel areas is very low. The embedded mitigation measure of maintaining vegetated groundcover was intended to describe the management of sediment and silt in surface water runoff rather than the removal of hydrocarbons or heavy metals. Additional protection against hydrocarbons and other pollutants is secured through the measures set out in the ES Appendix 10.1 FRADS Report [REP5-021] and the OCEMP [EX6/GH7.1_C], which require the use of lined drainage, shut-off valves, and controlled discharge or tanker removal in the event of any accidental spill. These controls ensure that risks to controlled waters are avoided. The Applicant will update the text at the next iteration to clarify that vegetation provides a slowing and filtering effect for sediment and silt only. The assessments in the ES Appendix 10.1</p>	<p>protections against other pollutants are secured in the OCEMP, whilst we acknowledge that there is good oil and fuel management in the OCEMP (EX6/GH7.1_C), it but doesn't explicitly mention heavy metals. Chapter 10 and the OCEMP should be updated before EA/WQ/07 can be resolved.</p> <p>We await to see updated documents at the next Deadline.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We note that Chapter 10 does not appear to have been updated but the relevant comment of "No reliance will be placed on infiltration for the treatment of hydrocarbons or heavy metals" in Table 3.4 of the OCEMP, therefore this commitment is secured and EA/WQ/07 is resolved.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>FRADS Report Revision A [REP5-021] and supporting annexes remain valid, with no significant risk to controlled waters identified.</p> <p>Applicant Response to Consultee Position</p> <p>The Applicant will update Environmental Statement Chapter 10 Hydrology Flood Risk and Drainage [EX6/GH6.2.10_C] to clarify that vegetated groundcover is relied upon for managing runoff characteristics and sediment only, and is not relied upon as mitigation for hydrocarbons or heavy metals.</p> <p>Solar panelled areas are limited to sediment and silt mobilisation, for which maintaining vegetated groundcover is an appropriate and proportionate control.</p> <p>Additional pollution prevention and response controls for accidental contamination,</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>where relevant, are secured through the drainage strategy and construction management measures set out in Flood Risk Assessment and Drainage Strategy Report [REP5-021] and the Outline Construction Environmental Management Plan [EX6/GH7.1_C], which apply to contaminants generally.</p> <p>These clarifications have been provided for Deadline 5.</p>		



3.4 Ground Conditions and Contamination

3.4.1 Below are the matters that have been identified through consultation, grouped into Matters Agreed and Matters Under Discussion.

Table 3.3: Ground Conditions and Contamination

	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
GCC-01	Groundwater Sensitivity	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/05</p> <p>Issue:</p> <p>Sensitivity of groundwater receptors is not defined in this chapter. 8 Discussion around sensitivity of groundwater receptors is based on an unsuitable risk classification. Additional narrative / explanation:</p> <p>In 10.8.16, it states: “The sensitivity of ... groundwater receptors is Medium.” This is repeated in 10.8.42 and 10.8.55. The sensitivity of groundwater receptors (such as aquifers) is not defined in Table 10.3, so this statement is unsupported. In Chapter 22, Table 22.3, Principal aquifers are defined as High sensitivity, and principal</p>	<p>The ES Chapter 22: Ground Conditions [REP1-025] sets out the baseline geology, hydrogeology and identified receptors, including superficial deposits such as alluvium and head deposits, Source Protection Zones and the potential for shallow groundwater emergence. These are addressed through the Preliminary Risk Assessments and managed by commitments in the OCEMP Revision A [EX6/GH7.1_C]. Any potential sources from the BESS or substations are already mitigated in ES Chapter 10: Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] through the embedded drainage design, which includes lined systems with shut-off valves and storage sized for 1 in 100 plus climate change and fire water events. On that basis this is not a flood risk issue. It is</p>	<p>Remains under discussion. The applicant has made some updates, but we have comments on how these have been done, and other changes that should have been made due to the revisions.</p> <p>We are pleased to note that aquifers have been added to Table 10.3. However, it appears that all superficial aquifers are defined as Low sensitivity. This is not appropriate, as superficial aquifers are also designated as principal, secondary, etc. Whether an aquifer is superficial or bedrock is not itself a means of determining its sensitivity.</p> <p>Paragraph 10.6.7 (newly added) discusses the site with reference to the definitions added to Table 10.3, so will need to be updated in line with our comments above.</p>	Matter Under Discussion



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>bedrock aquifer is present directly underlying the site in some areas. Overall status of the WFD groundwater bodies covering most of the site is Good, which is defined as High sensitivity in Table 10.3.</p>	<p>explicitly covered in ES Chapter 22: Ground Conditions and Contamination [REP1-025] with drainage design controls in ES Chapter 10: Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] ensuring the source is managed.</p> <p>Applicant Response to Consultee Position</p> <p>The Applicant has reviewed and updated Chapter 10 [EX6/GH6.2.10_C] and the WFD [REP5-081] for submission at Deadline 5.</p> <p>Applicant Response to Consultee Position 24/03/2026</p> <p>The Applicant has reviewed and updated Section 10.8 of Chapter 10 [EX6/GH6.2.10_C] submission at Deadline 6 to recognise the sensitivity of groundwater receptors. Following the implementation of embedded mitigation measures no significant effects have been identified.</p>	<p>The applicant still states in 10.8.20 (which was 10.8.16): “The sensitivity of ... groundwater receptors is Medium.” This statement is not consistent with the definitions given in the updated Table 10.3. Some areas of the site are underlain by principal and unproductive aquifer, which are not defined as being medium sensitivity. Additionally, as we noted previously, WFD bodies with a Good status are defined High sensitivity and this would apply to most of the site for WFD Groundwater bodies.</p> <p>We are satisfied with the changes made to Table 22.3.</p> <p>This was not raised as a flood risk issue.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We are satisfied with many of the changes made. However, 10.8.20 has not been updated.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
				<p>The sensitivity of some groundwater receptors immediately underlying some areas of the site is high, as outlined in 10.8.2. The assessment of significance should be updated accordingly. Where relevant, any proposed mitigation should be reviewed to ensure it would be suitable for a higher significance of effects.</p>	
GCC-02	Water Receptors	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/06</p> <p>Issue: Insufficient detail about water receptors.</p> <p>Additional narrative / explanation: We would expect the applicant to define the groundwater aquifer types. The entry “water bodies of medium quality” is far too vague to be used in an assessment such as this. Principal and secondary aquifers are discussed later in this report so it would be useful to define them here. Water Framework Directive (WFD) classifications could also be in</p>	<p>Definitions of groundwater receptors, including Principal, Secondary and Unproductive Aquifers, are provided in ES Chapter 22: Ground Conditions and Contamination [REP1-025], supported by aquifer classification mapping. These receptors are assessed alongside surface water bodies with reference to Water Framework Directive classifications in the Water Framework Directive Assessment [REP5-081]. The sensitivity of these receptors has also been considered in ES Chapter 10: Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] and the ES</p>	<p>Resolved.</p> <p>We are satisfied with the changes made to Table 22.3. However, see also our comments in response to GCC-01 which remain under discussion.</p>	Matter Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>this table. While this information is in Chapter 10, it is also relevant here. The same applies to Table 22.4.</p>	<p>Appendices 10.1 to 10.11 FRADS Report Revision A [REP1-053,REP1-055,REP1-057, APP-098 to APP-108], which apply the aquifer and WFD definitions in assessing potential effects.</p> <p>The Applicant will ensure consistency between the hydrology and ground conditions chapters in the final documentation and agrees that reference to formal aquifer classifications provides clearer context than generic terms such as “water bodies of medium quality.”</p> <p>Table 22.3 of ES Chapter 22: Ground Conditions and Contamination [REP1-025] and Table 10.3 of ES Chapter 10: Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] have been updated in response to Relevant Representations made by the Environment Agency.</p>		
GCC-03	Decommissioning	<p><u>EA Relevant Representation Feedback</u></p>	<p>Potential effects during decommissioning have been considered in the ES Chapter 10:</p>	<p>Resolved. We are satisfied with mitigation outlined in the ODS. Our query</p>	<p>Matter Agreed</p>



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>EA ref: EA/WQ/10</p> <p>Issue: Only considers “or release hazardous contamination for the operational timescale of the development.” This does not appear to include decommissioning and any time thereafter.</p> <p>Additional narrative / explanation: Contamination may persist beyond the operational timescale of the development.</p>	<p>Hydrology, Flood Risk and Drainage [EX6/GH6.2.10_C] the ES Appendix 10.1 FRADS Report [REP5-021] and the ODS [EX6/GH7.3_C]. These confirm that decommissioning will follow the same embedded principles as construction, with drainage managed through appropriate SuDS measures and with no uncontrolled discharges to ground or surface waters. Any residual contamination risks persisting beyond the operational life of the Scheme will be managed through measures secured in the OCEMP [EX6/GH7.1_C], the OOEMP Revision B [EX6/GH7.2_D], and the OSMP [EX6/GH7.4_A], which require appropriate testing, handling, removal and disposal of any contaminated materials, including any SuDS or drainage components within the BESS compounds. The Applicant will also comply with any permitting requirements in consultation with the Environment Agency. This approach is consistent with the commitments set out under ‘EA-011’, which address the</p>	<p>was a minor point, relating to specific wording in Chapter 2, Table 22.4, which has not been updated.</p> <p>The Applicant Position states: “residual contamination risks persisting beyond the operational life of the Scheme will be managed through measures secured in the OCEMP [EX6/GH7.1_C], the OOEMP Revision B [EX6/GH7.2_D], and the OSMP [EX6/GH7.6_A]”. This is confusing, as none of these documents apply beyond the operational life of the scheme. We suggest this statement be reconsidered.</p> <p>Consultee Position following Applicant Response 17/03/2026</p> <p>We are satisfied that the applicant commits to the ODS including the measures required to manage residual</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>management of previously unidentified contaminants. Accordingly, the Applicant confirms that potential impacts to the water environment during decommissioning and thereafter have been assessed and are controlled through the submitted management plans and secured by the Draft DCO [EX6/GH3.1_E].</p> <p>Applicant Response to Consultee Position</p> <p>We acknowledge the mention of the OCEMP [EX6/GH7.1_C], OOEMP [EX6/GH7.2_D], and OSMP [EX6/GH7.6_A] in relation to the management of residual contamination risks beyond the operational life of the Scheme is confusing as they are not applicable to that stage of the Scheme. We confirm that the ODS [EX6/GH7.3_C] will document the measures required to manage residual contamination risks post operational life of the scheme.</p>	contamination risks post operational life of the scheme.	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
GCC-04	Unidentified contaminants	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/11</p> <p>Issue: Proposed discovery strategy has a focus on the identified sources and is not explicitly clear that it applies to the whole development. Proposed strategies in appendices are inadequate.</p> <p>Additional narrative/ explanation: In Chapter 22, Section 22.7.5, we are happy that the discovery strategy has a focus on the identified sources, but it needs to be clear it applies to the whole development. It should be added that the EA may also need to be notified about contamination if it affects receptors within our remit. The LPA may be able to assist with this latter part. The same comments apply for GH7.1 (OCEMP) Table 3.16 and GH7.3 (ODEMP) Table 3.1 [Ground Conditions row]. These should be updated accordingly. In GH7.1 (OCEMP) Table 3.4, the paragraph beginning “If any</p>	<p>The discovery strategy is to apply for the entire site. This has been clarified and set out in Table 3.16 of the OCEMP [EX6/GH7.1_C] which is secured by Schedule 2, Requirement 13 of the Draft DCO [EX6/GH3.1_E]. Notifications are to be made to the EA or relevant regulatory authorities if conditions impact receptors within their jurisdiction. Additionally, the proposed remedial measures are to remain flexible, depending on the nature and extent of the contamination identified and the conditions at hand.</p> <p>Applicant Response to Consultee Position 24/03/2026</p> <p>Updates have been made to the Outline Operational Environmental Management Plan [EX6/GH7.2_D] and Outline Decommissioning Statement [EX6/GH7.3_C] to reflect the inclusion of a discovery strategy.</p>	<p>Under discussion.</p> <p>We are satisfied with revisions made to OCEMP Table 3.16.</p> <p>The applicant has not updated the ODS as requested. We would like to see this actioned.</p> <p>Additionally, an equivalent narrative should be added to the relevant section of the OOEMP. This would apply if, for example, previously unknown contamination is identified during excavations as part of routine maintenance in an area not previously accessed.</p> <p>Consultee Position following Applicant Response</p> <p>We look forward to reviewing updated documents in due course. This matter remains under discussion until updated documents have been reviewed and agreed to.</p>	Matter Under Discussion



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>suspected contaminated material is discovered during the works” is insufficient. The procedure outlined is not acceptable and differs from the process detailed elsewhere. A detailed CEMP based on the content of this part of the OCEMP is likely to be lacking.</p> <p>Appendix 22.2 (PRA – Cable Route) Part 6 of 6, Appendix G – Hotspot Protocol:</p> <ul style="list-style-type: none"> - Contact with regulatory authorities should be raised earlier in this process and more prominent - The process does not include assessment of the lateral and vertical extent of the suspected contamination. The action “removal of the ‘hotspot’” may not be the most appropriate action in all cases - This procedure does not work for contaminated groundwater 			
GCC-05	Bedrock Limestone	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/12</p>	Applicant confirms that the mitigation measures outlined in the OCEMP [EX6/GH7.1_C] ,	Resolved. We thank the applicant for confirming.	Matter Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>Issue:</p> <p>Implication mitigation measures will only be implemented where bedrock limestone is unconfined.</p> <p>Additional narrative/ explanation:</p> <p>We agree with the overview of Blisworth Limestone Formation (BLF), and the associated assessment of risks in Section 22.8.15. It states: “In the areas where the BLF is unconfined and a slightly increased risk exists to sensitive groundwater receptors, the mitigation measures outlined within the CEMP, OEMP and DEMP will be implemented to reduce risk.” It could be interpreted that where the BLF is not unconfined, the mitigation measures will not be implemented. This would apply to the vast majority of the site, and we strongly disagree with this instruction if it is intended in this way.</p>	<p>OOEMP Revision B [EX6/GH7.2_D] and ODS [EX6/GH7.3_C] will be applied site wide. The focus was to emphasize the importance of measures, particularly in areas where the Principal Aquifer is unconfined by clay-rich superficial deposits (e.g., the Oadby Member), such as in Green Hill F, due to its increased sensitivity. While the Principal Aquifer remains a key controlled water receptor across the site, the sensitivity is lower in areas where overlying clay-rich formations are present, creating a natural barrier. Nevertheless, mitigation measures are to be implemented across the site for the protection of the Principal Aquifer.</p>		
GCC-06	Risks to Controlled Waters	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/13</p>	Risks to controlled waters are assessed in the ES Chapter 22: Ground Conditions and Contamination [REP1-025] and	Resolved. We do not agree with some of the applicant’s response,	Matter Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>Issue:</p> <p>Incorrect use of sensitivity tables. Potentially significant effect concluded to be “not significant”.</p> <p>Additional narrative/ explanation:</p> <p>The applicant states that, where principal aquifer is unconfined, there is a High to Medium Sensitivity and Low Magnitude, which has a worst-case Moderate significance of impact with embedded mitigation, but could also be Moderate/Minor significance. This agrees with Table 22.5, the significance matrix. The applicant goes on to conclude this is “not significant”. The definition in 22.4.13 is that “Moderate/Minor” and lesser effects can be defined as “not significant”. As such, Moderate significance should be treated as Significant, which the applicant has not done. Further mitigation may be required to manage the significant risks to controlled waters where principal aquifer is unconfined. We require further</p>	<p>the Water Framework Directive Assessment [REP5-081]. Chapter 22 applies the receptor sensitivity and significance criteria set out in Tables 22.3 to 22.5. For unconfined Principal Aquifers, a receptor sensitivity of High to Medium and a Low magnitude of effect was identified, giving a classification of “Moderate to Moderate/Minor.” As defined in paragraph 22.4.13 of the ES Chapter 22: Ground Conditions and Contamination [REP1-025], effects of Moderate/Minor or less are considered not significant, whereas Moderate effects are considered significant. The Applicant considers that this assessment has been applied correctly and consistently within the Environmental Statement. The outcome of “Moderate to Moderate/Minor” reflects the conservative nature of the methodology. The matrix applied resulted in two conflicting outcomes and therefore, it was necessary to apply professional judgement to determine the overall significance. In addition, the</p>	<p>however in general we are satisfied that the risk is not significant due to the proposed embedded mitigation.</p> <p>We consider a conservative approach, as suggested by the applicant, would use the worst-case scenario. That would be Moderate significance.</p> <p>The “Moderate to Moderate/Minor” classification was determined including embedded mitigation, and no additional mitigation measures are proposed (Table 22.6). As such, we question the strength of this part of the Applicant’s Position.</p> <p>It would have been beneficial for the applicant to acknowledge the two conflicting outcomes in the main report and provide some commentary therein. Use of professional judgement is acceptable, and we note this is mentioned in 22.4.9, but not repeated directly in relation to this classification.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>information to provide surety this is in place. Significant risk to principal aquifers should be included in Chapter 26 (summary of significant effects).</p>	<p>inclusion of embedded mitigation incorporated into the Scheme design further reduces risk, confirming that the effects will be 'non-significant'. These mitigation measures are secured through the OCEMP Revision A [EX6/GH7.1_C], the OSMP [EX6/GH7.6_A], and the OBSSMP Revision A [REP5-075], and include pollution prevention controls, lined containment for hazardous materials, firewater isolation and removal procedures, and strict requirements for the handling and storage of soils and fuels.</p> <p>On this basis, the Applicant maintains its conclusion that the residual effects on controlled waters are not significant. This conclusion is consistent with the findings of the Water Framework Directive Assessment [REP5-081], which confirms that the Scheme will not result in deterioration of WFD water body status.</p>	<p>Consultee Position following Applicant Response 17/03/2026</p> <p>We thank the applicant for their acknowledgment of the hydrogeological setting. We are satisfied with the mitigation measures proposed.</p>	



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>Applicant Response to Consultee Position</p> <p>Whilst we recognise that sections of the route run through areas of high sensitivity groundwater (principal aquifer), overall, the risk with reference to hydrogeology is considered to be moderate/minor and it is considered that further mitigation over and above the embedded mitigation measures as part of the construction and operation of the Scheme is not a requirement.</p>		
GCC-07	Water Framework Directive	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/14</p> <p>Issue:</p> <p>Very limited information or discussion on WFD Groundwater bodies. No proposed mitigation (Section 8) specifically mentions groundwater. We are concerned WFD Groundwater bodies have not been fully assessed or understood.</p> <p>Additional narrative/ explanation:</p>	<p>WFD groundwater bodies underlying the Scheme have been scoped into the assessment, as set out in the Water Framework Directive Assessment [REP5-081]. The assessment concluded that the Scheme will not cause deterioration in the status of any groundwater body or prevent the achievement of WFD objectives. The Applicant acknowledges that the presentation of groundwater information in the Water Framework Directive Assessment [REP5-081] is less detailed than that provided for</p>	<p>Resolved.</p> <p>We thank the applicant for the additional narrative given herein, the additional data added to Table 2 of the WFD Assessment, and the detail added as paragraphs 5.6.3 to 5.6.6. We look forward to reviewing detailed designs in due course.</p>	Matter Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>Table 2 does not give the chemical status of groundwater bodies, which is one of the two basic classification categories. Annex A does not have tabulated WFD status for all groundwater elements, as it does for surface water. One of the WFD Groundwater bodies has an overall Poor classification. We expect a report such as this to detail the reason(s) for not achieving Good. Section 3.2.5 refers to the “objective year” for Good status, but the years are not given in the report. All WFD Groundwater bodies are all scoped in (Section 6.3.1), so the absence of further detail is concerning. The groundwater level and flow assessment (Section 2.6.1) is based on a single borehole record where groundwater was not recorded. The depth of borehole is not stated, but our records show it was only to 3.30mbgl. This is clearly not enough information to support a groundwater level and flow assessment. We are concerned</p>	<p>surface waters. However, the supporting baseline is provided in the ES Chapter 22: Ground Conditions and Contamination [REP1-025], which describes the underlying aquifer designations, geology and hydrogeology, and confirms that the Sites are not located within any Source Protection Zones. The groundwater bodies relevant to the Scheme are the Nene and Ouse management catchments, one of which has an overall Poor chemical classification. The reasons for status are identified within the Environment Agency’s published data, and no activities associated with the Scheme are identified as pressures contributing to poor chemical quality. Potential pathways for impact are limited due to the nature of the Scheme, which has very low water demand, no requirement for groundwater abstraction, and embedded pollution prevention measures secured through the OCEMP [EX6/GH7.1_C], the OSMP [EX6/GH7.6_A] and the</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>the applicant has not fully considered, or does not understand, WFD groundwater bodies underlying the site.</p>	<p>OBSSMP [REP5-075]. These measures include impermeable containment for hazardous materials, isolation and removal of any contaminated firewater, and strict controls on soils, fuels and construction materials. On this basis, the Applicant maintains that the Scheme will not adversely affect WFD groundwater body status. The Applicant is content to clarify within the final detailed drainage design and management plans secured under the DCO how groundwater bodies have been considered, including reference to chemical status and objective years, to provide greater transparency, but no change to the assessment conclusions of the Water Framework Directive Assessment [REP5-081] is required.</p>		
GCC-08	Preliminary Risk Assessment	<p><u>EA Relevant Representation Feedback</u></p> <p>EA ref: EA/WQ/15</p> <p>Issue:</p> <p>Preliminary risk assessment lacking important information.</p>	<p>A request for additional borehole data in ES Appendix 22.1 Geo Environmental PRA [REP1-081 to REP1-094] did not appear to have been made during scoping. Previous scoping feedback has been reviewed with all requested</p>	<p>Resolved.</p> <p>We are satisfied with the applicant's response, and various changes made to the relevant reports listed. See also our response to GCC-04.</p>	Matter Agreed



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>Information from data search has not been used. Potential contamination sources have been ignored. CSM is not sufficient. Our comments from EIA Scoping have not been taken into account.</p> <p>Additional narrative/ explanation: At the scoping stage, we expressed concerns about the quality and completeness of reporting in this assessment. An updated report was not available at PEIR review stage. This report was updated for the Environmental Statement, but we have still found it to be inadequate. At scoping we queried why in Section 2.2, Site-Specific Geology section, only boreholes from Land at Grendon and Green Hill F had been reviewed. This has not been updated. We are pleased to see that groundwater levels from other boreholes, one for each panel area, are given later in the table. Section 2.4.2 states “Within the wider area, Sywell Airfield is located in the central</p>	<p>amendments having been undertaken. Site-Specific Geology, BGS Borehole data has been added for all sites. See Section 2.2 of ES Appendix 22.1 Geo-Environmental PRA [REP1-081 to REP1-094]. In addition, ES Appendix 22.2 Geo-Environmental PRA Cable Route Corridor [REP1-095 to REP1-106] includes nearby BGS Borehole data along the entire length of the cable route corridor. Both reports should be reviewed in conjunction. Wording on the location of Sywell Airfield in relation to Green Hill C has been amended in Section 2.4.2 ES Appendix 22.1 Geo-Environmental PRA [REP1-081 to REP1-094]. PFAS has been listed as a potential contaminant of concern associated with Sywell Airfield and included within the Conceptual Site Model (Section 3.0) of both ES Appendix 22.1 Geo-Environmental PRA [REP1-081 to REP1-094] and ES Appendix 22.2 Geo-Environmental PRA Cable Route Corridor [REP1-095 to</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>area”. This is immediately adjacent to the cable route and Green Hill C. We consider this is a potential source of contamination including PFAS (Per- and polyfluoroalkyl substances). It should be in the CSM (Section 3.3); it is in the CSM for Appendix 22.2, but not Appendix 22.1. PFAS are not listed as a potential contaminant in Appendix 22.2, and we consider they should be. Risks from the Earls Barton Quarry (identified in Section 2.5) are not ruled out in the report text, and this source should be in the CSM. The fact that the landfill is off site does not preclude the risk to sensitive receptors on the site. Risk from Sywell Range landfills is ruled out in Appendix 22.1 Section 3.3 (CSM), but other landfills are not mentioned. The landfill is included as a source in Appendix 22.2 (PRA for cable route), Section 3.3 (CSM). There is no explanation why the assessment of risk differs between the two reports. We have records of historical</p>	<p>REP1-106]. Landfills associated with Earls Barton Quarry, Mears Ashby Road, Sywell Range, and OS Fields Bozeat are discussed and assessed within the relevant report sections, including the Conceptual Site Model (Section 3.0) of both ES Appendix 22.1 Geo-Environmental PRA [REP1-081 to REP1-094]] and ES Appendix 22.2 Geo-Environmental PRA Cable Route Corridor [REP1-095 to REP1-106]. It should be noted that the historical landfill at OS Fields Bozeat is not included in ES Appendix 22.2 due to its distance from the Cable Route. In contrast, Sywell Range is discussed in greater detail within ES Appendix 22.2, given its closer proximity to the Cable Route, in comparison to Green Hill C. Landfills near Earls Barton Quarry, Sywell Range, and Mears Ashby Road (Barton Plant Ltd) are addressed in ES Chapter 22: Ground Conditions and Contamination [REP1-025]. The landfill at OS Fields Bozeat assessed in ES Appendix 22.1 Geo-Environmental PRA [REP1-</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
		<p>landfills adjacent to the site boundary which are not mentioned in Appendix 22.1 at all (Ashby Road and OS Fields, Bozeat). Both landfills are included in the attached Envirocheck reports, along with numerous records of Local Authority Landfill Coverage. Some of these are within or immediately adjacent to the site boundary but have not been discussed in the main PRA and therefore are not considered in the main ES Chapter 22. This is a disappointing omission. Risks from historical landfills have not been assessed or understood.</p>	<p>081 to REP1-094], is located at closest approx. 75m north of the Green Hill F boundary and is therefore considered unlikely to be encountered during the development. The Hotspot Protocol has been amended in Appendix G of both ES Appendix 22.1 Geo-Environmental PRA [REP1-081 to REP1-094] and ES Appendix 22.2 Geo-Environmental PRA Cable Route Corridor [REP1-095 to REP1-106]. A Discovery Strategy will be implemented if suspected landfill material is encountered during construction or decommissioning. This is set out in the OCEMP [EX6/GH7.1_C] and secured in Schedule 2, Requirement 13 of the Draft DCO [EX6/GH3.1_E]. The EA historical landfill sites have been assessed for potential impacts on controlled waters (see Sections 22.8.11 22.8.14). Applicant acknowledges that ES Appendix 22.1 Geo-Environmental PRA [REP1-081 to REP1-094] and ES Appendix 22.2 Geo-Environmental PRA Cable Route Corridor [REP1-095</p>		



	Matter	Details of Matters for Discussion	Applicant Position	Consultee Position	Status
			<p>to REP1-106] were prepared at different times by different authors, alignment of both reports has been undertaken, with risks and recommendations outlined in the CSM. Both reports should be read in conjunction.</p>		



4 Signatories

4.1 Overview

4.1.1 The above SoCG is agreed between Green Hill Solar Farm Ltd. (the Applicant) and the Environment Agency, as specified below.

4.1.2 Duly authorised for and on behalf of **Green Hill Solar Farm Ltd.**

Name:	
Job Title:	
Date:	
Signature:	

4.1.3 Duly authorised for and on behalf of the Environment Agency.

Name:	
Job Title:	
Date:	
Signature:	