

Document Ref: 6.3

Planning Inspectorate Ref: EN0110001

The Keadby Next Generation Power Station Development Consent Order [year]

Environmental Statement (ES)

Volume II – Appendix 13C Potential Areas of Contamination Further Risk and Impact Assessment

The Planning Act 2008

The Infrastructure Planning (Environmental Impact Assessment) Regulations 2017

Applicant: Keadby Next Generation Limited

Date: August 2025

Version: V0









A collaboration between SSE Thermal and Equinor

Document History

Document Ref	6.3.21 / Appendix 13C	
Issue	V0	
Document Owner	Arup	

Glossary

Abbreviation/	Description		
CSM	Conceptual Site Model		
ES	Environmental Statement		
LWS	Local Wildlife Site		
PAH	Polyaromatic Hydrocarbons		
PCB	Polychlorinated Biphenyls		
PPE	Personal Protective Equipment		
SAC	Special Area of Conservation		
SSSI	Site of Special Scientific Interest		
SVOC	Semi Volatile Organic Compounds		
TPH	Total Petroleum Hydrocarbons		
VOC	Volatile Organic Compounds		



Contents

CONTEN	IIS
13C. INT	RODUCTION4
13C.1.	OVERVIEW
13C.2.	FURTHER RISK AND IMPACT ASSESSMENT
Tables	
Table 13	C.1: Potential areas of contamination4
Table 13	C.2: Risk and impact assessments for each group/ individual site10
Table 13	C.3: Risk and impact assessment for the current Keadby 1 and 2
Power S	tation (S1) located within the Proposed Development Site boundary .15
	C.4: Baseline CSM: current Keadby 1 Power Station (S1) located
within th	ne Proposed Development Site boundary17
	SC.5: During construction CSM: current Keadby 1 and 2 Power Station
(S1) loca	ated within the Proposed Development Site boundary21
	SC.6: Post-construction CSM: current Keadby 1 and 2 Power Station
	ated within the Proposed Development Site boundary25
	SC.7: Current Keadby 1 and 2 Power Station (S1) located within the
	ed Development Site boundary – significance of effect assessment30
	C.8: Risk and impact assessment for the historical landfill (S2) located ne Proposed Development Site boundary
Table 13	C.9: Baseline CSM: historical landfill (S2) located within the Proposed
Develop	ment Site boundary36
Table 13	C.10: During construction CSM: historical landfill (S2) located within
the Prop	osed Development Site boundary40
Table 13	SC.11: Post-construction CSM: historical landfill (S2) located within the
Propose	ed Development Site boundary45
	SC.12: Historical landfill (S2) located within the Proposed Development
	ndary – significance of effect assessment51
	C.13: Risk and impact assessment for the historic landfills (S4, S5, S6)
located	within the Proposed Development Site boundary56

Keadby Next Generation Power Station Project



the Proposed Development Site boundary60
Table 13C.15: During construction CSM: historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary64
Table 13C.16: Post-construction CSM: historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary69
Table 13C.17: Historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary – significance of effect assessment74
Table 13C.18: Risk and impact assessment for the former tanks (S19) located within the Proposed Development Site boundary78
Table 13C.19: Baseline CSM: former tanks (S19) located within the Proposed Development Site boundary80
Table 13C.20: During Construction CSM: former tanks (S19) located within the Proposed Development Site boundary83
Table 13C.21: Post-construction CSM: former tanks (S19) located within the Proposed Development Site boundary86
Table 13C.22: Former tanks (S19) located within the Proposed Development Site boundary – significance of effect assessment89
Table 13C.23: Risk and impact assessment for the former railway (S11) located within the Proposed Development Site boundary92
Table 13C.24: Baseline CSM: former railway (S11) located within the Proposed Development Site boundary94
Table 13C.25: During Construction CSM: former railway (S11) located within the Proposed Development Site boundary97
Table 13C.26: Post-construction CSM: former railway (S11) located within the Proposed Development Site boundary101
Table 13C.27: Former railway (S11) located within the Proposed Development Site boundary – significance of effect assessment105
Table 13C.28: Risk and impact assessment for the current and former railways (S9 and S10) located within the Proposed Development Site boundary109
Table 13C.29: Baseline CSM: current and former railways (S9 and S10) located within the Proposed Development Site boundary113
Table 13C.30: During construction CSM: current and former railways (S9 and S10) located within the Proposed Development Site boundary117
Table 13C.31: Post-construction CSM: current and former railways (S9 and S10) located within the Proposed Development Site boundary







13C. Introduction

13C.1. Overview

- This Technical Appendix supplements **ES Volume I Chapter 13**: Geology, Hydrogeology and Land Contamination (**Application Document Ref. 6.2**) and describes the additional details for the approach to assessment for land quality for the Proposed Development.
- 13C.1.2. In accordance with the screening methodology presented in Section 13.3 of ES Volume I Chapter 13: Geology, Hydrogeology and Land Contamination (Application Document Ref. 6.2), a baseline risk score has been assigned to each of these areas and is presented in Table 13C.1 (below). It is also visually represented on ES Volume III Figure 13.1: Identified Historical and Current Areas of Potential Contamination (Application Document Ref. 6.4). It has been assumed at this stage that excavation (cut) may occur anywhere within the Proposed Development Site boundary.

Table 13C.1: Potential areas of contamination

Site ID	Site name	Proximity zone ¹	Land use class ²	Relationship to cut/ fill/ construction work	Baseline risk score ³
S1	Keadby Power Station (formerly coal fired, current gas fired). Keadby Power Landfill (deposited waste included inert and industrial waste) also within S1 area, along with numerous tanks and former railway (southern-most boundary) and	Zone 1	Class 3	Cut	5

Keadby Next Generation Power Station Project



Site ID	Site name	Proximity zone ¹	Land use class ²	Relationship to cut/ fill/ construction work	Baseline risk score ³
	former farms (west and north).				
S2	Historic Landfill and BGS Recorded Landfill Site - Keadby Power Station. Deposited waste included inert and industrial waste.	Zone 1	Class 3	Cut	5
S3	Historic Landfill and Licensed Waste Management Facility - John Brown Engineering Landfill. Deposited waste included inert and industrial waste, and liquid sludge.	Zone 2	Class 3	Cut	4
S4	Historic Landfill and Licensed Waste Management Facility - Keadby Power Station. Deposited waste included inert, commercial and household waste.	Zone 1	Class 3	Cut	5



Site ID	Site name	Proximity zone ¹	Land use class ²	Relationship to cut/ fill/ construction work	Baseline risk score ³
S5	Historic Landfill - Keadby Central Electricity Generating Board. Deposited waste included inert, industrial, commercial and household waste, ash (from Keadby Power Station after lagoon settlement), construction, colliery tailings, refractories (from Keadby Power Station), asbestos.	Zone 1	Class 3	Cut	5
S6	Historic Landfill - Former Keadby Power Station and Registered Landfill - Transtore Industries. Deposited waste included industrial, commercial, household and special waste.	Zone 1	Class 3	Cut	5
S7	Historic Landfill Site - PFA Settlement Lagoon	Zone 2	Class 3	Cut	4



Site ID	Site name	Proximity zone ¹	Land use class ²	Relationship to cut/ fill/ construction work	Baseline risk score ³
S8	Historic Landfill Site - Keadby Power Station	Zone 3	Class 3	Cut	3
S9	Current railway	Zone 1	Class 2	Cut	4
S10	Former railway	Zone 1	Class 2	Cut	4
S11	Former railway sidings and conveyor system	Zone 1	Class 2	Cut	4
S12	Current PD Ports Marina and wharf including current warehouse and former railway and gasometer and infilled pond.	Zone 1	Class 2	Cut	4
S13	Current depot	Zone 3	Class 2	Cut	2
S14	Current pumping station	Zone 1	Class 1	Cut	3
S15	Current pumping station	Zone 2	Class 1	Cut	2
S16	Current pumping station	Zone 3	Class 1	Cut	1
S17	Current pumping station	Zone 3	Class 1	Cut	1
S18	Current pumping station	Zone 1	Class 1	Cut	3
S19	Former tanks	Zone 1	Class 3	Cut	5
S20	Current Roe Farm	Zone 2	Class 1	Cut	2



Site ID	Site name	Proximity zone ¹	Land use class ²	Relationship to cut/ fill/ construction work	Baseline risk score ³
S21	Former S L Cleaning Services; commercial cleaning services	Zone 3	Class 2	Cut	2
S22	Potential current tanks	Zone 3	Class 3	Cut	3
S23	Current North Pilfrey Farm	Zone 3	Class 1	Cut	2
S24	Current Pilfrey Farm	Zone 2	Class 1	Cut	1

¹ Proximity zone definition is included within **Table 1, Appendix 13B** (ES).

² Land use class types are defined within **Table 2, Appendix 13B** (ES).

³ Baseline risk scoring method is defined within **Table 3, Appendix 13B** (ES).



13C.2. Further risk and impact assessment

- 13C.2.1. The sites from Table 13C.1 with a baseline risk score of three and above have been considered for further risk and impact assessment in the following tables. The sites from Table 13C.1 with a baseline risk score of two or below are not considered to pose an unacceptable risk within the context of the Proposed Development construction or operation and have therefore been scoped out of any further assessment.
- 13C.2.2. Sites considered for further risk and impact assessment have been grouped where they share similar risk profiles and proximity from the Proposed Development, including whether they are within the Proposed Development Site boundary or outside of it. The risk and impact assessments for each group/ individual site (which are presented and defined in Table 13C.2 below) are presented as a series of tables comprising: a baseline Conceptual Site Model (CSM), a construction phase CSM, a post-construction CSM and then a significance of effect assessment table.
- 13C.2.3. All sites with a baseline risk score of 5 have been assessed on their own, with the exception of S4, S5 and S6. These have been grouped as they are all landfills and they are all located within the same area (in the west of the Proposed Development Site). There is considered to be the same risk outcome for all the receptors assessed from these three sites.
- 13C.2.4. The remaining sites with a baseline risk score of 3 and 4 have been grouped based on their land use type which is either; landfills, industrial sites, railway land or light industrial sites.
- 13C.2.5. Peat deposits are known to be present but could not be identified as a site, or defined area, as the Peat deposits are not mapped. They could therefore be present anywhere within the superficial deposits layer (which has been proven to be up to 1.6m in thickness). Therefore, for Peat and the potential for ground gas, a more generalised risk and impact assessment has been undertaken.



Table 13C.2: Risk and impact assessments for each group/ individual site

Group/ individual site	Site title (site ID) and land use class	Baseline risk score ¹	Additional Information regarding grouping of the sites
Potential areas	of contamination located within the P	roposed De	evelopment Site boundary
Baseline risk score 5 industrial site – current Keadby 1 and 2 Power Station	Keadby 1 Power Station (formerly coal fired, current gas fired), and Keadby 2 Power Station. Keadby Power Landfill (deposited waste included inert and industrial waste) also within S1 area, along with numerous tanks and former railway (southern-most boundary) and former farms (west and north) – (S1) Class 3.	5	S1 is located partly within and partly outside of the Proposed Development Site boundary. As at least half of S1 is located where multiple services and access routes are proposed, it has been assessed as being 'within' the Proposed Development Site boundary.
Baseline risk score 5 landfill site – historic landfill	Historic Landfill and BGS Recorded Landfill Site - Keadby Power Station. Deposited waste included inert and industrial waste – (S2) Class 3.	5	S2 is located partly within and partly outside of the Proposed Development Site boundary. As a significant proportion of S2 crosses the northern area of the main development area, it has been assessed as being 'within' the Proposed Development Site boundary.
Baseline risk score 5 landfill	Historic Landfill and Licensed Waste Management Facility - Keadby Power Station. Deposited waste included	5	S4, S5 and S6 extend slightly to within the Proposed Development Site boundary within an area proposed for vehicular site access with a track already present.



Group/ individual site	Site title (site ID) and land use class	Baseline risk score ¹	Additional Information regarding grouping of the sites
sites – historic landfills	inert, commercial and household waste – (S4) Class 3.		Therefore, it has been assumed that cut operations are likely to be limited in this area. These sites have been
	Historic Landfill - Keadby Central Electricity Generating Board. Deposited waste included inert, industrial, commercial and household waste, ash (from Keadby Power Station after lagoon settlement), construction, colliery tailings, refractories (from Keadby Power Station), asbestos – (S5) Class 3.		assessed as being 'within' of the Proposed Development Site boundary.
	Historic Landfill - Former Keadby Power Station and Registered Landfill - Transtore Industries. Deposited waste included inert, industrial, commercial, household and special waste – (S6) Class 3.	5	
Baseline risk score 5	Former tanks – (S19) Class 3.	5	S19 is located entirely within the Proposed Development Site boundary.



Group/ individual site	Site title (site ID) and land use class	Baseline risk score ¹	Additional Information regarding grouping of the sites
industrial site – former tanks			
Railway sites – current and former railways	Former railway – (S10) Class 2. Current railway – (S9) Class 2.	4	S9 and S10 extends slightly within the Proposed Development Site boundary which is an area proposed for canal water supply connection works and access roads. It is assumed that cut operations are likely to be limited in this area. It has been considered 'within' the Proposed Development Site boundary.
Railway site – former railway	Former railway sidings and conveyor system – (S11) Class 2.	4	S11 is located partly within and partly outside the Proposed Development Site boundary. As a significant proportion of S11 crosses the southern area of the main development, it has been considered as 'within' the Proposed Development Site boundary.
Industrial site – current marina and wharf including current warehouse,	Current PD Ports Marina and wharf including current warehouse, former railway and gasometer and infilled pond – (S12) Class 2.	4	S12 is located partly within and partly outside of the Proposed Development Site boundary. Approximately a quarter of S12 is located within the Proposed Development Site boundary which has been proposed for a haulage route and transport offloading. As this area does not currently have any access road, it has been assumed that



Group/ individual site	Site title (site ID) and land use class	Baseline risk score ¹	Additional Information regarding grouping of the sites
former railway and gasometer and infilled pond			cut operations are likely in this area. Therefore, S12 has been conservatively considered as being 'within' the Proposed Development Site boundary.
Light industrial site – current pumping station	Current pumping station – (S14) Class 1.	3	S14 is located entirely within the Proposed Development Site boundary.
Potential areas	of contamination located outside of th	e Propose	d Development Site boundary
Landfill sites – historic landfills	Historic Landfill and Licensed Waste Management Facility - John Brown Engineering Landfill. Deposited waste included inert and industrial waste, and liquid sludge – (S3) Class 3.	4	S3, S7 and S8 are located entirely outside of the Proposed Development Site boundary.
	Historic Landfill Site - Pulverised Fuel Ash (PFA) Settlement Lagoon – (S7) Class 3.	4	
	Historic Landfill Site - Keadby Power Station – (S8) Class 3.	3	



Group/ individual site	Site title (site ID) and land use class	Baseline risk score ¹	Additional Information regarding grouping of the sites
Industrial site – potential current tanks	Potential current tanks – (S22) Class 3.	3	S22 is located entirely outside of the Proposed Development Site boundary.
Light industrial site – current pumping station	Current pumping station – (S18) Class 1.	3	S18 is located entirely outside of the Proposed Development Site boundary.

¹ Baseline risk scoring method is defined within **Table 13B.3, Appendix 13B** (ES).



Table 13C.3: Risk and impact assessment for the current Keadby 1 and 2 Power Station (S1) located within the Proposed Development Site boundary

Site ID (IDS)	S1						
Site group	Baseline risk score 5 industrial site – current Keadby 1 Power Station located within the Proposed Development Site boundary						
Site title (Site ID) and land use class	Keadby 1 Power Station (formerly coal fired, current gas fired) and Keadby 2 Power Station. Keadby Power Landfill (deposited waste included inert and industrial waste) also within S1 area, along with numerous tanks and former railway (southern-most boundary) and former farms (west and north) – (S1) Class 3.						
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)		
Keadby Power Station, Keadby Power Landfill also	Current commercial users at Keadby 1 and 2 Power Station (on-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	Unnamed drains (onsite) North Soak Drain (onsite)	LWS (all off- site); Keadby Wetland	Keadby 1 and 2 Power Station buildings (on-site) Future Proposed Development foundations and services (on-site)		



within S1	Future	Bedrock geology	Sheffield and South	South Soak
area, along	commercial users	(Mercia Mudstone	Yorkshire Navigation/	Drain, Keadby
with	at Proposed	Formation) –	Stainforth and Keadby	Stainforth and
numerous	Development (on-	Secondary B aquifer	Canal (off-site)	Keadby Canal
tanks and	site)		South Soak Drain (off-	Corridor
former			site)	
railway and former farms – (S1)			Two surface water abstractions (not	
			potable) (off-site, adjacent to the south)	

Notes/ assumptions;

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

²S1 is located partly within and partly outside of the Proposed Development Site boundary. As at least half of S1 is located where multiple services, access routes and laydown areas are proposed, it has been assessed as being 'within' the Proposed Development Site boundary.



Table 13C.4: Baseline CSM: current Keadby 1 Power Station (S1) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Ground gas (from landfill located within	n. (from ed within dary, as of ade Commercial users at Keadby 1 and 2 Power Station on to and	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
the S1 boundary, and any areas of significant Made Ground). Landfill known to		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
contain inert and industrial waste.		Inhalation of ground gases.	Unlikely	Medium	Low risk
Potential for a range of inorganic and contaminants including but not	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
limited to metals, metalloids, acids, alkalis, organic	Bedrock Secondary B				
compounds, inorganic compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils, VOC, SVOC, timber and water treatment chemicals, PCB, methane, hydrogen sulphide and carbon dioxide.	Controlled waters – surface waters – North Soak Drain (onsite) Two surface water abstractions (not potable) (off-site, adjacent to the south)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – Unnamed drains (on- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Controlled waters – surface waters –	Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal, South Soak Drain (off-site)				
	Ecological receptors – Keadby Wetland LWS, South Soak Drain, Keadby LWS, Stainforth and Keadby Canal Corridor LWS (all off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Medium	Low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk
Notes/ assumptions;	1	1	ı	ı	ı



Source Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
-----------------	---------	--------------------------	---------------------------	------------------

¹ Site is assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.5: During construction CSM: current Keadby 1 and 2 Power Station (S1) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Ground gas (from landfill located within	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
the S1 boundary, and any areas of significant Made Ground).	Commercial users at Keadby 1 and 2 Power Station	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
Landfill known to contain inert and industrial waste.		Inhalation of ground gases.	Unlikely to low likelihood	Medium	Low to moderate/ low risk
Potential for a range of inorganic and organic contaminants including but not limited to metals,	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Medium	Moderate/ low to moderate risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
metalloids, acids, alkalis, organic					
compounds, inorganic compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils, VOC, SVOC, timber and water treatment chemicals, PCB,	Controlled waters – surface waters – North Soak Drain (onsite) Two surface water abstractions (not potable) (off-site, adjacent to the south)	Groundwater migration, direct run- off from site.	Low likelihood	Medium	Moderate/ low risk
methane, hydrogen sulphide and carbon dioxide.	Controlled waters – surface waters – Unnamed drains (on- site)	Groundwater migration, direct run- off from site.	Low likelihood	Mild	Low risk
	Controlled waters – surface waters – Sheffield and South Yorkshire Navigation/	Groundwater migration, direct run- off from site.	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Stainforth and Keadby Canal, South Soak Drain (off-site)				
	Ecological receptors – Keadby Wetland LWS, South Soak Drain, Keadby LWS, Stainforth and Keadby Canal Corridor LWS (all off- site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
E	Property receptors – Buildings, foundations	Exposure to explosive gases.	Unlikely to low likelihood	Medium	Low to moderate/ low risk
	and services (on-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk
Notes/ assumption	ns;	1	1	1	1



Source Receptor Pathway Probability Consequence Ris	Risk during construction
---	--------------------------

- ¹ Site investigation will be required prior to construction of the Proposed Development. This should include further groundwater and gas monitoring.
- ² S1 partly lies within the footprint of the Proposed Development and therefore may require remediation in the areas located within the Proposed Development Site boundary.
- ³ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ⁴ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.
- ⁵ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁶ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁷ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary. This might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources identified or it may alter ground gas pathways. This may result in a temporary worsening in groundwater quality or increased ground gas risk compared to baseline.



Table 13C.6: Post-construction CSM: current Keadby 1 and 2 Power Station (S1) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Ground gas (from landfill located within the S1 boundary,	On-site users – Commercial users at Keadby 1 and 2 Power Station Future commercial users at Proposed Development	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild to medium	Very low to low risk
and any areas of significant Made Ground). Landfill known to contain inert and industrial waste.		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild to medium	Very low to low risk
Potential for a range of inorganic and		Inhalation of ground gases.	Unlikely	Mild to medium	Very low to low risk
organic and organic contaminants including but not	Controlled waters – groundwater –	Leaching, vertical and lateral migration from	Unlikely to low likelihood	Medium	Low to moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
limited to metals, metalloids, acids, alkalis, organic compounds, inorganic	Superficial Secondary A Bedrock Secondary B	contaminated soils and waters.			
compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils, VOC, SVOC, timber and water treatment chemicals, PCB, methane, hydrogen sulphide and carbon dioxide.	Controlled waters – surface waters – North Soak Drain (on-site) Two surface water abstractions (not potable) (off-site, adjacent to the south)	Groundwater migration, direct run-off from site.	Unlikely to low likelihood	Medium	Low to moderate/ low risk
	Controlled waters – surface waters – Unnamed drains (on-site)	Groundwater migration, direct run-off from site.	Unlikely to low likelihood	Mild	Very low to low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters –				
	Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal, South Soak Drain (off-site)	Groundwater migration, direct run-off from site.	Unlikely	Mild to medium	Very low to low risk
	Ecological receptors - Keadby Wetland LWS, South Soak Drain, Keadby LWS, Stainforth and Keadby Canal Corridor LWS (all off-site)	Vertical and lateral migration, direct contact.	Unlikely to low likelihood	Mild	Very low to low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Property receptors – Buildings,	Exposure to explosive gases.	Unlikely	Mild to medium	Very low to low risk
	foundations and services (on-site)	Aggressive ground conditions.	Unlikely to low likelihood	Mild	Very low to low risk
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (on-site and off-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

Notes/ assumptions;

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
--------	----------	---------	-----------------------------	------------------------	----------------------------

³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.

⁴ Assumes that for the areas of S1 located outside of the Proposed Development Site boundary, the risks to the identified receptors will be as it was at baseline, as no direct intervention to remediate these areas will have taken place.



Table 13C.7: Current Keadby 1 and 2 Power Station (S1) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site users – Commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
On-site users – Commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
On-site users – Commercial users Inhalation of ground gases.	Low risk	Low to moderate/ low risk	Very low to low risk	Neutral to minor adverse	Neutral to minor beneficial
On-site users – Future commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	N/A	N/A	Very low to low risk	N/A	N/A
On-site users – Future commercial users	N/A	N/A	Very low to low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.					
On-site users – Future commercial users Inhalation of ground gases.	N/A	N/A	Very low to low risk	N/A	N/A
Controlled waters – groundwater Secondary A and B aquifers and abstraction (on-site) Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low to moderate risk	Low to moderate/ low risk	Neutral to minor adverse	Neutral to minor beneficial
Controlled waters – surface waters – North Soak Drain (on-site), abstractions (off-site, adjacent) Groundwater migration, direct run-off from site.	Moderate/ low risk	Moderate/ low risk	Low to moderate/ low risk	Neutral	Neutral to minor beneficial
Controlled waters – surface waters – unnamed drains (on-site) Groundwater migration, direct run-off from site.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – surface waters – Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal, South Soak Drain (off-site)	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Groundwater migration, direct run-off from site.					
Ecological receptors – LWS Vertical and lateral migration, direct contact.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Property receptors – Buildings, foundations and services (on-site) Exposure to explosive gases.	Low risk	Low to moderate/ low risk	Very low to low risk	Neutral to minor adverse	Neutral to minor beneficial
Property receptors – Buildings, foundations and services (on-site) Aggressive ground conditions.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Future property receptors – Buildings, foundations and services (on-site and offsite)	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Exposure to explosive gases.					
Future property receptors – Buildings, foundations and services (on-site and offsite) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance	Neutral to minor adverse	Neutral to minor beneficial			

Notes/ assumptions;

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.8: Risk and impact assessment for the historical landfill (S2) located within the Proposed Development Site boundary

Site ID (IDS)	S2						
Site group	Baseline risk score 5	landfill site – historic lan	dfill located within the Propo	osed Development	Site boundary.		
Site title (Site ID) and land use class	Historic Landfill and BGS Recorded Landfill Site - Keadby Power Station. Deposited waste included inert and industrial waste – (S2) Class 3.						
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)		
Historic Landfill and BGS Recorded Landfill Site -	Current public open space users at Keadby Common (on-site and off- site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	Keadby Boundary Drain and various unnamed drains (on-site)	Keadby Boundary Drain Local Wildlife Site (LWS) (on- site)	Electricity Distribution Centre buildings (on-site)		



Keadby Power Station – (S2)	Current commercial site users at the electricity distribution centre (on-site)	Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	Surface water abstraction (not potable) (off-site, adjacent to the north)	Future Proposed Development buildings (on- site)
	Future commercial users of Proposed Development (onsite)			

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S2 is located partly within and partly outside of the Proposed Development Site boundary. As a significant proportion of S2 crosses the northern area of the main development of the Proposed PCC Site, it has been as assessed as being 'within' the Proposed Development Site boundary.



Table 13C.9: Baseline CSM: historical landfill (S2) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Ground gas.	On-site users – Commercial users	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfill known to contain inert and industrial waste. Potential for a range of inorganic and		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low likelihood	Medium	Moderate/ low risk
organic contaminants including but not		Inhalation of ground gases.	Low likelihood	Medium	Moderate/ low risk
limited to metals, metalloids, acids, organic compounds, inorganic	On-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
asbestos, hydrocarbons (TPH), polyaromatic hydrocarbons (PAH), solvents, lubricants, fuel oils, alkalis,		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
volatile organic compounds (VOC),		Inhalation of ground gases.	Unlikely	Medium	Low risk
semi-volatile organic compounds (SVOC), polychlorinated biphenyls (PCB), dioxins, furans, methane, hydrogen sulphide and carbon dioxide.	Off-site users – Public open space users at Keadby	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
	Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – Keadby Boundary Drain and various unnamed drains (on-site) Surface water abstraction (not potable) (off-site, adjacent)	Groundwater migration, direct run- off from site.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Ecological receptors – Keadby Boundary Drain LWS (on- site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors	Exposure to explosive gases.	Low likelihood	Medium	Moderate/ low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk

¹ Site is assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.10: During construction CSM: historical landfill (S2) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Ground gas.	On-site users – Commercial users at the electricity distribution centre	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfill known to contain inert and industrial waste. Potential for a range of inorganic and		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low likelihood	Medium	Moderate/ low risk
organic contaminants including but not	Inhalation of ground gases.	Low likelihood to likely	Medium	Moderate/ low to moderate risk	
limited to metals, metalloids, acids, organic compounds,	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
inorganic compounds,	Public open space users at Keadby	from contaminated soils.			
asbestos, TPH, PAH, solvents, lubricants, fuel oils, alkalis, VOC, SVOC, PCB, dioxins, furans, methane, hydrogen	Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
sulphide and carbon dioxide.		Inhalation of ground gases.	Unlikely	Medium	Low risk
	Off-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
		Direct contact, ingestion, inhalation of vapour with/ from	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
		contaminated waters.			
		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Medium	Moderate/ low to moderate risk
	Controlled waters – surface waters – Keadby Boundary Drain and various unnamed drains (on-site)	Groundwater migration, direct run- off from site.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Surface water abstraction (not potable) (off-site, adjacent)				
Drain LWS (on-site)	receptors – Keadby Boundary Drain LWS (on-	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors	Exposure to explosive gases.	Unlikely to low likelihood	Severe	Moderate/ low to moderate risk
	foundations and	Aggressive ground conditions.	Low likelihood	Mild	Low risk

¹ Site investigation will be required prior to construction of the Proposed Development. This should include further groundwater and gas monitoring.



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
--------	----------	---------	-----------------------------	------------------------	--------------------------

- ² S2 partly lies within the footprint of the Proposed Development and therefore may require remediation within the areas of S2 that are within the Proposed Development Site boundary.
- ³ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ⁴ During construction, standard mitigation procedures are assumed to be implemented in accordance with a Construction Environmental Management Plan (CEMP).
- ⁵ Construction workers have been excluded from the assessment due to the use of Personal Protective Equipment (PPE)/ risk management protocols and in accordance with CIRIA C692, 2010.
- ⁶ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁷ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary. This might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources identified or it may alter ground gas pathways. This may result in a temporary worsening in groundwater quality or increased ground gas risk compared to baseline.



Table 13C.11: Post-construction CSM: historical landfill (S2) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Ground gas. On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Mild to medium	Low to moderate/ low risk	
Landfill known to contain inert and industrial waste.	contain inert and industrial waste. distribution centre	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low likelihood	Mild to medium	Low to moderate/ low risk
		Inhalation of ground gases.	Low likelihood	Mild to medium	Low to moderate/ low risk
range of inorganic and organic contaminants including but not limited to metals, metalloids, acids,	On-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
organic compounds, inorganic compounds,		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
asbestos, TPH, PAH, solvents, lubricants, fuel oils,		Inhalation of ground gases.	Unlikely	Medium	Low risk
alkalis, VOC, SVOC, PCB, dioxins, furans, methane, hydrogen sulphide and carbon dioxide.	Off-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild to medium	Very low to low risk
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Minor to mild	Very low risk
		Inhalation of ground gases.	Unlikely	Minor to mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	On-site users – Future commercial users of Proposed Development	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Minor	Very low risk
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Minor	Very low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely to low likelihood	Medium	Low to moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters –				
	Keadby Boundary Drain and various unnamed drains (on-site) Surface water	Groundwater migration, direct run- off from site.	Unlikely to low likelihood	Medium	Low to moderate/ low risk
	abstraction (not potable) (off-site, adjacent)				
	Ecological receptors – Keadby Boundary Drain LWS (on- site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Medium to severe	Low to moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Unlikely to low likelihood	Mild	Very low to low risk
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.

³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
			(Likelillood)	(Octority)	Construction

⁴ Assumes that for the areas of S2 located outside of the Proposed Development Site boundary, that upon completion of construction the risks to the identified receptors will be as it was at baseline, as no direct intervention to remediate these areas will have taken place.

⁵ The on-site public open space users at Keadby Common and the ecological receptor (Keadby Boundary Drain LWS) are located entirely within the area of S2 outside of the Proposed Development Site boundary. Therefore, no beneficial effects are considered likely.



Table 13C.12: Historical landfill (S2) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site users – Commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Moderate/ low risk	Moderate/ low risk	Low to moderate/ low risk	Neutral	Neutral to minor beneficial
On-site users – Commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Moderate/ low risk	Moderate/ low risk	Low to moderate/ low risk	Neutral	Neutral to minor beneficial
On-site users – Commercial users Inhalation of ground gases.	Moderate/ low risk	Moderate/ low to moderate risk	Low to moderate/ low risk	Neutral to minor adverse	Neutral to minor beneficial
On-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
On-site users – Public open space users	Low risk	Low risk	Low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.					
On-site users – Public open space users Inhalation of ground gases.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Off-site users – Public open space users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site users – Future commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	N/A	N/A	Very low risk	N/A	N/A
On-site users – Future commercial users	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.					
On-site users – Future commercial users Inhalation of ground gases.	N/A	N/A	Very low risk	N/A	N/A
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low to moderate risk	Low to moderate/ low risk	Neutral to minor adverse	Neutral to minor beneficial
Controlled waters – surface waters – Keadby Boundary Drain and various unnamed drains (on-site), abstraction (off-site) Groundwater migration, direct run-off from site.	Moderate/ low risk	Moderate/ low risk	Low to moderate/ low risk	Neutral	Neutral to minor beneficial
Ecological receptors – LWS Vertical and lateral migration, direct contact.	Low risk	Low risk	Low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Property receptors – Buildings, foundations and services (on-site) Exposure to explosive gases.	Moderate/ low risk	Moderate/ low to moderate risk	Low to moderate/ low risk	Neutral to minor adverse	Neutral to minor beneficial
Property receptors – Buildings, foundations and services (on-site) Aggressive ground conditions.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Future property receptors – Buildings, foundations and services (on-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A
Future property receptors – Buildings, foundations and services (on-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance	<u> </u>			Neutral to minor adverse	Neutral to minor beneficial
Notes/ assumptions;				I	I .



Contaminant linkage	Baseline risk	Construction	Post-	Construction	Post-
		risk	construction	significance	construction
			risk		significance

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.

³ Note that a large proportion of S2 is located outside of the Proposed Development Site boundary which will not be remediated. Therefore, post-construction, no significant beneficial effects are considered likely.



Table 13C.13: Risk and impact assessment for the historic landfills (S4, S5, S6) located within the Proposed Development Site boundary

Site ID (IDS)	S4, S5, S6								
Site group	Baseline risk so	Baseline risk score 5 landfill sites – historic landfills located within the Proposed Development Site boundary							
Site title (Site ID) and land use class	Historic Landfill and Licensed Waste Management Facility - Keadby Power Station. Deposited waste included inert, commercial and household waste – (S4) Class 3. Historic Landfill - Keadby Central Electricity Generating Board. Deposited waste included inert, industrial, commercial and household waste, ash (from Keadby Power Station after lagoon settlement), construction, colliery tailings, refractories (from Keadby Power Station), asbestos – (S5) Class 3. Historic Landfill - Former Keadby Power Station and Registered Landfill - Transtore Industries. Deposited waste included inert, industrial, commercial, household and special waste – (S6) Class 3.								
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)				



	Current	Superficial geology (Alluvium/	North Soak Drain (off-site)	Stainforth	Future
	public open	Warp) – Secondary A aquifer		and	Proposed
	space users			Keadby	Development
Historic Landfill	at Keadby		Sheffield and South Yorkshire	Canal	foundations
and Licensed	Common (on-	Bedrock geology (Mercia	Navigation/ Stainforth and	Corridor	and services
Waste	site and off-	Mudstone Formation) –	Keadby Canal (off-site)	LWS (off-	(on-site)
Management	site)	Secondary B aquifer		site)	
Facility -	Future		Surface water abstraction (not		
Keadby Power	commercial		potable) (off-site, 170m south)		
Station – (S4)	users of		,		
	Proposed				
	Development				
	(on-site)				



Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)
Historic Landfill - Keadby Central Electricity Generating Board – (S5)	Current public open space users at Keadby Common (on- site and off- site) Future commercial users of Proposed Development (on-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	North Soak Drain (off-site) Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site) Surface water abstraction (not potable) (off-site, 190m south- east)	Stainforth and Keadby Canal Corridor LWS (off- site)	Future Proposed Development foundations and services (on-site)



Historic Landfill - Former Keadby Power Station and Registered Landfill -	urrent ublic open pace users t Keadby ommon (on- te and off- te) uture	Superficial geology (Alluvium/ Warp) – Secondary A aquifer Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	Unnamed drain (off-site) North Soak Drain (off-site) Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site)	None	Future Proposed Development foundations and services (on-site)
Landfill - Transtore Industries – (S6) Pr					

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S4, S5 and S6 extend slightly to within the Proposed Development Site boundary within an area proposed for vehicular site access with a track already present. Therefore, it has been assumed that cut operations are likely to be limited in this area. These sites have been assessed as being 'within' the Proposed Development Site boundary.



Table 13C.14: Baseline CSM: historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Ground gas.	groundwater contamination. Ground gas. On-site users – Public open space users at Keadby Common Commercial, household, special,	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfills known to contain inert, industrial, commercial, household, special, ash and asbestos waste.		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
		Inhalation of ground gases.	Unlikely	Mild	Very low risk
Potential for a range of inorganic and organic	Off-site users –	Direct contact, ingestion, inhalation of dust/	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
contaminants including but not limited to metals, metalloids, acids, organic compounds, inorganic compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils,	Public open space users at Keadby Common	vapour with/ from contaminated soils.			
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
alkalis, VOC, SVOC, PCB, dioxins, furans, methans, hydrogen		Inhalation of ground gases.	Unlikely	Mild	Very low risk
methane, hydrogen sulphide and carbon dioxide.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters – Unnamed drain (off- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Controlled waters – surface waters – North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off- site) Surface water abstraction (not potable) (off-site, 170m – 190m distance)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Ecological receptors - Stainforth and Keadby Canal Corridor LWS (off- site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk

¹ Sites are assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.15: During construction CSM: historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Ground gas.	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfills known to contain inert, industrial, commercial, household, special, ash and asbestos waste.	Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
		Inhalation of ground gases.	Unlikely	Mild	Very low risk
Potential for a range of inorganic and organic	Off-site users –	Direct contact, ingestion, inhalation of dust/	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
contaminants including but not limited to metals, metalloids, acids, organic compounds, inorganic compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils,	Public open space users at Keadby Common	vapour with/ from contaminated soils.			
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
alkalis, VOC, SVOC, PCB, dioxins, furans, methans, hydrogen		Inhalation of ground gases.	Unlikely	Mild	Very low risk
methane, hydrogen sulphide and carbon dioxide.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Medium	Moderate/ low to moderate risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Controlled waters – surface waters – Unnamed drain (off- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Controlled waters – surface waters – North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off- site) Surface water abstraction (not potable) (off-site, 170m – 190m distance)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Ecological receptors - Stainforth and Keadby Canal Corridor LWS (off- site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk

¹ Site investigation will be required prior to construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

³ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.

⁴ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.

⁵ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction

⁶ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources (including those beyond the Proposed Development Site boundary) or alter ground gas pathways which may cause a temporary worsening in groundwater quality or increased ground gas risk compared to baseline.



Table 13C.16: Post-construction CSM: historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
groundwater contamination. Ground gas. Landfills known to contain inert, industrial, commercial, household, special, ash and asbestos	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
	Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Off-site users –	Direct contact, ingestion, inhalation of dust/	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Potential for a range of inorganic and	Public open space users at Keadby Common	vapour with/ from contaminated soils.			
organic contaminants including but not limited to metals, metalloids, acids, organic compounds, inorganic		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
compounds, asbestos, TPH,		Inhalation of ground gases.	Unlikely	Mild	Very low risk
PAH, solvents, lubricants, fuel oils, alkalis, VOC, SVOC, PCB, dioxins, furans, methane, hydrogen sulphide and carbon dioxide.	On-site users – Future commercial users of Proposed Development	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Minor	Very low risk
dioxido.		Direct contact, ingestion,	Unlikely	Minor	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
		inhalation of vapour with/ from contaminated waters.			
			Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – Unnamed drain (off- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters –				
	North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (offsite)	Groundwater	Low likelihood	Medium	Moderate/ low risk
	Surface water abstraction (not potable) (off-site, 170m – 190m distance)				
	Ecological receptors - Stainforth and Keadby Canal	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Corridor LWS (off-site)				
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Foundations and services (on-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

- ³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway interventions as appropriate.
- ⁴ Assumes that for the areas of S4, S5 and S6 located outside of the Proposed Development Site boundary, that upon completion of construction the risks to the identified receptors will be as it was at baseline, as no direct intervention to remediate these areas will have taken place.

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.



Table 13C.17: Historic landfills (S4, S5, S6) located outside of the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
On-site users – Public open space users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Public open space users	Very low risk	Very low risk	Very low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.					
Off-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site users – Future commercial users Direct contact, ingestion, inhalation of dust/vapour with/ from contaminated soils	N/A	N/A	Very low risk	N/A	N/A
On-site users – Future commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters	N/A	N/A	Very low risk	N/A	N/A
On-site users – Future commercial users Inhalation of ground gases	N/A	N/A	Very low risk	N/A	N/A
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low to moderate risk	Moderate/ low risk	Neutral to minor adverse	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – surface waters – unnamed drain (off-site) Groundwater migration, direct run-off from site.	Low risk	Low risk	Low risk	Neutral	Neutral
Controlled waters – surface waters – North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off- site), abstraction (off-site)	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
Groundwater migration, direct run-off from site. Ecological receptors – LWS Vertical and lateral migration, direct contact.	Low risk	Low risk	Low risk	Neutral	Neutral
Future property receptors – Foundations and services (on-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A
Future property receptors – Foundations and services (on-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Overall significance				Neutral to minor adverse	Neutral

3 Note that a large proportion of S4, S5 and S6 is located outside the Proposed Development Site boundary which will not be remediated. Therefore, post-construction, no significant beneficial effects are considered likely.

¹ The construction column assumes that a CEMP will be in place to mitigate inputs from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.18: Risk and impact assessment for the former tanks (S19) located within the Proposed Development Site boundary

Site ID (IDS)	S19								
Site group	Baseline risk so	Baseline risk score 5 industrial site – former tanks located within the Proposed Development Site boundary							
Site title (Site ID) and land use class	Former tanks – (S19) Class 3.								
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)				
Former tanks – (S19)	Current residential users (off-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	River Trent (Humber Upper) (off-site)	Ramsar, Special Area of Conservation (SAC) and Site	Pumping station building (off-site)				



Bedrock geology	Two surface water	of Special	Residential buildings (off-
(Mercia Mudstone	abstractions (not	Scientific	site)
Formation) – Secondary	potable) (off-site, 50m	Interest	
B aquifer	east)	(SSSI): Humber Estuary (off- site)	Future Proposed Development foundations and services (on-site)

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

 $^{^{2}\,\}mathrm{S19}$ is located entirely within the Proposed Development Site boundary.



Table 13C.19: Baseline CSM: former tanks (S19) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination.	Off-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Low potential for ground gas. Potential for inorganic and organic contaminants including lead, fuels/ TPH, PAH.	Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters –				
	River Trent (Humber Upper) (off-site)	Groundwater migration, direct run-	Unlikely	Medium	Low risk
	Two surface water abstractions (not potable) (off-site, 50m distance)	off from site.			
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off-site)	Vertical and lateral migration, direct contact.	Unlikely	Medium	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk

¹ Site is assessed against baseline condition without construction of the Proposed Development.



Source F	Receptor	Pathway		Consequence (Severity)	Risk at baseline
----------	----------	---------	--	------------------------	------------------

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.20: During Construction CSM: former tanks (S19) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination.	Off-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Low potential for ground gas. Potential for	Low potential for ground gas. Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
inorganic and organic		Inhalation of ground gases.	Unlikely	Minor	Very low risk
contaminants including lead, fuels/ TPH, PAH.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Medium	Moderate/ low to low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Controlled waters – surface waters –				
	River Trent (Humber Upper) (off-site)	Groundwater migration, direct run-	Unlikely	Medium	Low risk
	Two surface water abstractions (not potable) (off-site, 50m distance)	off from site.			
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off-site)	Vertical and lateral migration, direct contact.	Unlikely	Medium	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk	



Source Rece	Receptor	Pathway	Probability	Consequence	Risk during
Source	Receptor	rauiway	(Likelihood)	(Severity)	construction

- ¹ Site investigation will be required prior to construction of the Proposed Development. This should include further groundwater and gas monitoring.
- ² S19 is located within the footprint of the Proposed Development and therefore may require remediation in this area.
- ³ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ⁴ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.
- ⁵ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁶ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁷ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources which may cause a temporary worsening in groundwater quality compared to baseline.
- ⁸ The potential for ground gas from S19 is not considered significant enough to result in an increased risk during construction.



Table 13C.21: Post-construction CSM: former tanks (S19) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination.	Off-site users – Current residential users	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild to medium	Very low to low risk
Low potential for ground gas. Potential for		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild to medium	Very low to low risk
inorganic and organic contaminants		Inhalation of ground gases.	Unlikely	Minor	Very low risk
including lead, fuels/ TPH, PAH.	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely to low likelihood	Medium	Low to moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Bedrock Secondary B				
	Controlled waters – surface waters –				
	River Trent (Humber Upper) (off-site)	Groundwater migration, direct run-	Unlikely Mild to medium	Very low to low	
	Two surface water abstractions (not potable) (off-site, 50m distance)	off from site.			IISK
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off-site)	Vertical and lateral migration, direct contact.	Unlikely	Mild to medium	Very low to low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	and services (off-site)	Idings, foundations I services (off-site) Aggressive ground conditions.	Unlikely	Minor to mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Aggressive ground conditions.	Unlikely	Minor	Very low risk	

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.

³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.



Table 13C.22: Former tanks (S19) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Residential users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Off-site users – Residential users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Off-site users – Residential users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low to low risk	Low to moderate/ low risk	Neutral to minor adverse	Neutral to minor beneficial



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – surface waters – River Trent (Humber Upper) (off-site), abstractions (off-site) Groundwater migration, direct run-off from site.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Ecological receptors – Ramsar, SAC and SSSI Vertical and lateral migration, direct contact.	Low risk	Low risk	Very low to low risk	Neutral	Neutral to minor beneficial
Property receptors – Buildings, foundations and services (off-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Aggressive ground conditions.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Foundations and services (on-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Future property receptors – Foundations and services (on-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance				Neutral to minor adverse	Neutral to minor beneficial

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.23: Risk and impact assessment for the former railway (S11) located within the Proposed Development Site boundary

Site ID (IDS)	S11	S11								
Site group	Railway site – former	railway located within the	Proposed Development Site	boundary						
Site title (Site ID) and land use class	Former railway sidings and conveyor system – (S11) Class 2.									
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)					
Former railway sidings and conveyor system – (S11)	Current public open space users at Keadby Common (on-site and off-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer Bedrock geology (Mercia Mudstone	Unnamed drain (off-site, adjacent) North Soak Drain (off-site)	Stainforth and Keadby Canal Corridor LWS (off-site)	Future Proposed Development buildings (on- site)					



Future commercial	Formation) –	Surface water abstraction	
users at the	Secondary B aquifer	(not potable) (off-site,	
Proposed		250m south)	
Development (on-			
site)			

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S11 is located partly within and partly outside of the Proposed Development Site boundary. As a significant proportion of S11 crosses the southern area of the main development of the Proposed PCC Site, it has been assessed as being 'within' the Proposed Development Site boundary.



Table 13C.24: Baseline CSM: former railway (S11) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Low potential for	On-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Mild	Low risk
ground gas. Railway land can be impacted by		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Unlikely	Mild	Very low risk
asbestos as well as the preservatives such as creosote used on railway	Off-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
sleepers and herbicides.		Direct contact, ingestion, inhalation of	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Railway embankments may contain		vapour with/ from contaminated waters.			
material high in ash and other		Inhalation of ground gases.	Unlikely	Minor	Very low risk
waste.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – North Soak Drain (off- site) Surface water abstraction (not potable) (off-site, 250m distance)	Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters – Unnamed drain (off-site, adjacent)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Ecological receptors – Stainforth and Keadby Canal Corridor LWS (off-site)	Vertical and lateral migration, direct contact.	Unlikely	Mild	Very low risk

¹ Site is assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.25: During Construction CSM: former railway (S11) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination.	On-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Mild	Low risk
Low potential for ground gas. Railway land can be impacted by		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Unlikely	Mild	Very low risk
asbestos as well as the preservatives such as creosote used on railway sleepers and herbicides.	Off-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
	at iteauby common	Direct contact, ingestion, inhalation of	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other waste.		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and	Low likelihood to likely	Medium	Moderate/ low to moderate risk
	Bedrock Secondary B Controlled waters – surface waters – North Soak Drain (offsite) Surface water abstraction (not potable)	waters. Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk
	(off-site, 250m distance)				



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Controlled waters – surface waters – Unnamed drain (off-site, adjacent)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Ecological receptors – Stainforth and Keadby Canal Corridor LWS (off-site)	Vertical and lateral migration, direct contact.	Unlikely	Mild	Very low risk

¹ Site investigation will be required prior to construction of the Proposed Development. This should include further groundwater and gas monitoring.

² S11 partly lies within the footprint of the Proposed Development and therefore may require remediation in the areas located within the Proposed Development Site boundary.

³ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

⁴ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.



Source	Receptor	Pathway	Probability	Consequence	Risk during
			(Likelihood)	(Severity)	construction

- ⁵ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁶ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁷ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources which may cause a temporary worsening in groundwater quality compared to baseline.
- ⁸ The potential for ground gas from S11 is not considered significant enough to result in an increased risk during construction.



Table 13C.26: Post-construction CSM: former railway (S11) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Mild	Low risk
ground gas. Railway land can be impacted by	On-site users – Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Unlikely	Mild	Very low risk
asbestos as well as the preservatives such as creosote used on railway sleepers and herbicides.	Off-site users – Public open space users	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
		Direct contact, ingestion, inhalation of	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other		Inhalation of ground gases.	Unlikely	Minor	Very low risk
waste.	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Minor	Very low risk
	Future commercial users of Proposed Development	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Minor	Very low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Mild to moderate	Low to moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Bedrock Secondary B				
	Controlled waters – surface waters – North Soak Drain (off- site) Surface water abstraction (not potable) (off-site, 250m distance)	Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk
	Controlled waters – surface waters – Unnamed drain (off-site, adjacent)	led waters – waters – ed drain (off-site, Groundwater migration, direct run-off from site. Mild	Mild	Low risk	
	Ecological receptors – Stainforth and Keadby Canal Corridor LWS (off-site)	Vertical and lateral migration, direct contact.	Unlikely	Minor to mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Future property receptors –		Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

- ¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.
- ³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.
- ⁴ Assumes that for the areas of S11 located outside of the Proposed Development Site boundary, the risks to the identified receptors will be as it was at baseline, as no direct intervention to remediate these areas will have taken place.
- ⁵ The on-site and off-site public open space users at Keadby Common and unnamed drain are located entirely within/ nearby the area of S11 outside of the Proposed Development Site boundary. Therefore, no beneficial effects from remediation are considered likely.



Table 13C.27: Former railway (S11) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
On-site users – Public open space users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Public open space users	Very low risk	Very low risk	Very low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.					
Off-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Future commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	N/A	N/A	Very low risk	N/A	N/A
Off-site users – Future commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	N/A	N/A	Very low risk	N/A	N/A
Off-site users – Future commercial users Inhalation of ground gases.	N/A	N/A	Very low risk	N/A	N/A
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low to moderate risk	Moderate/ low to low risk	Neutral to minor adverse	Neutral to minor beneficial



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – surface waters – North Soak Drain (off-site) and abstraction (off-site) Groundwater migration, direct run-off from site.	Low risk	Low risk	Low risk	Neutral	Neutral
Controlled waters – surface waters – unnamed drains (off-site, adjacent) Groundwater migration, direct run-off from site.	Low risk	Low risk	Low risk	Neutral	Neutral
Ecological receptors – LWS Vertical and lateral migration, direct contact.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Buildings, foundations and services (on-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A
Future property receptors – Buildings, foundations and services (on-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Overall significance				Neutral to minor adverse	Neutral to minor beneficial

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.28: Risk and impact assessment for the current and former railways (S9 and S10) located within the Proposed Development Site boundary

Site ID (IDS)	S9, S10						
Site group	Railway sites – curr	ent and former railways lo	ocated outside of the Proposed	d Development S	ite boundary		
Site title (Site ID) and land use class	Current railway – (S9) Class 2. Former railway – (S10) Class 2.						
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)		



Current railway – (S9)	Current commercial users at Keadby 1 and Keadby 2 Power Station (off-site) Current residential users (off-site) Future commercial users of Proposed Development (on- site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	North Soak Drain (off-site, adjacent) Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site, adjacent) South Soak Drain (off-site, adjacent) Two surface water abstractions (not potable) (off-site, 100m north-east) Surface water abstraction (not potable) (off-site, 130m south)	LWS (all offsite); Keadby Wetland South Soak Drain, Keadby Stainforth and Keadby Canal Corridor Keadby Wet Grassland	Residential buildings (off-site) Keadby 1 and Keaby 2 Power Station foundations and services (off- site) Future Proposed Development buildings (on-site)
------------------------------	--	--	--	--	--



users and K Power site) Former railway – Currer		1km)	surface water abstractions (within 250m)	and/ or <50m)	(on-site, adjacent and/ or <50m)
users	rent residential rs (off-site) are commercial rs of Proposed elopment (on-	Superficial geology (Alluvium/ Warp) – Secondary A aquifer Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	North Soak Drain (off- site, adjacent) Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site, adjacent) South Soak Drain (off- site) Two surface water abstractions (not potable) (off-site, adjacent to the north)	LWS (all off-site); Keadby Wetland South Soak Drain, Keadby Stainforth and Keadby Canal Corridor	Keadby 1 and Keadby 2 Power Station buildings (off-site) Residential buildings (off-site) Future Proposed Development foundations and services (on-site)



- ¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ² S10 and S9 extends to slightly within the Proposed Development Site boundary which is an area proposed for canal water supply connection works and access routes. It is assumed that cut operations are likely to be limited in this area.



Table 13C.29: Baseline CSM: current and former railways (S9 and S10) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
ground gas. Railway land can be impacted by	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Unlikely	Minor	Very low risk
asbestos as well as the preservatives such as creosote used on railway sleepers and herbicides.	Off-site users – Commercial users at Keadby 1 and 2 Power	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Mild	Low risk
	Station	Direct contact, ingestion, inhalation of	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other		Inhalation of ground gases.	Unlikely	Minor	Very low risk
waste.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Mild	Low risk
	Controlled waters – surface waters – North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal and South Soak Drain (off-site)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Surface water abstractions (not potable) (off-site, adjacent to 130m distance)				
	Ecological receptors – Keadby Wetland LWS, South Soak Drain, Keadby LWS, Stainforth and Keadby Canal Corridor LWS and Keadby Wet Grassland LWS	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
--------	----------	---------	-----------------------------	------------------------	------------------

¹ Sites are assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.30: During construction CSM: current and former railways (S9 and S10) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
ground gas. C Railway land can be impacted by fuels, lubricants, metals and asbestos as well as the preservatives such as creosote used on railway	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Off-site users – Commercial users at Keadby 1 and 2 Power	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
	sleepers and	Station	Direct contact, ingestion, inhalation of	Unlikely	Mild



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other waste.		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Mild	Low to moderate/ low risk
	Controlled waters – surface waters – North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal and South Soak Drain (off-site) Surface water abstractions (not	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	potable) (off-site, adjacent to 130m distance)				
	Ecological receptors – Keadby Wetland LWS, South Soak Drain, Keadby LWS, Stainforth and Keadby Canal Corridor LWS and Keadby Wet Grassland LWS	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk
Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk	

¹ Site investigation will be required prior to construction of the Proposed Development.



Source	Receptor	Pathway	Probability	Consequence	Risk during
		ratiiway	(Likelihood)	(Severity)	construction

- ² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ³ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.
- ⁴ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁵ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁶ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources (including those located outside of the Proposed Development Site boundary) which may cause a temporary worsening in groundwater quality compared to baseline.
- ⁸ The potential for ground gas from S9 and S10 is not considered significant enough to result in an increased risk during construction.



Table 13C.31: Post-construction CSM: current and former railways (S9 and S10) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Low potential for ground gas. Railway land can be impacted by		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Unlikely	Minor	Very low risk
asbestos as well as the preservatives such as creosote used on railway sleepers and herbicides.	Off-site users – Commercial users at Keadby 1 and Keadby 2	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low Likelihood	Mild	Low risk
	Power Station	Direct contact, ingestion, inhalation of	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other		Inhalation of ground gases.	Unlikely	Minor	Very low risk
waste.	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Minor	Very low risk
	Future commercial users of Proposed Development	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Minor	Very low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Bedrock Secondary B				
	Controlled waters – surface waters –				
	North Soak Drain, Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal and South Soak Drain (off-site)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Surface water abstractions (not potable) (off-site, adjacent to 130m distance)				
	Ecological receptors – Keadby Wetland LWS, South Soak Drain, Keadby LWS, Stainforth	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	and Keadby Canal Corridor LWS and Keadby Wet Grassland LWS				
	Property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



	Source	Receptor	Pathway	_	•	Risk post- construction		
ĺ	2 Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed							

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.



Table 13C.32: Current and former railway (S9 and S10) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Residential users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Residential users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Residential users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Commercial users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site users – Future commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	N/A	N/A	Very low risk	N/A	N/A
On-site users – Future commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	N/A	N/A	Very low risk	N/A	N/A
On-site users – Future commercial users Inhalation of ground gases.	N/A	N/A	Very low risk	N/A	N/A
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Low risk	Low to moderate/ low risk	Low risk	Neutral to minor adverse	Neutral
Controlled waters – surface waters – North Soak Drain, Sheffield and South Yorkshire	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Navigation/ Stainforth and Keadby Canal and South Soak Drain (off-site) and abstraction (off-site) Groundwater migration, direct run-off from site.					
Ecological receptors – LWS Vertical and lateral migration, direct contact.	Low risk	Low risk	Low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Aggressive ground conditions.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Buildings, foundations and services (off-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Future property receptors – Buildings, foundations and services (off-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance				Neutral to minor adverse	Neutral

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.33: Risk and impact assessment for the current marina and wharf (S12) located within the Proposed Development Site boundary

Site ID (IDS)	S12								
Site group	Industrial site – current marina and wharf including current warehouse, former railway and gasometer and infilled pond located within the Proposed Development Site boundary								
Site title (Site ID) and land use class	Current PD Ports Marina and wharf including current warehouse, former railway and gasometer and infilled pond – (S12) Class 2.								
Site title (Site ID)	Human receptor	Groundwater, including	Surface water,	Ecological	Property e.g.				
	(on-site, adjacent and/ or <50m)	aquifer designation, and active groundwater abstractions (within 1km)	including watercourses (on- site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	designation (on-site, adjacent and/ or <50m)	buildings and structures (on-site, adjacent and/ or <50m)				
Current PD Ports Marina and wharf including current warehouse and former railway and	Current commercial users at PD Ports Marina (on-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	Unnamed drains (on- site)	Ramsar, SAC and SSSI: Humber Estuary (off- site)	PD Ports Marina buildings (on- site)				



gasometer and infilled pond – (S12)	Current residential users (off-site)	Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	River Trent (Humber Upper) (off-site, adjacent)	LWS (both off-site);	Residential buildings (off-site)
	Current commercial users (public house) (off- site)		Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off- site, adjacent) Two surface water abstractions (not potable) (off-site, 90m north-east)	Keadby Wetland Stainforth and Keadby Canal Corridor	Commercial building (off-site) Future Proposed Development foundations and services (on-site)

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S12 is located partly within and partly outside of the Proposed Development Site boundary. Approximately a third of S12 is located within the Proposed Development Site boundary which has been proposed for a haulage route and transport offloading.



As this area does not currently have any access road, it has been assumed that cut operations are likely in this area. Therefore, S12 has been conservatively assessed as being 'within' the Proposed Development Site boundary.



Table 13C.34: Baseline CSM: current marina and wharf (S12) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Railway land can be impacted by fuels, lubricants, metals and asbestos as well as the preservatives such as creosote Ports Marin Prots Ma	Commercial users at PD Ports Marina	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
		Inhalation of ground gases.	Low likelihood	Mild	Low risk
	Off-site users – Current residential users	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
sleepers and herbicides.		Direct contact, ingestion, inhalation of	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other		Inhalation of ground gases.	Unlikely	Mild	Very low risk
waste. Marinas can be	Off-site users – Current commercial users (public house)	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
impacted by metals and metalloids, inorganic chemicals, asbestos, phenol, PAH, TPH and PCB.		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
Potential for some elevated	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
carbon dioxide and methane	Bedrock Secondary B				
from fill materials of former railway land and infilled pond.	Controlled waters – surface waters – River Trent (Humber Upper) (off-site, adjacent)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site, adjacent) Two surface water abstractions (not potable) (off-site, 90m north-east)	Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters – Unnamed drains (on- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off- site)	Vertical and lateral migration, direct contact.	Low likelihood	Medium	Moderate/ low risk
	Ecological receptors – Keadby Wetland LWS and Stainforth and Keadby Canal Corridor LWS (off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Property receptors – Buildings, foundations and services (off-site)	Exposure to explosive gases.	Unlikely	Mild	Very low risk
		Aggressive ground conditions.	Unlikely	Mild	Very low risk

¹ Site is assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.35: During construction CSM: current marina and wharf (S12) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination.		Direct contact, ingestion, inhalation of dust/ vapour with/ from	Unlikely	Medium	Low risk
Low potential for ground gas. Railway land can be impacted by	On-site users – Commercial users at PD Ports Marina	contaminated soils. Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Low likelihood	Mild	Low risk
asbestos as well as the preservatives such as creosote used on railway	Off-site users – Current residential users	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
sleepers and herbicides.		Direct contact, ingestion, inhalation of	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other waste. Marinas can be impacted by metals and metalloids, inorganic chemicals, asbestos, phenol, PAH, TPH and PCB.		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Off-site users – Current commercial users (public house)	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
Potential for some elevated	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Mild	Low to moderate/ risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
carbon dioxide and methane	Bedrock Secondary B				
from fill materials of former railway land and infilled	Controlled waters – surface waters –	Groundwater			
pond.	River Trent (Humber Upper) (off-site, adjacent)	migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters –				
	Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site, adjacent)	Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk
	Two surface water abstractions (not potable) (off-site, 90m north-east)	nom one.			



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Controlled waters – surface waters – Unnamed drains (on- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off- site)	Vertical and lateral migration, direct contact.	Low likelihood	Medium	Moderate/ low risk
	Ecological receptors – Keadby Wetland LWS and Stainforth and Keadby Canal Corridor LWS (off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk
Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk	

- ¹ Site investigation will be required prior to construction of the Proposed Development. This should include further groundwater and gas monitoring.
- ² S12 partly lies within the footprint of the Proposed Development and therefore may require remediation in the areas located within the Proposed Development Site boundary.
- ³ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ⁴ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.
- ⁵ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁶ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to



Source	Receptor	Pathway		Consequence (Severity)	Risk during construction
--------	----------	---------	--	------------------------	--------------------------

unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.

⁷ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources which may cause a temporary worsening in groundwater quality compared to baseline.

⁸ The potential for ground gas from S12 is not considered significant enough to result in an increased risk during construction.



Table 13C.36: Post-construction CSM: current marina and wharf (S12) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination.		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Low potential for ground gas. Railway land can be impacted by	On-site users – Commercial users at PD Ports Marina	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
fuels, lubricants, metals and		Inhalation of ground gases.	Low likelihood	Mild	Low risk
as the preservatives such as creosote used on railway	asbestos as well as the preservatives such as creosote Off-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
sleepers and herbicides.		Direct contact, ingestion, inhalation of	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Railway embankments		vapour with/ from contaminated waters.			
may contain material high in ash and other		Inhalation of ground gases.	Unlikely	Mild	Very low risk
waste. Marinas can be impacted by	Off-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
metals and metalloids, inorganic chemicals,	Current commercial users (public house)	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
asbestos, phenol, PAH, TPH and PCB.		Inhalation of ground gases.	Unlikely	Minor	Very low risk
Potential for some elevated	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
carbon dioxide and methane	Bedrock Secondary B				
from fill materials of former railway land and infilled pond.	Controlled waters – surface waters – River Trent (Humber Upper) (off-site, adjacent)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site, adjacent) Two surface water abstractions (not potable) (off-site, 90m north-east)	Groundwater migration, direct run-off from site.	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters – Unnamed drains (on- site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Ecological receptors – Ramsar, SAC and SSS Humber Estuary (off- site)	Vertical and lateral migration, direct contact.	Low likelihood	Medium	Moderate/ low risk
	Ecological receptors – Keadby Wetland LWS and Stainforth and Keadby Canal Corridor LWS (off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk
	Buildings, foundations and services (on-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Property receptors – Buildings, foundations and services (off-site) Future property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk
		Aggressive ground conditions.	Unlikely	Mild	Very low risk
		Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.

³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.



Source	Receptor	Pathway	Consequence (Severity)	Risk post- construction

⁴ Assumes that for the areas of S12 located outside of the Proposed Development Site boundary, the risks to the identified receptors will be as it was at baseline, as no direct intervention to remediate these areas will have taken place.

⁵ The on-site current commercial users and buildings at PD Ports Marina are located entirely within/ nearby the area of S12 outside of the Proposed Development Site boundary. Therefore, no beneficial effects from remediation are considered likely.



Table 13C.37: Current marina and wharf (S12) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site users – Commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
On-site users – Commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low risk	Low risk	Low risk	Neutral	Neutral
On-site users – Commercial users Inhalation of ground gases.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Residential users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Residential users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low risk	Low risk	Low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Residential users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Commercial users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Low risk	Low to moderate/ risk	Low risk	Neutral to minor adverse	Neutral
Controlled waters – surface waters – River Trent (Humber Upper) (off-site)	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Groundwater migration, direct run-off from site.					
Controlled waters – surface waters – Sheffield and South Yorkshire Navigation/ Stainforth and Keadby Canal (off-site), abstractions (off-site)	Low risk	Low risk	Low risk	Neutral	Neutral
Groundwater migration, direct run-off from site.					
Controlled waters – surface waters – unnamed drains (on-site)	Low risk	Low risk	Low risk	Neutral	Neutral
Groundwater migration, direct run-off from site.					
Ecological receptors – Ramsar, SAC and SSSI Vertical and lateral migration, direct contact.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
Ecological receptors – LWS Vertical and lateral migration, direct contact.	Low risk	Low risk	Low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (on-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Property receptors – Buildings, foundations and services (on-site) Aggressive ground conditions.	Low risk	Low risk	Low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Aggressive ground conditions.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Foundations and services (on-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A
Future property receptors – Foundations and services (on-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Overall significance				Neutral to minor adverse	Neutral

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.38: Risk and impact assessment for the current pumping station (S14) located within the Proposed Development Site boundary

Site ID (IDS)	S14	S14							
Site group	Light industrial site – current pumping station located within the Proposed Development Site boundary								
Site title (Site ID) and land use class	Current pumping sta	Current pumping station – (S14) Class 1.							
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (onsite, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)				
Current pumping station – (S14)	Current residential users (off-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	River Trent (Humber Upper) (off-site) Two surface water abstractions (not	Ramsar, SAC and SSSI: Humber Estuary (off- site)	Pumping station building (on-site)				



	Bedrock geology (Mercia	potable) (off-site, 20m	Residential
	Mudstone Formation) –	east)	buildings (off-
	Secondary B aquifer		site)
		Two surface water	
		abstractions (not	Future Proposed
		potable) (off-site,	Development
		220m north-east)	foundations and
			services (on-site)

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S14 is located entirely within the Proposed Development Site boundary.



Table 13C.39: Baseline CSM: current pumping station (S14) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
ground gas. Off-site users –	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
organic contaminants		Inhalation of ground gases.	Unlikely	Minor	Very low risk
including metals, ammonia, acids, asbestos, TPH, solvents, fuel oils and alkalis.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters –				
	River Trent (Humber Upper) (off-site)	Groundwater	Unlikely	Medium	Low risk
	Surface water abstractions (not potable) (off-site, 20m to 220m distance)	migration, direct run-off from site.		Wediam	LOW HSK
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off- site)	Vertical and lateral migration, direct contact.	Unlikely	Medium	Low risk
	Property receptors – Buildings, foundations and services (off-site)	Exposure to explosive gases.	Unlikely	Mild	Very low risk
		Aggressive ground conditions.	Unlikely	Mild	Very low risk
Notes/ assump	tions;	<u> </u>			I .



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
--------	----------	---------	-----------------------------	------------------------	------------------

¹ Site is assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.40: During construction CSM: current pumping station (S14) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Mild	Very low risk
ground gas. Off-site user	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
organic contaminants		Inhalation of ground gases.	Unlikely	Mild	Very low risk
including metals, ammonia, acids, asbestos, TPH, solvents, fuel oils and alkalis.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely to low likelihood	Mild	Very low to low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction		
	Controlled waters – surface waters –						
	River Trent (Humber Upper) (off-site)	from site.	Unlikely	Medium	Low risk		
	Surface water abstractions (not potable) (off-site, 20m to 220m distance)				LOW HOK		
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off- site)	Vertical and lateral migration, direct contact.	Unlikely	Medium	Low risk		
	Property receptors –	Exposure to explosive gases.	Unlikely	Mild	Very low risk		
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Mild	Very low risk		
Notes/ assum	Notes/ assumptions;						



Source	Receptor	Pathway		Consequence (Severity)	Risk during construction
--------	----------	---------	--	---------------------------	--------------------------

¹ Site investigation will be required prior to construction of the Proposed Development.

- ² S14 is located within the footprint of the Proposed Development and therefore may require remediation in this area.
- ³ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ⁴ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.
- ⁵ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁶ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁷ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources which may cause a temporary worsening in groundwater quality compared to baseline.
- ⁸ The potential for ground gas from S14 is not considered significant enough to result in an increased risk during construction.



Table 13C.41: Post-construction CSM: current pumping station (S14) located within the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Low potential for		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Minor to mild	Very low risk
ground gas. Potential for inorganic and	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Minor to mild	Very low risk
organic contaminants		Inhalation of ground gases.	Unlikely	Minor	Very low risk
including metals, ammonia, acids, asbestos, TPH, solvents, fuel oils and alkalis.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely	Minor to mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters –				
	River Trent (Humber Upper) (off-site)	Groundwater migration, direct run-off	Unlikely Me	Medium	Low risk
	Surface water abstractions (not potable) (off-site, 20m to 220m distance)	from site.		Mediam	LOW HISK
	Ecological receptors – Ramsar, SAC and SSSI: Humber Estuary (off- site)	Vertical and lateral migration, direct contact.	Unlikely	Medium	Low risk
E	Property receptors –	Exposure to explosive gases.	Unlikely	Minor to mild	Very low risk
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Minor to mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Foundations and services (on-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.

³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.



Table 13C.42: Current pumping station (S14) located within the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Residential users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Residential users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Residential users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Very low risk	Very low to low risk	Very low risk	Neutral to minor adverse	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – surface waters – River Trent (Humber Upper) (off-site), abstractions (off-site)	Low risk	Low risk	Low risk	Neutral	Neutral
Groundwater migration, direct run-off from site. Ecological receptors – Ramsar, SAC and SSSI Vertical and lateral migration, direct contact.	Low risk	Low risk	Low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Aggressive ground conditions.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Foundations and services (on-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Future property receptors – Foundations and services (on-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance				Neutral to minor adverse	Neutral

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.

² The post-construction significance column assumes remediation required has been undertaken and the benefits of remediation realised. Assumes construction works are complete.



Table 13C.43: Risk and impact assessment for the historic landfills (S3, S7 and S8) located outside of the Proposed Development Site boundary

Site ID (IDS)	S3, S7, S8								
Site group	Landfill sites – histe	oric landfills located outside of the Prop	oosed Development Site	boundary					
Site title (Site ID) and land use class	included inert and in	Historic Landfill and Licensed Waste Management Facility - John Brown Engineering Landfill. Deposited waste included inert and industrial waste, and liquid sludge – (S3) Class 3. Historic Landfill Site - PFA Settlement Lagoon – (S7) Class 3. Historic Landfill Site - Keadby Power Station – (S8) Class 3.							
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (onsite, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)				
Historic Landfill and	Current public open space users	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	Unnamed drain (off- site)	None	Future Proposed				



Licensed Waste Management Facility - John Brown Engineering Landfill - (S3)	at Keadby Common (on-site and off-site) Future commercial users of Proposed Development (off-site)	Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	North Soak Drain (off-site) Surface water abstraction (not potable) (off-site, 210m south)		Development foundations and services (off-site)
Historic Landfill Site - PFA Settlement Lagoon – (S7)	Current public open space users at Keadby Common (on- site) Future commercial users of Proposed Development (off-site)	Superficial geology (Alluvium/ Warp) – Secondary A aquifer Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	Various unnamed drains (off-site) No surface water abstractions present within 250m of the site.	None	Future Proposed Development buildings (off- site)
Historic Landfill Site - Keadby Power Station – (S8)	Current public open space users at Keadby	Superficial geology (Alluvium/ Warp) – Secondary A aquifer	Unnamed drain (offsite) No surface water abstractions present	None	None



Common (on-site and off-site)	Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	within 250m of the site.	

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

²S3, S7 and S8 are located entirely outside of the Proposed Development Site boundary.



Table 13C.44: Baseline CSM: historic landfills (S3, S7 and S8) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Ground gas.	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfills known to contain inert and industrial waste and liquid sludge. Potential for a range	Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
of inorganic and organic		Inhalation of ground gases.	Unlikely	Mild	Very low risk
contaminants including but not limited to metals,	Off-site users –	Direct contact, ingestion, inhalation of dust/	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
metalloids, acids, organic compounds, inorganic	Public open space users at Keadby Common	vapour with/ from contaminated soils.			
compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils, alkalis, VOC, SVOC, PCB, dioxins, furans, methane, hydrogen		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
sulphide and carbon dioxide.		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk
	В	and watere.			



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters – Various unnamed drains (off-site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk
	Controlled waters – surface waters – North Soak Drain (off-site) Surface water abstraction (not potable) (off-site, 210m distance)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk

¹ Sites are assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.45: During construction CSM: historic landfills (S3, S7 and S8) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Ground gas.	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfills known to contain inert and industrial waste and liquid sludge. Potential for a range	Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
of inorganic and organic		Inhalation of ground gases.	Unlikely	Mild	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
contaminants including but not limited to metals, metalloids, acids, organic compounds, inorganic	Off-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
compounds, asbestos, TPH, PAH, solvents, lubricants, fuel oils, alkalis, VOC, SVOC, PCB, dioxins, furans, methane, hydrogen	Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
sulphide and carbon dioxide.		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Controlled waters – groundwater – Superficial Secondary A	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood to likely	Medium	Moderate/ low to moderate risk



Bedrock Secondary B Controlled waters – surface waters – Various unnamed drains (off-site) Controlled waters – surface waters – North Soak Drain (off-site) Surface water abstraction (not potable) (off-site, Groundwater migration, direct run-off from site. Low likelihood Mild Low risk Low risk Low likelihood Medium Moderate/ lo Moderate/ lo	Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Surface waters – Various unnamed drains (off-site) Controlled waters – surface waters – North Soak Drain (off-site) Surface water abstraction (not Groundwater migration, direct run-off from site. Low likelihood Mild Low risk Low risk Low likelihood Mild Low risk Low likelihood Mild Low risk Low likelihood Mild Low risk						
Surface waters – North Soak Drain (off-site) Surface water abstraction (not Groundwater migration, direct run-off from site. Low likelihood Medium Moderate/ lo		surface waters – Various unnamed	migration, direct	Low likelihood	Mild	Low risk
210m distance)		surface waters – North Soak Drain (off-site) Surface water abstraction (not potable) (off-site,	migration, direct	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
--------	----------	---------	--------------------------	------------------------	--------------------------

- ¹ As these sites are located outside of the Proposed Development Site boundary, it is assumed that no ground investigations or remediation will be undertaken on these sites. However, these sites may have the potential to influence conditions on the Proposed Development Site during construction.
- ² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.
- ³ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.
- ⁴ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.
- ⁵ While a CEMP will make it unlikely that there will be adverse consequences resulting from construction there may still be temporary minor adverse effects from ground disturbance in these areas. The adoption of a CEMP generally results in a low to unlikely probability of a consequence, but in some cases the actual consequence may temporarily increase from that defined at baseline.
- ⁶ It is assumed that earthworks may require cut operations anywhere within the Proposed Development boundary which might temporarily worsen groundwater quality, for example, as a result of dewatering activities, which may potentially draw contaminated groundwater away from the sources (including sources outside of the Proposed Development Site boundary) or alter ground gas pathways which may cause a temporary worsening in groundwater quality or increased ground gas risk compared to baseline.



Table 13C.46: Post-construction CSM: historic landfills (S3, S7 and S8) located outside the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Ground gas.	On-site users –	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low likelihood	Medium	Moderate/ low risk
Landfills known to contain inert and industrial waste and liquid sludge. Potential for a range	Public open space users at Keadby Common	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
of inorganic and organic		Inhalation of ground gases.	Unlikely	Mild	Very low risk
contaminants including but not limited to metals,	Off-site users –	Direct contact, ingestion, inhalation of dust/	Unlikely	Medium	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
organic compounds, u	Public open space users at Keadby Common	vapour with/ from contaminated soils.			
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Mild	Very low risk
sulphide and carbon dioxide.		Inhalation of ground gases.	Unlikely	Mild	Very low risk
	Off-site users – Future commercial users of Proposed Development	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Minor	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Minor	Very low risk
		Inhalation of ground gases.	Unlikely	Minor	Very low risk
	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk
	Controlled waters – surface waters – Various unnamed drains (off-site)	Groundwater migration, direct run-off from site.	Low likelihood	Mild	Low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters –				
	North Soak Drain (off-site)	Groundwater migration, direct	Low likelihood	Medium	Moderate/ low risk
	Surface water abstraction (not potable) (off-site, 210m distance)	run-off from site.	Low intellinous		
	Future property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (off-site)	ations and Aggressive ground		Minor	Very low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
--------	----------	---------	-----------------------------	------------------------	----------------------------

² Assumes for sites outside of the Proposed Development Site boundary that upon completion of construction, the risk from this group of sites to the identified receptors will be as it was at baseline, as no direct intervention to remediate these sites will have taken place.



Table 13C.47: Historic landfills (S3, S7 and S8) located outside of the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
On-site users – Public open space users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Public open space users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Public open space users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Off-site users – Future commercial users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	N/A	N/A	Very low risk	N/A	N/A
Off-site users – Future commercial users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	N/A	N/A	Very low risk	N/A	N/A
Off-site users – Future commercial users Inhalation of ground gases.	N/A	N/A	Very low risk	N/A	N/A
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low to moderate risk	Moderate/ low risk	Neutral to minor adverse	Neutral
Controlled waters – surface waters – unnamed drains (off-site)	Low risk	Low risk	Low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Groundwater migration, direct run-off from site.					
Controlled waters – surface waters – North Soak Drain (off-site), abstraction (off-site) Groundwater migration, direct run-off from site.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
Future property receptors – Foundations and services (off-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A
Future property receptors – Foundations and services (off-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance	Neutral to minor adverse	Neutral			

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.



Table 13C.48: Risk and impact assessment for the potential current tanks (S22) located outside of the Proposed Development Site boundary

Site ID (IDS)	S22							
Site group	Industrial site –	potential current tanks locate	ed outside of the Proposed Develop	oment Site bound	lary			
Site title (Site ID) and land use class	Potential currer	Potential current tanks – (S22) Class 3.						
Site title (Site	Human	Groundwater, including	Surface water, including	Ecological	Property e.g.			
ID)	receptor (on-site, adjacent and/ or <50m)	aquifer designation, and active groundwater abstractions (within 1km)	watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	designation (on-site, adjacent and/ or <50m)	buildings and structures (on-site, adjacent and/ or <50m)			



	Current	Superficial geology	Torne/ Three Rivers (includes	Three Rivers	Residential
	residential	(Alluvium/ Warp) –	South Engine Drain and Folly	LWS (off-site)	buildings (off-
	users (off-	Secondary A aquifer	Drain) (off-site)		site)
Potential	site)				
current tanks – (S22)		Bedrock geology (Mercia Mudstone Formation) – Secondary B aquifer	No surface water abstractions present within 250m of the site.		

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S22 is located entirely outside of the Proposed Development Site boundary.



Table 13C.49: Baseline CSM: potential current tanks (S22) located outside the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination.	and groundwater contamination. Low potential for ground gas. Off-site users – Current residential users Potential for inorganic and	Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Low potential for ground gas.		Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
inorganic and organic		Inhalation of ground gases.	Unlikely	Minor	Very low risk
contaminants including lead, fuels/ TPH, PAH.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Controlled waters – surface waters – Torne/ Three Rivers (includes South Engine Drain and Folly Drain) (off-site)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Ecological receptors – Three Rivers LWS (off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Buildings, foundations - and services (off-site)	Exposure to explosive gases.	Unlikely	Minor	Very low risk
		Aggressive ground conditions.	Low likelihood	Mild	Low risk

¹ Sites are assessed against baseline condition without construction of the Proposed Development.



urce Receptor Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
-----------------------	-----------------------------	------------------------	------------------

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.50: During construction CSM: potential current tanks (S22) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination.		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Low potential for ground gas.	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
Potential for inorganic and organic		Inhalation of ground gases.	Unlikely	Minor	Very low risk
contaminants including lead, fuels/ TPH, PAH.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Controlled waters – surface waters – Torne/ Three Rivers (includes South Engine Drain and Folly Drain) (off-site)	Groundwater migration, direct run-off from site.	Low likelihood	Medium	Moderate/ low risk
	Ecological receptors – Three Rivers LWS (off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors – Buildings, foundations and services (off-site)	Exposure to explosive gases.	Unlikely	Minor	Very low risk
		Aggressive ground conditions.	Low likelihood	Mild	Low risk

¹ As S22 is located outside of the Proposed Development Site boundary, it is assumed that no ground investigations or remediation will be undertaken.



Source	Receptor	Pathway	Probability	Consequence	Risk during
		,	(Likelihood)	(Severity)	construction

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

³ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.

⁴ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.

⁵ Due to the proximity of S22 from the proposed haulage route and transport offloading area (approximately 190m), it is unlikely that S22 would present an impact on the Proposed Development Site during construction.



Table 13C.51: Post-construction CSM: potential current tanks (S22) located outside the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination.		Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Unlikely	Medium	Low risk
Low potential for ground gas.	Off-site users – Current residential users	Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Unlikely	Medium	Low risk
Potential for inorganic and organic		Inhalation of ground gases.	Unlikely	Minor	Very low risk
contaminants including lead, fuels/ TPH, PAH.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Low likelihood	Medium	Moderate/ low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Controlled waters – surface waters – Torne/ Three Rivers (includes South Engine Drain and Folly Drain) (off-site) Groundwater migration, direct run-off from site.		Low likelihood	Medium	Moderate/ low risk
	Ecological receptors – Three Rivers LWS (off-site)	Vertical and lateral migration, direct contact.	Low likelihood	Mild	Low risk
	Property receptors –	Exposure to explosive gases.	Unlikely	Minor	Very low risk
	Buildings, foundations and services (off-site)	Aggressive ground conditions.	Low likelihood	Mild	Low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Source	Receptor	Pathway		Consequence (Severity)	Risk post- construction
--------	----------	---------	--	------------------------	----------------------------

² Assumes for sites outside of the Proposed Development Site boundary that upon completion of construction, the risk from this group of sites to the identified receptors will be as it was at baseline, as no direct intervention to remediate these sites will have taken place.



Table 13C.52: Potential current tanks (S22) located outside of the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Off-site users – Residential users Direct contact, ingestion, inhalation of dust/ vapour with/ from contaminated soils.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Residential users Direct contact, ingestion, inhalation of vapour with/ from contaminated waters.	Low risk	Low risk	Low risk	Neutral	Neutral
Off-site users – Residential users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – surface waters – Torne/ Three Rivers (includes South Engine Drain and Folly Drain) (off-site) Groundwater migration, direct run-off from site.	Moderate/ low risk	Moderate/ low risk	Moderate/ low risk	Neutral	Neutral
Ecological receptors – LWS Vertical and lateral migration, direct contact.	Low risk	Low risk	Low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Property receptors – Buildings, foundations and services (off-site) Aggressive ground conditions.	Low risk	Low risk	Low risk	Neutral	Neutral
Overall significance	1	ı	ı	Neutral	Neutral

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.



Table 13C.53: Risk and impact assessment for the current pumping station (S18) located outside of the Proposed Development Site boundary

Site ID (IDS)	S18					
Site group	Light industri	ial site – current pumping sta	ation located outside of the Prop	osed Developme	nt Site boundary	
Site title (Site ID) and land use class	Current pum	Current pumping station – (S18) Class 1.				
Site title (Site ID)	Human receptor (on-site, adjacent and/ or <50m)	Groundwater, including aquifer designation, and active groundwater abstractions (within 1km)	Surface water, including watercourses (on-site, adjacent and/ or <50m) and active surface water abstractions (within 250m)	Ecological designation (on-site, adjacent and/ or <50m)	Property e.g. buildings and structures (on-site, adjacent and/ or <50m)	



	None	Superficial geology	None	None	Future Proposed
		(Alluvium/ Warp) –			Development building
Current		Secondary A aquifer			foundations and
pumping					services (off-site)
station -					
(S18)		Bedrock geology (Mercia			
		Mudstone Formation) –			
		Secondary B aquifer			

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² S18 is located entirely outside of the Proposed Development Site boundary.



Table 13C.54: Baseline CSM: current pumping station (S18) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
Soil, leachate and groundwater contamination. Low potential for ground gas. Potential for inorganic and organic contaminants including metals, ammonia, acids, asbestos, TPH, solvents, fuel oils and alkalis.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely	Mild	Very low risk

¹ Site is assessed against baseline condition without construction of the Proposed Development.



	Source Pathway Probability Consequence (Likelihood) Risk at baseline
--	--

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.



Table 13C.55: During construction CSM: current pumping station (S18) located outside the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Soil, leachate and groundwater contamination. Low potential for ground gas. Potential for inorganic and organic contaminants including metals, ammonia, acids, asbestos, TPH, solvents, fuel oils and alkalis.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely	Mild	Very low risk

¹ As S18 is located outside of the Proposed Development Site boundary, it is assumed that no ground investigations or remediation will be undertaken.



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
--------	----------	---------	--------------------------	------------------------	--------------------------

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

³ During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.

⁴ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.

⁵ Due to the very low potential for contamination from S18, it is unlikely that S18 would have the potential to influence groundwater conditions on the Proposed Development Site during construction, despite the proximity to the cooling water discharge pipeline (approximately 5m).



Table 13C.56: Post-construction CSM: current pumping station (S18) located outside of the Proposed Development Site boundary

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Soil, leachate and groundwater contamination. Low potential for ground gas.	Controlled waters – groundwater – Superficial Secondary A Bedrock Secondary B	Leaching, vertical and lateral migration from contaminated soils and waters.	Unlikely	Mild	Very low risk
Potential for inorganic and organic contaminants	Future property	Exposure to explosive gases.	Unlikely	Minor	Very low risk
including metals, ammonia, acids, asbestos, TPH, solvents, fuel oils and alkalis.	receptors – Foundations and services (off-site)	Aggressive ground conditions.	Unlikely	Minor	Very low risk
Notes/ assumptions;	<u> </u>	<u> </u>	<u>l</u>	<u>l</u>	<u> </u>



Source Receptor Pathway Probability Consequence (Severity) Risk post-construction	Source	Receptor	Pathway			
---	--------	----------	---------	--	--	--

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes for sites outside of the Proposed Development Site boundary that upon completion of construction, the risk from this group of sites to the identified receptors will be as it was at baseline, as no direct intervention to remediate these sites will have taken place.



Table 13C.57: Current pumping station (S18) located outside of the Proposed Development Site boundary – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
Controlled waters – groundwater Secondary A and B aquifers Leaching, vertical and lateral migration from contaminated soils and waters.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Foundations and services (off-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A
Future property receptors – Foundations and services (off-site) Aggressive ground conditions.	N/A	N/A	Very low risk	N/A	N/A
Overall significance	Neutral	Neutral			

¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction.



Table 13C.58: Risk and impact assessment for peat deposits located within and outside of the Proposed Development Site

Site title and land use class	Peat deposits – Class 1.					
Site title	Human receptor	Property e.g. buildings and structures				
	(adjacent and/ or <50m)	(adjacent and/ or <50m)				
	Current commercial users at Keadby 1 and Keadby 2	Keadby 1 and Keadby 2 Power Station buildings and				
	Power Station	services				
	Current residential users (eastern-most extent of the Proposed Development Site)	Residential buildings				
Peat deposits	Other current commercial users (eastern-most extent	Tresidential buildings				
	of the Proposed Development Site)	Other commercial buildings				
	Public open space users at Keadby Common	Caror commercial ballange				
	Future commercial users of Proposed Development	Future Proposed Development buildings and services				
Notes/ assumptions;						



- ¹ Peat deposits may be found anywhere within the Proposed Development Site boundary or study area. Peat has previously been encountered in isolated areas, up to 1.6m thickness in the superficial deposits.
- ² Ground gas is the only potential contamination source from marshlands/ peat deposits. Therefore, the other pathways are excluded from the assessment.



Table 13C.59: Baseline CSM: peat deposits located within and outside of the Proposed Development Site

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	On-site and off-site users –				
Potential low levels of ground gas – methane and carbon dioxide.	Current commercial users at Keadby 1 and Keadby 2 Power Station	Inhalation of ground gases	Unlikely to low likelihood	Mild	Very low to low risk
	Other current commercial users (eastern-most extent of the Proposed Development Site)				
	On-site and off-site users – Current residential users (eastern-most extent of the	Inhalation of ground gases	Unlikely to low likelihood	Mild	Very low to low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk at baseline
	Proposed Development Site)				
	On-site and off-site users – Public open space users at Keadby Common	Inhalation of ground gases	Unlikely	Minor	Very low risk
	On-site and off-site property receptors – Keadby 1 and Keadby 2 Power Station buildings and services Residential buildings Other commercial buildings	Exposure to explosive gases	Unlikely	Minor	Very low risk



Source Receptor Pathway	nsequence everity) Risk at baseline
-------------------------	--

¹ Sites are assessed against baseline condition without construction of the Proposed Development.

² 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary. The on-site and off-site receptors were considered to have the same risk at baseline outcome. Therefore, have been assessed together within the same row.



Table 13C.60: During construction CSM: peat deposits located within and outside of the Proposed Development Site

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
Potential low levels of ground gas – methane and carbon dioxide.	On-site and off-site users – Current commercial users at Keadby 1 and Keadby 2 Power Station Other current commercial users (eastern-most extent of the Proposed	Inhalation of ground gases	Unlikely to low likelihood	Mild	Very low to low risk
	On-site and off-site users – Current residential users (eastern-most extent of the	Inhalation of ground gases	Unlikely to low likelihood	Mild	Very low to low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk during construction
	Proposed Development Site)				
On-site and off-site users – Public open space users at Keadby Common		Inhalation of ground gases	Unlikely	Minor	Very low risk
	On-site and off-site property receptors – Keadby 1 and Keadby 2 Power Station buildings and services	Exposure to explosive gases	Unlikely	Minor	Very low risk
	Residential buildings Other commercial buildings				



Source Receptor Pathway	Probability Consequence Risk during (Likelihood) (Severity) construction
-------------------------	--

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² During construction, standard mitigation procedures are assumed to be implemented in accordance with a CEMP.

³ Construction workers have been excluded from the assessment due to the use of PPE/risk management protocols and in accordance with CIRIA C692, 2010.

⁴ The potential for ground gas from peat deposits is not considered significant enough to result in an increased risk during construction.



Table 13C.61: Post-construction CSM: peat deposits located within and outside of the Proposed Development Site

Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
Potential low levels of ground gas – methane and carbon dioxide.	On-site and off-site users – Current commercial users at Keadby 1 and Keadby 2 Power Station Other current commercial users (eastern-most extent of the Proposed Development Site)	Inhalation of ground gases	Unlikely to low likelihood	Mild	Very low to low risk
	On-site and off-site users – Current residential users (eastern-most extent of the Proposed Development Site)	Inhalation of ground gases	Unlikely to low likelihood	Mild	Very low to low risk
	On-site and off-site users – Public open space users at Keadby Common	Inhalation of ground gases	Unlikely	Minor	Very low risk
	On-site and off-site users –	Inhalation of ground gases	Unlikely	Minor	Very low risk



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
	Future commercial users at of Proposed Development				
	On-site and off-site property receptors –				
	Keadby 1 and Keadby 2 Power Station buildings and services	Exposure to explosive gases	Unlikely	Minor	Very low risk
	Residential buildings Other commercial buildings				
	On-site and off-site property receptors – Future Proposed Development buildings and services	Exposure to explosive gases	Unlikely	Minor	Very low risk

¹ 'On-site' and 'off-site' are terms used here to describe whether a receptor is at or adjacent (within 50m) of the potential areas of contamination being assessed. It does not refer to whether the receptor is within or outside of the Proposed Development Site boundary.

² Assumes construction works are complete and remediation has been carried out where necessary on areas within the Proposed Development boundary.



Source	Receptor	Pathway	Probability (Likelihood)	Consequence (Severity)	Risk post- construction
--------	----------	---------	-----------------------------	------------------------	----------------------------

³ A range may be given as remediation strategies will vary in design. Remediation strategies may involve source removal or pathway intervention as appropriate.

⁴ Assumes that for the peat areas located outside of the Proposed Development Site boundary, that upon completion of construction the risks to the identified receptors will be as it was at baseline, as no direct intervention to remediate these areas will have taken place.



Table 13C.62: Peat deposits located within and outside of the Proposed Development Site – significance of effect assessment

Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance
On-site and off-site users – Commercial users Inhalation of ground gases.	Very low to low risk	Very low to low risk	Very low to low risk	Neutral	Neutral
On-site and off-site users – Residential users Inhalation of ground gases.	Very low to low risk	Very low to low risk	Very low to low risk	Neutral	Neutral
On-site and off-site users – Public open space users Inhalation of ground gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
On-site and off-site users – Future commercial users Inhalation of ground gases.	N/A	N/A	Very low risk	N/A	N/A
Property receptors – Buildings and services (on-site and off-site) Exposure to explosive gases.	Very low risk	Very low risk	Very low risk	Neutral	Neutral
Future property receptors – Buildings and services (on-site and off-site) Exposure to explosive gases.	N/A	N/A	Very low risk	N/A	N/A



Contaminant linkage	Baseline risk	Construction risk	Post- construction risk	Construction significance	Post- construction significance		
Overall significance Neutral Neutral							
Notes/ assumptions;							
¹ The construction column assumes that a CEMP will be in place to mitigate impacts from construction							