# East Midlands Gateway Phase 2 (EMG2)

Document DCO 6.14I/MCO 6.14I

**ENVIRONMENTAL STATEMENT** 

**Technical Appendices** 

Appendix 14I

# EMG1 Factual Ground Investigation Report

October 2025



The East Midlands Gateway Phase 2 and Highway Order 202X and The East Midlands Gateway Rail Freight and Highway (Amendment) Order 202X





**Roxhill Developments Limited** 

# East Midlands Gateway Strategic Rail Freight Interchange

# **Zone 1 Main Development Plateau** and Rail Freight Terminal

Factual Ground Investigation Report

312494-01 - 02 (00)





#### **RSK GENERAL NOTES**

Project No.:	312494	1/1 – 02 (00)		
Title:	Zone 1	idlands Gateway: Strateg Main Development Plate I Ground Investigation Re	au and Rail Freight Tern	-
Client:	Roxhill	Developments Limited		
Date:	2 <sup>nd</sup> Dec	cember 2013		
Office:	Tel No:	nvironment Limited, Abbe : 02476 505600 :t: Darren Bench	y Park, Humber Road, C	Coventry, CV3 4AQ.
Status:	Draft			
Author		Gareth Shaw Katie Foster	Technical reviewer	Darren Bench
Signature			Signature	
Date:		27 <sup>th</sup> November 2013	Date:	3 <sup>rd</sup> December 2013
Project manager		Darren Bench	Quality reviewer	Marc Steward
Signature			Signature	
Date:		3 <sup>rd</sup> December 2013	Date:	5 <sup>th</sup> December 2013

RSK Environment Limited (RSK) has prepared this report for the sole use of the client, showing reasonable skill and care, for the intended purposes as stated in the agreement under which this work was completed. The report may not be relied upon by any other party without the express agreement of the client and RSK. No other warranty, expressed or implied, is made as to the professional advice included in this report.

Where any data supplied by the client or from other sources have been used, it has been assumed that the information is correct. No responsibility can be accepted by RSK for inaccuracies in the data supplied by any other party. The conclusions and recommendations in this report are based on the assumption that all relevant information has been supplied by those bodies from whom it was requested.

No part of this report may be copied or duplicated without the express permission of RSK and the party for whom it was prepared.

Where field investigations have been carried out, these have been restricted to a level of detail required to achieve the stated objectives of the work.

This work has been undertaken in accordance with the quality management system of RSK Environment Ltd.



## **CONTENTS**

1	INT	RODUC	TION	3
	1.1	Introdu	uction	3
	1.2	Terms	of reference	3
	1.3	Propos	sed development	3
	1.4	Object	ive	4
_				
2			ILScation	
	2.1		opography, geography and geomorphology	
	2.2		escription	
	2.4		hed geology and expected ground conditions	
3			NVESTIGATION	
	3.1	Introdu	uction	11
	3.2	Investi	gation strategy and methodology	11
		3.2.1	Health and safety	12
		3.2.2	Location of exploratory hole positions and service clearance	
		3.2.3	Investigation techniques	13
		3.2.4	Zone 1 investigation	
		3.2.5	Soil sampling, in-situ testing and laboratory analysis	
		3.2.6	Instrumentation and monitoring	19
TA	BLES	S		
Tal	ole 1:	Expect	ed geology	8
Tal	ole 2:	Constr	aints to investigation	10
Tal	ole 3:	Summa	ary of soakaway test results	15
			ary of geotechnical testing programme undertaken	
			ary of analytical chemical and contamination testing programme undertaken on soil	
	-			17
			ary of analytical chemical and contamination testing programme undertaken on mples	19
_			ring well installation details	
FIC	SURE	S		
Fig	ure 1		Site location plan	
Fig	ure 2	!	Proposed development plan and zones for reporting	
Fig	ure 3	}	Zone 1 plan	
Fig	ure 4	ļ	Exploratory hole location plan	



#### **APPENDICES**

Appendix A	Service constraints
Appendix B	Provisional exploratory hole schedule
Appendix C	Trial pit logs and photographs
Appendix D	Cable percussion borehole logs
Appendix E	Rotary cored borehole logs and photographs
Appendix F	In-situ soakaway test results
Appendix G	Geotechnical laboratory testing results
Appendix H	Chemical laboratory certificates for soil analysis
Appendix I	Chemical laboratory certificates for groundwater water analysis
Appendix J	Gas and groundwater monitoring results



## 1 INTRODUCTION

#### 1.1 Introduction

RSK Environment Limited (RSK) has been commissioned by Roxhill Developments Limited (the Client) to carry out a series of Factual Ground Investigation Reports for the site of the proposed East Midlands Gateway: Strategic Rail Freight Interchange (the Main Development Site).

This report is subject to the RSK service constraints given in Appendix A.

#### 1.2 Terms of reference

This report comprises a factual report in general accordance with the requirements of;

- BS5930:1999+A2:2010 'Code of practice for site investigations'
- Environment Agency CLR 11 2004a 'Model Procedures for the Management of Land Contamination' (Contaminated Land Risk Assessment),
- Highways Agency HD22/08, 'Managing Geotechnical Risk' (Ground Investigation).
- BS EN 1997-2:2007. Eurocode 7 Geotechnical design Part 2: Ground investigation and testing.

#### 1.3 Proposed development

It is understood that the site is being considered for development to provide a Strategic Rail Freight Interchange for the East Midlands regions. This includes a large distribution warehousing complex, major trunk road improvements to the A453, A50 and M1 Junctions 24 and 24a, a new bypass to the south of Kegworth including bridge over the M1, and a new rail freight terminal and associated branch line from the Castle Donington line

For the purpose of discussion, and to facilitate reporting; the site has been divided into four Zones, on the basis of the four main elements of the proposals as follows. The extent of each of the four Zones is defined by the proposed general arrangement presented as Figure 2.

Zone 1: Main Development Plateau and Rail Freight Terminal

Zone 2: Rail Branch Line (Network Rail)

• Zone 3: Major Trunk Road Improvements



Zone 4: Kegworth Bypass including bridge over the M1

This report presents the investigation relating to Zone 1; Main Development Plateau and Rail Freight Terminal.

#### 1.4 Objective

The subject of this report is Zone 1, the proposed Main Development Plateau for the construction of distribution warehouses and the Rail Freight Terminal. In accordance with the Client's specific objectives, requirements and brief; the objective for the works was developed with the aim of providing sufficient preliminary data to:

- provide sufficient data to confirm the ground model
- obtain data to provide a chemical and geotechnical characterisation of each strata
- assist with master planning design
- provide data to support planning applications

In line with Eurocode 7, BS5930, BS10175 and CLR 11 further phases of targeted investigation (post Planning Approval) may be required to provide specific data and information for detailed design of individual elements of the scheme as the design evolves.

#### 1.5 Scope

The project has been carried out to an agreed brief as set out in RSK's proposal (ref. East Midlands Gateway; Geotechnical and Geo-environmental Services - Master Planning and EIA Support, dated 13<sup>th</sup> August 2013).

The ground investigation fieldwork carried out on Zone 1 was undertaken in general accordance with the Site Investigation Steering Group's UK Specification for Ground Investigation 2nd edition (2012), BS 5930 and A2: 2010 'Code of practice for site investigations', BS EN ISO 14688-1:2002, BS EN ISO 14689 – 1:2003 and in general accordance with the recommendations made within BS10175:2011 'Investigation of Potentially Contaminated Sites – Code of Practice'.



### 2 SITE DETAILS

#### 2.1 Site location

The Development Site covers approximately 374 hectares and currently consists of farmland with some areas of woodland. The M1 motorway, A453 runs roughly north to the east of the main development area of the site. The village of Castle Donington is situated approximately 600m to the west of the site. Hemington and Lockington villages are present directly to the north and East Midlands Airport is adjacent to the southern boundary of the site. The site location is presented within Figure 1.

Zone 1 covers an area of approximately 231Ha, the centre of which is defined by the following National Grid co-ordinates: 447330, 326660. The Zone is bound to the east by the A453 road, to the south by the East Midlands Airport; to the west and north there are no physical boundaries other than the hedgerows which form the field boundaries.

#### 2.2 Local topography, geography and geomorphology

The site sits within a formerly glaciated area signified by rolling hills created by the harder geological formations and erosion of the glacial deposits.

Zone 1 generally slopes from the high plateau where East Midlands Airport is located with a general ground level of approximately 88m AOD down to the north east which has a ground level of approximately 44m AOD. The land across Zone 1 is rolling farmland dissected by minor streams with a knoll located in the north west. Two very minor drainage ditch / streams are shown to dissect Zone 1 and appear to originate from springs or rises in the southern part of Zone 1, although they are also fed by the surrounding watershed from the rolling farm lands which they dissect. One stream originates broadly in the middle of the eastern portion of Zone 1 close to Field Farm and runs west and then north through Zone 1 and beyond through Lockington Village, whilst a second stream originates further west and follows a similar path through natural folds in the ground west then north along Zone 1 western boundary through Hemington Village.

The ground beyond the northern boundary of Zone 1 is relatively flat but for the disturbance of manmade features, forming a river terrace to the River Trent which runs broadly west to east approximately 3km north of the Zone 1. The land to the east and west of Zone 1 follows a similar rolling farm land form with a general fall to the north, although further east the land falls east toward the River Soar which flows south to north to join the River Trent.



The geological sequence of the area is understood to be one of interbedded clays, mudstones, siltstones and sandstones deposited within sea conditions and eroded by periods of glaciations and later deposition and erosion from the River Trent which has cut through the geological strata depositing Alluvium and River Gravels along its course and flood plain.

#### 2.3 Site description

A site walkover was undertaken on the 9<sup>th</sup> September 2013. Zone 1 is predominately used for arable farming with hedgerow field boundaries including a variety of small, medium and mature sized trees with occasional small areas of woodland. There is one field located in the far north west corner of Zone 1 which was used as a paddock for horses. The majority of fields were under crop or stubble from recent harvesting.

There are two main public footpaths which cross Zone 1 one east west and one north south broadly intersecting each other in the centre of Zone 1 and connecting to the nearby villages of Lockington and Castle Donington.

King Street Plantation located in the centre of Zone 1 is understood to be protected woodland comprising of mature deciduous trees.

Field Farm located in the south eastern quadrant of Zone 1 is the principal set of buildings on Zone 1. The farm is operational and buildings comprise a brick built two storey farm house with outbuildings, office and store including a small garden to the south east and courtyard to the west. The Farm House buildings are surrounded to the west and north by farm sheds, silage bays, a pond/lagoon feature and small overgrown stockpile of soil materials understood to originate from the excavation of the more recent crop drying shed footprint. The crop drying shed is a large aluminium clad grain drying store located in the south western corner of the complex and is heated by a Calor Gas system with two gas tanks being located on its north eastern corner. The larger farm buildings are predominantly steel framed and many appear to be clad and roofed in a corrugated cement bonded boards which may contain asbestos. These barns are used to house tractors, plant and machinery, seed, fertiliser and other ancillary arable farming equipment. There are an extensive number of smaller disused wooden framed former cattle sheds and large bays for the storage of silage and cattle waste together with a heavily overgrown area anticipated to house a lagoon/pond although this was not visible at the time of the walkover. The farmyard area is a combination of mainly concrete hardstanding with some more open gravel at the periphery extents. A large trailer water tank is located centrally and is understood to be topped up with mains water and utilised for spraying. Two large modern diesel tanks are present in the farm yard and are understood to be used for fuel to plant and machinery. A single large tank is located on the northern periphery of the farm yard and is used for fertiliser storage. There are a number of small containers used for storing equipment in too. No spills or obvious areas of contamination were observed and the farmyard was in good order.



A small stand of what appeared to be Japanese Knotweed is located on the perimeter of the farm garden.

Power is received via low level overhead feed from the east with an above ground small substation mounted on the pole to the east of the farm.

The farm is connected by concrete access roads to Lockington Lane in the north east and the A453 in the south east. Further farm tracks and set aside field margins are present around many of the fields affording access for farm machinery to each of the arable fields. Anecdotal evidence suggests that cattle carcases may be buried in the north eastern corner of the farm yard beneath the arising from when the drying warehouse was constructed.

The area of the airport land and the land enclosed within the Airport land in the south western corner of Zone 1 was not accessible at the time of the site walkover.

It is understood from conversations with the Farm Foreman that the farm had until 2000 been used predominantly for milk production with cattle using the fields. From 2000 the farm was turned over to arable crops. It is also understood that the area owned by the airport (formerly part of the RAF Castle Donington) had had some form of earth bunding and partially buried bunkers but that it was believed that these had been decommissioned and removed after the war with only concrete hard standing access roads still being retained.

The springs and streams locations were examined, however in the main the streams were dry or not flowing and only soft boggy ground with occasional stagnant water pools were present at the time of the visit.

#### 2.4 Published geology and expected ground conditions

The British geological Survey (BGS) plans and maps obtained have been reviewed to determine the anticipated geology beneath Zone 1.

It is envisaged that the local geology beneath Zone 1 will be in line with the summary below detailed within Table 1.



Table 1: Expected geology

Geology	Comment
Surfacing and Buried Structures: (source: Envirocheck History Maps, Site Observation)	The main surfacing area is associated with farm located in the south eastern quadrant of the Zone. There is also the main access road which runs from the north of the Zone to the south to the farm yard and then to the southern boundary. Additional hardstanding tracks and bunkers may still be present in the south western corner of Zone 1.
Made Ground:	There are several minor areas of made ground deposits located across
(source: BGS Maps, Available Borehole Logs, Envirocheck Geology & History Maps, memoirs)	the zone. An area of disturbed ground is located in the north western corner of Zone 1 likely to be associated with a former quarry. There are four small areas of made ground deposits and infilled materials located in the south western corner of Zone 1 within the East Midlands Airport land probably associated with the former RAF base operations. There are areas of worked and disturbed ground located in the centre of Zone 1 near to the King Street Plantation. Further made ground deposits are shown within the farm yard area.
Drift Deposits: (source: BGS Maps, Available Borehole Logs, Envirocheck Geology &	A cap of <b>Thrussington Member</b> (Glacial Till) expected to take the form of sandy gravelly Clay is noted in the north western area of Zone 1 forming the knoll feature.
History Maps, memoirs)	There is a finger of <b>Head</b> deposits indicated to be located within the centre of Zone 1 orientated north to south, with further Head deposits indicated to be located in northern area wrapping round along the eastern boundary with a small area in the north western corner. Head deposits are expected to vary between silts, clays, sands and gravels.
	A thin finger of <b>Eagle Moore Sand and Gravel</b> is anticipated to be located in the northern part of Zone 1 with further sand and gravel deposits located in the north of Zone 1 orientated north west to south east, these been defined as the <b>Egginton Common Sand and Gravel</b> and the <b>Wanlip Member</b> .
Bedrock (source: BGS Maps, Available Borehole Logs, Envirocheck Geology & History Maps, memoirs)	Zone 1 is underlain by the Mercia Mudstone Group which is sub divided into the following differing lithologies; The majority of Zone 1 is underlain by the <b>Taporley Siltstone Formation</b> which comprises interbedded mudstones, siltstone and sandstones. The southern boundary of Zone 1 is underlain by the <b>Gunthorpe Member</b> which comprises of interbedded mudstone and dolomitic siltstone. The far north of the Zone 1 is underlain by the <b>Edwalton Member</b> which comprises primarily of mudstone with siltstone and sandstone skerry bands. The underlying <b>Bromsgrove Sandstone Formation</b> is indicated to be present in two small areas to the east and the west.
	It is anticipated that where no drift deposits overlay the solid deposits the Mudstones will have weathered to clays, siltstones to silt and sandstones to sand.
Soil Chemistry (source: Envirocheck / BGS)	Available soil chemistry data suggests that the natural soils anticipated to be present across the site do not have any elevated concentrations of contaminants that would be considered to represent a risk to Human Health for the elements tested for.



Geology	Comment
Mining	None expected.
(source: Coal Authority web viewer, BGS Maps, Available Borehole Logs, Envirocheck records, Geology & History Maps)	
Faults (source: BGS Maps, Available Borehole Logs, Envirocheck Geology Maps, memoirs)  A major fault (Normanton Hills Fault) is shown crossing the rarea of Zone 1 with an orientation of east to west down thrown north which is the division between the Taporley Siltstone and Edwalton Formation.	
	Two further faults are shown in the western half of the Zone which is orientated north to south and both are down thrown to the east.
Opencast Quarrying (source: Coal Authority web viewer, BGS Maps, Envirocheck History Maps)	Two areas of disturbed ground are shown; one in the north western corner and one to the west of the King Street Plantation in the centre of Zone 1.
Mineral Protection (source: Local Authority Plan)	Zone 1 does not fall within the Mineral Protection area.
Groundwater Levels: (source: Available GI)	Due to the variable deposits anticipated to be present across Zone 1 and in particular the interbedded nature of the majority of the solid deposits it is expected that more permeable strata (sandstone and siltstone) beds confined between less permeable mudstones may yield local water tables. Initial monitoring of the preliminary Ground Investigation undertaken by others confirms that when drilled most boreholes were dry; however minor water strikes were encountered in discrete permeable beds. Monitoring of wells installed to different depths and with differing response zones suggest a variety of water tables are present confined within the various confined permeable strata. Several installations remained dry, while others collected only small amounts of groundwater.  Given the rural location of Zone 1, it is considered unlikely that the development will be affected by rising groundwater levels associated with diminished abstraction by industry.



The constraints to investigations undertaken in Zone 1 are summarised below in Table 2;

**Table 2: Constraints to investigation** 

Issue	Comment
Landowners	The majority of Zone 1 is owned by Mr Coker.
Permissions	Airport land was not investigated as the client had not been able to obtain an agreement to undertake investigations on this land at the time of investigations.
Utilities & Services	Overhead power lines are present across the centre of the site running east to west.
	A <b>gas main</b> is present along the northern eastern corner of the Zone.
Live Carriageway	No live carriageways were investigated within Zone 1.
East Midlands Airport	It was necessary to inform East Midlands Airport of the position (Coordinates and ground level) and height of all exploratory works to ensure that no breach regulated airspace would occur.
Farming, Crops & Livestock	No investigation was feasible within the area of the <b>farmyard</b> at this time as the farm remained in operation.
	The location of exploratory holes was constrained by the planting and ongoing harvest and replanting being undertaken at the time of the works.
	It was not possible to undertake TP318. As the landowner/farmer refused entry to the area as it was required that RSK avoid significant crop damage.
	Horses were present in the area of CP216 and TP301.



### 3 GROUND INVESTIGATION

#### 3.1 Introduction

RSK prepared a site specific Stage 2 Preliminary Ground Investigation Specification in accordance with the Site Investigation Steering Group's UK Specification for Ground Investigation 2nd edition (2012) and BS 5930 and A2: 2010 'Code of practice for site investigations', BS EN ISO 14688-1:2002 and BS EN ISO 14689-1:2003. It was decided that the Mercia Mudstone Formation strata were to be logged for weathering grades in accordance with the guidelines in Chandler and Davis (1973): Further work on the engineering properties of Keuper Marl (CIRIA Report 47) so that the logs maybe readily compared to available historical exploratory hole data to facilitate interpretation.

The specification for the works was developed with the aim of providing sufficient preliminary data to assist with master planning design taking account of the anticipated ground conditions detailed within the Preliminary Sources Study Report.

The site work for the investigation of the East Midlands Strategic Rail Freight Interchange across all four zones was undertaken between 23<sup>rd</sup> September and 11<sup>th</sup> October 2013.

#### 3.2 Investigation strategy and methodology

The techniques adopted for the intrusive investigation were appropriate to the expected geology and were also chosen to provide general preliminary non targeted arrangement covering both plan area and depth of strata sufficient to allow the ground model to be confirmed. In addition specific exploratory holes were targeted in order to provide data for specific critical design elements. The investigation and sampling strategy was primarily focused on the assessment of the shallow soils and weathered bedrock.

The rationale for each planned exploratory hole location is detailed within the Stage 2 Preliminary Ground Investigation Specification and summarised within the Provisional Exploratory Hole Schedule included in Appendix B. This formed the basis for the works decision making as works progressed.

Following completion of fieldworks and upon preparation of exploratory hole logs a series of samples were scheduled for a selection of geotechnical and chemical laboratory testing to help characterise the strata properties. Groundwater samples were also taken and analysed where it was viable.

An initial programme of four weekly soil gas and groundwater level monitoring was undertaken to establish the groundwater and ground gas conditions beneath the site.



The results of the monitoring are provided within Appendix J. Monitoring of 6 existing serviceable boreholes CP/RC101 – 106 installed in 2012 by others was also included for completeness.

#### 3.2.1 Health and safety

Services data was obtained and overlaid upon plans to aid in the design and safe positioning of exploratory holes.

RSK liaised with East Midlands Airport and Landowners to agree suitable and safe exploratory hole locations, access routes and to obtain all necessary permits and permissions.

RSK prepared site specific works H&S Plan, risk assessments and method statements for the undertaking of the works. These were reviewed by an independent CDMC appointed by Roxhill Developments Ltd.

A HSE Form F10, notification of construction project, was issued to the HSE to cover the works by the CDMC and was displayed on site throughout the works.

#### 3.2.2 Location of exploratory hole positions and service clearance

RSK met with landowners and stakeholders to confirm suitable access routes and viable exploratory hole locations prior to finalising the ground investigation specification and commencing works.

Services data was obtained and overlaid upon plans to aid in the safe positioning of exploratory holes.

RSK SafeGround team used a number of techniques and equipment to check all exploratory hole positions and the surrounding areas were free of buried services and utilities. SafeGround used the following equipment:

- CAT & Genny (Radiodetection RD8000),
- Ground Penetrating Radar (GPR) GSSI SIR-3000 console with the GSSI 400MHz antenna (standard frequency, used in high risk clearances) and the GSSI 200MHz antenna (low frequency, used in locating the high pressure water pipe)
- EM31 (Geonics)

Hand excavated service avoidance inspection pits were excavated to depths of 1.2mbgl prior to commencing all boreholes.



Upon completion of the works an as-built survey of the exploratory hole positions was commissioned and the coordinates and levels of each position were recorded using a Leica Viva GPS accurate to +/-5mm in horizontal positioning and +/-10mm in elevation. The coordinates and level data are recorded upon each exploratory hole log whilst the position of each exploratory hole is shown upon the exploratory hole location plan presented as Figure 4.

#### 3.2.3 Investigation techniques

#### Trial pits

Machine excavated trial pits were utilised to provide coverage across the site and to provide data on the shallow near surface strata. Trial pits also allowed bulk disturbed samples to be taken for strata classification and earthworks testing.

Specific trial pits were undertaken at defined locations to facilitate soakaway testing to provide infiltration data to aid drainage design.

The trial pit logs and photographs are presented in Appendix C.

#### Cable percussion boring

150mm diameter cable percussion boreholes were utilised to penetrate shallow near surface drift strata to full depth and to prove the top of rock head. This technique was also used to provide in-situ strength and density testing (SPT), representative disturbed and undisturbed samples for laboratory testing and to facilitate installation of monitoring instrumentation within the shallow near surface deposits to facilitate long term soil gas and groundwater monitoring.

The cable percussion borehole logs are presented in Appendix D.

#### Rotary coring boreholes

92mm diameter ('P' size) rotary core drilling techniques were used to core solid strata at locations adjacent to selected cable percussion boreholes. This allowed representative rock core to be obtained for accurate logging and sub sampled for testing within the laboratory. The boreholes were installed with deep standpipes and standpipe piezometers to allow long term monitoring of groundwater and ground gas.

The rotary borehole logs and photographs are presented in Appendix E.



#### 3.2.4 Zone 1 investigation

The investigation undertaken at Zone 1 comprised the following:

- Setting out and service Clearance (RSK SafeGround).
- Excavation of twenty seven trial pits using an operated wheeled excavator to provisional depths of between 1.50m and 4.60m bgl.
- Carry out six soakaway tests in selected trial pits in general accordance with BRE 365.
- Sinking of nineteen boreholes to depths of between 2.32m and 10.94m bgl using a standard cable percussive drilling rig.
- Sinking of six rotary cored boreholes (air /mist) open holed to rock head and cored (P size) to depth of between 20.00m and 30.00m bgl.
- Installation of twenty eight combined groundwater/gas monitoring wells and piezometers to varying depths including provision of flush lockable covers and 1.5m high wooden marker stakes (in fields).
- Four initial return visits to monitor groundwater levels/ground gas concentrations
- One groundwater sampling visit.
- Surveying in of as built exploratory hole positions using GPS surveying equipment.
- Associated sampling and insitu testing.
- Soil and rock sample geotechnical laboratory testing.
- Soil sample chemical and contamination laboratory testing.
- Groundwater sample chemical and contamination laboratory testing.

#### 3.2.5 Soil sampling, in-situ testing and laboratory analysis

Details of the soil samples obtained during the intrusive investigation are recorded on the exploratory hole logs presented within Appendices C, D and E.

In-situ SPTs were undertaken within the cable percussion boreholes and are presented on the borehole logs included within Appendix D.

In-situ soakaway testing was undertaken in selected trial pit locations as denoted upon the exploratory hole plan presented as Figure 4. Preliminary soakaway tests were undertaken in unsupported shallow trial pits and were attempted in general accordance with the recommendation of BRE 365. Tests undertaken within TPs 301, 302, 303, 304, 305, 351 & 352 did not soakaway sufficiently to allow calculation of infiltration rates. The strata in which these tests were undertaken were predominantly cohesive and not considered to be conducive to soakaway and the testing undertaken has confirmed this. The in-situ soakaway test results are presented in Appendix F and the results are summarised below within Table3.



Table 3: Summary of soakaway test results

Hole	Test Zone (Depth m bgl)	Calculated Infiltration Rate m/s	Strata
TPS301	2.10 – 2.80	Insufficient soakage	Tarporley Siltstone Formation - Clay
TPS302	1.60 – 2.50	Insufficient soakage	Tarporley Siltstone Formation - Clay
TPS303	2.20 – 3.15	Insufficient soakage	Edwalton Member - Clay
TPS304	1.62 – 2.50	Insufficient soakage	Edwalton Member - Clay
TPS305	1.68 – 2.65	Insufficient soakage	Eggington Common Sand and Gravel Member
TPS351	1.97 – 2.65	Insufficient soakage	Wanlip Member – clayey sand and gravel
TPS352	1.85 – 2.55	Insufficient soakage	Wanlip Member –clayey gravely sand

A programme of laboratory testing was scheduled by RSK to be carried out on selected suitable samples, in order to provide characteristic geotechnical strata properties.

The programme of geotechnical testing undertaken is summarised below within Table 4.

Table 4: Summary of geotechnical testing programme undertaken

Stratum	Analysis Undertaken	Number
	Coefficient of consolidation c <sub>v</sub> (m <sup>2</sup> /year)	1
Head Deposits	Undrained shear strength measured by triaxial testing (kN/m²)	1
	Sulphate Characterisation (BRE SD1)	1
Thrussington Member	Undrained shear strength measured by triaxial testing (kN/m²)	1
Egginton Common Sand and Gravel	Sulphate Characterisation (BRE SD1)	2
Wanlip Member	Classification tests (natural moisture content)	1



Stratum	Analysis Undertaken	Number
	Sulphate Characterisation (BRE SD1)	1
	Classification tests (Atterberg Limits)	1
	Classification tests (natural moisture content)	7
Gunthorpe Member	Undrained shear strength measured by shear vane testing (kN/m²)	1
	Undrained shear strength measured by triaxial testing (kN/m²)	2
	Point load testing (Axial/ Diametral)	5
	Sulphate Characterisation (BRE SD1)	10
	Classification tests (Atterberg Limits)	12
	Classification tests (natural moisture content)	32
	Dry density (kN/m³)	1
	Sieve analysis	6
	Sedimentation analysis	6
	Dry density/moisture content relationship	4
Tarporley Siltstone	California Bearing Ratio	6
Formation	Moisture condition value	4
	Moisture condition value/moisture content relationship	2
	Unconfined compressive strength testing (MPa)	2
	Coefficient of consolidation c <sub>v</sub> (m²/year)	2
	Undrained shear strength measured by triaxial testing (kN/m²)	6
	Point load testing (Axial/ Diametral)	9
	Sulphate Characterisation (BRE SD1)	3
	Classification tests (Atterberg Limits)	2
	Classification tests (natural moisture content)	3
Edwalton Member	Coefficient of consolidation c <sub>v</sub> (m²/year)	2
	Undrained shear strength measured by triaxial testing (kN/m²)	2



Stratum	Analysis Undertaken	Number
Bromsgrove Sandstone Formation	Sulphate Characterisation (BRE SD1)	4
	Classification tests (natural moisture content)	1
	Unconfined compressive strength testing (MPa)	3
	Point load testing (Axial/ Diametral)	20

The results of the geotechnical laboratory testing are presented in full within Appendix G.

In addition a programme of non targeted analytical chemical and contamination suites of tests were scheduled upon selected soil and groundwater samples obtained to confirm characteristic soil and groundwater chemistry and contamination potential.

The programme of analytical chemical and contamination suites of tests undertaken on soil samples is summarised below within Table 5.

Table 5: Summary of analytical chemical and contamination testing programme undertaken on soil samples

Stratum	Analysis Undertaken	Number
	pH, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	4
	Total Organic Carbon (TOC)	1
	Asbestos in Soil	2
Subsoil	Pesticides	4
	Polycyclic Aromatic Hydrocarbons (PAHs)	4
	Triazine Herbicides	4
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	4
	pH, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	1
Made Ground	Total Organic Carbon (TOC)	1
	Polycyclic Aromatic Hydrocarbons (PAHs)	1
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	1



Stratum	Analysis Undertaken	Number
	pH, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	1
	Total Organic Carbon (TOC)	1
Head Deposits	Asbestos in Soil	1
	Polycyclic Aromatic Hydrocarbons (PAHs)	1
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	1
	pH, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	1
Egginton Common	Total Organic Carbon (TOC)	1
Sand and Gravel	Polycyclic Aromatic Hydrocarbons (PAHs)	1
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	1
	pH, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	1
	Total Organic Carbon (TOC)	1
Wanlip Member	Polycyclic Aromatic Hydrocarbons (PAHs)	1
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	1
	pH, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	3
Tarporley Siltstone	Total Organic Carbon (TOC)	3
Formation	Polycyclic Aromatic Hydrocarbons (PAHs)	3
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	3

The results of the analytical chemical and contamination suites of tests are presented in full within Appendix H.

The programme of analytical chemical and contamination suites of tests undertaken on groundwater samples is summarised below within Table 6.



Table 6: Summary of analytical chemical and contamination testing programme undertaken on groundwater samples

Sample	Analysis Undertaken	Number
	pH, Redox potential, Electrical conductivity, dissolved oxygen, hardness, ammoniacal nitrogen, Phenols, Arsenic, Cadmium, Copper, Chromium, Chromium (hexavalent), Lead, Mercury, Nickel, Selenium, Zinc	7
Groundwater	Polycyclic Aromatic Hydrocarbons (PAHs)	7
	Semi-Volatile Organic Compounds (SVOCs)	7
	Volatile Organic Compounds (VOCs)	7
	Total Petroleum Hydrocarbons Criteria Working Group (TPH CWG) + BTEX and MTBE	

The results of the analytical chemical and contamination suites of tests for the groundwater samples are presented in full within Appendix I.

#### 3.2.6 Instrumentation and monitoring

Long term monitoring of gas and groundwater levels was made possible by the installation of standpipes and standpipe piezometers as shown within Table 7. It should be appreciated that monitoring included monitoring of boreholes installed previously (2012) by Geotechnics Ltd as well where still serviceable (Zone 1 only):

Table 7: Monitoring well installation details

Hole	Standpipe Response Zone / Piezometer Response Zone	Standpipe Slotted zone/Piezometer Tip Depth	Strata
	(m)	(m)	
CP203	1.00 – 4.00	1.00 – 4.00	Tarporley Siltstone Formation
CP204	1.00 – 4.30	1.00 – 4.00	Gunthorpe Member
CP205	1.00 – 4.30	1.00 – 4.30	Tarporley Siltstone Formation
CP206	1.00 – 3.30	1.00 – 3.30	Tarporley Siltstone Formation and Bromsgrove Sandstone Formation



•			
CP207	1.00 – 2.70	1.00 – 2.70	Tarporley Siltstone Formation
CP208	1.00 – 2.32	1.00 – 2.00	Tarporley Siltstone Formation
CP210	8.50 – 9.50	8.50 – 9.50	Tarporley Siltstone Formation
CP211	1.00 – 7.00	1.00 – 7.00	Gunthorpe Member
CP212	1.00 – 3.45	1.00 – 3.30	Thrussington Member and Tarporley Siltstone Formation
CP213	1.00 – 4.20	1.00 – 4.20	Tarporley Siltstone Formation
CP214	1.00 – 4.20	1.00 – 4.20	Tarporley Siltstone Formation
CP215	1.00 – 4.80	1.00 – 4.80	Bromsgrove Sandstone Formation
CP216	0.50 – 2.40	0.50 – 2.40	Tarporley Siltstone Formation
CP217	1.00 – 4.60	1.00 – 4.60	Tarporley Siltstone Formation
CP218	1.00 – 4.60	1.00 – 4.60	Thrussington Member and Tarporley Siltstone Formation
CP219	1.00 – 7.70	1.00 – 7.50	Thrussington Member, Tarporley Siltstone Formation and Edwalton Member
CP220	1.00 – 5.90	1.00 – 5.70	Head Deposits and Edwalton Member
CP221	1.00 – 10.90	1.00 – 10.70	Egginton Common Sand and Gravel Member and Edwalton Member
CP222	2.50 – 6.00 (S)	6.00(P)	Edwalton Member
CP(R)203	7.00 – 25.00	7.00 – 25.00	Tarporley Siltstone Formation and Bromsgrove Sandstone Formation
	28.80 – 30.00 (S)	29.00 (P)	Bromsgrove Sandstone Formation (P)
CP(R)204	14.00 – 20.00	14.00 – 20.00	Gunthorpe Member
CP(R)205	4.10 – 20.00	4.10 – 19.00	Tarporley Siltstone Formation and Bromsgrove Sandstone Formation



CP(R)206	9.00 – 21.00	9.00 – 21.00	Bromsgrove Sandstone Formation
	23.80 – 25.00 (S)	24.00 (P)	
CP(R)207	11.00 – 13.00 (S)	12.00 (P)	Tarporley Siltstone Formation (P)
	17.00 – 25.00	17.00 – 25.00	Bromsgrove Sandstone Formation
CP(R)208	5.00 – 20.00	5.00 – 20.00	Tarporley Siltstone Formation and Bromsgrove Sandstone Formation

(p) = Piezometer (S) = Sand Filter

Instrumentation installed within the boreholes has been monitored by trained technicians from RSK.

Initial Gas and Groundwater Monitoring was undertaken on 4 separate occasions over a five week period as follows;


- 16<sup>th</sup> and 17<sup>th</sup> October 2013
- 22<sup>nd</sup> and 23<sup>rd</sup> October 2013
- 30<sup>th</sup> and 31<sup>st</sup> October 2013
- 11<sup>th</sup> November 2013


Groundwater sampling was undertaken from Borehole CP210, CP212, CP213, CP217, CP220, CPR204 and CPR206 on the 22<sup>nd</sup> and 23<sup>rd</sup> October 2013. Groundwater sampling was undertaken in accordance with RSK Procedure No; SHEQ MS TP210 Groundwater and Surface Water – sampling and routine in-situ testing. This has been formulated in accordance with current published guidance. Samples obtained were sent to Envirolab for testing and the results are presented within Appendix I. Details of the insitu water quality results are presented within Appendix J.


Gas and groundwater level monitoring was undertaken in accordance with RSK Group SHEQMS Technical Procedure TP211 Ground Gas (Permanent gases) Monitoring and Sampling. This has been formulated in accordance with current published guidance. Groundwater levels were established using a hand held dipmeter with levels recorded with reference to depth below ground level. Gas monitoring was carried out using a Geotechnical Instruments GA2000+ Infra red gas analyser and Gas Data GFM610 flow pod. Monitoring was carried out to check for Methane, Carbon Monoxide, Carbon dioxide, Hydrogen Sulphide, Oxygen, Barometric pressure and Flow rate. In addition a Mini RAE 3000 Photo Ionisation Detector (PID) was used to confirm if volatile organic compounds were also present. The detailed results of the gas and groundwater level monitoring are presented within Appendix J.




# **FIGURES**











# APPENDIX A SERVICE CONSTRAINTS

- 1. This report and the site investigation carried out in connection with the report (together the "Services") were compiled and carried out by RSK Environment Limited (RSK) for Roxhill Developments Limited in accordance with the terms of a contract between RSK and the "client", dated 3<sup>rd</sup> September 2013. The Services were performed by RSK with the skill and care ordinarily exercised by a reasonable environmental consultant at the time the Services were performed. Further, and in particular, the Services were performed by RSK taking into account the limits of the scope of works required by the client, the time scale involved and the resources, including financial and manpower resources, agreed between RSK and the client.
- 2. Other than that expressly contained in paragraph 1 above, RSK provides no other representation or warranty whether express or implied, in relation to the Services.
- 3. Unless otherwise agreed the Services were performed by RSK exclusively for the purposes of the client. RSK is not aware of any interest of or reliance by any party other than the client in or on the Services. Unless expressly provided in writing, RSK does not authorise, consent or condone any party other than the client relying upon the Services. Should this report or any part of this report, or otherwise details of the Services or any part of the Services be made known to any such party, and such party relies thereon that party does so wholly at its own and sole risk and RSK disclaims any liability to such parties. Any such party would be well advised to seek independent advice from a competent environmental consultant and/or lawyer.
- 4. It is RSK's understanding that this report is to be used for the purpose described in the introduction to the report. That purpose was a significant factor in determining the scope and level of the Services. Should the purpose for which the report is used, or the proposed use of the site change, this report may no longer be valid and any further use of or reliance upon the report in those circumstances by the client without RSK 's review and advice shall be at the client's sole and own risk. Should RSK be requested to review the report after the date hereof, RSK shall be entitled to additional payment at the then existing rates or such other terms as agreed between RSK and the client.
- 5. The passage of time may result in changes in site conditions, regulatory or other legal provisions, technology or economic conditions which could render the report inaccurate or unreliable. The information and conclusions contained in this report should not be relied upon in the future without the written advice of RSK. In the absence of such written advice of RSK, reliance on the report in the future shall be at the client's own and sole risk. Should RSK be requested to review the report in the future, RSK shall be entitled to additional payment at the then existing rate or such other terms as may be agreed between RSK and the client.
- 6. The observations and conclusions described in this report are based solely upon the Services which were provided pursuant to the agreement between the client and RSK. RSK has not performed any observations, investigations, studies or testing not specifically set out or required by the contract between the client and RSK. RSK is not liable for the existence of any condition, the discovery of which would require performance of services not otherwise contained in the Services. For the avoidance of doubt, unless otherwise expressly referred to in the introduction to this report, RSK did not seek to evaluate the presence on or off the site of asbestos, electromagnetic fields, lead paint, heavy metals, radon gas or other radioactive or hazardous materials.
- 7. The Services are based upon RSK's observations of existing physical conditions at the Site gained from a walk-over survey of the site together with RSK's interpretation of information including documentation, obtained from third parties and from the client on the history and usage of the site. The Services are also based on information and/or analysis provided by independent testing and information services or laboratories upon which RSK was reasonably entitled to rely. The Services clearly are limited by the accuracy of the information, including documentation, reviewed by RSK and the observations possible at the time of the walk-over survey. Further RSK was not authorised and did not attempt to independently verify the accuracy or completeness of information, documentation or materials received from the client or third parties, including laboratories and information services, during the performance of the Services. RSK is not liable for any inaccurate information or conclusions, the discovery of which inaccuracies required the doing of any act including the gathering of any information which was not reasonably available to RSK and including the doing of any independent investigation of the information provided to RSK save as otherwise provided in the terms of the contract between the client and RSK.
- 8. The phase II or intrusive environmental site investigation aspects of the Services is a limited sampling of the site at pre-determined borehole and soil vapour locations based on the operational configuration of the site. The conclusions given in this report are based on information gathered at the specific test locations and can only be extrapolated to an undefined limited area around those locations. The extent of the limited area depends on the soil and groundwater conditions, together with the position of any current structures and underground facilities and natural and other activities on site. In addition chemical analysis was carried out for a limited number of parameters [as stipulated in the contract between the client and RSK] [based on an understanding of the available operational and historical information,] and it should not be inferred that other chemical species are not present.
- 9. Any site drawing(s) provided in this report is (are) not meant to be an accurate base plan, but is (are) used to present the general relative locations of features on, and surrounding, the site.



# APPENDIX B PROVISIONAL EXPLORATORY HOLE SCHEDULE

## Exploratory Hole Schedule

									Position			Estimated Design Ground Level	Diff in level
Hole	Hole Type	Provisional Depth m bgl	Anticipated CP depth mbgl	Anticipated Coring length m	Provisional Instrumentation	Current Use/surfacing	Purposed end use	Special insitu testing / sampling /Likely Lab Testing Requirements	E	N	mAOD	mAOD	m
						Boreholes	S						
CPR 203	CP & RC	3	<b>30</b> 8	22	To Be confirmed by Engineer depending upon		Deep Rail Head Cut				69	44	25
CPR 204	CP & RC	2	<b>20</b> 7	13	ground conditions and water strikes		Development Cut Slope				83	70	13
CPR 205	CP & RC	3	<b>30</b> 7	23	encountered. In general shallow combined gas and Groundwater monitoring stanpipes using	Cropped Fields Beware sewer running S-N along eastern hedge boundary foot					57	44	13
CPR 206	CP & RC		<b>25</b> 7		50mm HDPE pipe to be utilised in Cable	of A453???	Deep Rail Head Cut				52		_
CPR 207	CP & RC		<b>25</b> 7	18	Percussion boreeholes around main buildings and plateaus to allow sahhlwo gas and						60		
CPR 208	CP & RC	-	20 7	13	perched or shallow groundwater strikes to be			4			65	ł	5.5
CP 210	CP	+	12 12		monitored . Deeper Standpipes or stand pipe						80	72	
CP 211 CP 212	CP CP	1	12 12		piezometers to be utilised and installed in sperate deep rotary boreholes to allow deeper		Development Cut Slope				82 69		
CP 212	CP	+	0 0		sub artesian or artesian water levels to be		Development out Slope				65		
CP 213 CP 214	CP		8 8		monitored.						63	72	1
CP 215	CP		8 8		1			1			60		,
CP 216	CP	1	8 8		1	Cropped Fields					64		
CP 217	CP	1	8 8		1		Screening Embankment Foundation				71		
CP 218	СР		8 8		1						66	76	-10
CP 219	СР		8 8		1						55	55	0
CP 220	СР		8 8		1		Rail Head				44	43	1
CP 221	CP		8				Screening Embankment Foundation				40	58	-18
CP 222	CP	1	10 10			Farm Entrance	Rail embankment and possible underpass structure				37	41	4
						Trial Pits							0
TPS301	TP & Soakaway	2.	.5				Area of propsoed SUDS/attenuation ponds  General Ground Conditions, foundations				55	53	2
TPS302	TP & Soakaway	2.	.5					Soakaway Infiltration tests at 1 - 2.5m depth			68		
TPS303	TP & Soakaway	2.									56		
TPS304	TP & Soakaway	2.									53		
TPS305	TP & Soakaway	2.									40	38	
TP 307	TP	4.									72		
TP 308	TP	4.				-		HV and Std geotech and Env	'		60		
TP 309	TP	4.				-		Sampling			63	ł	
TP 310	TP TP	4.				-		HV and Std geotech and Env			44	59.5	Ū
TP 311 TP 312	TP	4.				1	General Ground Conditions, foundations, cut soils for earthworks.	Sampling, large bulks for			50 52		1
TP 313	TP	4.						earthworks classification and			53		•
TP 314	TP	-	.5			1		compactuion test suites in			60		_
TP 315	TP	1	.5			Cropped Fields		near top 1-5m depth			56	1	1
TP 316	TP	4.						HV and Std geotech and Env			68		
TP 317	TP	4.				1	General Ground Conditions, foundations	Sampling			73	1	1
TP 318	TP	4.				1					66	67	
ΓP 319	TP	4.	.5			]					78	73	5
TP 320	TP	4.	.5								72	73	-1
TP 321	TP	4.	.5					HV and Std geotech and Env	,		69		-3
TP 322	TP	4.					General Ground Conditions, foundations, cut soils for	Sampling, large bulks for			73		
TP 323	TP		.5			l .	earthworks.	earthworks classification and			62		1
ΓP 324	TP	4.				1		compactuion test suites in near top 1-5m depth			69		_
ΓP 325	TP	4.						noar top i om doptil			62		1
ΓP 326	TP	4.				1					60	60	
TP 327	TP 0 October		.5								60		
TP 351	TP & Soakaway	2.				Cropped Fields	Flood compensation & ponds Main Development				39		
TP 352 IP401-405	TP & Soakaway	2.	.5			l	<u> </u>		<u> </u>		41.6	39.6	2
16401-405						ı	Elead componentian required to examine don't to be de-		Г		1	1	
HP406	Hand Pit	<u> </u>	2			Cycle Path	Flood compensation, required to examine depth to bridge foundations	Log Only/			<u> </u>		-1
NK = Not Kn		TBC= To Be Co					open holed to the depth acchieved by Cable Percussion p	rior to commencing coring.					0
					irmed by client and landowner. Do not under	take these investigation positions unti	II can confirm.					4	
	Sateground GPI	ห required as hiç	gh risk utilities in a	area								]	



# APPENDIX C TRIAL PIT LOGS AND PHOTOGRAPHS



Contract Reference: 312494

#### KEY TO EXPLORATORY HOLE LOGS - SUMMARY OF ABBREVIATIONS

#### **SAMPLING**

Sample type codes

B = Bulk disturbed sample.

C = Core sample.

CS = Core sample taken from rotary core for lab testing.

D = Small disturbed sample.

DSPT = Small disturbed sample originating from SPT test.

ES = Soil sample for environmental testing.

U = Undisturbed driven tube sample - Number of blows indicated. % recovery reported.

Undisturbed sample detail codes

 $U_{(100)} = 100$ mm diameter undisturbed sample.

#### **IN-SITU TESTING**

 $SPT_{(c)}$  = Standard Penetration Test using a solid 60 degree cone.

 $SPT^{(c)}$  = Standard Penetration Test using split spoon sampler. ( $SPT_{(NR)}$  indicates 'No Sample Recovery').

\* denotes extrapolated N value. NP denotes 'No Penetration'.

V = Field Vane Test. Peak value (c<sub>n</sub>) & Residual value (c<sub>n</sub>), given as shear strength in kPa.

#### **ROTARY DRILLING INFORMATION**

W = Water flush returns (%) TCR = Total core recovery (%) SCR = Solid core recovery (%)

RQD = Rock quality designations (%)

If = Fracture spacing (mm).

In the fracture column (i) denotes discontinuity is infilled (refer to Fracture Table for details).

Where variable the minimum - average - maximum spacing may be quoted.

'NI' denotes non-intact core. 'NA' denotes not applicable.

All lengths used to determine rock core mechanical properties taken along the centre line of the core.

Obvious induced fractures have been ignored.

The assessment of solid core is based on lengths that show a full diameter and not necessarily a full circumference.

AZCL = Assessed zone of core loss.

#### ADDITIONAL NOTES

1. All soil and rock descriptions and legends in general accordance with BS EN ISO 14688-1, 14688-2, 14689-1, and BS5930:1999 including Amendment 2 (2010).

2. Material types divided by a broken line (- - - ) indicates an unclear boundary.

3. The data on any sheet within the report showing the AGS icon is available in the AGS format.

GINT LIBRARY V8 05.GLBIGrfcText G - LEGEND - 1 OF 2 | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 29/11/13 - 10:00 | KF.
RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract Reference: 312494

#### KEY TO EXPLORATORY HOLE LOGS - SUMMARY OF GRAPHIC SYMBOLS

#### WATER COLUMN SYMBOLS



First water strike, second water strike etc.

Standing water level following first strike, standing water level following second strike etc.

Seepage.

Standing water level recorded at documented date.

#### **MATERIAL GRAPHIC LEGENDS**



CLAY



Clayey gravelly SAND



Gravelly clayey SAND



Clayey gravelly SAND with COBBLES

Clayey SAND



Clayey SAND with COBBLES



Clayey sandy GRAVEL



GRAVEL

GRAVEL with COBBLES



Gravelly CLAY



Gravelly silty CLAY



Silty gravelly CLAY

Ø=\_= -0 × × 0 ° Silty gravelly CLAY with COBBLES



Gravelly SAND



Gravelly clayey SILT



Gravelly SILT



MADE GROUND



Mudstone



SAND



SAND with COBBLES

#### **INSTRUMENTATION SYMBOLS**



Backfill



Bentonite seal



Concrete



Gravel filter



Sand filter



Stopcock cover



Piezometer tip



Plain pipe




Slotted pipe



# **TRIAL PIT LOG**

Contract:				Client:			Trial Pit:		
East Midlands	Gate	way		Roxhil	l Developments Ltd			TP	<b>30</b> ′
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		72.61	E:445822.3 N:327327.8		1	of	1

	5124	194	End:	26.9.1.	12.	.01	E:445822.3 N:32/32/.8		1	of I	
Sam	ples a		tu Tests  Results	Water Backfill		]	Description of Strata		Depth (Thick ness)	Material Graphic Legend	
0.10-0.20	1	ES	Tx2+J+Vx2		slightly grave to coarse qu	Sparse vegetation over stiff to very stiff dark brown slightly sandy slightly gravelly very silty CLAY. Gravel is subangular to rounded fine to coarse quartzite and rare angular brick and medium flint. (SUBSOIL)					
-					CLAY. Gr	ery stiff dark orange brown slightly sandy slightly gravelly very silty LAY. Gravel is subangular to rounded fine to coarse quartzite.  [THRUSSINGTON MEMBER]					
0.70	2	V B	c <sub>u</sub> =98/74/102		with occas occasional s coarse mud	ional subangu sandy pockets.	vn slightly sandy slightly gravelly silty dar to angular sandstone cobbles an Gravel is tabular angular to rounded e and occasional sandstone. IBER)	d with	(0.35)	\$ - 0	
- - -					occasional to siltstone lith	tabular to angu norelicts. g Grade IVb)	tly sandy very silty CLAY. Recovery i lar fine to medium gravel sized mudston.  NE FORMATION)	ncludes one and	- - -		
1.50-2.00	3	В			💢 angular silt	tstone and fir	covery includes occasional to some tabute sandstone cobbles and occasional	llar and 0.25m	-(1.80)	X X X X X X X X X X X X X X X X X X X	
-						ed brown SIL	TSTONE/MUDSTONE recovered as ty very gravelly tabular and angular cob		2.80	× × × × × × × × × × × × × × × × ×	
-					(Weathering	g Grade II) LEY SILTSTO	NE FORMATION) t terminated at 3.00m depth.		3.00	× × × × × × × × × × × × × × × × × × ×	
-									-		
-									- - -		
-									- - -		




GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log TRIAL PIT LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:51 | KF. RSK Environment Ltd. The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Trial Pi	t:			
East Midlands	Gate	eway	Roxhill Developments Ltd					TI	P3(	<b>)8</b>
Contract Ref:	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	25.9.13		54.24	E:446515.8 N:327287.5		1	of	f .	1


	114		Eliu.		7.13	57.27 E.770515.0 1\.527207.5		01 1
	ples a	nd In-si		Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Туре	Results	W	m B M	•	ness)	Legend
-						Grass over brown slightly gravelly very silty CLAY, with frequent rootlets. Gravel is angular to rounded fine to medium occasional coarse quartzite, flint and rare fine brick.  (SUBSOIL)	(0.30)	X X
-						Orange brown slightly gravelly silty CLAY, with occasional rootlets. Gravel is angular to rounded fine to coarse quartzite, flint, occasional subangular fine to medium charcoal. (HEAD DEPOSITS)	- - -	X X
0.80	1	ES	Tx2+J+Vx2				(0.90)	XO
-						Stiff fissured red brown occasionally mottled green grey slightly silty	1.20	x x
1.50-1.70	2	В				CLAY. Recovery includes occasional tabular to angular fine to medium gravel siltstone fragments. (Weathering Grade IVb)	-	
-		Б				(TARPORLEY SILTSTONE FORMATION) 1.20m bgl, brick and mortar in side of pit. (Land drain) 1.30m bgl, 15cm diameter land drain with flowing water.	-(0.80)	
-							2.00	
-						Red brown bedded green grey SILTSTONE bands (~ 0.1m thick) and fine SANDSTONE recovered within clayey matrix as tabular and angular cobble sized fragments. (Grade II)	-	X X X X X X X X X X X X X X X X X X X X
-						(TARPORLEY SILTSTONE FORMATION)	(0.80)	X X X X X X X X X X X X X X X X
-						Trial sittems in stad at 2.00m January	2.80	× × × × × × × × × × × × × × × × × × ×
_						Trial pit terminated at 2.80m depth.	-	
-							-	
-							-	
-							<u>-</u>	
-							-	
-							- -	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	way		Roxhil		1	TP	309	
Contract Ref:	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	25.9.13		63.52	E:446680.1 N:327302.3		1	of	1


		• / •	Ena.		, ,,,	20112000011100210		· -
San	noles a	nd In-si	tu Tests	늄	ΞΞ		Depth	Material
Depth	No	Туре	Results	Water	Backfill	Description of Strata	(Thick ness)	Graphic Legend
0.10	1	ES	Tx2+J+Vx2			Crop stubble over very stiff brown slightly sandy slightly gravelly to gravelly silty CLAY, with frequent rootlets. Gravel is angular to rounded fine to coarse quartzite and flint. \((SUBSOIL)\)	0.25	x _ x
- - - -						Brown very clayey angular to rounded fine to coarse quartzite and siltstone to fine sandstone GRAVEL/ very gravelly CLAY.  (HEAD DEPOSITS)  Very stiff red brown occasionally mottled light grey silty CLAY. Recovery includes occasional angular to subangular fine to coarse sandstone fragments.	0.45	
- -0.95-1.20 -	2	В				(Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION) 0.80m bgl, slightly gravelly.	1.20	
- - - -						Very stiff fissured red brown mottled green grey silty CLAY. Recovery includes occasional tabular and angular fine to coarse mudstone lithorelicts and siltstone and fine sandstone fragments. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	-	
- - - -						below 1.90m bgl, recovery includes occasional to some cobble sized tabular mudstone fragments.	(1.50)	
_							2.70	
- - -						Red brown bedded green grey SILTSTONE and fine SANDSTONE recovered as gravel and tabular and angular cobbles within clay matrix. (Weathering Grade II) (TARPORLEY SILTSTONE FORMATION)  Trial pit terminated at 2.80m depth.	2.80	X X X X X X X X X X X X X X X X X X X
- - -							-	
- - -							- - -	
- - -							- - -	
				1			Ī	





Contract:				Client:		Trial Pit	:		
East Midland	ls Gate	eway		Roxhil	l Developments Ltd			TP.	310
Contract Ref:	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	25.9.13		44.47	E:447071.9 N:327481.3		1	of	2

Į	3	124	194	End:	25.	9.13	44.4		of <b>2</b>
	Sam <sub>p</sub> Depth	ples a	nd In-sit	tu Tests Results	Water	Backfill	Description of Strata	Depth (Thick ness)	Material Graphic Legend
-	· · · · · · · · · · · · · · · · · · ·						Crop over brown slightly gravelly silty very sandy CLAY, with occasional to some rootlets. Gravel is angular to rounded fine to coarse quartzite and flint.  (SUBSOIL)  Dark orange brown mottled brown slightly clayey silty gravelly fine to medium SAND with occasional rootlets. Gravel is angular to rounded fine to coarse flint and quartzite.  (EGGINTON COMMON SAND AND GRAVEL)	(0.30)	
	0.80-0.90	1	ES	Tx2+J+Vx2			0.90m bgl, active land drain encountered.	1.20	
	1.50-1.80	2	В				Orange brown clayey very silty slightly gravelly SAND. Gravel is rounded to angular fine to coarse quartzite and occasional tabular angular sandstone and flint. (EGGINTON COMMON SAND AND GRAVEL)	-	
Sady 1 common grammy, coronally, coronally coronally many coronall	3.30-3.60	3	В				below 2.10m bgl, orange slightly clayey silty SAND.	-(3.40)	





											TRI	AL	Ы.	T L	.OG
Contract:							Client:						Trial Pi		
		Iidland							ll Develo	pment	s Ltd			]	ГР310
Contract Re			Start:		9.13	Groun	d Level (m		National C				Sheet:		
	312494	1	End:	25.	9.13		44.47		E:447	071.9 N	1:3274	81.3		2	of <b>2</b>
Sam Depth		In-situ Tes vpe R	ts esults	Water	Backfill				Description	n of Strata				Depth (Thick ness)	Graphic
								Trial p	oit terminated	d at 4.60m	depth.			4.60	000.
-														- - -	
-														-	
-														-	
-														- - -	
-														-	
-														-	
-														-	
-														-	
-														-	
-														-	
-														-	
														-	
Plan (Not to	Scale)							(	General	Rema	rks				
06.0	<b>←</b>	2.70 —													
	<b>V</b>														


GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log TRIAL PIT LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:51 | KF. RSK Environment Ld, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

1:25 All dimensions in metres Scale: Method Used: Plant Used: Logged By: Checked By: JCB-3CX Machine dug MHocking



Contract:				Client:		Trial Pit	:		
East Midlands	Gate	way		Roxhil			TP	<b>31</b>	
Contract Ref:	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	25.9.13		50.03	E:447067.7 N:327271.9		1	of	1


Sam	ples a	nd In-si	tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	8	Ba	•	ness)	Legend
0.00-0.30	2	B	Tx2+J+Vx2			Crop stubble over very stiff brown slightly gravelly silty sandy CLAY with occasional subrounded quartzite cobbles and rootlets. Gravel is angular to rounded fine to coarse quartzite and flint, and rare angular fine brick.  (SUBSOIL)  Very stiff dark orange brown mottled brown slightly gravelly very silty CLAY with occasional rootlets. Gravel is subrounded to rounded fine to medium occasional coarse quartzite.  (HEAD DEPOSITS)  Very stiff red brown occasionally bedded green grey silty CLAY.	(0.30)	x
- - - - - - - - -						Very stiff red brown occasionally bedded green grey silfy CLAY. Recovery includes occasional angular to subrounded fine to medium occasionally coarse gravel sized mudstone lithorelicts and siltstone fragments. (Weathering Grade IVb) (EDWALTON MEMBER)	(1.50)	
- - - - - - - - -						Orange brown occasionally bedded grey very weathered SILTSTONE and fine SANDSTONE recovered as tabular and angular fine to coarse gravel and cobbles within clay matrix.  (Weathering Grade II)  (EDWALTON MEMBER)  below 2.10m bgl, gravelly silty.	(1.35)	X X X X X X X X X X X X X X X X X X X
- - - - -						Trial pit terminated at 3.75m depth.	-	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	way		Roxhil			TP.	312	
Contract Ref:	Start:	27.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	27.9.13		51.47	E:447222.9 N:327107.5		1	of	1_


	J 1 2	T/T	Elia.	41.	7.13	31.47 E.447222.7 N.327107.3	1	01 1
San	ples a	ınd In-si	tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	<b>×</b>	Вас	•	ness)	Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over very soft dry slightly sandy slightly gravelly very silty CLAY with occasional rootlets. Gravel is angular to rounded fine to medium quartzite and flint.  (SUBSOIL)	(0.30)	× × ×
-						Very stiff orange brown slightly sandy silty CLAY. Recovery includes frequent tabular and angular sandstone cobbles. (Weathering Grade IVb/III) (TARPORLEY SILTSTONE FORMATION)	(0.65)	
-							0.95	
1.00-1.20	2	В				Very stiff fissured red brown bedded green grey silty CLAY. Recovery includes tabular and angular fine to coarse sandstone and siltstone fragments.  (Weathering Grade III)  (TARPORLEY SILTSTONE FORMATION)  @ 1.10m bgl, green grey bands.	(0.75)	
						@ 1.40m bgl, green grey bands.	-	
1.60-1.70	3	В				below 1.60m bgl, recovery includes occasional to some tabular and angular sandstone and siltstone cobbles.	1.70	
-						Red brown bedded green grey fine SANDSTONE and SILTSTONE recovered as tabular and angular cobbles and occasional boulders upto 0.25m diameter within clay matrix.  (Weathering Grade II)	(0.40)	
						(TARPORLEY SILTSTONE FORMATION) @ 1.85m bgl, green grey bands @ 2.00m bgl, green grey bands.	-	
-						Trial pit terminated at 2.10m depth.	-	
-							-	
							-	
-							-	
							-	
3								
							-	
ļ.							1	






Contract:				Client:		Trial Pit:				
East Midlands	Gate	way		Roxhil		,	TP.	313		
Contract Ref:	Start:	24.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	24.9.13		52.57	E:447140.3 N:327118.1		1	of	1_	

•	)12	<del>+</del> フサ	Ena:	24.9.13	32.37	E:44/140.5 N:52/110.1	1	01 1
	1	1	tu Tests	Water Backfill		Description of Strata	Dept (Thic	
Depth	No	Type	Results	W		•	ness	
0.20-0.30	1	ES	Tx2+J+Vx2		CLAY with frequent roc coarse quartzite and flint. (SUBSOIL)		e to $\begin{bmatrix} 0.35 \\ 0.35 \end{bmatrix}$	
					Very stiff orange brow occasional rootlets. Gr quartzite and sandstone. (HEAD DEPOSITS)	n slightly gravelly silty sandy CLAY vavel is subangular to rounded fine to co	with -	
- - -					Very stiff light red bro some to frequent tabula sandstone cobbles. (Weathering Grade IVa) (TARPORLEY SILTST	wn slightly sandy CLAY. Recovery incluir and angular fine grained light grey brown one FORMATION)	ıdes	
1.30-1.50	2	В			between 1.60m and 2 of stiff red brown mottled	2.00m bgl, cobble to small boulder sized poc I green grey silty CLAY.	-(1.60 kets	
2.10-2.30	3	В			SANDSTONE recovered and fine to coarse grave slightly clayey sand.	gl, light brown grey fine to medium graid as tabular cobbles and 0.50m diameter cobel in interbedded slightly sandy silty clay	bles [	
					Trial g	oit terminated at 2.30m depth.	- - -	
-							- - -	
							- - -	
							-	
-							- - -	
							ļ	






C						CI:t	INIAL			
Contract:	Foot	. M:J	lands Gate	NAME OF THE OWNER		Client:	ll Developments Ltd	Trial F		ГР314
Contract Re		ı ıvııu	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:		11314
	 3124	<b>194</b>	End:	<b>25.9.13 25.9.13</b>		<b>59.81</b>	E:446965.9 N:327121.7	Sheet.		of <b>1</b>
		ınd In-si	tu Tests						Depth	
Depth	No		Results	Water Backfill			Description of Strata		(Thick ness)	
-					with occas \(SUI Very CLA	frequent rootlets. sionally coarse quart 3SOIL) stiff orange brown	stiff brown slightly sandy gravelly silty Gravel is angular to rounded fine to zite and flint.  n mottled brown slightly gravelly silt botlets. gravel is subangular to subroun	medium  y sandy	0.25	X
0.60-0.70	1	ES	Tx2+J+Vx2		(HE	AD DEPOSITS)			1.00	X
1.00-1.20	2	В			CLÁ siltst (Wea	Y. Recovery include one and fine sandsto othering Grade IVb)	brown occasionally bedded green grees occasional angular fine to coarse grant ne fragments.  ONE FORMATION)		(0.85)	
2.15-2.35	3	В			recov some (Wea	vered as tabular and e cobble sized fragmenthering Grade III)	en grey SILTSTONE and fine SAND angular fine to coarse gravel and occasents within a clay matrix.  ONE FORMATION)	STONE sional to	(1.00)	X X X X X X X X X X X X X X X X X X X
- - - -				XXXX		Trial p	it terminated at 2.85m depth.		-	





Contract:	East Midlands Gateway			Client:		Trial Pit:	:		
East Midlands	Gate	eway		Roxhi	ll Developments Ltd			TP	315
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		56.37	E:446555.6 N:327118.9		1	of	1


								-
Sam	ples a	nd In-si	tu Tests	Water	Backfill	Description of Strata	Depth	Material Graphic
Depth	No	Туре	Results	Ä	Bac	·	ness)	Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Grass over stiff brown slightly gravelly silty CLAY with frequent rootlets. Gravel is angular to rounded fine to medium coarse quartzite and flint.  (SUBSOIL)	(0.30)	xoxcx
-						Very stiff dark orange brown slightly gravelly very silty CLAY with occasional rootlets. Gravel is angular to rounded fine to coarse quartzite. (HEAD DEPOSITS)	(0.50)	X X
0.70		V	c <sub>u</sub> =92/68/78			Firm to stiff fissured red brown occasionally mottled green grey silty CLAY. Recovery includes occasional fine to coarse siltstone and fine	0.80	xo xo
1.20-1.40	2	В				sandstone fragments. (Weathering Grade IVa-III) (TARPORLEY SILTSTONE FORMATION) below 1.00m bgl, sandy very silty CLAY and slightly gravelly sandy very clayey SILT.	- - -	
-							-	
-							(2.90)	
-						below 2.90m bgl, recovery includes occasional tabular and angular siltstone and fine sandstone cobbles.	-	
-						below 3.55m bgl, light green grey interlaminated stiff silty CLAY and tabular and angular fine to coarse siltstone and fine sandstone (GRAVEL. (Grade III)	3.70	 
- - -						Light green grey SILTSTONE and fine SANDSTONE recovered as tabular and angular cobbles within clay matrix. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)  Trial pit terminated at 3.80m depth.	- - -	
-							-	





Contract:				Client:		Trial Pit:				
East Midlands	Gate	way		Roxhil	l Developments Ltd		1	TP.	316	
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	26.9.13		68.16	E:446322.8 N:327059.6		1	of	1	


•	714	177	Ena:	20.	9.13	00.10 E.440322.0 N.327039.0		01 1
Sam	ples a	nd In-si	tu Tests	Water	Backfill	Description of Strata	Depth	Material Graphic
Depth	No	Type	Results	W	Вас	Description of Strata	ness)	Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over very stiff brown slightly gravelly slightly sandy silty CLAY with frequent rootlets. Gravel is subangular to rounded fine to coarse quartzite and rare brick.  (MADE GROUND)	(0.30)	
0.50		V	>120 x 3			Very stiff dark orange brown slightly gravelly silty sandy CLAY with occasional rootlets. Gravel is subrounded to rounded fine to coarse quartzite.  (THRUSSINGTON MEMBER) below 0.40m bgl, rare gravel.	(0.50)	
0.80-0.90	2	B V	>120 x 3			Very stiff fissured red brown occasionally mottled grey silty CLAY. Recovery includes rare tabular and angular fine sandstone cobbles. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	-	
		p				below 1.50m bgl, recovery includes frequent grey fine to coarse gravel and cobbles of fine sandstone and siltstone.  below 1.70m bgl, recovery includes frequent grey fine to coarse gravel and cobbles of fine sandstone and siltstone.	1.95	
1.90-2.00	3	В				Light grey banded red brown SILTSTONE and fine SANDSTONE recovered as tabular and angular cobbles within clay matrix (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)	(0.45)	× × × × × × × × × × × × × × × × × × ×
						Trial pit terminated at 2.40m depth.		





Contract:				Client:	Trial Pit:				
East Midlands	Gate	way		Roxhil		,	TP	317	
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		73.04	E:446107.4 N:327052.1		1	of	1_


•	3124	494	End:	26.9.13	/3.04 E:4	46107.4 N:327052.1	1	of I
	<u> </u>	I	tu Tests	Water Backfill	Descrip	otion of Strata	(Thick	Material Graphic
Depth 0.10-0.30	No 1	Type ES	Results Tx2+J+Vx2	B	Crop stubble and grass over vegravelly very silty CLAY with cangular to rounded fine to coarse (SUBSOIL)	ery stiff brown slightly sandy slightly occasional to some rootlets. Gravel is quartzite and flint.	(0.30) (0.30)	Legend  XO X X X X X X X X X X X X X X X X X X
-					Very stiff dark orange brown slig is subrounded to rounded fine to (THRUSSINGTON MEMBER)	thtly gravelly very silty CLAY. Gravel medium quartzite.	(0.30)	x x
0.65		V	>120 x 3		Very stiff red brown slightly silty (Weathering Grade IVb) (TARPORLEY SILTSTONE FO		-	<u>x _ x</u>
0.90-1.00 -0.90-1.00	2 3	B ES	Tx2+J+Vx2				-	xx xx xx
-							(1.30)	xx xx
1.60	4	В					-	X X
2.00	5	В			Green grey and red brown fir recovered as tabular fine to coars upto 0.30m in size. (Weathering Grade III) (TARPORLEY SILTSTONE FO	ne SANDSTONE and MUDSTONE see gravel with frequent tabular cobbles	2.10	
-						nated at 2.10m depth.	- - -	
-							-	
-							-	
-							-	
							-	
-							-	
							-	





Contract:				Client:		Trial Pit	:		
East Midlands	Gate	eway		Roxhil	ll Developments Ltd			TP	319
Contract Ref:	Start:	25.9.13	Groun	nd Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	25.9.13		77.59	E:446010.2 N:326684.3		1	of	1


•	712	<del>1</del> 24	Ena:	25.3	9.13	11.39 E:440010	J.2 T1.320004.3	1	01 1
Sam Depth	ples a	T	tu Tests Results	Water	Backfill	Description of S	Strata	Depth (Thick ness)	Material Graphic Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over stiff orange brown sligh CLAY with occasional rootlets. Gravel coarse quartzite and igneous rock. (SUBSOIL)  Red brown occasionally mottled green SANDSTONE recovered as tabular and occasional boulders up to 0.30m in size wi (Weathering Grade III)  (TARPORLEY SILTSTONE FORMATION)	grey SILTSTONE and fine to angular gravel, cobbles and thin a clayey matrix.	- 0.25	× × × × × × × × × × × × × × × × × × ×
1.10-1.20	2 3	B B						1.50	X X X X X X X X X X X X X X X X X X X
						Trial pit terminated at 1	.50m depth.	_	
								-	
-								-	
								-	
_								-	
•								-	
•									
								_	
								-	
								-	
								_	
								-	
								-	
-									
								_	
								-	
								_	
								-	
								-	
•								-	
•									
_								L	
								-	
								-	
-								-	
	1	1			1			L	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	way		Roxhil	l Developments Ltd			TP	<b>320</b>
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		71.48	E:446101.0 N:326806.1		1	of	1


•	<u>) 1 2 '</u>	+ <i>7</i> +	Ena:	40.	9.13	/1.40 E.440101.0 N.320000.1	1	01 1
Sam	ples a	ınd In-si	tu Tests	er	119		Depth	Material
Depth	No	T	Results	Water	Backfill	Description of Strata	(Thick ness)	Graphic Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over very soft brown slightly gravelly slightly sandy silty CLAY with occasional some rootlets. Gravel is angular to rounded fine to medium quartzite.  (SUBSOIL)	(0.30)	x x
-						Stiff orange brown slightly sandy slightly gravelly very silty CLAY. Gravel is subrounded to rounded fine to medium quartzite. (THRUSSINGTON MEMBER)	(0.75)	× × × ×
- 0.75 -		V	c <sub>u</sub> =112/90/99				- 1.05	× × × × × × × × × × × × × × × × × × ×
-						Stiff light orange brown grey slightly gravelly silty CLAY. Gravel is angular to rounded fine to medium flint and quartzite. \((THRUSSINGTON MEMBER)\) Very stiff red brown bedded green grey slightly sandy very silty CLAY.	1.20	xoxo
1.50-1.70 1.50-1.70	2 3	B B		,		Recovery includes occasional tabular fine sandstone and siltstone cobbles.  (Weathering Grade IVa/ III)  (TARPORLEY SILTSTONE FORMATION)	-	
- -				<u></u>		below 1.80m bgl, recovery includes some to frequent cobbles. (Grade III)	- -	
- - -							(1.90)	
- - -							-	
-							- -	
-						Trial pit terminated at 3.10m depth.	3.10	
_						That pit commuted at 3.10m depail.	-	
_							-	
_							-	
_							-	
-							-	
_							_	
_							_	
_							-	
-							-	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	way		Roxhil	l Developments Ltd		1	TP.	321
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		68.58	E:446307.6 N:326646.9		1	of	1


•	114	17 1	Eliu.	20.	7.13	10.30 E.440307.0 11.320040.9	-	01 1
Sam	ples a	nd In-si	tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	× ×	Вас	•	ness)	Legend
0.20-0.30	1	ES	Tx2+J+Vx2			Grass over very stiff brown slightly gravelly slightly sandy very silty CLAY with frequent rootlets. Gravel is subrounded to rounded fine to medium quartzite. (SUBSOIL)  Red brown slightly gravelly sandy very silty CLAY. Gravel is	0.35	× × × × × × × × × × × × × × × × × × ×
0.80-0.90	2	В				subangular to rounded fine to medium occasional coarse quartzite and sandstone with rare rounded fine quartzite pebbles. (HEAD DEPOSITS)	(0.75)	
-						Stiff to very stiff red brown mottled light grey and green grey slightly sandy silty CLAY. Recovery includes occasional tabular and angular fine to coarse siltstone and fine sandstone fragments. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	-(1.40)	
2.70-2.80	3	В		1		Red brown SILTSTONE and fine SANDSTONE recovered as tabular and angular fine to coarse gravel and frequent cobbles within clay matrix.  (Weathering Grade III)  (TARPORLEY SILTSTONE FORMATION)  Trial pit terminated at 2.85m depth.	2.50	******  ******  ******  ******  ******  ****





									_	_
Contract:					Client:		Trial Pi	it:		
East Midland	s Gate	eway	7		Roxhi	ll Developments Ltd		1	<b>P3</b>	322
Contract Ref:	Start:	27.	9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	27.	9.13		74.20	E:446496.5 N:326577.7		1	of	1
Samples and In-situ Tes	ts	/ater	ackfill			Description of Strata		Depth (Thick		terial aphic


				_				
	ples a		tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Materia Graphic
Depth	No	Type	Results	≱	Ba	·	ness)	Legend
						Crop stubble over very stiff dry brown slightly gravelly slightly sandy very silty CLAY with occasional rootlets and small roots. Gravel is subrounded to rounded fine to medium quartzite. (SUBSOIL)  Very soft orange brown slightly sandy slighty gravelly very silty CLAY	(0.40)	X
0.60	1	ES	Tx2+J+Vx2			with occasional small roots. Gravel is angular to rounded fine to coarse quartzite and sandstone. (HEAD DEPOSITS)	(0.70)	x
						Very stiff slightly red brown silty CLAY. Occasional rootlets. Recovery includes subangular to rounded fine occasional medium gravel sized siltstone fragments.  (Weathering Grade IVb)  (TARPORLEY SILTSTONE FORMATION)	1.10	×
				1		between 1.70m and 1.90m bgl calcareous band.	(1.05)	
2.20-2.50 2.20-2.50	2 3	B B		-		Very stiff fissured red brown silty CLAY. Recovery includes tabular and angular fine to coarse gravel sized siltstone and mudstone and fine sandstone fragments. (Weathering Grade IVa III) (TARPORLEY SILTSTONE FORMATION)	(0.55)	XO
						between 2.30m and 2.45m green gray band. between 2.60m and 2.75m bgl green grey band.	2.70	
-					*****	Red brown bedded green grey SILTSTONE and fine SANDSTONE recovered as tabular and angular cobbles with occasional to some boulders up to 0.30m size in clayey matrix.  (Weathering Grade II)  (TARPORLEY SILTSTONE FORMATION)	2.80	×××
						Trial pit terminated at 2.80m depth.	_	
							_	
							_	
							_	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	eway		Roxhil	ll Developments Ltd			TP	323
Contract Ref:	Start:	24.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	24.9.13		61.47	E:446507.7 N:326876.3		1	of	1


	312	494	End:	24.9.13	61.4/ E:4	46507.7 N:326876.3	<u> </u>	of I
Sa Depth	mples a	and In-si	tu Tests Results	Water Backfill	Descript	tion of Strata	Depth (Thick ness)	Material Graphic Legend
-		31			Crop stubble over stiff red brown (SUBSOIL)		(0.30)	
0.50	1	ES	Tx2+J+Vx2		pockets of grey or green grey silt. to subangular fine to coarse sandst (Weathering Grade IVb) (TARPORLEY SILTSTONE FOI	_		
165 195		D			sandstone and siltstone fragments.		1.65	
1.65-1.85 1.65-1.85 1.65-1.85 1.65-1.85	2 3 4 5	B B B B			Interbedded extremely weak red weak to very weak yellow a SANDSTONE. (Weathering Grade III) (TARPORLEY SILTSTONE FOR	I brown SILTSTONE and extremand grey fine to medium grain RMATION)	ned -	× × × × × × × × × × × × × × × × × × ×
-					Trial nit termin	ated at 2.20m depth.	2.20	× × × ×
					i nai pit termin	ated at 2.20m depth.	- - - - - - - - - - - - - - - - - - -	
-							-	
L							Ļ	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	way		Roxhil	l Developments Ltd			TP	<b>32</b> 4
Contract Ref:	Start:	24.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	24.9.13		68.40	E:446934.7 N:326646.1		1	of	1


•	114	·/ ·	Eliu.	47.7	.15	00.T0 E.TTU/ST./ 11.5200T0.1		01 1
	<u> </u>	nd In-si		Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	8	Ba	•	ness)	Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over very stiff brown slightly gravelly silty sandy CLAY with frequent rootlets. Gravel is angular to rounded fine to coarse quartzite.  (SUBSOIL)	(0.30)	X X X
- - - 0.65-0.85	2	В				Crange brown very rare very silty fine SAND with occasional rootlets. Gravel is angular to rounded quartzite and flint. (HEAD DEPOSITS)	(0.70)	β × β × β × β × β × β × β × β × β × β ×
-						Very stiff red brown bedded green grey fissured silty CLAY. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	-(1.40)	X X X X X X X X X X X X X X X X X X X
2.00-2.50 - 2.00-2.50 - 2.00-2.50 - 2.30-2.50	3 4 5	B B B				$\dots$ below 2.00m bgl, recovery includes occasional tabular and angular fine to coarse gravel sized siltstone and fine sandstone fragments.	2.40	X X
-						Red brown bedded green grey extremely weak to very weak SILTSTONE and fine SANDSTONE recovered as tabular and angular fine to coarse gravel, cobbles and boulders up to 0.30 in size. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)	-(0.60)	X
-					^^^	Trial pit terminated at 3.00m depth.	-	
-							- -	
-							-	
-							- - -	
-							- -	





Contract:				Client:		Trial Pit	:		
East Midlands	Gat	eway		Roxhi	ll Developments Ltd			TP	325
Contract Ref:	Start:	10.10.13	Groun	nd Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	10.10.13		61.76	E:447107.9 N:326883.5		1	of	1


•	712	<del>1</del> 24	Eng:	10.10.1	13	01.70	E:44/10/.9 N:320003.3		1	01 1
	1	T	tu Tests	Water	Backfill		Description of Strata		Depth (Thick	Material Graphic
Depth	No	Type	Results		ß		•		ness)	Legend
- 0.05	1	ES	Tx2+J+Vx2			to very silty CLAY with fine to coarse quartzite an \(\((\subset)(SUBSOIL)\)		ided /	0.25	x _ x
-						angular to rounded fine to (HEAD DEPOSITS)	slightly gravelly silty sandy CLAY. Grave medium flint and quartzite.  7 CLAY. Recovery includes occasional tab		(0.50)	
- 0.85-1.05	2	В				(Weathering Grade IVb) (TARPORLEY SILTSTO			- 0.85	  
-						tabular and angular cobbl (TARPORLEY SILTSTO	es.	-	-	X
- 1.45-2.05	3	В				between 1.45m and 1	.65m bgl, interlaminated with soft grey clay	•	[(1.20)	X
-						\grained SANDSTONE.	2.00m bgl, green grey SILTSTONE and	fine	- - 2.05	× × × × × × × × × × × × × × × × × × ×
-						Trial p	it terminated at 2.05m depth.		_	
-									-	
-									-	
-									_	
-									-	
-									-	
									-	
-									_	
-									-	





Contract:				Client:		Trial Pi	t:	
East Midlands	Gate	way	7	Roxhi	ll Developments Ltd		T	<b>P326</b>
Contract Ref:	Start:	24.	9.13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:		
312494	End:	24.	9.13	59.29	E:447181.0 N:326760.8		1	of 1
Samples and In-situ Tests		Vater	ackfill		Description of Strata		Depth (Thick	Material Graphic


Sam	ples a	nd In-si	tu Tests	Water	Backfill	Description of Strata	Depth (Thick	
Depth	No	Туре	Results	×	Bac	·	ness)	Legend
						Crop stubble over very soft brown slightly sandy CLAY with frequent rootlets. Gravel is angular to rounded fine to coarse quartzite and rare fine brick.  (SUBSOIL)	0.25	* · · · ×
0.60-0.70	1	ES	Tx2+J+Vx2			Orange brown slightly gravelly very silty fine SAND with occasional rootlets. Gravel is angular to rounded fine to medium quartzite and flints.  (HEAD DEPOSITS)	0.50	* * * * * * * * * * * * * * * * * * *
-						Red brown friable clayey sandy SILT. (TARPORLEY SILTSTONE FORMATION)	(1.40)	*
1.50-1.70	2	В				below 1.40m bgl, brown and slightly clayey slightly gravelly very sandy SILT.	1.90	* · · · · · · · · · · · · · · · · · · ·
-						Very stiff fissured red brown bedded green grey slightly sandy slightly silty CLAY. Recovery includes occasional tabular and angular fine to medium gravel sized siltstone fragments. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	-(1.20)	X X X X X X X X X X X X X X X X X X X
						Red brown bedded green grey extremely weak to very weak SILTSTONE and fine SANDSTONE recovered as tabular and angular fine to coarse gravel and occasional cobbles with clay laminations. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)  Trial pit terminated at 3.30m depth.	3.10	<u>x                                    </u>





Contract:				Client:		Trial Pit	:		
East Midlands	Gate	eway		Roxhi	l Developments Ltd			TP	327
Contract Ref:	Start:	24.9.13	Groun	nd Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	24.9.13		59.53	E:447299.6 N:326692.1		1	of	1


	J12	• / •	Eliu.	47.7	•••	37.33 E.447277.0 11.320072.1		01 1
Sar	nples a	ınd In-si	tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	W	Ва	Description of State	ness)	Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over very soft brown slightly gravelly silty sandy CLAY with frequent rootlets. Gravel is angular to subrounded fine to medium flint and quartzite.  (SUBSOIL)	(0.30)	xx
- - - -						Dark orange brown mottled slightly purple brown slightly clayey slightly gravelly very sandy SILT with occasional rootlets. gravel is angular to rounded fine to medium quartzite and flint. (HEAD DEPOSITS)	(0.70)	× · × × × × × × × × × × × × × × × × × ×
1.20-1.40	2	В				Stiff to very stiff fissured red brown bedded green grey silty CLAY. Recovery includes occasional tabular and angular fine to coarse gravel sized siltstone and fine sandstone fragments. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	(0.90)	
- - - -						Red brown bedded green grey extremely weak SILTSTONE and fine SANDSTONE recovered as silty tabular and angular fine to coarse gravel and occasional cobble sized and rare boulder sized fragments.	1.90	×××× ×××× ××××
2.60-2.80	3	В				(~0.30m) (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)	-(1.00)	X
-					*****	Trial pit terminated at 2.90m depth.	2.50	^ ^ ^
-							- - - - - - - - -	





Contract:				Client:		Trial Pit	:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		T	PS.	301
Contract Ref:	Start:	3.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	3.10.13		55.46	E:445476.8 N:327171.9		1	of	1


	Samj	oles a	nd In-si	tu Tests	Water	cfill	Description 600 t	Depth	Material Graphic
	Depth	No	Type	Results	Wa	Backfill	Description of Strata	(Thick ness)	Legend
	0.50 0.60 0.70-1.00	1 2	ES V B	Tx2+J+Vx2 c <sub>u</sub> =56/66/54			Grass and weeds over stiff to very stiff brown desicated slightly gravelly silty sandy CLAY, with frequent rootlets and occasional roots. Gravel is angular to rounded fine to medium sandstone, quartzite and flint. (SUBSOIL)  Firm becoming stiff red brown slightly sandy very silty CLAY. Recovery includes occasional subangular to rounded fine occasional medium sandstone fragments. Occasional quartzite gravel at the subsoil interface. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	0.20	
	- - - - -						below 1.30m bgl, recovery includes fine to medium and occasional coarse gravel sized sandstone fragments.	(2.65)	
. 041/0 20011, 1150	2.10-2.80	3	В				between 2.10m and 2.30m bgl, recovery includes occasional to some tabular sandstone cobbles below 2.30m bgl, recovery includes tabular and angular fine to coarse gravel sized sandstone, and rare cobbles.	- - - - -	
.,	-						Trial pit terminated at 2.85m depth.	2.85	
versity reciniology raik, Covenity, CA1 21A. 161. 024/0 230610, rax. 024/0 230014, web.	- - - - - - - - - -							- - - - - - - - - - -	





Contract:				Client:	Trial Pit	:			
East Midlands	Gate	eway		Roxhil	l Developments Ltd		T	PS.	302
Contract Ref:	Start:	3.10.13	Groun	nd Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	3.10.13		67.94	E:445940.3 N:327428.4		1	of	1


	J12 <sup>2</sup>	+7 <b>+</b>	Ena:	3.1	0.13	07.34 E.443340.3 N.327420.4	1	01 1
Samples and In-situ Tests  Depth No Type Results		Water	Backfill	Description of Strata	Depth (Thick	Material Graphic		
Depth	No	Type	Results	≥	Ba	·	ness)	Legend
0.40-0.60	1	ES	Tx2+J+Vx2			Very stiff brown desicated slightly gravelly slightly sandy silty CLAY. Gravel is angular to rounded fine to medium occasional coarse quartzite, occasional sandstone and rare brick. (SUBSOIL) Stiff dark orange grey slightly sandy slightly silty to very silty slightly gravelly to gravelly CLAY. Gravel is angular to rounded fine to coarse	0.30	X X X
-						quartzite, sandstone and occasional coal. (THRUSSINGTON MEMBER)@ 0.50m bgl,land drain in side of pit, dry.	(0.80)	
_							1.10	
_						Very stiff red brown fissured slightly sandy slightly silty CLAY. Recovery includes occasional tabular sandstone cobbles.  (Weathering Grade IVb)	-	
						(TARPORLEY SILTSTONE FORMATION)	-	
1.60.1.00								
1.60-1.80	2	В					-	
-							(1.40)	
2.00-2.40	3	В					-	
-							-	
-							-	
							2.50	
_						Trial pit terminated at 2.50m depth.		
-							-	
-							-	
							-	
-							-	
-							-	
-							_	
-							-	
-							-	
-							-	
-							-	
}							-	
-							}	





Contract:				Client:	Client:				
East Midlands	Gate	eway		Roxhil	Roxhill Developments Ltd				
Contract Ref:	Start:	3.10.13	Groun	nd Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	3.10.13		54.36	E:446258.9 N:327473.2		1	of	1


San	nples a	ınd In-si	tu Tests	ter	III	- · · · · · · · · · · · ·	Depth	Material
Depth	No	Туре	Results	Water	Backfill	Description of Strata	(Thick ness)	Graphic Legend
0.10-0.20	1	ES	Tx2+J+Vx2			Crop stubble over stiff to very stiff brown desicated slightly gravelly silty sandy CLAY with occasional rootlets. Gravel is angular to rounded fine to medium occasional coarse quartzite and flint.  (SUBSOIL)	(0.30)	x · · x
1.00-1.40	2	В				Very stiff orange brown slightly gravelly silty sandy CLAY with rare rootlets. Gravel is angular to rounded fine to coarse quartzite and rare flint and sandstone. (THRUSSINGTON MEMBER) below 0.70m bgl, rare subangular to rounded quartzite cobbles.	(1.55)	
2.50-3.00 - 2.50-3.00 - 2.50-3.00	3 4	B D V	c <sub>u</sub> =54/30/34			Firm to stiff red brown slightly silty CLAY. Recovery includes occasional tabular and angular fine to medium gravel sized mudstone lithorelicts, siltstone and sandstone fragments. (Weathering Grade IVb) (EDWALTON MEMBER) @ 1.90m and 2.20m bgl, partings of green grey siltstone and sandstone.  @ 2.50m bgl, soft to firm.	(1.35)	
-						Trial pit terminated at 3.20m depth.	3.20	





Contract:				Client:		Trial Pit:			
East Midlands	Gate	way		Roxhil		T	PS.	304	
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13		52.85	E:446679.4 N:327528.5		1	of	1


L		114-	177	Ellu.	1.1	0.15	32.03 E.TT0077.T11.327320.3		01 1
	Samj	ples a	nd In-si	tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
	Depth	No	Type	Results	×	Вас	Description of Strate	ness)	Legend
-	0.20-0.30	1	ES	Tx2+J+Vx2			Crop stubble over very stiff very dry brown desicated slightly sandy slightly gravelly silty CLAY with occasional rootlets. Gravel is subangular to rounded fine to coarse quartzite.  (SUBSOIL)  Very stiff red brown slightly gravelly sandy to very sandy CLAY. Gravel is subangular to rounded fine to medium occasional coarse	(0.30) 0.30 - 0.45	x · · x
-	0.80		V	c <sub>u</sub> =84			quartzite. (HEAD DEPOSITS)  Stiff red brown slightly sandy to sandy very gravelly CLAY. Gravel is angular to rounded and tabular fine to medium occasional coarse quartzite, flint and sandstone. (HEAD DEPOSITS)  Stiff to very stiff fissured red brown mottled green grey slightly sandy	0.90	x · · · x · · · · · · · · · · · · · · ·
-	- - - - -						CLAY. Recovery includes occasional tabular and angular fine to coarse gravel sized siltstone and fine sandstone fragments. (Grade IVa) (EDWALTON MEMBER) below 1.20m bgl, occasional tabular siltstone cobbles.	-(1.60)	
	1.80-2.30	2	В				below 2.00m bgl, recovery includes some to frequent tabular siltstone and fine sandstone cobbles between 2.00m and 2.15m bgl, green clay.	2.50	
ł	-					××××	Trial pit terminated at 2.50m depth.	2.30	
								- - - - - - - - - - - - - - - - - - -	





Contract:				Client:	Trial Pit:				
East Midlan	ds Gate	eway		Roxhi		T	PS.	305	
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13		39.42	E:447372.8 N:327628.6		1	of	1


L		12	177	Enu.	1.1	0.13	57.42 E.447572.0 11.527020.0		01 1
				tu Tests	Water	Backfill	Description of Strata	Depth (Thick	Material Graphic
	Depth	No	Type	Results	*	, Ba	•	ness)	Legend
-	0.60	1	ES	Tx2+J+Vx2			Crop stubble over very stiff very dry desicated slightly sandy slightly gravelly silty CLAY with occasional rootlets. Gravel is subangular to rounded fine to medium occasional coarse quartzite.  (SUBSOIL)  Very stiff slightly orange brown slightly sandy slightly gravelly to gravelly silty CLAY. Gravel is subangular to rounded fine to coarse quartzite.  (WANLIP MEMBER)	(0.30)	
-	-						below 0.70m bgl, sandy to very sandy.  Stiff to very stiff orange grey mottled red brown slightly gravelly sandy	1.05	X X X
	1.20-1.50	2	В				to very sandy CLAY. Gravel is angular to rounded fine to coarse quartzite and occasional flint.  \( (WANLIP MEMBER) \)	1.30	
-	- - -						Red brown very clayey very gravelly fine to medium occasionally coarse SAND. Gravel is angular to rounded fine to coarse quartzite and occasional flint.  (WANLIP MEMBER)  below 1.30m bgl red brown.	(1.25)	
, , , , , , , , , , , , , , , , , , , ,	2.10-2.30	3	В				below 2.40m bgl, recovery includes rare tabular sandstone cobbles.	(1.35)	
	-						below 2.40th ogt, recovery metades rare tabular sandstone cooles.	2.65	<u> </u>
	-					XXXXXX	Trial pit terminated at 2.65m depth.	2.03	
								-	





Contract:				Client:	Trial Pit:				
East Midlands	Gate	eway		Roxhill Developments Ltd			T	PS	351
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13		38.54	E:447112.1 N:327771.9		1	of	1


	312	<del>1</del> 24	Ena:	1.1	0.13	30.34 E.44/112.1 N.32///1.9	1	01 1
	Samples and In-situ Tests		Water	Backfill	Description of Strata	Depth (Thick	Material Graphic	
Depth	No	Type	Results	3	Ba	·	ness)	Legend
0.10-0.20	1	ES	Tx2+J+Vx2			New crop and crop stubble over very stiff brown sightly gravelly sandy silty CLAY with occasional rootlets. Gravel is angular to rounded fine to medium occasional coarse quartzite and occasional flint.  (SUBSOIL)	(0.30)	~ · · · · · · · · · · · · · · · · · · ·
0.60-0.80	2	В				Orange grey slightly clayey to very clayey very gravelly fine to coarse SAND with occasional subrounded to rounded quartzite cobbles. Gravel is angular to rounded fine to coarse quartzite and occasional flint. (WANLIP MEMBER)	(0.80)	
-						below 0.80m bgl, occasional cobble sized clay pockets.	1.10	
1.20-1.40	3	В				Stiff to very stiff red brown mottled orange and grey slightly silty slightly sandy slightly gravelly CLAY. Gravel is angular to rounded fine to medium quartzite and occasional flint.  (WANLIP MEMBER)	- -	X X
-							1.90	X X
2.20-2.60	4	В				Red brown slightly clayey SAND and GRAVEL. Sand is fine to coarse. gravel is angular to rounded and tabular fine to coarse quartzite, flint and occasional sandstone. (WANLIP MEMBER)	(0.75)	
				<b>*</b>			2.65	
\						Trial pit terminated at 2.65m depth.	-	
-							- - -	
-							-	
							-	
3 -							-	
,							_	





Contract:				Client:		Trial Pit:				
East Midlands	Gate	eway		Roxhill Developments Ltd			T	PS	35	<b>52</b>
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	1.10.13		41.14	E:446959.7 N:327760.9		1	of	1	l

Į	<u>3</u>	124	194	End:	1.10	J.13	41.14 E:446959	9./ N:32//60.9	1	of I
	Samp Depth	oles a No	nd In-sit	tu Tests Results	Water	Backfill	Description of S	Strata	Depth (Thick ness)	Material Graphic Legend
	0.50	1	ES	Tx2+J+Vx2			New crop and crop stubble over very stift CLAY with occasional rootlets. Gravel medium quartzite and flint. (SUBSOIL)  Very stiff orange grey slightly gravelly Gravel is angular to rounded fine to media and flint. (WANLIP MEMBER)	is angular to rounded fine to sandy to very sandy CLAY.	0.30	
	- - -						Stiff to very stiff red brown mottled orange sandy to sandy slightly gravelly CLAY. fine to coarse quartzite and flint. (WANLIP MEMBER)	e and grey slightly silty slightly Gravel is angular to rounded	0.90	
	- - -						Red brown clayey very silty very gravel coarse SAND with occasional angular fli Gravel is angular to rounded fine to quartz (WANLIP MEMBER)	int and rare quartzite cobbles.		0
	1.90-2.10	2	В				below 1.90m bgl, recovery includes small boulder sized cemented sand clasts.	occasional to some cobble to	-	0.000 0.000 0.000 0.000
							Trial pit terminated at 2	.55m depth.	- 2.55	.··;.·() · .]





#### PHOTOGRAPHIC LOG - Trial pits - Zone 1

Photo No. Date:

1

3.10.13

Direction Photo Taken:

N/A

**Description:** 

TPS301 – soakaway test completed within trial pit



Photo No. Date:

2

3.10.13

Direction Photo Taken:

N/A

**Description:** 

TPS302 – soakaway test completed within trial pit





Photo No.

Date:

3

3.10.13

Direction Taken:

**Photo** 

N/A

#### **Description:**

TPS303 – soakaway test completed within trial pit



Photo No. Da

Date:

4

1.10.13

Direction Taken:

Photo

N/A

#### **Description:**

TPS304 – soakaway test completed within trial pit





**5** 1.10.13

Direction Photo Taken:

N/A

**Description:** 

TPS305 – soakaway test completed within trial pit



Photo No. Date:

6 26.09.13

Direction Photo Taken:

N/A

**Description:** 





**7** 25.09.13

Direction Photo Taken:

N/A

**Description:** 

TP308



Photo No. Date:

**8** 25.09.13

Direction Photo Taken:

N/A

**Description:** 





9

25.09.13

Direction Photo Taken:

N/A

**Description:** 

TP310



Photo No. Date:

10

25.09.13

Direction Photo Taken:

N/A

**Description:** 





Photo No.

Date:

11

27.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP312



Photo No. Date:

12

24.09.13

Direction Taken:

Photo

N/A

**Description:** 





13

25.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP314



Photo No. Date:

14

26.09.13

Direction Photo Taken:

N/A

**Description:** 





**15** 26.09.13

Direction Photo Taken:

N/A

**Description:** 

TP316



Photo No. Date:

**16** 26.09.13

Direction Photo Taken:

N/A

**Description:** 





Photo No.

Date:

17

25.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP319



Photo No.

Date:

18

26.09.13

Direction Taken:

Photo

N/A

**Description:** 





19

26.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP321



Photo No. Date:

20

27.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP322





Photo No.

Date:

21

24.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP323



Photo No.

Date:

**22** 

24.09.13

Direction Taken:

Photo

N/A

**Description:** 

TP324





**23** 10.10.13

Direction Photo Taken:

N/A

**Description:** 

TP325



Photo No. Date:

**24** 24.09.13

Direction Photo Taken:

N/A

**Description:** 

TP326





25

24.09.13

Direction Taken:

**Photo** 

N/A

**Description:** 

TP327



Photo No. Date:

26

1.10.13

**Direction** Photo

N/A

Taken:

**Description:** 

TPS351 - Soakaway test carried out on completion of trial pit





**27** 1

1.10.13

Direction Photo Taken:

N/A

#### **Description:**

TPS352 – Soakaway test carried out on completion of trial pit





# APPENDIX D CABLE PERCUSSION BOREHOLE LOGS



Contract Reference: 312494

#### KEY TO EXPLORATORY HOLE LOGS - SUMMARY OF ABBREVIATIONS

#### **SAMPLING**

Sample type codes

B = Bulk disturbed sample.

C = Core sample.

CS = Core sample taken from rotary core for lab testing.

D = Small disturbed sample.

DSPT = Small disturbed sample originating from SPT test.

ES = Soil sample for environmental testing.

U = Undisturbed driven tube sample - Number of blows indicated. % recovery reported.

Undisturbed sample detail codes

 $U_{(100)}$  = 100mm diameter undisturbed sample.

#### **IN-SITU TESTING**

 $SPT_{(c)}$  = Standard Penetration Test using a solid 60 degree cone.

 $SPT^{(c)}$  = Standard Penetration Test using split spoon sampler. ( $SPT_{(NR)}$  indicates 'No Sample Recovery').

\* denotes extrapolated N value. NP denotes 'No Penetration'.

V = Field Vane Test. Peak value (c<sub>n</sub>) & Residual value (c<sub>n</sub>), given as shear strength in kPa.

#### **ROTARY DRILLING INFORMATION**

W = Water flush returns (%)
TCR = Total core recovery (%)
SCR = Solid core recovery (%)

RQD = Rock quality designations (%)

If = Fracture spacing (mm).

In the fracture column (i) denotes discontinuity is infilled (refer to Fracture Table for details).

Where variable the minimum - average - maximum spacing may be quoted.

'NI' denotes non-intact core. 'NA' denotes not applicable.

All lengths used to determine rock core mechanical properties taken along the centre line of the core.

Obvious induced fractures have been ignored.

The assessment of solid core is based on lengths that show a full diameter and not necessarily a full circumference.

AZCL = Assessed zone of core loss.

#### ADDITIONAL NOTES

- 1. All soil and rock descriptions and legends in general accordance with BS EN ISO 14688-1, 14688-2, 14689-1, and BS5930:1999 including Amendment 2 (2010).
- 2. Material types divided by a broken line (- - ) indicates an unclear boundary.
- 3. The data on any sheet within the report showing the AGS icon is available in the AGS format.



Contract Reference: 312494

#### KEY TO EXPLORATORY HOLE LOGS - SUMMARY OF GRAPHIC SYMBOLS

#### **WATER COLUMN SYMBOLS**



First water strike, second water strike etc.

Standing water level following first strike, standing water level following second strike etc.

Seepage.

Standing water level recorded at documented date.

#### **MATERIAL GRAPHIC LEGENDS**



CLAY



Clayey gravelly SAND



Gravelly clayey SAND



Clayey gravelly SAND with COBBLES

Clayey SAND



Clayey SAND with COBBLES



Clayey sandy GRAVEL



**GRAVEL** 



GRAVEL with COBBLES



Gravelly CLAY



Gravelly silty CLAY



Silty gravelly CLAY



Silty gravelly CLAY with COBBLES



Gravelly SAND



Gravelly clayey SILT



Gravelly SILT



MADE GROUND



Mudstone



SAND



SAND with COBBLES

#### **INSTRUMENTATION SYMBOLS**



Backfill



Bentonite seal



Concrete



Gravel filter



Sand filter



Stopcock cover



Piezometer tip



Plain pipe



Slotted pipe



Contract:  Client:  Roxhill Developments Ltd  Client:  Contract:  Roxhill Developments Ltd												
		N # 1						ID 1 4 141	Boreho		TD202	
		VIIa	Start:	·		Cmanna	ROXNII l Level (m AOD):	National Grid Co-ordinate:	Sheet:		CP203	
Contract Re	ı: 3124	10.4			9.13	Ground	,	E:447184.9 N:326594.2	Sneet:	1	a 1	
			End:		9.13	.1	67.92	E:44/184.9 N:320394.2			of 1	
Sam	ples a		tu Tests	Water	Backfill & Instru-			Description of Strata		Depth (Thick	Material Graphic	
Depth	No	Type	Results	≥	Back In			•		ness)	Legend	
0.20	1	D				fine to	Brown slightly gravelly sandy CLAY. Gravel is angular to subangular fine to medium brick, sandstone. Occasional rootlets. (SUBSOIL)  Red Brown slightly gravelly clayey fine SAND. Gravel is angular to subangular fine to medium sandstone. Occasional rootlets.  (Weathering Grade IVa)					
0.50	2	D				suban (Weat	subangular fine to medium sandstone. Occasional rootlets. (Weathering Grade IVa) (TARPORLEY SILTSTONE FORMATION)					
0.80-0.80	3	В				G.: 22	Stiff red brown clayey SILT. Occasional black staining. (Weathering Grade IVa)					
1.00	4	D				(Weat	Stiff red brown clayey SILT. Occasional black staining. (Weathering Grade IVa) (TARPORLEY SILTSTONE FORMATION)					
1.20-1.65	5	U	29 blows 90% recovery			0	(TARPORLEY SILTSTONE FORMATION)					
1.70	6	D				angul	Stiff red brown silty CLAY. Recovery includes occasional fine to angular to subangular fine to medium sandstone skerries fragments. (Weathering Grade IVb)					
2.00	7	D				(TAR	PORLEY SILTSTO	ONE FORMATION) own silty clay becoming very weak red	brown	2.00	×	
2.20-2.65 - 2.20-2.70	1 8	SPT B	N=33			<ul><li>MUD</li><li>spots</li><li>(Weat</li></ul>	STONE. Occasion and sandstone skerr thering Grade III)	al silt bedding and occasional grey re-	luction	_		
- - -										_		
2.90 3.00-3.45	9 2	D SPT	N=38									
3.70-4.00	3 10	SPT D	N=100*			at 3.70m bgl, very weak to weak.						
4.00-4.11	4	SPT	N=333*			at 4.00m bgl, moderately weak.						
4.00	11	D			• · • · • · • · • · • · • · • · • · •	Borehole terminated at 4.11m depth.						
-								•				

		Boring Pr	rogress and	Water Ob	servations		Chiselli	ing / Slow	Progress	Company	D amandra		
îΓ	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General	Remarks		
5 L	Dute	Time	Depth	Depth	(mm)	Depth	110111	10	(mi.min)	Location scanned with CA	T and signal generator prior		
	25/09/13		1.20	1.20	150	Dry	3.70	4.00	01:00	to breaking ground. No se			
1	25/09/13		2.20	1.50	150	Dry				2. Hand dug inspection pit excavated to 1.20m bgl			
1 /	25/09/13		3.00	3.00	150	Dry				Groundwater not encounte     Gas and groundwater mon			
2	25/09/13				150	Dry				4.00m bgl upon completio			
1	25/09/13		4.00	4.00 3.00		150 Dry							
										A 11 di	Scale: 1:25		
ł L										All dimensions in metres	1,20		
i []	Method			Plan	t <b>Pilco</b>	n Wayfa	arer	Drilled		Logged	Checked		
	Used:	Cable p	percussio	n Used	l:	1500 <sup>°</sup>	]	By:	GH	By: <b>GShaw</b>	By: AGS		

GINT\_LIBRARY\_V8\_05.GLB LibVersion; v8\_05 - Lib0004 PŋVersion; v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:43 | KF. RSK Environment\_Ld\_, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI\_2TX. Tel: 02476\_236816, Fax: 02476\_236014, Web: www.rsk.co.uk.



Contract:					Client: Boreho  Roxhill Developments Ltd				ole:				
F	Cast	t Mid	lands Gat	ewa	y	Roxhill Developments Ltd  Ground Level (m AOD): National Grid Co-ordinate: Sheet:							
Contract Ref			Start:	24.	9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
3	124	194	End:	24.	9.13		82.82	E:446669.2 N:326418.6		1	of 1		
		nd In-si		Water	Backfill & Instru-			Description of Strata		(Thick	Material Graphic		
Depth	No	Туре	Results	>	Bac Ir Ime			_		ness)	Legend		
-						subr	t brown slightly gra ounded fine to mediu BSOIL)	welly clayey SILT. Gravel is subang m sandstone, quartzite with occasional re	ular to ootlets.	(0.45)	× × × × × × × × × × × × × × × × × × ×		
-						subro rootl (Wea (GU	athering Grade IVa) NTHORPE MEMBE	th rare	0.70	* * - x - x - x - x			
-						(Wea	to stiff red brown sil athering Grade IVa) NTHORPE MEMBE	oands.	(0.70)	x x			
1.20-1.65	1	SPT	N=15			9.00	4	1.40	xx				
2.20-2.65	6	$U_{(100)}$	63 blows 70% recovery			and to	Stiff red brown CLAY with grey reduction spots and occasional siltstone and mudstone bands. (Weathering Grade IVb) (GUNTHORPE MEMBER)						
2.70	7	D					stiff grey mottled br	11. 07.177		2.80			
2.90 3.00-3.43 3.00-3.50	8 2 9	D SPT B	N=55*			Very (Wea	(0.50)	X X					
-						Very weak red brown MUDSTONE with grey siltstone bands and occasional grey reduction spots. (Weathering Grade III) (GUNTHORPE MEMBER)					- X - X		
3.90 4.00-4.33	10 3	D SPT	N=86*				_			(1.02)			
L							Boreho	le terminated at 4.32m depth.		ļ			

	Boring P	rogress and	Water Ob	servations		Chiselli	ing / Slow	Progress	General Remarks
Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General Remarks
		Depth	Depth	(mm)	Depth			(1111.111111)	1. Location scanned with CAT and signal generator prior
24/09/13		4.32	3.00	150	Dry				to breaking ground. No services encountered.  2. Hand dug inspection pit excavated to 1.20m bgl  3. Groundwater not encountered.  4. Gas and groundwater monitoring well installed to  4.00m bgl upon completion.
									All dimensions in metres   Scale: 1:25
Method Used:	Cable r	percussio	n Plant Used		on Wayfa 1500		Drilled By:	GH	Logged By: GShaw Checked By: AGS

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



4.37

								CIT.		CHC			
Contract:	Zaad	L:M:	landa	Cata				Client:	II Davidonmanta I ta		Boreho		D205
Contract Ref		IVIIQ	lands	Start:		9.13	Groun	d Level (m AOD):	Il Developments Ltd  National Grid Co-ordinate:		Sheet:		CP205
	3124	104					Groun	56.42	E:447286.1 N:326		Silect.	1	.c 1
				End:		9.13	1	50.42	E:44/200.1 N:320	0/30.4			of 1
Sam Depth	ples a No	nd In-si Type	tu Tests Res	sults	Water	Backfill & Instru- mentation			Description of Strata			Depth (Thick ness)	Materia Graphic Legend
0.20	1	D					Brown slightly clayey fine SAND with occasional black organic spots and rootlets. (SUBSOIL)				(0.60)		
0.70	2	D					Brown sandy CLAY with occasional rootlets. (HEAD DEPOSITS)					(0.30)	
-							Stiff red brown silty CLAY. Recovery includes occasional angular,					0.90	
1.00	3	D					tabulated fine to coarse sandstone and mudstone lithorelicts. (Weathering Grade IVa)					(0.50)	
1.20-1.65 1.20-1.70	1 4	SPT B	N=	=18			(Weathering Grade IVa) (TARPORLEY SILTSTONE FORMATION)  Stiff red brown mottled grey CLAY. Recovery includes occasional				1.40	x	
2.00	5	D					angu (Wea	lar fine to coarse san thering Grade IVb)	ndstone, mudstone and siltstone	e lithorelicts.	sionai	-	
2.20-2.65	2	SPT	N=	=29				at 2.20m bgl, becomes stiff to very stiff.				(1.90)	
2.90 3.00-3.40 - 3.00-3.40	6 3 7	D SPT B	N=	61*			• • • • • • • • • • • • • • • • • • • •					3.30	
3.70	8	D					reduc (Wea	ction spots and sand athering Grade III)	ed brown MUDSTONE with stone skerries.  ONE FORMATION)	n occasional	grey	(1.07)	
3.80-4.05	4	SPT	N=1	158*		.•.H•.	.1					[(1.07)	

		Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Canaral Dam	orlea	
Centre, C	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General Rem		
≓ I - 1	5/09/13 6/09/13		2.65 4.36	1.50 3.00	150 150	Dry Dry	3.40 3.80	3.80 4.30	01:00 01:00	1. Location scanned with CAT and signal generator prior to breaking ground. No services encountered.     2. Hand dug inspection pit excavated to 1.20m bgl     3. Groundwater not encountered.     4. Gas and groundwater monitoring well installed to 4.30m bgl upon completion.		
	Iethod sed:					on Wayfa		Drilled By:	СН	All dimensions in metres   Scale:   Logged   Chec   By:   <b>CShaw</b>   By:	1120	

at 4.30m bgl, moderately weak to moderately strong.

Borehole terminated at 4.37m depth.

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PrjVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment.Ld, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

4.30-4.37 4.30 SPT D N=500\*



Contract:				Client:		Boreho	le:		
East Midlands	s Gate	eway		Roxhil	l Developments Ltd			CP	206
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	2.10.13		51.90	E:447411.8 N:326888.7		1	of	1
		ي د	-1						

	Samp	oles a	nd In-si	tu Tests	Water	Backfill & Instru- mentation	Description of Strata	Depth (Thick	Material Graphic
	Depth	No	Type	Results	$\bowtie$	Back Ins ment	•	ness)	Legend
0.0	00-1.00	1	В				Red brown sandy CLAY. Recovery includes occasional angular fine to coarse sandstone skerries fragments. (Weathering Grade IVa) (TARPORLEY SILTSTONE FORMATION)	(2.00)	
-	00-1.50	2	В						
-	50-1.95	3	U <sub>(100)</sub>	60 blows 75% recovery				2.00	
2.0	00-2.15 00 00-2.45	1 4 5	SPT D B	N=200*			Weak to moderately weak red brown thinly bedded MUDSTONE and SANDSTONE. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)	(1.00)	
2.0	50-3.00	6	В					3.00	
3.0	00-3.05 00-3.30	2 7	SPT B	N=600*			Moderately weak to moderately strong grey and red/brown fine grained thinly bedded SANDSTONE. (Weathering Grade III) (BROMSGROVE SANDSTONE FORMATION)	(0.35)	
3.3	80-3.35	3	SPT(c)	N=600*		° ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° ° °	Borehole terminated at 3.35m depth.	3.35	

) veni		Boring Pr	ogress and	Water (	Observations		Chisel	ling / Slow	Progress	Canaral Damarka
ciine,	Date	Time	Borehole Depth	Casing Depth	Diameter	Water Depth	From	То	Duration (hh:mm)	General Remarks
= I	01/10/13 02/10/13		2.00 3.35	1.50 1.50	150 150	Dry Dry	3.00	3.30	01:00	Location scanned with GPR a CAT and signal generator prior to breaking ground. No services encountered.     Hand dug inspection pit excavated to 1.20m bgl     Groundwater not encountered.     Borehole backfilled with arisings upon completion.
Kon Luvii	Method Used:				ant sed: <b>D</b>	ando 15	0	Drilled By:	TC	All dimensions in metres Scale: 1:25  Logged By: GShaw Checked By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Boreho	le:		
East Midland	s Gate	eway		Roxhil	l Developments Ltd			<b>CP</b> 2	207
Contract Ref:	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	25.9.13		63.04	E:447086.9 N:326841.6		1	of	1
		l b) =							

•	712	<del>1</del> 24	Ena:	25.9.13	<u> </u>	05.04 E:447000.9 IN:320041.0	1	01 1
Sam	ples a	nd In-si	tu Tests	Water Backfill & Instru-	tation	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	W Back Ins	men	•	ness)	Legend
0.20	1	D				Brown slightly gravelly slightly clayey fine SAND. Gravel is angular fine to coarse brick, clinker, quartzite and concrete. (MADE GROUND)	(0.50)	
0.60	2	D				Stiff red brown silty CLAY. Recovery includes occasional angular fine to coarse mudstone lithorelicts. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	(0.50)	X X X X X X X X X X X X X X X X X X X
1.10 1.20-1.61 1.20-1.70	3 1 4	D SPT B	N=59*	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		Very stiff to very weak red brown CLAY with grey sandstone skerries. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	(0.40)	× ×
2.00		D				Very weak to weak red brown MUDSTONE occasional grey reduction spots and sandstone skerries. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)	1.40	
2.10-2.41	5 2	D SPT	N=94*				(1.57)	
2.70-2.98 2.70	3 6	SPT D	N=120*				2.97	
_					^ 1	Borehole terminated at 2.97m depth.	-	
-							-	

over		Boring Pr	rogress and	Water Ob	servations		Chisel	ling / Slow	Progress	Canaral	D amarlza
entre, (	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General	Remarks
ronment Ltd, The Enterprise C	25/09/13		2.97	1.50	150	Dry	2.40	2.70	01:00	Location scanned with CA to breaking ground. No se     Hand dug inspection pit et     Groundwater not encounte     Gas and groundwater mon     70m bgl upon completio     Made ground associated w  All dimensions in metres	scavated to 1.20m bgl ered. itoring well installed to n.
SK Envi	Method Used:	Cable r	ercussio	Plan Used		n Wayfa	arer	Drilled By:	СН	Logged By: GShaw	Checked By:

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:			Client:		Boreho	le:	
East Midlands	Gate	way	Roxhi	ll Developments Ltd		(	CP208
Contract Ref:	Start:	24.9.13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:		
312494	End:	24.9.13	66.58	E:446836.4 N:326895.9		1	of <b>1</b>
Samples and In-situ Tests  Depth No Type Re:	sults	Water sackfill & Instru-		Description of Strata		Depth (Thick ness)	Materia Graphi Legen

San	<u> </u>	nd In-si	tu Tests	Water	Backfill & Instru-	tation	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	≽	Back	men		ness)	Legend
0.20	1	D					Brown slightly gravelly silty CLAY. Gravel is angular fine to medium sandstone with occasional rootlets. (TOPSOIL)	0.30	1/2 · 24 · 1/2 · 24 · 1/2 1/2 · 24 · 1/2 · 24 · 1/2 1/2 · 24 · 1/2 · 24 · 1/2
0.40	2	D					Very stiff red brown slightly sandy silty CLAY. Recovery includes occasional angular and tabulated fine to coarse fragments. (Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	-	X X
0.90	3	D			•••	* * * *		- -	xx
1.20-1.53	1	SPT	N=83*		· · · · · · · · · · · · · · · · · · ·		at 1.20m bgl, becomes very weak.	(2.02)	X X X X X X X X X X X X X X X X X X X
2.00-2.32 2.00	2 4	SPT D	N=86*					2.32	X X
- - - - - - - - - - - - - - -							Borehole terminated at 2.32m depth.		

	Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	General	Domorto
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)		
24/09/13	24/09/13 Depth 2.32			150	Dry	1.50	2.00	01:00	Location scanned with CA to breaking ground. No se     Hand dug inspection pit e;     Groundwater not encounte     Gas and groundwater mon     2.00m bgl upon completio	ervices encountered. ccavated to 1.20m bgl stred. itoring well installed to n.
									All dimensions in metres	Scale: 1:25
Method Used:	Cable p	ercussio	n Plan Used		on Wayfa 1500		Drilled By:	GH	Logged By: <b>GShaw</b>	Checked By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



C 4 4 -							CI:t				D 1	1	
Contract:	T o o i	4 Mid	lands Gate		17		Client:	g <b>hi</b> ll	<b>Developments Ltd</b>		Boreho		P210
Contract Ref		ı ıvııu	Start:		y 9.13	Grour	nd Level (m AOI		National Grid Co-ordinate:		Sheet:		1 210
		494			9.13 9.13	Gioui	78.01	).	E:446234.1 N:326		Silect.	1	of <b>3</b>
			End:				70.01		E.440234.1 N.320	407.2			
Samp Depth	oles a	and In-si Type	tu Tests  Results	Water	Backfill & Instru-			Ι	Description of Strata			Depth (Thick ness)	Material Graphic Legend
1.00-1.20	2 3	B U(100)	20 blows 100% recovery			Brov subr orga (TO Firm sker (We	rounded fine to onic remains. PSOIL)  n becoming stiff ries and grey reduction at the strength of the strengt	red to uction Va)	clayey fine SAND. Gravel equartzite with many rootlet brown CLAY with occasional spots.  NE FORMATION)	s and occa	sional	0.05	
2.00-2.45 2.00-2.45	1 6	SPT B	N=15									- - - -	
2.50-3.00 - 3.00-3.45	8	D U <sub>(100)</sub>	35 blows 100% recovery									- - - - - -	
3.50 3.50-4.00	9 10	D D				₹ (We	athering Grade Γ	Vb)	y SILT, occasional grey reduc	ction spots.		3.50	× × × × × × × × × × × × × × × × × × ×
4.00-4.45	2 11	SPT B	N=35			sand (We	lstone skerries. athering Grade II	II)	red brown MUDSTONE NE FORMATION)	with occa	sional	4.00	* ×

oven		Boring Pr	rogress and	Water Ol	servations		Chiselli	ing / Slow	Progress	Canaral	Remarks
entre, (	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh;mm)	General	Kemarks
3			Depth	Depth	(mm)	Depth			(1111.11111)	1. Location scanned with GP	DD a CAT and signal
nment Ltd, The Enterprise	26/09/13		9.55	1.50	150	9.40	9.00	9.50	01:00	generator prior to breaking encountered.  2. Hand dug inspection pit e: 3. Groundwater not encounte 4. Gas and groundwater mon 9.50m bgl.	g ground. No services excavated to 1.20m bgl ered. itoring well installed to
5										All dimensions in metres	Scale: 1:25
KSK Em	Method Used:	Cable p	ercussio	n Plar Use		on Wayfa 1500		Drilled By:	GH	Logged By: <b>GShaw</b>	Checked By: AGS

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



										•			
Contract:							Client:				Boreho		
		t Mid	lands Gate						<b>Developments L</b>			(	CP210
Contract Ref			Start:		9.13	Grour	nd Level (m AOI	D):	National Grid Co-ordinat		Sheet:		
3	3124	194	End:	26.	9.13		78.01		E:446234.1 N:3	<u>26489.2</u>		2	of <b>3</b>
	·	nd In-si		Water	Backfill & Instru-			Ι	Description of Strata			Depth (Thick	Graphic
Depth	No	Туре	Results		M M	<b>1</b>	1.00 1	1	1.1 10070	VIE - 24	. 1	ness)	Legend
5.00-5.45	12	$U_{(100)}$	35 blows 100% recovery			sand (We (TA (stra	Istone skerries.  athering Grade I RPORLEY SIL  atum copied from  weak red brow clay bands	II) TSTOI n 4.00r	red brown MUDSTO!  NE FORMATION)  In from previous sheet)  ISTONE with occasional			5.00	× × × × × × × × × × × × × × × × × × ×
5.50 5.50-6.00	13 14	D D				(TA	amening Grade i	TSTO	NE FORMATION)			-	\( \times
6.00-6.31	3 15	SPT B	N=94*									- - - - -	
7.00-7.45	16	$U_{(100)}$	55 blows 70% recovery									(4.00)	
7.50 7.50-8.00	17 18	D B										-	$\times \times \times \times$
8.00-8.15 8.00-8.50	4 19	SPT B	N=200*				at 8.00m bgl, be	comes	moderately weak.			-	
-												9.00	X X X X X X X X X X X X X X X X X X X

	Boring Pr	rogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Canaral	Remarks
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General	Remarks
		•	•		•					
									All dimensions in metres	Scale: 1:25
Method	~	_	Plan	t Pilco	n Wayfa	arer	Drilled		Logged	Checked
Used:	Cable p	ercussio	n Used	l:	1500		By:	GH	By: <b>GShaw</b>	By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Boreho	le:		
East Midlands	Gate	eway		Roxhi	ll Developments Ltd		(	CP210	
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		78.01	E:446234.1 N:326489.2		3	of <b>3</b>	
Samples and In-situ Tests	avlta	Water ckfill & nstru-entation			Description of Strata		Depth (Thick		С

ĺ	Samp	oles a	nd In-si	tu Tests	Water	Backfill & Instru- mentation	Description of Strata	Depth (Thick	Material Graphic Legend
	Depth	No	Type	Results	W	Back Inst	Description of Strata	ness)	Legend
	9.00-9.15	5 20	SPT B	N=200*			Weak red brown MUDSTONE with occasional grey sandstone skerries. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)	(0.55)	
	9.50-9.55	6	SPT	N=600*		• • • • • • • • • • • • • • • • • • •	Borehole terminated at 9.55m depth.	9.55	
one construction of the contract of the contra									

		Boring Pr	ogress and	Water Ob	servations		Chisel	ing / Slow	Progress	General	Damarl	lza	
	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General	Keman	72	
			1	-1	,	1							
Ļ	f (1 1			D1	D'1	XX/C		D :11 1		All dimensions in metres	<u> </u>	1:25	
	Method Jsed:	Cable p	ercussio	n Plant	t Pilco	n Wayfa 1500	arer	Drilled By:	GH	By: <b>GShaw</b>	Checked By:		AGS

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:			Client:			Boreho	ole:		
East Midland	ls Gate	eway		Roxhil	l Developments Ltd		(	CP2	211
Contract Ref:	Start:	27.9.13	Ground Level (	(m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	27.9.13	80.9	8	E:445728.3 N:326608.2		1	of	2
		ء (ج	:					14.	. 4

Į	•	)124	174	End:	27.9.13	00.90 E:445/20.3 N:320000.2	1	of Z
	Sam	ples a	nd In-si	tu Tests	Water Backfill & Instru- mentation	Description of Strata	Depth (Thick	
	Depth	No	Type	Results	W Back Ins	Description of Strate	ness)	Legend
	0.00-1.00	1	В			Brown slightly gravelly silty CLAY. Gravel is angular to subangular fine to medium quartzite and sandstone. (SUBSOIL)	(0.40)	xx
						Red brown silty CLAY. Recovery includes occasional angular to subangular fine to medium sandstone skerries fragments. (Weathering Grade IVa) (GUNTHORPE MEMBER)	0.40	X X X X X X X X X X X X X X X X X X X
	1.00-1.20	2	В		· · · · · · · · · · · · · · · · · · ·		(1.60)	
	1.20-1.65	3	U <sub>(100)</sub>	15 blows 50% recovery			(1.60)	XX X X X
	1.70 1.70-2.00	4 5	D D				2.00	X
	2.00-2.45 2.00-2.45	1 6	SPT B	N=23		Stiff becoming very stiff red brown very clayey SILT. Recovery includes occasional angular to subangular fine to medium sandstone skerries fragments, with occasional grey reduction spots. (Weathering Grade IVb) (GUNTHORPE MEMBER)	2.00	× × × × × × × × × × × × × × × × × × ×
	2.50-3.00	7	D				(1.50)	× × × × × × × × × × × × × × × × × × ×
	3.00-3.45	8	U <sub>(100)</sub>	55 blows 75% recovery			2.50	× × × × × × × × × × × × × × × × × × ×
	3.50 3.50-4.00	9 10	D D			Very stiff to very weak red brown MUDSTONE. Occasional grey sandstone skerries, and grey reduction spots. (Weathering Grade III) (GUNTHORPE MEMBER)	3.50	
	4.00-4.45 4.00-4.45	2 11	SPT B	N=49		at 4.00m bgl, becomes weak to moderately weak with depth.	-	X X X X X X X X X X X X X X X X X X X

	Boring Pr	rogress and	Water Ob	servations		Chisell	ing / Slow	Progress	General Remarks			
Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General Remarks			
		Depth	Depth	(mm)	Depth			(1111.111111)	1. Location scanned with CAT and signal gener	ator prior		
26/09/13		1.70	1.20	150	Dry	6.60	7.00	01:00	to breaking ground. No services encountered	•		
27/09/13		7.00	-		7.00				2. Hand dug inspection pit excavated to 1.20m l	ogl		
									3. Groundwater seepage encountered at 7.00m b 4. Gas and groundwater monitoring well installed	ogl.		
									7.00m bgl.	ed to		
									,,,,,,,,,,,,,,,,			
									All dimensions in metres   Scale: 1:25	5		
Method		•	Plant	t Pilco	n Wayfa	arer	Drilled		Logged Checked			
Used:	Cable p	percussio	n Used		1500		By:	GH	By: GShaw By:	AGS		

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:43 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:	Borehole:				
East Midlands	Gate	eway		Roxhil	<b>Roxhill Developments Ltd</b>				
Contract Ref:	Start:	27.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	27.9.13		80.98	E:445728.3 N:326608.2		2	of	2

San	nples a	nd In-si	tu Tests	Water	Backfill & Instru- mentation	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	≽	Back Ins men	Description of Strata	ness)	Legend
4.50-5.00	13	D U <sub>(100)</sub>	90 blows 70% recovery			Very stiff to very weak red brown MUDSTONE. Occasional grey sandstone skerries, and grey reduction spots. (Weathering Grade III) (GUNTHORPE MEMBER) (stratum copied from 3.50m from previous sheet)	(3.60)	X X X X X X X X X X X X X X X X X X X
5.50 5.50-6.00	14 15	D D						X X X X X X X X X X X X X X X X X X X
6.00-6.45	3 16	SPT B	N=50				-	X X X X X X X X X X X X X X X X X X X
7.00-7.40	4	SPT	N=50	<b>*</b>		Borehole terminated at 7.10m depth.	7.10	× × × × × × × × × × × × × × × × × × ×
-						·		
-							-	
-							-	
-							-	

	Boring Pr	ogress and	Water Ob	servations		Chiselling / Slow Progress			Conoral	Remarks
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General	Remarks
			•		•					
									All dimensions in metres	
Method Used:						arer	Drilled By:	GH	By: <b>GShaw</b>	Checked By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:											
	Eas	t Mid	lands Gate	way		Roxhi	ill Developments Ltd		(	CP212	
Contract Re	ef:		Start:	27.9.13	Ground L	evel (m AOD):	National Grid Co-ordinate:	Sheet:			
	312	494	End:	27.9.13	(	69.14	E:445896.8 N:3268	374.4	1	of 1	
Sar Depth	nples a	and In-si	tu Tests Results	Water Backfill & Instrumentation			Description of Strata		Depth (Thick ness)	Material Graphic Legend	
0.00-1.00	1	В	23000000			own gravelly CLA	AY with angular fine to medium	quartzite.	(0.30)		
-					quartzite	stiff red browr e gravel, with gra SSINGTON ME	gravelly CLAY with angular ey reduction spots. MBER)	fine to medium	0.30		
1.00-1.20	2	В			•				(1.70)		
1.20-1.65	3	U <sub>(100)</sub>	35 blows 80% recovery		o o o o o				- - -		
1.70 1.70	4 5	D D			•				2.00		
2.00-2.45	1 6	SPT B	N=44		(Weathe	ering Grade III)	ed brown thinly bedded SILTST ONE FORMATION)	ONE.	(1.00)	× × × × × × × × × × × × × × × × × × ×	
2.50-3.00	7	D			o o o o o				3.00	\( \times	
3.00-3.10 3.00-3.45	2 8	SPT B	N=600*		(Weathe	ering Grade III)	own MUDSTONE thinly bedded ONE FORMATION)		(0.45)		
-					•				3.45		
-						Boreh	ole terminated at 3.45m depth.				

	Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	General Remarks
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	
27/09/13		3.45	1.50	150	Dry	3.00	3.30	01:00	Location scanned with CAT and signal generator prior to breaking ground. No services encountered.     Hand dug inspection pit excavated to 1.20m bgl.     Groundwater not encountered.     Gas and groundwater monitoring well installed to 3.30m bgl.
									All dimensions in metres   Scale: 1:25
Method Used:				Plant Used: Dando 150			Drilled By:	TC	Logged By: Checked By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:	Borehole	e:			
East Midlands	s Gate	eway		Roxhil	ll Developments Ltd			CP.	213
Contract Ref:	Start:	25.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	25.9.13		65.13	E:446274.7 N:326846.0		1	of	1_

		124	194	End:	25.	9.13	65.13 E:4462/4./ N:326846.0	1	of <b>I</b>
	Com	alac o	nd In-si	tu Toete	H	& . u		Depth	Material
	Sam	pies a	na m-si	tu Tests	Water	Backfill & Instru- mentation	Description of Strata	(Thick	
	Depth	No	Туре	Results	≥	Sack Ins	Description of Strata	ness)	Legend
	0.00-0.30	1	D				Brown clayey fine SAND with occasional rootlets.		74 18. 74 18. 7
	0.00-0.30	1	D			M M	(TOPSOIL)	(0.30)	, ,
	-						(TOT SOLE)	- '	
	-							0.30	<u> </u>
	0.30-1.00	2	D				Firm to stiff red brown silty CLAY with occasional thin sandstone		× ×
							skerries.		× ×
							(Weathering Grade IVb) (TARPORLEY SILTSTONE FORMATION)	(0.50)	×
	_						(TARI ORDET SIETSTONE FORMATION)	(0.70)	<u>xx</u>
ı	-							ļ .	×]
	_							-	× _ ×
	-							1.00	× ×
	1.00-1.20	3	D			• • • • • •	Very mode and become MIDCTONE with according this and dates	1.00	
	1.00-1.20	)	D				Very weak red brown MUDSTONE with occasional thin sandstone skerries.	-	
	-					l::H::	(Weathering Grade III)	-	
	1.20-1.65	4	$U_{(100)}$	45 blows			(TARPORLEY SILTSTONE FORMATION)		
				80% recovery					
İ	-					₿₿₿₿			
	-							ŀ	
	1.70	5	D					<b> </b>	
	1.70-2.00	5 6	D			l::H:::		-	
<u>.</u>	-							-	
7.03	2.00-2.38	1	SPT	N=67*			at 2.00m bgl, very weak.	-	
Ver.	2.00-2.38	7	B	N-0/.			at 2.00m ogi, very weak.	-	
230014, W cd. W WW.15K.cd.	-	,						-	
	-							ļ.	
\$	_							-	
† 	_								
	2.50-3.00	8	В					(3.28)	
2								(3.20)	
0.					<b>1</b>				
Lay	-				<u>*</u>				
,10,	-							<u> </u>	
7007	3.00-3.08	2	SPT	N=300*		╠╬╣	at 3.00m bgl, moderately weak.	<u> </u>	
2	3.00-3.50	2 9	В					ŀ	
70.	-							-	
15	-							-	
<u> </u>	-							-	
VI ZIA. 161. 024/0 230810, Fax. 024/0	2.50.4.00	10	ъ					-	
)	3.50-4.00	10	В					-	
IIII	_				_				
2	_				‡			L	
ب					=				
<u> </u>									
(8)	Γ								
1	-								
5	4.20-4.28	3	SPT(c)	N=300*				4.28	
mversity recimology rain, covering,							Borehole terminated at 4.28m depth.		
III	-						-	†	

		Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Canaral Damarka
	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General Remarks
<i>!</i> [			Depth	Depth	(mm)	Depth			(1111.111111)	1. Location scanned with CAT and signal generator prior
	25/09/13	00:00	4.00	1.50	150	2.85	3.90	4.20	01:00	to breaking ground. No services encountered.
	25/09/13	00:20	4.00	1.50	150	4.00				2. Hand dug inspection pit excavated to 1.20m bgl
1	25/09/13		4.25	1.50	150	3.80				3. Groundwater encountered at 4.00m bgl.
										Gas and groundwater monitoring well installed to     4.20m bgl.
į										1.2011 081
										All dimensions in metres   Scale: 1:25
i [	Method			Plant	t Pilco	n Wayfa	arer	Drilled	•	Logged Checked
	Used:	Cable p	ercussio	n Used		1500		By:	GH	By: GShaw By:

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:43 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



4.25

Contract							BOILLI			
Contract:						Client:		Boreho	ole:	
·	East	t Mid	lands Gate	eway		Roxhi	ll Developments Ltd		(	P214
Contract Re			Start:	25.9.	13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:		
	3124	<b>194</b>	End:	25.9.	13	60.97	E:446644.1 N:326900.8		1	of 1
			tu Tests				ı		Depth	
	No	Type	Results	Water Backfill &	Instru- mentation		Description of Strata		(Thick	Graphic
Depth 0.00-0.30	0.30 1 D			Tă Th	Brown silty CLAY with	accessional recetlets		ness)	Legend	
0.00-0.30	1	D		2			occasional rooticts.		(0.30)	1 <sub>2</sub> · <u>\ \ 1</u> · <u>\ \ \ 1</u> ·
_					- ME				0.30	<u>\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ </u>
0.30-1.00	2	D				Soft orange brown slightl (HEAD)	y clayey SILT.		-	× × × ×
-						(HEAD)			-	× × × ×
=									(0.70)	× × ×
-										* * * *
-										× × ×
1.00-1.20	3	D		• • •	∄∙∴∘	Soft to firm red brown r	nottled grey sandy CLAY. Recovery is	ncludes	1.00	_ x _ x
_						occasional angular fine to	coarse sandstone skerries fragments.			
1.20-1.65 1.20-1.65	1 4	SPT B	N=8			(Weathering Grade IVa) (TARPORLEY SILTSTO	ONE FORMATION)		_	
1.20 1.00	'	Б							-	<u> </u>
									-	
-										
-					∄::				-	<u> </u>
				***					-	
2.00-2.45	2	SPT	N=13			at 2.00m bgl, become	es firm.			<u> </u>
2.00-2.45	5	В							(2.50)	
-					∄::				(2.30)	
-									-	
-					H::				-	
-									-	
-				ا ا	H:				Ī	<del></del>
-				ľ	H∴.					
-					Ħ∴					
3.00-3.45	6	$U_{(100)}$	50 blows		部					
-			90% recovery		Ħ∷:					<u></u>
-					∄∷					
_					∄∷					<u></u>
=					H∷				3.50	
3.50	7	D			H.	Red brown interbedded	thinly bedded MUDSTONE and SILTS	STONE	2.20	
3.50-4.00	8	В			H.	recovered as a tabulated f	ine to coarse gravel.		(0.40)	
†					Ħ.ºº	(Weathering Grade III)	ONE EODMATIONS		[	
_				::	Red brown interbedded thinly bedded MUDSTONE and SILTSTONE recovered as a tabulated fine to coarse gravel. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)  Very weak grey thinly bedded medium to coarse SANDSTONE. (Weathering Grade III) (TARPORLEY SILTSTONE FORMATION)			3.90		
-					Ħ÷:	Very weak grev thinly be	dded medium to coarse SANDSTONE.		2.70	
4.00-4.45	3	SPT	N=50			(Weathering Grade III)			(0.35)	
İ				•••	H::	(TARPORĽEY SILTŚTO	ONE FORMATION)			
-	1		I .	. ° ا	، ۱۳۰۰				1 25	1

	Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	General Remarks				
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)					
25/09/13		Time Depth 4.25		150	Dry	3.90	4.20	01:00	Location scanned with CA to breaking ground. No se     Hand dug inspection pit e:     Groundwater not encounte     Gas and groundwater mon     4.20m bgl.	ervices encountered.  Accavated to 1.20m bgl  Bered.  Beritationing well installed to			
									All dimensions in metres	Scale: 1:25			
Method Used:				t Pilco	n Wayfa 1500		Drilled By:	GH	Logged By: <b>GShaw</b>	Checked By: AGS			

Borehole terminated at 4.25m depth.

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PŋVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd. The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

4.20-4.65

SPT

N=50



Contract:				Client:	Borehole	e:			
East Midlands	Gate	eway		Roxhi			CP	215	
Contract Ref:	Start:	30.9.13	Groun	nd Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	30.9.13		59.07	E:445575.8 N:327009.1		1	of	2

	)124	7/7	End:	30.9.13	59.07 E:445575.0 N:527009.1	1	01 4
Sam	ples a	nd In-sit	tu Tests	Water Backfill & Instrumentation	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	Wa Back Inst	•	ness)	Legend
0.00-1.00	1	В			Soft brown slightly gravelly clayey SILT. Gravel is subrounded to rounded fine to medium quartzite and sandstone. (THRUSSINGTON MEMBER)	(1.00)	× × × × × × × × × × × × × × × × × × ×
-						1.00	× — × × — × × — ×
1.00-1.20	2	В		***	Loose brown slightly gravelly clayey fine to coarse SAND. Gravel is subangular to subrounded fine to coarse sandstone and quartzite.	- 1.00	
1.20-1.65 1.20-1.65	1 3	SPT B	N=4		(Weathering Grade IVa) (BROMSGROVE SANDSTONE FORMATION)	-	######################################
-	3	Б				(1.00)	######################################
-						-	
2.00-2.45		SPT	N=16		Medium dense yellow grey slightly gravelly clayey fine to medium	2.00	- <del>σ</del>
2.00-2.45	2 4	В	14-10		SAND. Gravel is angular fine to medium sandstone. (Weathering Grade IVa) (BROMSGROVE SANDSTONE FORMATION)	-	θ
2.50-3.00	5	D				-	
3.00-3.45	3 6	SPT B	N=15			(2.00)	
-						-	
4.00-4.45	4 7	SPT B	N=46	<b>1</b>	Dense brown slighty gravelly slightly clayey fine SAND. Gravel is angular fine to coarse sandstone. (Weathering Grade IVb) (BROMSGROVE SANDSTONE FORMATION)	4.00	

	Boring Pr	rogress and	Water Ob	servations		Chiselli	ing / Slow	Progress	Canaral	Remarks
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)		
30/09/13 30/09/13		4.50 4.85	1.50 4.50	150 150	4.50 4.25	4.50	4.80	01:00	Location scanned with GP generator prior to breaking encountered.     Hand dug inspection pit e.     Groundwater encountered     Gas and groundwater mon     4.80m bgl.	g ground. No services excavated to 1.20m bgl at 4.50m bgl.
									All dimensions in metres	Scale: 1:25
Method Used:	Cable p	ercussio	Plan Used		ando 15		Drilled By:	TC	Logged By: <b>GShaw</b>	Checked By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



												D	Ur	KEI		)LI		UG
Contract:								Client:							I	Boreho	le:	
	East	t Mid	lands	Gate	way	y			Roxh	ill D	)evelo <sub>l</sub>	pment	s Ltd	l			(	CP215
Contract Re	f:			Start:	30.	9.13	Groun	d Level (	(m AOD):	Na	ational Gr	id Co-or	dinate:		S	Sheet:		
	3124	<b>494</b>		End:	30.	9.13		59.0	)7	]	E:4455	5 <b>75.8</b> I	N:327	7009	.1		2	of <b>2</b>
	<u> </u>	and In-si	1		Water	Backfill & Instru- mentation				Des	scription of	of Strata					Depth (Thick	Graphic
Depth	No	Туре	Re	sults	*	Bac					_						ness)	Legend
Depth  4.80-4.85	5 5	SPT		sults 600*	M .	\$ \cdot \cdo	Dens angu (Wea	lar fine to hthering ( DMSGR)	n slighty g o coarse sa Grade IVb OVE SAN ied from 4. Borel	gravel andsto ) IDST( 00m f	ly slightly one.	y clayey  RMATIO  ious shee	fine S	AND.	Grav	vel is		Legend
-																	- - -	
- -																	- -	
-																	-	

	Boring Pr	ogress and	Water Ob	servations		Chiselling / Slow Progress			General Remarks			
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General	Remarks		
									All dimensions in metres	Scale: 1:25		
Method Used:							Drilled By:	TC	Logged By: GShaw	Checked By: AGS		

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:43 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:							Client:			Boreho	ole:	
F	Cast	t Mid	lands	Gate	•				<b>Developments Ltd</b>		(	CP216
Contract Ref				Start:	2.10	0.13	Ground Level (m AOD)	):   ]	National Grid Co-ordinate:	Sheet:		
3	124	194		End:		0.13	64.46		E:445621.9 N:327310.9		1	of <b>1</b>
Samp	oles a	nd In-si	tu Tests		Water	Backfill & Instru- mentation		Γ	Description of Strata		Depth (Thick	
Depth	No	Type	Res	sults	$\Rightarrow$	Back Ins men			vescription of Struct		ness)	Legend
0.00-1.00 1.00-1.20 1.20-1.65	2 3	B B U <sub>(100)</sub>		olows			Stiff red brown mott	e to c'b)	grey sandy silty CLAY. Recovery in coarse sandstone skerries fragments.  NE FORMATION)	ncludes	(1.70)	
1.70 1.70-2.00	4 5	D B					Weak to moderately voccasional grey reduct	weak	red brown thinly bedded MUDSTON	IE with	1.70	
							(Weathering Grade III (TARPORLEY SILTS	)		_	2.00	
2.00-2.13	1 6	SPT B		300*				/eak g	grey finely grained SANDSTONE.	/	(0.45)	
2.40-2.48	2	SPT	N=3	300*		<u>. ` . ` . ` . `</u>	Bor	ehole	e terminated at 2.45m depth.		- 2.43	
-											-	

		Boring Pr	ogress and	Water Ob	servations		Chiselling / Slow Progress			General Remarks			
,	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General	Remarks		
3 [			Depth	Depth	(mm)	Depth			(1111.111111)	1 Location scanned with CA	AT and signal generator prior		
ment ruy, the construct	02/10/13		2.45	1.50	150	Dry	2.00	2.40	01:00	to breaking ground. No see 2. Hand dug inspection pit e 3. Groundwater not encounte 4. Gas and groundwater mor 2.40m bgl.	ervices encountered. xcavated to 1.20m bgl ered.		
										All dimensions in metres	Scale: 1:25		
NON CIN	Method Used:	Cable p	ercussio	**	Plant Used: Dando 150			Drilled By:	TC	Logged By: <b>GShaw</b>	Checked By: AGS		

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:44 | KF. RF. First Contents and Carle Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:			Client:		Boreho	ole:		-
East Midlan	ds Gate	eway	Roxhi	ll Developments Ltd			CP.	217
Contract Ref:	Start:	30.9.13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13	71.51	E:445967.3 N:327306.0		1	of	2
Samples and In-situ Te	ete	7 8 7 E				Dent	M	lateria

	3	124	494 End: 1.10.									of <b>2</b>
	Sam <sub>p</sub> Depth	oles a				Backfill & Instru-	elitation	D	escription of Strata		Depth (Thick ness)	Material Graphic Legend
	0.00-1.00	1	В	results	2			Dark brown silty CLAY. (TOPSOIL)			(0.30)	20gond (2/1/2-1/2-1/2-1/2-1/2-1/2-1/2-1/2-1/2-1/
								Firm to stiff brown slightly subrounded to rounded fine (THRUSSINGTON MEME	y sandy slightly gravelly CLAY. Gra to medium quartzite. BER)	vel is	(0.70)	
	1.00-1.20	2	В		•		°°	Stiff red brown silty CLAY	7. Recovery includes occasional angula	r fine	1.00	<u>xo</u> xo
	1.20-1.65	3	U <sub>(100)</sub>	20 blows 75% recovery			• • • • • • • • • • • • • • • • • • • •	to medium mudstone lithore fragments. (Weathering Grade IVb) (TARPORLEY SILTSTON	elicts, with occasional grey sandstone sk	terries	-	× × × × × × × × × × × × × × × × × × ×
	1.70 1.70-2.00	4 5	D D		< < < <						-	
	2.00-2.45 2.00-2.45	1 6	SPT B	N=18							(2.00)	#0
	3.00-3.45	7	U <sub>(100)</sub>	65 blows 75% recovery	<			Weak red brown MUDSTO (Weathering Grade III) (TARPORLEY SILTSTON	NE, with occasional grey reduction spor	ts.	3.00	xoxoxoxoxoxoxoxo_
	3.50 3.50-4.00	8 9	D D		< < < < < < < < < < < < < < < < < < <		*******				(1.65)	
33	4.00-4.30 4.00-4.60	2 10	SPT B	N=100*	< < < < < < < < < < < < < < < < < < <						- - -	

		Boring Pr	ogress and	Water Ob	servations		Chiselli	ing / Slow	Progress	General	Damarla
D	ate	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)		
Z	09/13 10/13		3.50 4.65	3.00 3.00	150 150	Dry Dry	4.20	4.60	01:00	Location scanned with CA to breaking ground. No se     Hand dug inspection pit er     Groundwater not encounte     Gas and groundwater mon     4.60m bgl upon completio	ervices encountered. Excavated to 1.20m bgl ered. itoring well installed to
	Method Used: Cable percussion				Plant Used: Dando 150			Drilled By:	TC	All dimensions in metres  Logged By: GShaw	Scale: 1:25 Checked By: AGS

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:44 | KF. RF. First Contents and Carle Coventry University Technology Park, Coventry, CVI 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



		N					BOREH	OLI	ΕL	.OG
Contract:						Client:		Boreho	le:	
	East	Mid	lands Gate	way		Roxhi	ll Developments Ltd		(	CP217
Contract Re	f:		Start:	30.9	.13 Gro	ound Level (m AOD):	National Grid Co-ordinate:	Sheet:		
	3124	194	End:	1.10	.13	71.51	E:445967.3 N:327306.0		2	of <b>2</b>
Sam	ples a	nd In-si	tu Tests	Water	Instru- mentation		Description of Strata		Depth	Material Graphic
Depth	No	Type	Results	W	Insi		Description of Strata		(Thick ness)	Legend
4.60-4.68	3	SPT	N=300*	٠					4.65	
						Boreho	ole terminated at 4.65m depth.		- - - - - - - - - - - -	

10	-					
8. 05 - Core+Logs 0002   Log CABLE PERCUSSION LOG   312494 - EAST MIDLANDS GATEWAY.GPJ - v8_05   10. ogy Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.	-					
- ^	-				_	
.GP.	-				•	
ΝΑΥ					-	
TE.						
S G/ o.uk						
ND rsk.c	_					
IDL/ ww.	_				-	
T W	_					
EAS t, W.	-					
94 -	-				_	
3124 76 23	-				-	
024 024	-				-	
N L( Fax:	-					
SSIO 816,	-					
236 236					•	
PER 2476						
BLE el: 0						
S CA	_					
Log 71.2T	_				_	
0002 ', CV	_					
ogs ( entry	-					
Get Cov	_				-	
- Co ?ark,	-					
3_05 ogy]	-					

in y												·	
0,00		Boring Pr	ogress and	Water C	bservations		Chisell	ing / Slow l	Progress	Canaral	Damarl	- 0	
ue, c	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration	General	Remark	S	
2	Date	Title	Depth	Depth	(mm)	Depth	110111	10	(hh:mm)				
).   													
1211													
100													
r, 1													
III F													
DILL													
VIIC							L			All dimensions in metres	Scale: 1	1:25	
II I	Method			Pla				Drilled		Logged	Checked		
ugy ugy	Used:	Cable p	ercussio	n Us	ed: D	ando 15	0	By:	TC	By: <b>GShaw</b>	By:		AGS

8\_05 | 10/12/13 - 10:44 | KF. GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PifVersion: v8 05 - RSK Environment Ltd, The Enterprise Centre, Coventry University Technology F



Contract:				Client:		Borehole	e:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd			CP	218
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13		65.61	E:446269.8 N:327306.0		1	of	2

Į	•	3124	194	End:	1.10.13	05.01	E:446269.8 N:32/306.0		1	of <b>Z</b>
		<u> </u>	ınd In-si		Water Backfill & Instru- mentation		Description of Strata		Depth (Thick	Material Graphic
	Depth	No	Type	Results	W Back Ins		Description of Strata		ness)	Legend
	0.00-1.00	1	В			Brown slightly clayey sli rounded fine to medium o (THRUSSINGTON MEN	ghtly gravelly SILT. Gravel is subround uartzite. MBER)	ded to	(1.00)	× × × × × × × × × × × × × × × × × × ×
	1.00-1.08	1 2	SPT(c) B	N=300*		Very dense red brown Gravel is angular fine to (THRUSSINGTON MEN	mottled grey slightly gravelly clayey S coarse sandstone. MBER)	AND.	-	
.0.un.	1.50-2.00	3	В						(2.00)	
2001+, w.cu. w.ww.ish.c	2.00-2.45	5	U <sub>(100)</sub>	65 blows 90% recovery					-	
500010, 1.av. 02470 2	2.50	6	D SPT	N=100*		Weak red brown MUC	OSTONE thinly bedded with grey ban	ds of	3.00	-00. -000
OHIVERSHY I COHINDERS FAIR, COVEHRY, C. V. I. Z. I.A. 101-024/10 200010, I.AA. 024/10 200014, W.CO. WWW.ISK.CO.UK.	- 3.00-3.45 - 3.00-3.45 	7	B	14 100		weak led blown MOL sandstone. (Weathering Grade III) (TARPORLEY SILTSTO		us UI	-(1.65)	
y chiversity rechifology raik, c	4.00-4.10	3 8	SPT B	N=300*		at 4.00m bgl, become	es moderately weak with depth.		- - - -	

200		Boring Pr	rogress and	Water O	oservations		Chisell	ing / Slow	Progress	Canaral	Damarla
entre, c	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)		Remarks
Ironment Ltd, The Enterprise C	01/10/13		4.65	1.00	150	Dry	4.40	4.60	01:00	Location scanned with CA to breaking ground. No se 2. Hand dug inspection pit e: 3. Groundwater not encounte 4. Gas and groundwater mon 4.60m bgl upon completio  All dimensions in metres	xcavated to 1.20m bgl ered. hitoring well installed to
SN Eliv	Method Used:	Cable r	percussio	Plan Use	•	ando 150		Drilled By:	TC	Logged By: <b>GShaw</b>	Checked By:

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:44 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



												BOR	REH	OLI	ΕL	.OG
Contract:								Client:						Boreho	le:	
	Eas	t Mid	lands	s Gate	way	y			Roxhi	ill I	Developmo	ents Ltd	l		(	<b>P218</b>
Contract Re	f:			Start:	1.1	0.13	Grour	nd Level	(m AOD):	N	ational Grid Co	o-ordinate:		Sheet:		
	312	<b>494</b>		End:	1.1	0.13		65.	61		E:446269.	8 N:327	306.0		2	of <b>2</b>
San	nples a	ınd In-si	tu Tests		Water	Backfill & Instru-				Da	scription of St	rata			Depth (Thick	Material Graphic
Depth	No	Туре	Re	sults	N N	Back Inst				De	scription of St	iala			ness)	Legend
4.60.470		CDT	3.7	200*											4.65	
4.60-4.70	4	SPT	N=	300*			1		Boreh	ole t	erminated at 4.	65m depth.			-	
-															_	
_																
=															-	
_															_	
-															_	
-															-	
-															_	
_																
=															_	
-															_	
_																
-															-	
-															_	
_															L	

0:45   KF.	- - -												-	
10/12/13 - 1	- - -												-	
J - v8_05	-												-	
ſEWAY.GP	- - -												-	
ANDS GA7	- - -												-	
SAST MIDI , Web: www	- - -												-	
312494 - 1	 -												-	
SSION LOG 816, Fax: 02	-												-	
05 - Lib0004 PjtVersion: v8_05 - Core+Logs 0002   Log CABLE PERCUSSION LOG   312494 - EAST MIDLANDS GATEWAY.GPJ - v8_05   10/12/13 - 10:45   KF. Soventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.	- - -												-	
2   Log CAB V1 2TX. Tel	- - 												-	
e+Logs 0002 Coventry, C	- - -												-	
v8_05 - Corology Park,	- -												-	
PrjVersion:	-												-	
- Lib0004]	-							I						
r: v8 05 tre, Cove	Dete	Boring F	Progress and Borehole	Casing	Boreh Diam (mn	ons nole v	Water		ng / Slow I	Progress  Duration (hh:mm)	Gene	eral Rema	ırks	
JbVersion prise Cent	Date	Time	Depth	Depth	(mn	n) I	Depth	From	10	(hh:mm)				
3 05.GLB I														
GINT LIBRARY V8 05.GLB LibVersion: v8 RSK Environment Ltd. The Enterprise Centre, C											All dimensions in n	metres Scale:	1:25	
GINT LIE RSK Envii	Method Used:	Cable	percussio	Plant Used	•	Dan	ndo 150	) I	Drilled By:	TC	Logged By: GSh	Checke	1.23	AGS



Contract:				Client:		Borehole	:		
East Midlands	Gate	way		Roxhil	l Developments Ltd		(	CP	219
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	27.9.13		54.46	E:446922.2 N:327317.5		1	of	2

	114	·	Eliu.	21.7.13	57.70 E.770/22.2 11.52/51/.5		01 _
Samp	oles a	nd In-si	tu Tests	Water Backfill & Instru- mentation	Description of Strate	Depth (Thick	Material Graphic
Depth	No	Type	Results	Wash Inst	Description of Strata	ness)	Legend
0.20	1	D			Brown slightly gravelly clayey fine SAND. Gravel is subangular to rounded fine to medium quartzite, sandstone and occasional rootlets. (TOPSOIL)	0.30	70.70 7.74.77 7.7.7
0.60	2	D			Firm to stiff red brown slightly gravelly sandy CLAY. Gravel is subangular to rounded fine to medium quartzite, sandstone and occasional rootlets. (THRUSSINGTON MEMBER)	- - -	
1.20-1.65	3	U <sub>(100)</sub>	56 blows 100% recovery			(1.50)	
1.70	4	D			Seiff and and house diabete and a its CLAV Decrease includes	1.80	
1.90 2.00-2.45 2.00-2.50	5 1 6	D SPT B	N=22		Stiff grey and red brown slightly sandy silty CLAY. Recovery includes occasional angular to subangular fine to medium mudstone and sandstone lithorelicts fragments.  (Weathering Grade IVb)  (TARPORLEY SILTSTONE FORMATION)	- -	
				\$\begin{array}{c c c c c c c c c c c c c c c c c c c		(1.00)	X X
2.90 3.00-3.45	7 8	D U <sub>(100)</sub>	75 blows 70% recovery		Stiff red brown slightly silty CLAY. Recovery includes occasional angular to subangular fine to coarse mudstone, with occasional sandstone skerries fragments.  (Weathering Grade IVb)  (EDWALTON MEMBER)	-	X
3.50	9	D				(1.50)	
 4.00 4.10-4.47 4.10-4.50	10 2 11	D SPT B	N=70*		at 4.10m bgl, becoming very stiff.	4.30	
-					Description on next sheet		X X

2		Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Canaral Damarka
omne,	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General Remarks
all Liu, the Emerphise 🛰	26/09/13 27/09/13		Depth 1.70 7.70	Depth - 3.00	(mm) 150 150	Depth Dry Dry	6.80 7.10	7.10 7.50	01:00 01:00	Location scanned with CAT and signal generator prio to breaking ground. No services encountered.     Hand dug inspection pit excavated to 1.20m bgl     Groundwater not encountered.     Gas and groundwater monitoring well installed to 7.50m bgl upon completion.
SIN HOHING	Method Used:	Cabla r	ercussio	Plan Used		on Wayfa 1500		Drilled By:	GH	All dimensions in metres Scale: 1:25  Logged By: GShaw Checked By: AG

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:46 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:			Client:		Boreho	le:	
East Midlands	Gate	way	Roxhi	ll Developments Ltd		(	CP219
Contract Ref:	Start:	26.9.13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:		
312494	End:	27.9.13	54.46	E:446922.2 N:327317.5		2	of <b>2</b>
Samples and In-situ Tests		Vater ckfill & nstru-		Description of Strata		Depth (Thick	Material Graphic

	_		tu Tests	Water	Backfill & Instru- mentation	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Туре	Results				ness)	Legend
4.90	12 3	D SPT	N=46			Very stiff to very weak red brown SILTSTONE with occasional grey sandstone skerries.  (Weathering Grade III)  (EDWALTON MEMBER)  at 4.30m bgl, becoming very stiff.(stratum copied from 4.30m from previous sheet)	(2.50)	
5.90 6.00-6.39 6.00-6.50	13 4 14	D SPT B	N=62*				-	
6.90	15	D				Weak red brown thinly bedded MUDSTONE with occasional grey sandstone skerries. (Weathering Grade III) (EDWALTON MEMBER)	6.80	x
7.10-7.34	5	SPT D	N=167*			(EDWALTON MEMBER)	(0.90)	X X X X X X X X X X X X X X X X X X X
7.50-7.71	6	SPT	N=158*		 	Borehole terminated at 7.70m depth.	7.70	× × × × × × × × × × × × × × × × × × ×
						Borchole terminated at 7.70m depuil.	-	

		Boring Pr	ogress and	Water Ob	servations		Chiselli	ing / Slow l	Progress	General	Domorl	7.0	
	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration	General	Keman	S	
	Dute	1 11110	Depth	Depth	(mm)	Depth	1 10111	10	(hh:mm)				
î													
										All dimensions in metres	Scale:	1:25	
M	lethod			Plant	t Pilco	n Wayfa	arer	Drilled		Logged	Checked		
U	sed:	Cable p	ercussio	n Used		1500		Ву:	GH	By: GShaw	By:		AGS

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:46 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Borehole	:		
East Midlands	Gate	way		Roxhil	l Developments Ltd		(	CP	<b>220</b>
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		43.62	E:447285.5 N:327287.4		1	of	2
		1.5							

3	124	194	End:	26.9.13					
Sami	iles a	nd In-si	tu Tests	er & To	Description of Strata				
Depth	No		Results	Water Backfill & Instru- mentation		Description of Strata	(T)	nick ess)	Material Graphic Legend
_					Brown slightly clayey silt	-		7/1/2 . 7/1/2 . 7	
0.20	1	D			(TOPSOIL)		-(0.	45)	17.7.1
0.20	1	Ъ					+		12 · 3 · 12 · 3 · 3 · 3 · 3 · 3 · 3 · 3 · 3 · 3 ·
					Orange brown slightly gra	velly silty fine SAND. Gravel is subroun		45	*····×
0.50-0.80 - 0.55	2 3	B D			rounded fine to coarse qua	rtzite.		35)	:: ở: :: : : : : : : : : : : : : : : :
-					(HEAD DEPOSITS)		- t	80	.o.×
-					Firm red brown slightly si	ty CLAY with occasional rootlets.		.00	X X
0.90	4	D		*.*⊟.*.	(HEAD DEPOSITS)		-		xx
-							(0.	70)	<u>xx</u>
1.20-1.65	5	$U_{(100)}$	29 blows 90% recovery						<u>×                                     </u>
-			90% recovery				-	50	
-					Red brown slightly clayey	medium to coarse SAND.		50	
					(HEAD DEPOSITS)		[0]	30)	
1.70	6	D			Eiron rad brazza mattla	d gray gondy CLAV Dagayary in		80	
-					Firm red brown mottle occasional subangular to	d grey sandy CLAY. Recovery in subrounded fine to coarse sandston	e and		
2.00	7	D			mudstone lithorelicts. (Weathering Grade IVb)				
2.20-2.65	1	SPT	N=9		(EDWALTON MEMBER	4)	<u> </u>	0.0	
2.20-2.03	8	B	N-9				[(1.	00)	<u> </u>
-							-		
-							2	80	<u> </u>
-					Very weak red brown I	MUDSTONE thinly bedded with sand	lstone.	.00	
2.90 3.00-3.45	9 10	D	87 blows		Occasional grey reduction	arse gravel sized tabular angular frag spots.	ments.		
3.00-3.43	10	$U_{(100)}$	80% recovery		(Weathering Grade III) (EDWALTON MEMBER		+		
_					(EB WILL FOR MEMBER	-7			
-							-		
3.50	11	D					(1	60)	
								00)	
-							}		
-							ŀ		
4.00	12	D					ļ		
4.10-4.51 - 4.10-4.50	2 13	SPT B	N=58*				}		
-							<u> </u>	40	
					Description on next sheet				× × × × ×

70.00		Boring Pr	ogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Canaral	D amortza
enne, c	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth	From	То	Duration (hh:mm)	General	Remarks
nment Lta, The Enterprise C	26/09/13		5.92	3.00	150	Dry	4.50 5.20	4.90 5.70	01:00 01:00	Location scanned with GP generator prior to breaking encountered.     Hand dug inspection pit et al. Groundwater not encounted. Gas and groundwater mon 5.70m bgl upon completion.	g ground. No services secavated to 1.20m bgl ered. itoring well installed to
VII.0I										All dimensions in metres	Scale: 1:25
ON DIE	Method Used:	Cable r	ercussio	Plar Use		on Wayfa 1500		Drilled By:	GH	Logged By: <b>GShaw</b>	Checked By: AGS

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:46 | KF. RSK Environment Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:	Client:				
East Midlands	Gate	eway		Roxhil	l Developments Ltd			CP2	<b>220</b>
Contract Ref:	Start:	26.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	26.9.13		43.62	E:447285.5 N:327287.4		2	of	2

	Samples and In-situ Tests  Depth No Type Results					2011/200101(102/2071)		· -
	_	1	1	'ater	Backfill & Instru- mentation	Description of Strata	Depth (Thick	Material Graphic
Depth	No	Type	Results	*	Bacl In mer		ness)	Legend
4.90-5.22	3 14	SPT D	N=88*			Red brown SILTSTONE with occasional grey reduction spots. (Weathering Grade III) (EDWALTON MEMBER) at 4.40m bgl, becoming weak. (stratum copied from 4.40m from previous sheet) at 4.90m bgl, becomes very weak.	(1.52)	X X X X X X X X X X X X X X X X X X X
5.60	15 4	D SPT	N=167*			at 5.70m bgl, becomes weak.	5.92	× × × × × × × × × × × × × × × × × × ×
-						Borehole terminated at 5.92m depth.	-	
-							-	
-							-	
-							-	
							_	
-							-	
-							-	
-							-	
_							-	
_							-	
-							-	
_							-	
-							-	
-							-	
_							L	
-							-	
-							-	
-							-	
-							-	
-							-	
-							-	

		Boring Pr	rogress and	Water Ob	servations		Chiselli	ing / Slow l	Progress	General	Domorl	7.C	
	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General	Keman	S	
; L	Duit	1 11110	Depth	Depth	(mm)	Depth	110111	10	(1111.111111)				
-													
										All dimensions in metres	Scale:	1:25	
N	lethod			Plant	Pilco	n Wayfa	arer	Drilled		Logged	Checked		
U	Used: Cable percussion			n Used	l:	1500 <sup>°</sup>		By:	GH	By: <b>GShaw</b>	By:		AGS

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:46 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:	Borehole	e:			
East Midlands	Gate	way		Roxhil	l Developments Ltd		(	CP.	221
Contract Ref:	Start:	27.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	30.9.13		41.66	E:447051.9 N:327694.5		1	of	3

L	<u>3</u>	124	194	End:	30.9	_	41.00	E:44/051.9 N:32/694.5	1	of <b>3</b>
			nd In-sit		Water	Backfill & Instru- mentation		Description of Strata	(Thick	Material Graphic
	Depth	No	Type	Results	<b>&gt;</b>	Pac Ir mei		_	ness)	Legend
-	0.10	1	D		2		Brown silty fine SAND w (TOPSOIL)	ith occasional rootlets.	(0.35)	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7
ŀ									- 0.35	<u> </u>
-	0.45 0.50-1.00	2 3	D B				rounded fine to coarse qua	velly fine SAND. Gravel is subangul artzite and flint. SAND AND GRAVEL MEMBER)	ar to	% · · · · · ×   · · · ∂ · · · · · ·     × · · · ×
-	0.50-1.00	3	В				(EGGINTON COMMON	SAND AND GRAVEL MEMBER)	(0.75)	××
-									-	× Ø
ŀ					•	•°, H•°•			1.10	× <sup>0</sup>
-			ana()		٥		Medium dense brown sli	ghtly gravelly clayey fine to medium SA unded fine to coarse quartzite.	AND.	o
-	1.20-1.65 1.20	1 4	SPT(c) D	N=15			(EGGINTON COMMON	SAND AND GRAVEL MEMBER)	-	
t									ţ	
-					٥				-	-0 - <del>5</del>
-					٥				(1.40)	
ļ					٥					
ŀ	2.00	5	D						-	
ļ					•				ţ	
ŀ	2.20-2.65	2	SPT(c)	N=16	٥				-	<u>o.                                  </u>
					0				2.50	- <u>0</u> <u>0</u> .
ŀ					٥		(Weathering Grade IVb)	occasional grey reduction spots.	-	
ŀ					٥		(EDWALTON MEMBÉR	<b>R</b> )	t	
-	2.90	6	D		٥				-	
ŀ	3.00-3.45	7	$U_{(100)}$	31 blows					-	
ļ				100% recovery	°					
-					٥				-	
-					٥				ļ	
-	3.50	8	D						(2.15)	
ŀ									ţ	
F					0				F	
+	4.00	9	D						+	
-	4.20.4.65	2	CDT	N=11	0				Ţ.	
-	4.20-4.65	3	SPT	N=11					ŀ	
t					٥					

		Boring P	rogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Conoral	Domortza
ciitic,	Date	Time	Borehole	Casing	Borehole Diameter	Water Depth	From	То	Duration (hh:mm)	General	Remarks
nom rea, the conservation of	27/09/13 27/09/13 30/09/13 30/09/13	09/13 00:00 4.65 4.00 150 09/13 00:20 9.65 6.00 150 09/13 9.65 6.00 150				4.65 9.65 9.65 10.94	10.30	10.70	01:00	Location scanned with CA to breaking ground. No se     Hand dug inspection pit es     Groundwater encountered     Gas and groundwater mon     10.70m bgl upon completi	ervices encountered. scavated to 1.20m bgl at 9.65m bgl. itoring well installed to
										All dimensions in metres	Scale: 1:25
	Method Used:	Cable 1	percussio	n Plan Used		on Wayfa 1500		Drilled By:	GH	Logged By: <b>GShaw</b>	Checked By: AGS

GINT LIBRARY V8 05,GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:47 | KF. RF. FintronmentLtd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Borehole	e:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd			CP2	221
Contract Ref:	Start:	27.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	30.9.13		41.66	E:447051.9 N:327694.5		2	of	3

		12-		Eliu.	30.7.13	11.00 12.777031.711.327077.3		01 5
	Samp	oles a	nd In-si	tu Tests	Water Backfill & Instru- mentation		Depth	Material
	Depth	No	Туре	Results	Wa Backf Instr	Description of Strata	(Thick ness)	Graphic Legend
					::H::			
	-					Firm brown CLAY with occasional sandstone skerries. Recovery	4.65	===
	-					includes occasional angular fine to medium gravel sized mudstone		
	- 4.00	10				lithorelicts and grey reduction spots.	-	
	4.90 5.00-5.45	10 4	D SPT	N=11		includes occasional angular fine to medium gravel sized mudstone lithorelicts and grey reduction spots.  (Weathering Grade IVb)  (EDWALTON MEMBER)	_	
	- 5.00-5.45	7	51 1	N-11			-	
	-						-	
	-							
	-						-	
	-						-	
	-						-	
	5.80	11	D				_	
	_							
	6.00-6.45	12	$U_{(100)}$	43 blows 100% recovery			-	===
	-			10070 recovery			-	
	-						_	
4	-						-	
38.0	6.50	13	D					
W CO. W W W.I.SN.CO. UN	-						-	
	-						-	
Ť.	-						-	
4,00014,	7.00	14	D				(4.85)	
Ì	-							
	7.20-7.65 7.20-7.70	5 15	SPT B	N=24		at 7.20m bgl, becoming stiff.	-	
, ,	-						-	
VI Z IX: IXI: 024/0 230810,	-						_	
1	-							
	-						-	
	-						-	
1	8.00	16	D				-	
, ć	-						-	
2	8.20-8.65	17	$U_{\scriptscriptstyle (100)}$	54 blows 100% recovery			-	
din,	-			100/01ecovery			-	
53	-						-	<u> </u>
1011	-						-	
5	8.70	18	D					
miversity reminings rain, covering,	-						-	
					I ⊮∷H∙∴I			

0.00		Boring Pr	ogress and	Water Ob	servations		Chisel	ling / Slow l	Progress	General	Domort	7.C	
inc, c	Date	Time	Borehole	U	Borehole Diameter	Water	From	То	Duration (hh:mm)	General	Remair	KS .	
3	Dute	Time	Depth	Depth	(mm)	Depth	110111	10	(nn.mm)				
35													
<u> </u>													
1													
į,													
=													
5										All dimensions in metres	Scale:	1:25	
å	Method			Plan	Plant Pilcon Wayfa			Drilled		Logged	Checked		
NON	Used:	Cable p	ercussio	n Used	l:	1500 <sup>°</sup>		By:	GH	By: GShaw	By:		AGS

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:48 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Borehole	e:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd			CP:	221
Contract Ref:	Start:	27.9.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	30.9.13		41.66	E:447051.9 N:327694.5		3	of	3

		· <u>·</u>	End.	•••	, ,,,	2011/0010/102/00/10		01 0
Sam	Samples and In-situ Tests					Description of Strata	Depth (Thick	Material Graphic
Depth	No	Туре	Results	Water	Backfill & Instru- mentation		ness)	Legend
9.10 9.20-9.65	19 6	D SPT	N=50	<b>3</b> <u>∓</u>		Firm brown CLAY with occasional sandstone skerries. Recovery includes occasional angular fine to medium gravel sized mudstone lithorelicts and grey reduction spots.  (Weathering Grade IVb)  (EDWALTON MEMBER)  (stratum copied from 4.65m from previous sheet)  at 9.20m bgl, becoming stiff to very stiff.	9.50	
10.00-10.34	7 20	SPT D	N=79*	<u>_</u>		Very stiff grey sandy CLAY. Recovery includes occasional angular fine to medium mudstone and sandstone lithorelicts. (Weathering Grade IVb) (EDWALTON MEMBER) at 10.00m bgl, becoming weak.	(1.00)	
-							10.50	<u> </u>
10.60	21	D SPT(c)	N=158*			Weak grey brown SANDSTONE recovered as subangular coarse gravel. (Weathering Grade III) (ARDEN SANDSTONE FORMATION)	(0.44)	
10.70 10.95		SI I(c)	1, 130					
-					*****	Borehole terminated at 10.94m depth.	10.94	
_						Botonote terminated at 10.5 mi depair.	_	
-							-	
-							-	
-							-	
-							-	
-								
_								
_							-	
F							-	
-							-	
-							-	
-							-	
							Ĺ	
-							-	
-							-	
-							-	
F							F	
-							-	
-							-	
-							-	
-							ļ .	

	Boring Progress and Water Observations							ing / Slow	Progress	Conoral	Domorl	7.0	
Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration	General Remarks				
Bute	Time	Depth	Depth	(mm)	Depth		10	(hh:mm)					
-													
î													
										All dimensions in metres	Scale:	1:25	
M	Method			Plan	Plant Pilcon Wayfa			Drilled		Logged	Checked		
U	<b>Used:</b> Cable percussion			n Used	l:	1500		Ву:	GH	By: GShaw	By:		AGS

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PŋVersion: v8\_05 - Core+Logs 0002 | Log CABLE PERCUSSION LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:48 | KF. RSK Environment\_Ltd, The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.



Contract:				Client:		Borehole	:		
East Midlands	Gate	way		Roxhil	l Developments Ltd		(	CP2	222
Contract Ref:	Start:	3.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	3.10.13		37.05	E:447259.3 N:327820.5		1	of	2

L		124	ナノサ	End:	3.10.13	57.05 E:447259.5 N:527620.5	1	of <b>Z</b>
	Samj	ples a	nd In-si	tu Tests	Water ackfill & Instru-	D : :: (G) :	Depth	Material
	Depth	No	Type	Results	Water Backfill & Instrumentation	Description of Strata	(Thick ness)	Graphic Legend
Ī	-					Grass over brown slightly clayey SAND, with occasional rootlets. (MADE GROUND)	0.15	
	0.25	1	D			Coarse angular GRAVEL of limestone.  \( \text{(MADE GROUND)} \)	0.30	
	0.40	2	D			Brown slightly clayey gravelly fine SAND. Gravel is subrounded to rounded quartzite and sandstone.	0.50	
	0.60	3	D			\(\(\text{(WANLIP MEMBER)}\)\) Medium dense brown slightly clayey gravelly fine SAND. Gravel is subrounded to rounded quartzite and sandstone.	-	
	0.80-1.20	4	В			(WANLIP MEMBER)	-	
	-						(1.10)	
	1.20-1.65 1.20-1.65	1 5	SPT(c)	N=12			-	
	-						1.60	
	1.70	6	D			Medium dense orange and red brown slightly gravelly clayey coarse SAND. Gravel is subangular to subrounded fine to coarse quartzite and	-	
	-					sandstone. (WANLIP MEMBER)	-	######################################
	-							-
. I	2.20-2.65	2	SPT	N=18				
							(1.80)	
	-							
, , ,	2.90	7	D				-	
	3.00-3.45	8	$U_{(100)}$	38 blows 100% recovery				-o - : : : : : : : : : : : : : : : : : : :
							3.40	
	3.50	9	D			Soft to firm red brown slightly sandy CLAY. Recovery includes occasional angular fine mudstone and sandstone lithorelicts, with	-	
	•					occasional grey reduction spots. (Weathering Grade IVa) (EDWALTON MEMBER)		
	3.90	10	D					
3	4.00-4.45 4.00-4.50	3 11	SPT B	N=7				
- Carrier 1							-	

200		Boring P	rogress and	Water Ob	servations		Chisell	ing / Slow	Progress	Canaral	Damarla
onne, c	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration (hh:mm)	General	Remarks
3	02/10/12	00.00	Depth	Depth	(mm)	Depth		0.00	` ′	1. Location scanned with GP	
pris	03/10/13	00:00	6.40	6.00	150	6.40	7.50	8.00	01:00	generator prior to breaking	g ground. No services
nter	03/10/13	00:20	6.40	6.00	150	5.66				encountered.  2. Hand dug inspection pit ex	xcavated to 1.20m bgl
ne E	03/10/13		8.29	7.50	150	Dry				3. Groundwater encountered	at 6.40m bgl.
Ĕ,										4. Gas and groundwater mon 6.00m bgl upon completio	
ant L											
ODITIO										All dimensions in metres	Scale: 1:25
Ž										An unnensions in metres	1120
ă	Method			Plan		n Wayfa		Drilled		Logged	Checked
3	Used:	Cable r	percussio	n Used	1:	1500		By:	GH	By: GShaw	By: AGS



												• • • • • • • • • • • • • • • • • • • •			
Contract:								Client:					Boreho	le:	
	Eas	t Mid	lands	s Gate	way	y			Roxhil	l Developr	nents L	ıtd		C	P222
Contract Re	f:			Start:	3.1	0.13	Groun	d Level (m	AOD):	National Grid	Co-ordinat	e:	Sheet:		
í	312	494		End:	3.1	0.13		37.05	)	E:44725	9.3 N:3	27820.5		2	of <b>2</b>
Sam	1	and In-si	tu Tests	S	/ater	ackfill & Instru-				Description of	Strata			Depth (Thick	Material Graphic
Depth	No	Type	Re	sults	$\Rightarrow$	Bac				1				ness)	Legend
-							Soft	to firm sional ang	red brown	n slightly sand mudstone and	y CLAY. d sandstor	Recovery in lithorelicts		-	

San	ipies a		tu Tests	Wate	<b>建筑</b>	tati	Description of Strata	(Thick	Graphic
Depth	No	Type	Results	W	Backfill Instru-	men	_	ness)	Legend
4.90	12 13	D U <sub>(100)</sub>	53 blows 90% recovery				Soft to firm red brown slightly sandy CLAY. Recovery includes occasional angular fine mudstone and sandstone lithorelicts, with occasional grey reduction spots. (Weathering Grade IVa) (EDWALTON MEMBER) (stratum copied from 3.40m from previous sheet)	(2.80)	
5.50	14	D		<u></u>				-	
6.00	15 4	D SPT	N=79*		=		Very weak red brown MUDSTONE with occasional grey sandstone	6.20	
-				<u></u>			very weak red brown MODSTONE with occasional grey sandstone skerries. (Weathering Grade III) (EDWALTON MEMBER)	- - - -	
7.00	16	D						_	
7.20-7.61	5	SPT	N=59*					(2.09)	
8.00-8.30 8.00	6 17	SPT D	N=103*					8.29	
-							Borehole terminated at 8.29m depth.	-	

		Boring Pr	ogress and	Water Ob	servations		Chiselli	ing / Slow l	Progress	General	Domorl	7.0	
	Date	Time	Borehole	Casing	Borehole Diameter	Water	From	То	Duration	General	Remair	KS .	
; L	Dute	Time	Depth	Depth	(mm)	Depth	110111	10	(hh:mm)				
-													
î													
										All dimensions in metres	Scale:	1:25	
1	Method			Plan	t Pilco	n Wayfa	arer	Drilled		Logged	Checked		
Į	Jsed:	Cable p	ercussio	n Used		1500 <sup>°</sup>		By:	GH	By: GShaw	By:		AGS



1

## APPENDIX E ROTARY CORED BOREHOLE LOGS AND PHOTOGRAPHS



Contract Reference: 312494

#### KEY TO EXPLORATORY HOLE LOGS - SUMMARY OF ABBREVIATIONS

#### **SAMPLING**

Sample type codes

B = Bulk disturbed sample.

C = Core sample.

CS = Core sample taken from rotary core for lab testing.

D = Small disturbed sample.

DSPT = Small disturbed sample originating from SPT test.

ES = Soil sample for environmental testing.

U = Undisturbed driven tube sample - Number of blows indicated. % recovery reported.

Undisturbed sample detail codes

 $U_{(100)}$  = 100mm diameter undisturbed sample.

#### **IN-SITU TESTING**

 $SPT_{(c)}$  = Standard Penetration Test using a solid 60 degree cone.

 $SPT^{(c)}$  = Standard Penetration Test using split spoon sampler. ( $SPT_{(NR)}$  indicates 'No Sample Recovery').

\* denotes extrapolated N value. NP denotes 'No Penetration'.

V = Field Vane Test. Peak value (c<sub>n</sub>) & Residual value (c<sub>n</sub>), given as shear strength in kPa.

#### **ROTARY DRILLING INFORMATION**

W = Water flush returns (%)
TCR = Total core recovery (%)
SCR = Solid core recovery (%)

RQD = Rock quality designations (%)

If = Fracture spacing (mm).

In the fracture column (i) denotes discontinuity is infilled (refer to Fracture Table for details).

Where variable the minimum - average - maximum spacing may be quoted.

'NI' denotes non-intact core. 'NA' denotes not applicable.

All lengths used to determine rock core mechanical properties taken along the centre line of the core.

Obvious induced fractures have been ignored.

The assessment of solid core is based on lengths that show a full diameter and not necessarily a full circumference.

AZCL = Assessed zone of core loss.

#### ADDITIONAL NOTES

- 1. All soil and rock descriptions and legends in general accordance with BS EN ISO 14688-1, 14688-2, 14689-1, and BS5930:1999 including Amendment 2 (2010).
- 2. Material types divided by a broken line (- - ) indicates an unclear boundary.
- 3. The data on any sheet within the report showing the AGS icon is available in the AGS format.



Contract Reference: 312494

## KEY TO EXPLORATORY HOLE LOGS - SUMMARY OF GRAPHIC SYMBOLS

#### **WATER COLUMN SYMBOLS**



First water strike, second water strike etc.

Standing water level following first strike, standing water level following second strike etc.

Seepage.

Standing water level recorded at documented date.

#### **MATERIAL GRAPHIC LEGENDS**



CLAY



Clayey gravelly SAND



Gravelly clayey SAND



Clayey gravelly SAND with COBBLES

Clayey SAND



Clayey SAND with COBBLES



Clayey sandy GRAVEL



**GRAVEL** 



GRAVEL with COBBLES



Gravelly CLAY



Gravelly silty CLAY



Silty gravelly CLAY



Silty gravelly CLAY with COBBLES



Gravelly SAND



Gravelly clayey SILT



Gravelly SILT



MADE GROUND



Mudstone



SAND



SAND with COBBLES

#### **INSTRUMENTATION SYMBOLS**



Backfill



Bentonite seal



Concrete



Gravel filter



Sand filter



Stopcock cover



Piezometer tip



Plain pipe



Slotted pipe



Contract:				Client:	Borehol					
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	(R)	2(	)3
Contract Ref:	Start:	2.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	3.10.13		67.92	E:447184.9 N:326594.0		1	of		5_

								<u> </u>		2011/1010/10200/10		
			Comple	s & Testing	1	/ooho	nicol	Backfill & Born Instru-				N f - 4 : - 1
			Samples	s & resumg	I.	viecna	meai		1 2		Depth	Material
I	Depth				TCD	CCD	DOD	TC # # # 2	ate	Description of Strata	(Thick	Graphic
	(m)	No	Type	Results	ICK	SCK	KŲD	II     3 E	Water	Description of Strata	(Tillek	Legend
	(111)	INO	1 ype	Results	(%)	(%)	(%)	(mm) 🖁 🗀 🖹	-		ness)	Legend
					· /	` ′				Daille desire Community		<del>→</del> - →
<b>-</b>										Drillers description - Grass over red brown silty	-	
F										CLAY.	-	l
F											-	<u> </u>
-											-	
F											(1.20)	~ ~
-											(1.20)	
-											-	⊢ <u>~</u> —
ļ.											_	××
L												
L											L	$ _{\times}{\times} $
L												
L											1.20	
										Drillers description - Weak red brown		
Γ										MUDSTONE.		
Γ										MODSTONE.		
Ī												
Ī											Γ	
ľ								▎  ▋▋▐			T .	
r								▎  ▋▋▐			†	
t								▎  ▋▋▐			†	
-											⊢ ⊢	
t								▎  ▋▋▐			t	
ŀ											t	
t								▎▗▗▋▋▐			t	
ŀ											-	
ŀ											-	
ŀ											-	
-											-	
F											-	
-											(2.70)	
-											-(3.70)	
-											-	
-											-	
-											-	
-											-	
ŀ											-	
-											-	
											F	
` <b> </b> -											-	
F											F	
-											-	
-											-	
ŀ											ŀ	
ŀ								▎  ▋▋▐			ŀ	
ŀ											ŀ	
·  -								▎  ▋▋▐			ŀ	
-								▎  ▋▋▐			ŀ	
ŀ								▎  ▋▋▐			ŀ	
ŀ								▎  ▋▋▐			4.90	
ŀ										Dill 1 1 2 D 11 1 D D 12	4.70	
-								▎  ▋▋▐		Drillers description - Red brown MUDSTONE.	⊢	
ŀ											F	
ŀ								▎▗▗▊▊▐			-(0.70)	
ŀ								▎  ▋▋▐			F` ′	
ŀ								▎▗▗▊▊▐			ŀ	
											5.60	
.   5.5	60-7.00				1	<b>^</b>	<b>↑</b>	▎  ▋▋▐		TTT 1	3.00	× × × × × × × × × × × × × × × × × × ×
,										Weak to strong thinly interlaminated to thinly	ŀ	$ \hat{x} \hat{x} \hat{x} \hat{x} $
ŀ							1	▎  ▋▋▐		interbedded light grey and red brown SILTSTONE	ŀ	$\times$ $\times$ $\times$
ŀ										and mudstone. Discontinuities are subhorizontal	F	$\times \times \times \times$
·  -							1	▎  ▋▋▐		very closely to medium spaced (28/130/230)	F	$ \hat{x} \hat{x} \hat{x} \hat{x} $
ŀ							1	▎  ▋▋▐		very closely to inequality spaced (26/130/230)	ŀ	$\times$ $\times$ $\times$
,					'		- '	▎  ▋▋▐		planar rough and undulating rough partly open to	F	$\times \times \times \times$
,					93	60	27	▎  ▋▋▐		open with some grey and orange brown staining,	ŀ	$ \stackrel{\circ}{\times}\stackrel{\circ}{\times}\stackrel{\circ}{\times} $
· .	0.6.60					I , I	,			occasional black speckling and occasional thin	ŀ	$ \hat{x} \hat{x} \hat{x} $
<b>∤</b> 6.4	0-6.60	1	CS				1	▎  ▋▋▐		clay smearing.	ŀ	$\times$ $\times$ $\times$
-										(Westhering Crade I)	ŀ	$ \times \times \times \times $
,							1	▎  ▋▋▐		(Weathering Grade I)	ŀ	$ \hat{\mathbf{x}} \times \hat{\mathbf{x}} \times \hat{\mathbf{x}} $
-										(TARPORLEY SILTSTONE FORMATION)	ŀ	$\times$ $\times$ $\times$
-						↓	↓			Description on next sheet	F	× × × × × × × × × × × × × × × ×
L							_1_				L	$\times$ $\times$ $\times$

Boring Progress and Water Observations											
Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth							
08:00	5.50	5.50	121	-							
17:00	28.00	5.50	121	-							
08:00	28.00	5.50	121	-							
17:00	30.00	5.50	121	-							
	Time  08:00 17:00 08:00	Time Borehole Depth  08:00 5.50 17:00 28.00 08:00 28.00	Time         Borehole Depth         Casing Depth           08:00         5.50         5.50           17:00         28.00         5.50           08:00         28.00         5.50	Time         Borehole Depth Depth         Casing Depth Diameter (mm)         Borehole Diameter (mm)           08:00         5.50         5.50         121           17:00         28.00         5.50         121           08:00         28.00         5.50         121							

Plant

Used:

Comacchio MC450-P

Rotary open hole + Rotary Cored

Method

Used:

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PijVersion: v8 05 - Core+Logs 0002 | Log COMPOSITE LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10:41 | KF. RSK Environment Ltd. The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

## General Remarks

- Location scanned with GPR and CAT and signal generator prior to breaking ground. Hand dug service pit to 1.20m bgl. No services encountered.
   Rotary open holed to 5.50m bgl.
   Borehole advanced to 30.00m bgl using coring techniques.
   Gas and groundwater monitoring well installed to 25.00m bgl upon completion.
   No groundwater strikes noted.
   Piezometer installed at 29.00m bgl.

	All dimensi	ions in metre	es	Scale:	1:39
 1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:



Contract:				Client:		Boreho	ole:		
I	East Midland	ls Gate	eway	Roxhi	ll Developments Ltd		CP(l	R)2	203
Contract Ref	:	Start:	2.10.13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:			
3	312494	End:	3.10.13	67.92	E:447184.9 N:326594.0		2	of	5
Donth	Samples & T	esting	Mecha	nnical Log 🕺 in its	D : :: CO: :		Depth		ateria

									_			
			Samples	& Testing	N	<b>Mecha</b>	nical	Log ≥ 1.5	H		Depth	Material
	Depth (m)	No	Туре	Results	TCR (%)	SCR	RQD	Backfill & Backfill when the mentation	Water	Description of Strata	(Thick ness)	
	7.00-8.50		1350	11000110	(%)	(%)	(%)			between 5.90m and 6.00m bgl, undulating subhorizontal fracturing	-	× × × × × × × × × × × × × × × × × × ×
	-				100	43	23			subhorizontal fracturing between 6.20m and 6.33m bgl, undulating subhorizontal fracturing between 6.64m and 7.00m bgl, undulating and stepped subhorizontal fracturing.  Weak to strong thinly interlaminated to thinly interbedded light grey and red brown SILTSTONE and mudstone. Discontinuities are subhorizontal very closely to medium spaced (28/130/230) planar rough and undulating rough partly open to open with some grey and orange brown staining,	(4.20)	X X X X X X X X X X X X X X X X X X X
	8.50-10.00				100	47	16			occasional black speckling and occasional thin clay smearing. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) (stratum copied from 5.60m from previous sheet) between 7.56m and 7.69m bgl, undulating subhorizontal fracturing between 8.72m and 8.97m bgl, undulating and stepped subhorizontal fracturing.		X
ŀ										Weak to medium strong thinly laminated to very	9.80	××××
ļ	-				<u> </u>	<u> </u>	<u> </u>		1	thinly bedded red brown MUDSTONE with very	Ĺ	
	10.00-11.50				100.	60	14			thinly to thinly interbedded light grey SILTSTONE. Discontinuities are subhorizontal very closely to medium spaced (35/100/290) planar rough or undulating rough partly open to open with some grey staining, black speckling and thin clay smearing. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) at 10.85m bgl, moisture on fracture surface between 10.96m and 11.25m bgl, undulating subvertical fracture.	(2.07)	
ŀ	11.50-13.00				1 1	Î	<b>│</b> ↑		1		-	
	12.10-12.37	2	CS		100	61	47	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		Medium strong to strong thinly to medium bedded light grey and red brown fine grained micaceous SANDSTONE with thickly interlaminated to thinly interbedded mudstone and siltstone. Discontinuities are subhorizontal very closely to medium spaced (38/250/330) planar rough partly open to open with some grey staining and thin clay smearing and occasionally micaceous. (Weathering Grade I)	(0.71)	
}	13.00-14.50				<b>X</b>	<b>X</b>				(TARPORLEY SILTSTONE FORMATION) at 11.98m bgl, open clean vug.  Description on next sheet	  -  -  -	
· -					100	67	41			between 13.45m and 13.65m bgl, very weak and	(2.80)	
L							Ш		1		L(2.80)	

		Boring Pr	ogress and	Water O	bservations				Ga	noro1	Remarks		
,	Date	Time	Borehole	C	Borehole Diameter	Water			Ge	iiciai	Kemarks		
3 L	Duit	1 11110	Depth	Depth	(mm)	Depth							
3													
17													
4													
<u>.</u>													
]													
3													
							A	All dimensi	ions in metre	es	Scale:	1:39	
1	Method	Rotary o	pen hole +	- Pla	nt			Drilled		Logged		Checked	
40	Used:		y Cored	Use	ed: Coma	cchio MC4	50-P1	By:	LS/PC	By:	LAlderman	By:	AGS



Contract:					Client:		Boreho	ole:		
E	ast Midlands	Gate	way		Roxhil	l Developments Ltd		CP(	R)2	203
Contract Ref:		Start:	2.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494 End: 3.10.13					67.92	E:447184.9 N:326594.0		3	of	5
Samples & Testing Mechanical					og 😽 Tiöl 🔭			Depth	Ma	ateria

3	124	194	End:	3.10.1	3	67.92	E:447184.9 N:326594.0	3	of <b>5</b>
		Samples	s & Testing	Mec	hanical	Log & . E .		Depth	Material
Depth (m)	No		Results	TCR SC (%) (%	R RQD	Tog Backfill & Instru- mentation Water	Description of Strata	(Thick ness)	
14.50-16.00				100 67			Weak to medium strong thinly laminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with thinly interbedded red brown fine micaceous sandstone. Discontinuities are subhorizontal very closely to medium spaced (38/90/230) planar rough with occasional grey staining and thin clay smearing and occassionally micaceous. (Weathering Grade I)	-	
16.00-16.50				100 67	7 20		(TARPORLEY SILTSTONE FORMATION) (stratum copied from 12.58m from previous sheet)  between 14.17m and 14.85m bgl, undulating subvertical fracture.  Medium strong to strong thickly laminated to thinly bedded light green grey and red brown fine grained micaceous SANDSTONE. Discontinuities are subhorizontal closely spaced planar rough partly open to open micaceous with occasional grey staining and thin clay smearing. (Weathering Grade I)	(0.69)	
17.50-19.00				<b>V V</b>			(TARPORLEY SILTSTONE FORMATION)  Weak to medium strong thinly laminated to thinly bedded red brown and light grey MUDSTONE and siltstone, with thickly interlaminated to thinly interbedded red brown fine grained micaceous sandstone. Discontinuities are subhorizontal very closely to closely spaced (50/100/180) partly open to open planar rough and undulating rough with grey staining, occasional black speckling and thin	17.43	
17.30-19.00	3	CS		100 87	7 73		clay smaring, occasional black specking and thin clay smearing.  (Weathering Grade I)  (BROMSGROVE SANDSTONE FORMATION)  between 16.40m and 16.55m bgl, undulating subvertical fracture.  Medium strong to strong thinly to medium bedded light green grey and red brown fine grained micaceous SANDSTONE. Discontinuities are subhorizontal very closely to medium spaced	-	
19.00-20.50	)			X X			(24/150/440) planar rough and undulating rough with thin clay smearing. (Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION) between 19.00m and 20.04m bgl, zone of core loss.	- - - - - - -	
- - - - - -				31 23	3 20			- - - - - -	
20.50-22.00				100 67	7 36			(6.17)	

; ; [		Boring Pr	rogress and	Water Ol	servations				Ca	noro1	Remarks		
,	Date	Time	Borehole	Casing	Borehole Diameter	Water			Ge	nerai	Remarks		
<i>i</i> [	Dute	Time	Depth	Depth	(mm)	Depth							
3													
7	,												
10	,												
3	,												
'n,	,		]										
<u> </u>	,												
₫	,												 
511							l l	All dimensi	ions in metre	es	Scale:	1:39	
1	Method	Rotary	open hole +	- Plan	ıt			Drilled		Logged		Checked	
157	Used:		ry Cored	Use	d: Coma	cchio MC4	50-P1	By:	LS/PC	By:	LAlderman	By:	AGS



Contract:				Client	t:			Boreho	le:		
1	East Midlands	Gate	eway		Roxhi	ill Develop	ments Ltd		CP(	<b>R</b> )2	203
Contract Ref	· ·	Start:	2.10.13	Ground Leve	el (m AOD):	National Gri	d Co-ordinate:	Sheet:			
3	End:	3.10.13	67	.92	E:4471	84.9 N:326594.0		4	of	5	
	Samples & Tes	tino	Mecha	nical Log 🕺	u				D1	M	otorio

3	124	494	End:	3.1	0.13		67.92	E:447184.9 N:326594.0 4 of 5
		Sample	s & Testing	1	Mecha	nical	Log & Log	Depth Materia
Depth (m)	No	Туре	Results	TCR (%)	SCR (%)	RQD (%)	Log Backfill	Description of Strata (Thick ness) Graphic Legence
22.00-23.50				100	67	36		Medium strong to strong thinly to medium bedded light green grey and red brown fine grained micaceous SANDSTONE. Discontinuities are subhorizontal very closely to medium spaced (24/150/440) planar rough and undulating rough with thin clay smearing. (Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION) (stratum copied from 17.43m from previous sheet)
				97	87	44		
- - -								at 23.02m bgl, 25mm vug with partial calcite infill.
23.50-25.00				+	<b>T</b>	1		at 23.39m bgl, 32mm vug with partial calcite infill.
23.83-24.12	4	CS		97	60	37		Weak to medium strong thinly interlaminated red brown and light grey MUDSTONE and siltstone with occasional thin interbeds of light grey fine grained micaceous sandstone. Discontinuities are subhorizontal closely to medium spaced (40/180/290) planar rough partly open to open with occasional grey staining and thin clay smearing.  (Weathering Grade I)
25.00-26.50				*	<b>X</b>	*		(BROMSGROVE SANDSTONE FORMATION) at 24.06m bgl, 8mm vug with partial calcite infill at 24.08m bgl, 12mm vug with partial calcite infill.
-				100	83	58		Weak to strong thinly to medium bedded light green grey and brown grey fine grained micaceous SANDSTONE. Discontinuities are subhorizontal very closely to medium spaced (39/200/500) planar rough and planar undulating partly open to open.  (Weathering Grade I)
26.50-28.00				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	X	V A		(BROMSGROVE SANDSTONE FORMATION) between 24.50m and 24.80m bgl, subvertical fracturing (possible drilling induced) between 25.98m and 26.12m bgl, band of red brown mudstone.
27.02-27.47	5	CS		92	87	54		between 27.38 and 27.52m bgl, honeycombed band of medium to coarse gravel sized vugs with partial calcite infill.

		Boring Pr	ogress and	Water O	bservations				Ga	noro1	Remarks		
,	Date	Time	Borehole	C	Borehole Diameter	Water			Ge	iiciai	Kemarks		
3 L	Duit	1 11110	Depth	Depth	(mm)	Depth							
3													
17													
4													
<u>.</u>													
]													
3													
							A	All dimensi	ions in metre	es	Scale:	1:39	
1	Method	Rotary o	pen hole +	- Pla	nt			Drilled		Logged		Checked	
40	Used:		y Cored	Use	ed: Coma	cchio MC4	50-P1	By:	LS/PC	By:	LAlderman	By:	AGS



Contract:				Client:		Boreho	le:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	( <b>R</b> )2	203
Contract Ref:	Start:	2.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	3.10.13		67.92	E:447184.9 N:326594.0		5	of	5

Į				Ena.						2011/10/05/1002005/100		· •
	Depth (m)	No		s & Testing  Results	TCR S	echanical SCR RQD (%) (%)	Log If	Backfill & Instru- nentation	Water	Description of Strata	Depth (Thick ness)	Material Graphic Legend
	28.00-29.50		CS			73 58	(11111)	B l		Weak to strong thinly to medium bedded light green grey and brown grey fine grained micaceous SANDSTONE. Discontinuities are subhorizontal very closely to medium spaced (39/200/500) planar rough and planar undulating partly open to open. (Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION) (stratum copied from 24.37m from previous sheet)		-
	29.50-30.00				100	40 24				between 29.50m and 30.00m bgl, possible drilling induced subhorizontal and subvertical fractures between 29.65m and 29.77m bgl, honeycombed band of medium to coarse gravel sized open clean vugs.	30.00	
											- - - - - - - -	
											- - - - - - - -	
											- - - - - - - -	
	- - - - - -										- - - - - -	
	-										- - - -	

; ; [		Boring Pr	rogress and	Water Ol	servations				Ca	noro1	Remarks		
,	Date	Time	Borehole	Casing	Borehole Diameter	Water			Ge	nerai	Remarks		
<i>i</i> [	Dute	Time	Depth	Depth	(mm)	Depth							
3													
7	,												
10	,												
3	,												
'n,	,		]										
<u> </u>	,												
₫	,												 
511							l l	All dimensi	ions in metre	es	Scale:	1:39	
1	Method	Rotary	open hole +	- Plan	ıt			Drilled		Logged		Checked	
157	Used:		ry Cored	Use	d: Coma	cchio MC4	50-P1	By:	LS/PC	By:	LAlderman	By:	AGS



Contract:				Client:		Borehol	e:			
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	(R)	2(	)4
Contract Ref:	Start:	3.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	3.10.13		82.81	E:446666.4 N:326419.4		1	of	3	3_

	1124	194	End:	3.10	J.13		82.81		E:440000.4 N:320419.4	1	of <b>3</b>
		Samples	s & Testing	N	Aecha	nical	Ion & E			D 4	Matarial
Depth (m)	No		Results	TCR	SCR	RQD	Backfill & Backfill when the structure of the structure o	Water	Description of Strata	(Thick ness)	Material Graphic Legend
-		31		(70)	(70)	(70)			Drillers description - Stiff red brown CLAY with gravels.	-	
- - -											
- - -										-	
-										(3.55)	
- - -											
- - -										-	
- - -										-	
3.50-5.00				_	_	_			↑ between 3.50m and 3.55m bgl, zone of core /	3.55	
3.30-3.00									\left  \left  \left  \left  \left  \left  \sin \text{Stiff red brown slightly sandy CLAY. Recovery} \right	-	
- - - -				97	73	20			includes angular to subangular medium to coarse mudstone lithorelicts. (Weathering Grade III)	(1.85)	
- - - -				<b>y</b>	_				(GUNTHORPE MEMBER) between 3.96m and 4.00m bgl, weak light grey siltstone band.	-	
5.00-6.50				1					brown fine grained sandstone band with honeycombed appearance.	5.40	
- - -				97	51	19			between 4.18m and 4.25m bgl, weak to medium strong light grey fine to grained sandstone band.	-	
- - - -									between 4.93m and 5.00m bgl, weak to medium strong light grey fine to grained sandstone band.	(1.92)	
6.50-8.00									loss between 5.00m and 5.05m bgl, zone of core loss between 5.05m and 5.40m bgl, several drilling		
- - -				100	59	40			induced fractures/disturbance and vegetation from surface.  Very weak to weak thinly laminated to very thinly	7.32	
- - - -									bedded red brown micaceous MUDSTONE. Discontinuities are subhorizontal very closely to closely spaced rough undulating tight to open with occasional black speckling and thin clay smearing.	- - - -	
8.00-9.50 8.25-8.50	1	CS		<b>I</b>					(Weathering Grade III) (GUNTHORPE MEMBER) between 5.90m and 6.15m bgl, with very	- - - -	
- - - -				97	77	43			thinly interbedded weak light grey siltstone bands between 6.82m and 7.04m bgl, recovered as soft to firm gravelly clay.	-	

Boring Progress and Water Observations												
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth							
03/10/13 03/10/13	08:00 17:00	5.00 20.00	5.00 7.00	121 121	-							

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PijVersion: v8 05 - Core+Logs 0002 | Log COMPOSITE LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10/41 | KF. RSK Environment Ltd. The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

## General Remarks

- Location scanned with GPR and CAT and signal generator prior to breaking ground. Hand dug service pit to 1.20m bgl. No services encountered.
   Rotary open holed to 3.55m bgl.
   Borehole advanced to 20.00m bgl using coring techniques.
   Gas and groundwater monitoring well installed to 20.00m bgl upon completion.
   No groundwater strikes noted.

					A	All dimens	sions in metre	es	Scale:	1:50
Method Used:	Rotary open hole + Rotary Cored	Plant Used:	Coma	cchio MC4	50-P1	Drilled By:	SC/JO	Logged By:	LAlderman	Checked By:



Contract:				Client:	Client:					
I	<b>East Midland</b>	s Gate	eway	Roxhi	ll Developments Ltd		CP(	R)2	204	
Contract Ref	:	Start:	3.10.13	Ground Level (m AOD):	National Grid Co-ordinate:	Sheet:				
3	312494	End:	3.10.13	82.81	E:446666.4 N:326419.4		2	of	3	
Depth	Samples & Te	sting	Mecha TCP SCP	nical Log &	Description of Strata		Depth (Thick		aterial	

	124	7/7	End:	3.10	J.13		02.01		E:440000.4 N:320419.4		of <b>3</b>
		Samples	s & Testing	N	Лесhа	nical Log	% _ uo	<u> </u>		Depth	Material
Depth (m)		Туре	Results			RQD If	Backfil Instru mentati	Water	Description of Strata	(Thick ness)	Graphic Legend
9.50-11.00				97	77	43			between 7.15m and 7.25m bgl, recovered as soft to firm gravelly clay between 7.25m and 7.32m bgl, medium strong light grey fine grained sandstone band between 8.00m and 8.05m bgl, zone of core loss.	(5.18)	
- - - - -				93	70 	43			between 8.40m and 8.55m bgl, stepped rough clean subvertical fracture; possible drilling induced between 8.55m and 8.57m bgl, firm to stiff gravelly clay.	-	
11.00-12.50				<b>X</b>	*	<del> </del>			Weak to medium strong thinly bedded red brown micaceous MUDSTONE. Discontinuities are subhorizontal very closely to medium closely spaced (20/150/300) undulating rough and planar	-	
- - - - -				100	67	32			rough tight to open with thin clay smearing and occasional black speckling. (Weathering Grade I) (GUNTHORPE MEMBER)	- - - -	
12.50-14.00					<del> </del>	<b>X</b>			(stratum copied from 7.32m from previous sheet) between 9.25m and 9.50m bgl, undulating rough clean subvertical fracture; possible drilling induced.	12.50	
- 12.90-13.20	2	CS							at 10.30m bgl, thin (2mm) subhorizontal calcite vein.	- - -	
	2	CS		100	68	28			between 10.65m and 10.78m bgl, stiff light grey silt band between 11.00m and 11.40m bgl, very weak between 12.08m and 12.17m bgl, weak light grey sandstone band.	- - - -	
14.00-15.50				*	+	<del> </del>			Medium strong to strong thinly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional very thin interbeds of fine grained light grey and red	- - - - -	
- - - - -				91	50	13			brown sandstone. Discontinuities are subhorizontal extremely closely to medium spaced (14/100/290) planar rough and undulating rough tight to open with thin clay smearing and	- - - -	
15.50-17.00				_	<del> </del>	<del> </del>			occasional black speckling. (Weathering Grade I) (GUNTHORPE MEMBER) between 14.00m and 14.14m bgl, zone of core loss.	-	
-									between 15.50m and 15.80m bgl, zone of core loss.	(7.50)	
- - - - - -				80	37	0			at 16.00m bgl, 35mm clean cavity.	(7.50)	
17.00-18.50				80	39				between 17.00m and 17.30m bgl, zone of core loss.	  -  -  -  -	
- - -											

	Boring Pr	rogress and	Water Ob	servations				Go	norol	Remarks		
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth			Ge	merai	Kemarks		
		Берш	Берш	(111111)	Берш							
							All dimens	ions in metre	es	Scale:	1:50	
Method Used:	Rotary	open hole + ry Cored	- Plan		rchio MC4	50_P1	Drilled By:	SC/JO	Logged By:	LAlderman	Checked By:	AGS



Contract:					Client:			Boreho	le:		
I	East Midlands	Gate	eway		Ro	xhil	l Developments Ltd		CP(	$(\mathbf{R})^2$	204
Contract Ref	:	Start:	3.10.13	Groun	d Level (m AOI	D):	National Grid Co-ordinate:	Sheet:			
3	312494	End:	3.10.13		82.81		E:446666.4 N:326419.4		3	of	3
	C1 0 T	d	N f 1								

L	<u> </u>	12	T/T	Eliu.	3.10				2.01		12.770000.711.320717.7		01 5
	Depth			s & Testing	TCR	Mecha SCR	nical RQD	Log	Backfill & Instru- mentation	Water	Description of Strata	(Thick	Material Graphic
	(m) 18.50-20.00 -18.87-19.04		CS	Results	(%) 	53	(%)   0   17   	(mm)		M	Medium strong to strong thinly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional very thin interbeds of fine grained light grey and red brown sandstone. Discontinuities are subhorizontal extremely closely to medium spaced (14/100/290) planar rough and undulating rough tight to open with thin clay smearing and occasional black speckling. (Weathering Grade I) (GUNTHORPE MEMBER) (stratum copied from 12.50m from previous sheet) at 18.26m bgl, 20mm honeycombed clean cavity.	ness)	Legend
											occasional bands of medium gravel sized clean wigs.  Rotary probehole terminated at 20.00m depth.		

	Boring Pr	ogress and	Water Ob	servations				Ca	noro1	Remarks		
Date	Time	Borehole	Casing	Borehole Diameter	Water			Ge	merai	Kemarks		
Bute	Time	Depth	Depth	(mm)	Depth							
<u> </u>												
i												
:												
3												
						A	All dimensi	ons in metre	es	Scale:	1:50	
Method		open hole +			11 1104	50 D1	Drilled	CCITO	Logged	T 411	Checked	<b>AGS</b>
Used:	Rota	ry Cored	Used	1: Coma	cchio MC4	50-P1	By:	SC/JO	By:	LAlderman	By:	AGS



Contract:				Client:		Boreho	le:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	(R)	205
Contract Ref:	Start:	3.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	4.10.13		56.42	E:447286.1 N:326753.4		1	of	4

	J 1 2-		Eliu.		0.15		30.72		L.77/200.1 11.320/33.7		01 4
Depth			& Testing	TCR	Mecha SCR	nical ROD	Fog (mm) Backfill & Instru-	Water	Description of Strata	Depth (Thick	Material Graphic
(m)	No	Type	Results	(%)	(%)	(%)	B E E E E	≥	Drillers description - Red brown silty CLAY.	ness)	Legend
-									Driners description - Red brown stity CLAY.	(1.20)	
- - - - -									Drillers description - Weak red brown	1.20	
- - - - - - - - -									MUDSTONE.		
- - - - - - - - -										(2.90)	
-							*		Drillers description - Red brown MUDSTONE.	4.10	
4.50-6.00				100	75	15			Weak to medium strong thinly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional very thinly interbedded light grey brown fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough extremely closely to medium spaced (10/90/120) tight to open with thin clay smearing, occasional orange	4.50	
6.00-7.50				<b>X</b>	<b>X</b>	*			brown staining and black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION)	(4.40)	
- - - - - -				100	91	60			between 6.87m and 7.11m bgl, undulating subvertical fracture between 6.90m and 7.06m bgl, medium strong light grey brown fine to medium grained sandstone	-	
7.50-9.00									band at 7.03m bgl, 31mm vug with partial calcite infill at 7.05m bgl, 22mm vug with partial calcite	-	
8.58-8.70	1	CS		97	78	42			infill between 7.20m and 7.80m bgl, medium strong light grey brown fine grained sandstone with thinly interlaminated light grey and red brown siltstone and mudstone.	8.90	

	Boring Pr	ogress and	Water Ob	servations							
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth						
Depth         Depth         (mm)         Depth           03/10/13         08:00         4.50         4.50         121         -											
03/10/13	17:00	28.50	4.50	121	_						
04/10/13	08:00	28.50	4.50	121	_						
04/10/13	17:00	30.00	4.50	121	-						
1				1							

Plant

Used:

Comacchio MC450-P

Rotary open hole + Rotary Cored

Method

Used:

## General Remarks

- Location scanned with GPR and CAT and signal generator prior to breaking ground. Hand dug service pit to 1.20m bgl. No services encountered.
   Rotary open holed to 4.50m bgl.
   Borehole advanced to 30.00m bgl using coring technicques.
   Gas and groundwater monitoring well installed to 19.00m bgl upon completion.
   No groundwater strikes noted.

Scale:

All dimensions in metres

	Drilled		Logged		Checked
1	By:	LS/PC	By:	LAlderman	By:



1:50



Contract:				Client:		Boreho	le:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	( <b>R</b> )	205
Contract Ref:	Start:	3.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	4.10.13		56.42	E:447286.1 N:326753.4		2	of	4

3	124	<del>1</del> 74	End:	4.10				6.42		E:44/286.1 N:326/53.4		of <b>4</b>
		Sample	s & Testing	1	/lecha	mical	Log	2 <sub>=</sub>			D. 4	Material
Depth (m)	No		Results	TCR (%)	SCR (%)	RQD (%)	Log If (mm)	Backfill Instru- mentatio	Water	Description of Strata	Depth (Thick ness)	Material Graphic Legend
9.00-10.50				A	<b>A</b>	A				at 7.35m bgl, large vugs up to 38mm with		
7.00-10.50										partial calcite infill.	+	
F							:			Medium strong to strong very thinly to thinly	F	
-										bedded light green grey and light brown grey fine	ļ	
9.70-9.92	2	CS		100	91	58				to medium grained SANDSTONE with occasional	t	
9.70-9.92		CS		100	91	50				honeycombed appearance, with thinly	-	
F										interlaminated to very thinly interbedded red	-	
ţ							•			brown and light grey mudstone and siltstone.	(2.05)	
-					₩	₩				Discontinuities are subhorizontal undulating rough	[(3.05)]	
10.50-12.00				<b>A</b>	<b>A</b>	<b>A</b>	] :			and planar rough closely to medium spaced (21/100/220) tight to open with thin clay smearing	F	
‡										occasional black speckling and occasionally	ļ	
10.02.11.11	2	CS								micaceous.	Ł	
10.92-11.11	3	CS								(BROMSGROVE SANDSTONE FORMATION)	-	
-				100	94	75		⊹∄≎₽		(stratum copied from 8.90m from previous sheet)	-	
<u> </u>					1					between 9.77m and 9.81m bgl, with medium	<u> </u>	
t							:			to coarse gravel sized vugs with partial calcite	t	
F										infill.	11.05	
<u> </u>				<u> </u>	_*_					between 10.60m and 11.40m bgl, medium	- 11.95	
12.00-13.50				1 1	1	1				strong thinly interlaminated to very thinly	t	
-										interbedded red brown and light grey	-	
-							•			MUDSTONE, siltstone and fine grained	-	
ţ					ı		:			sandstone between 10.90 and 10.92m bgl, gravelly clay.	-	
t				100	87	73				between 11.30m and 11.33m bgl, gravelly	t	
F					1					clay.	-	
-										Medium strong to strong very thinly to thinly	F	
ţ					Ţ		:			bedded red brown and light grey brown fine to	-	
13.50-15.00					+	<b>— X</b>	- 6			medium grained micaceous SANDSTONE with	t	
13.30-13.00										occasional honeycombed appearance with some	-	
-										thinly interlaminated to very thinly interbedded	F	
-							:			red brown and light grey mudstone and siltstone.	-	
E				100	51	19				Discontinuities are subhorizontal undulating rough	Ł	
-				100	31	1)				and planar rough extremely closely to medium	-	
										spaced (11/150/430) tight to open with thin clay smearing, occasional black speckling and orange	F	
ţ										brown staining and occasionally micaceous.	-	
Ł				₩	<b>V</b>	<b>V</b>	]			(Weathering Grade I)	Ł	
15.00-16.50				<b>A</b>	<b>A</b>	<b>A</b>	:			(BROMSGROVE SANDSTONE FORMATION)	-	
ļ.										at 12.57m bgl, 20mm clean vug.	ļ.	
<u> </u>										between 13.67m and 13.78m bgl, stepped	-	
t										rough subvertical fracture.	t	
-				93	79	56				at 13.88m bgl, up to 10mm thick	-	
F					1	l ,				subhorizontal string (interconnecting) of clean	ļ.	
								::H::1		vugs between 14.00m and 14.01m bgl, clayey	ļ.	
t										gravel.	Ł	
16 50 10 00					-		:	:::H:::\		between 14.18m and 14.21m bgl, clayey	+	
16.50-18.00				[	Ī	[				gravel.	F	
ţ.										between 14.38 and 14.93m bgl, undulating	ţ	
-										rough subvertical fracture with thin clay smear,	F	
-				100	0.4	60		:::H:::1		dark red brown staining and localised black	+	
17.28-17.53	4	CS		100	84	60				specking.	F	
ļ.										between 15.78m and 15.85m bgl, planar rough	ţ.	
t										subvertical fracture with black specking between 16.76m and 16.79m bgl, firm	t	
F					₩	↓				gravelly clay.	+	
							P			- Gratory Clay.		

	Boring Pr	ogress and	Water Ob					Go	norol	Remarks		
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth				Herai	Kemarks		 
-			•		•							
						A	All dimensi	ons in metre	s	Scale:	1:50	
Method Used:						50-P1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:	<b>AGS</b>



	Contract:					Client:			Boreho	le:		
	Ea	st Midlands	Gate	eway		Ro	xhil	l Developments Ltd		CP(	<b>R</b> )2	205
	Contract Ref:		Start:	3.10.13	Ground	d Level (m AO	D):	National Grid Co-ordinate:	Sheet:			
	31	2494	End:	4.10.13		56.42		E:447286.1 N:326753.4		3	of	4
Γ	Samples & Testing Mechanical I				nical L	ng 🕺 🗧				D1	1/1	otorio

	14	194	End:		<u>0.13</u>		56.42		E:44/286.1 N:326/53.4	3	of <b>4</b>
		Samples	s & Testing	Mechanical Log   SCR   ROD   If   SCR   ROD   If   SCR   ROD   Mentation   Mentation   Mentation   Mentation   Mentation   Mechanical Log   Me		- K		Depth	Material		
Depth (m)	No	Туре	Results	TCR (%)	SCR (%)	RQD (%)	Backfil Instru	Water	Description of Strata	(Thick ness)	Graphic Legend
18.00-19.50				1	1	1			between 17.01m and 17.06m bgl, firm to stiff		
_									gravelly clay.  Medium strong to strong very thinly to thinly	-	
-									bedded red brown and light grey brown fine to	-	
-				100	86	29			medium grained micaceous SANDSTONE with	-	
_				100	00	2)			occasional honeycombed appearance with some	Ł	
E									thinly interlaminated to very thinly interbedded red brown and light grey mudstone and siltstone.		
-									Discontinuities are subhorizontal undulating rough	-	
19.50-21.00				$\perp$	+	<b>-</b>			and planar rough extremely closely to medium	-	
19.30-21.00									spaced (11/150/430) tight to open with thin clay		
Ł							• • • • • •		smearing, occasional black speckling and orange brown staining and occasionally micaceous.	Ł	
_									(Weathering Grade I)	L	
E				100	56	36			(BROMSGROVE SANDSTONE FORMATION)	E	
_									(stratum copied from 11.95m from previous sheet)	E	
<u> </u>									between 19.07m and 19.14m bgl, medium to coarse gravel sized vugs, some clean occasionally	E	
_				<b>V</b>	₩	₩			with partial calcite infill.	(18.05)	
21.00-22.50				<b>A</b>	<b>A</b>	1			between 19.46m and 19.48m bgl, firm to stiff	-	
E									gravelly clay.  between 19.68m and 19.72m bgl, clayey	Ł	
_									gravel.	Ł	
				100	95	59			between 19.84m and 20.00m bgl, undulating		
_				100	)3				rough subvertical fracture with dark red brown	_	
-									staining between 21.15m and 22.01m bgl, clayey	E	
E									gravel.	Ł	
22.50-24.00				+	+	<b>-</b>			at 21.43m bgl, 32mm clean vug.		
22.30-24.00									at 21.93m bgl, 16mm clean vug.	_	
_									between 22.41m and 22.50m bgl, medium to coarse gravel sized clean vugs, rarely with partial	_	
_									calcite infill.	-	
-				100	83	55			between 22.86m and 22.96m bgl, undulating	-	
-						l i			rough subvertical fracture with thin clay smearing and micaceous.	_	
_									between 23.12m and 23.15m bgl, firm to stiff	-	
_				<b>_</b>	<b>V</b>	🔻			gravelly clay.	L	
24.00-25.50				1	1	↑			between 23.37m and 23.42m bgl, clayey	-	
-									gravel between 24.12m and 24.20m bgl, clay infilled	<u> </u>	
-									fractures.	-	
-				95	89	80				-	
<u>-</u>					1					-	
-									ot 25 15m hal along in filled for atoms	-	
-									at 25.15m bgl, clay infilled fracture.	-	
25.50-27.00					<b>—</b>	<b> </b>			between 25.50m and 25.70m bgl, zone of core	-	
==:.55 = 7.00									loss.	-	
-									between 25.86m and 25.92m bgl, with rare	<u> </u>	
-									medium to coarse gravel sized clean vugs.	-	
_				87	65	55				-	
-										-	
-									between 26.68m and 26.70m bgl, with rare	-	
_				<del> </del> _	₩	₩			subrounded to rounded medium to coarse gravel of	L	

Ξ													
) OVE		Boring Pr	rogress and	Water C	bservations				$C_{\alpha}$	maral	Damarla		
Centre, C	Date	Time	Borehole Depth	Casing Depth	Diameter	Water Depth			Ge		Remarks		
er prise				-									
, 1													
HIEL													
VII Ç								All dimens	ions in metre	es	Scale:	1:50	
N DII	Method Used:					echio MC4	50. D1	Drilled By:	I S/PC	Logged By:	I Aldarman	Checked	AGS

GINT\_LIBRARY\_V8\_05.GLB LibVersion: v8\_05 - Lib0004 PijVersion: v8\_05 - Core+Logs 0002 | Log COMPOSITE LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8\_05 | 10/12/13 - 10:41 | KF. RS. Environment\_Ltd\_The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

Rotary Cored Comacchio MC450-P1 LAlderman



												BUKER	OL		UG
Contract:								Cl	ient:				Boreho	le:	
I	East	t Mid	lands	Gate	eway	y				Ro	xhil	ll Developments Ltd		CP(l	R)205
Contract Ref				Start:		0.13	Grou	ınd L	evel (n	AO	D):	National Grid Co-ordinate:	Sheet:		
3	3124	194		End:	4.1	0.13			56.42	2		E:447286.1 N:326753.4		4	of <b>4</b>
		Samples	s & Test	ing	I	Mecha	nical	Log	II & u- tion	er				Depth	Material
Depth (m)	No	Туре	Res	sults	TCR (%)	SCR (%)	RQD (%)	If (mm)	Backfill & Instru- mentation	Water		Description of Strata		(Thick ness)	Graphic Legend
27.00-28.50	5	CS			97	87	53				roughed meconoccuthin red Dissand spars smeeth brown (We (BR (structure) sand coardinate	. at 27.24m bgl, 18mm clean vug between 28.32m and 28.38m bgl, recody gravel between 28.46m and 28.50m bgl, ads, gravel is subrounded to rounded urse quartzite, sandstone and mudstone between 28.50m and 28.52m bgl, zone	o thinly fine to JE with hh some rbedded diltstone. It is grough medium hin clay lorange of core wered as gravelly fine to gravelly fine to gravelly fine to gravelly fine to	30.00	

		Boring Progress and Water Observations    Borehole   Casing   Borehole   Wa							Go	norol	Remarks		
, Court,	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth				iici ai	IXCIIIai KS		
Title Press													
,													
Ommers -								All dimens	ions in metre	<u> </u>	Scale:	1:50	
Non-	Method Rotary open hole + Plant Used: Comacchio Mo					echio MC4	50-P1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:	AGS



Contract:				Client:		Borehol	e:			
East Midlands	Gate	way		Roxhil	l Developments Ltd		CP	(R)	20	6
Contract Ref:	Start:	4.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:				
312494	End:	4.10.13		51.84	E:447408.6 N:326891.6		1	of	4	ļ

	3124	194	End:	4.10	).13		21	.84		E:44/408.6 N:326891.6	1	of <b>4</b>
		Samplas	s & Testing	Ι .	/lacha	nical	Log &	п			<u> </u>	Matarial
Depth			s & resuing	TCR	SCR	ROD	Log & Backfill Backfi	stru- tatio	Water	Description of Strata	Depth (Thick	Material Graphic
(m)	No	Type	Results	(%)	(%)	(%)	(mm)	Ins	≱	Description of Strata	ness)	Legend
-										Drillers description - Firm to stiff red/brown	-	
E										CLAY.	t	
_											-	
į.											ţ	
-											+	
F											-	
+											-	
F											F	
ţ											ļ	
t											t	
-											(4.00)	
-											[,	
t											t	<u> </u>
+											}	
ļ.											ļ.	
ţ											t	
ŀ											F	
F											F	
t											t	
-											-	
F											F	
: ‡											ļ	
Ł											4.00	
4.00-5.50				🛉	<b>A</b>	♠				Medium strong to very strong very thinly to thinly	-	
<b>:</b>										bedded light grey brown and red brown fine to medium grained SANDSTONE with occasional	-	
:  -										medium grained SANDSTONE with occasional	t	
<u> </u>										honeycombed appearance, with occasional thinly	}	
: [				100	77	27				to thickly interlaminated mudstone and siltstone.	F	
<u> </u>										Discontinuities are subhorizontal undulating rough		
}										and planar rough very closely to medium spaced (22/130/250) tight to open with thin clay smearing,	+	
· [										occasional black speckling and occasionally	F	
} ‡				<u> </u>	_*_	<u> </u>				micaceous.	ļ	
5.50-7.00				1	<b>↑</b>	🐧				(Weathering Grade I)	t	
<u> </u>										(BROMSGROVE SANDSTONE FORMATION)	-	
F										between 5.50m and 5.55m bgl, zone of core	F	
					I					loss.	ţ	
<u> </u>				97	75	39					Ł	
i F											F	
: ‡											ļ	
ţ											t	
					lacksquare						F	
7.00-8.50				1	T I	🗍					F	
5											t	
}											}	
} F				100	02	-					F	
				100	83	52					ţ	
<u>.</u> –											F	
F											F	
‡										between 8.25m and 8.30m bgl, medium coarse	ţ	
8.50-10.00										gravel sized vugs with partial and some complete	t	
0.50-10.00				100	00	12				calcite infill.	}	
F				100	80	42					F	
· L			I.									

	Danina Da		Water Ob		
	Boring Pi	ogress and	water Ob		
Date	Time	Borehole	Casing	Borehole Diameter	Water
Date	1 IIIIC	Depth	Depth	(mm)	Depth
04/10/13	08:00	5.50	3.00	121	-
04/10/13	17:00	25.00	7.00	121	-

## General Remarks

- Location scanned with GPR and CAT and signal generator prior to breaking ground. Hand dug service pit to 1.20m bgl. No services encountered.
   Rotary open holed to 4.00m bgl.
   Borehole advanced to 25.00m bgl using coring technicques.
   Gas and groundwater monitoring well installed to 21.00m bgl upon completion.
   No groundwater strikes noted.
   Piezometer installed at 24.00m bgl.

				A	All dimens	sions in metre	es	Scale:	1:50
Method Used:	Rotary open hole - Rotary Cored	Plant Used:	cchio MC4	50-P1	Drilled By:	SC/JO	Logged By:	LAlderman	Checked By:





Contract:				Client:		Boreho	le:		
East Midlands	Gate	way		Roxhil	l Developments Ltd		CP	$(\mathbf{R})^2$	206
Contract Ref:	Start:	4.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	4.10.13		51.84	E:447408.6 N:326891.6		2	of	4

J	124	174	Ena:	4.1	U.13		31.04		E:44/400.0 N:320091.0		01 4
		Samples	s & Testing	1	Mecha	nical	Log & . E			Donth	Material
Depth (m)		Туре	Results	TCR (%)	SCR (%)	RQD (%)	Packfill & Instru-	Water	Description of Strata	(Thick ness)	
- - - - - - -				100	80	42			Medium strong to very strong very thinly to thinly bedded light grey brown and red brown fine to medium grained SANDSTONE with occasional honeycombed appearance, with occasional thinly to thickly interlaminated mudstone and siltstone. Discontinuities are subhorizontal undulating rough	(11.57)	
10.00-11.50				91	68	39			and planar rough very closely to medium spaced (22/130/250) tight to open with thin clay smearing, occasional black speckling and occasionally micaceous.  (Weathering Grade I)  (BROMSGROVE SANDSTONE FORMATION)  (stratum copied from 4.00m from previous sheet)  between 9.05m and 9.25m bgl, weak to	-	
11.50-13.00				<del>                                     </del>	<del> </del>	<u> </u>			medium strong thinly interlaminated red brown mudstone and siltstone at 9.60m bgl, 6mm subhorizontal calcite infilled fracture between 10.00m and 10.13m bgl, zone of core	- - - - -	
- - - - - -				97	73	30			loss between 11.50m and 11.55m bgl, zone of core loss between 11.80m and 11.83m bgl, firm red brown silty gravelly clay.	- - - - - - -	
13.00-14.50				87	59	39			strong thinly interlaminated red brown mudstone, siltstone and sandstone.  at 12.18m bgl, 32mm cavity with partial calcite infill.  at 12.20m bgl, medium to coarse gravel sized	- - - - - -	
- 14.50-16.00									vugs with partial calcite infill between 13.00m and 13.20m bgl, zone of core loss between 13.41m and 13.53m bgl, subvertical undulating rough fracture.	- - - - - -	
- - - - - - -				100	81	35			between 14.78m and 14.98m bgl, subvertical undulating rough fracture.	15.57	
16.00-17.50				<b>X</b>	<b>X</b>	X			Weak to strong thickly interlaminated to thinly interbedded red brown and light grey brown micaceous fine grained SANDSTONE and MUDSTONE with occasional honeycombed appearance. Discontinuities are subvertical	(1.68)	
- - - - - - -				93	45	15			undulating rough and planar rough closely to medium spaced (35/100/230) partly open to open with thin clay smearing, occasional black speckling and occasionally micaceous.  (Weathering Grade I)  (BROMSGROVE SANDSTONE FORMATION)	17.25	
17.50-19.00				90	80	62			loss between 16.28m and 16.40m bgl, subvertical planar rough fracture with calcite infill.	- - - - -	

	Boring Pr	rogress and	Water Ob	servations				Go	norol	Remarks		
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth			Ge	merai	Kemarks		
		Берш	Берш	(111111)	Берш							
							All dimens	ions in metre	es	Scale:	1:50	
Method Used:	Rotary	open hole + ry Cored	- Plan		rchio MC4	50_P1	Drilled By:	SC/JO	Logged By:	LAlderman	Checked By:	AGS



Contract:				Client:		Borehol	e:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	( <b>R</b> )	206
Contract Ref:	Start:	4.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	4.10.13		51.84	E:447408.6 N:326891.6		3	of	4

3	124	194	End:	4.10	0.13		51.84		E:447408.6 N:326891.6	3	of <b>4</b>
	9	Samples	& Testing	ı	Mecha	anical	Ing 🕺 🗧	$\equiv$		D 41.	Material
Depth (m)		Туре	Results	TCR (%)	SCR (%)	RQD (%)	Dackfill & losture Backfill & losture mentation	Water	Description of Strata	(Thick ness)	
19.00-20.50				90	80	62			between 17.50m and 17.65m bgl, zone of core loss.  Medium strong to strong thinly bedded red brown micaceous fine grained SANDSTONE with occasional honeycombed appearance. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced	(2.55)	
-				91	55	48			(30/150/290) partly open to open with thin clay smearing, occasional black speckling and occassionally micaceous. (Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION) (stratum copied from 17.25m from previous sheet) between 19.00m and 19.13m bgl, zone of core loss.	19.80	
20.50-22.00				97	73	49			Medium strong to strong thickly interlaminated to thinly interbedded red brown and light grey brown fine grained SANDSTONE, very occasional honeycombed appearance with thickly interlaminated to very thinly interbedded light grey and red brown siltstone and mudstone. Discontinuities are subhorizontal undulating rough and planar rough extremely closely to medium spaced (15/80/250) partly open to open with thin		
22.00-23.50				57	37	9			clay smearing between 20.50m and 20.55m bgl, zone of core loss between 21.29m and 21.37m bgl, subvertical undulating rough fracture between 21.50m and 22.00m bgl, medium to coarse grained between 22.00m and 22.75m bgl, zone of core loss.	(4.40)	
23.50-25.00				93	53	13			between 23.50m and 23.60m bgl, zone of core loss at 23.17m bgl, 14mm vug with partial calcite infill between 23.90m and 24.00m bgl, cross stratified between 23.90m and 24.05m bgl, medium to coarse between 24.17m and 24.19m bgl, flute clasts/evidence of scouring within mudstone band between 24.19m and 24.21m bgl,	(0.70)	
									conglomerate with subrounded to rounded medium to coarse quartzite, flint and sandstone clasts.  Red brown grey white subrounded to rounded coarse GRAVEL of sandstone, quartzite and siltstone.  (CONGLOMERATE)  Medium strong to strong thickly interlaminated to very thinly interbedded red brown, grey and grey brown fine grained SANDSTONE, siltstone and mudstone. Discontinuities are subhorizontal		

		Boring Pr	ogress and	Water C	bservations				Ga	noro1	Remarks			
,	Date	Time	Borehole		Borehole Diameter	Water			Ge	iiciai	Kemarks			
3 L	Duit	1 11110	Depth	Depth	(mm)	Depth								
3														
<u> </u>														
4														
<u>.</u>														
1														
3														
							A	All dimensi	ions in metre	es	Scale:	1:50		
1	Method	Rotary o	pen hole +	- Pla	nt			Drilled		Logged		Checked		
40	Used:		y Cored	Us	ed: Coma	cchio MC4	50-P1	By:	SC/JO	By:	LAlderman	By:	A	AGS



Contract:				Client:		Boreho	le:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	(R)	206
Contract Ref:	Start:	4.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	4.10.13		51.84	E:447408.6 N:326891.6		4	of	4

			Ena.						271171001011102007110		01
		Sample	s & Testing	M	[echanica	1 Ι οσ	& ⊑			D 4	Material
Depth (m)	No	_	Results	TCR (%)	Iechanica SCR RQI (%) (%)	O If (mm)	Backfill Instru- mentatic	Water	Description of Strata	(Thick ness)	Graphic Legend
-									undulating rough and planar rough closely to medium spaced (70/90/100) open with thin clay smearing. (Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION) Rotary probehole terminated at 25.00m depth.	- - - - - - - - - -	
-										- - - - - - - - - - - - - - - - - - -	
										- - - - - - - - - - - - - - - -	
-										- - - - - - - - - - - - - - - - - - -	
										- - - - - - - - - - - -	
-										- - - - - - - - - -	
-										- - - - - -	

		Boring Pr	ogress and	Water O	bservations				Ca	noro1	Remarks		
î [	Date	Time	Borehole		Borehole Diameter	vv atci			Ge	merai	Kemarks		
ł L	Bute	1 11110	Depth	Depth	(mm)	Depth							
4													
1													
i													
4													
î													
-													
							l A	All dimensi	ions in metre	es	Scale:	1:50	
I	Method	Rotary	open hole +	- Plai	nt			Drilled		Logged		Checked	
į   l	Used:	Rotar	ry Cored	Use	d: Coma	cchio MC4	50-P1	By:	SC/JO	By:	LAlderman	By:	AGS



Contract:				Client:		Boreho	le:		
East Midlands	Gate	way		Roxhil	l Developments Ltd		CP(	$\mathbf{R}$	207
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13		63.04	E:447086.9 N:326841.6		1	of	4

(m) No Type Results (%) (%) (%) (mm) = 5   5   10   10   10   10   10   10   1		3124	194	End:	1.10	0.13		63.04		E:447086.9 N:326841.6	1	of <b>4</b>
Drillers description - Red brown silty CLAY.  Drillers description - Weak red brown MUDSTONE.  1.20  Drillers description - Weak red brown MUDSTONE.  1.20  Very weak thickly laminated red brown MUDSTONE.  (0.40)  (0.40)  (0.40)  (0.40)  (0.40)  (0.40)  Weak to strong thickly interlaminated to thinly interbedded fine grained sandstone. Discontinuties are subbnizzonalu undulating rough and planar rough very closely to medium spaced (28/10/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional dark brown and orange brown staining and occasional black speckling and occasional wind occasional dark brown and orange brown staining and occasional black speckling and occasional wind occasional black speckling and occasional speckling and occasional speckling wind occasional wind occasional black speckling and occasional wind occasional black speckling and occasional wind occasional wind occasional wind occasional black speckling and occasional wind wind occasional wind occasional wind occasional wind occasional wind occasional wind oc			Sample	s & Testing	N	Лесhа	nical	Log & . 5			Donth	Material
Drillers description - Red brown silty CLAY.  Drillers description - Weak red brown MUDSTONE.  1.20  Drillers description - Weak red brown MUDSTONE.  1.20  Very weak thickly laminated red brown MUDSTONE.  (0.40)  (0.40)  (0.40)  (0.40)  (0.40)  (0.40)  Weak to strong thickly interlaminated to thinly interbedded fine grained sandstone. Discontinuties are subbnizzonalu undulating rough and planar rough very closely to medium spaced (28/10/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional dark brown and orange brown staining and occasional black speckling and occasional wind occasional dark brown and orange brown staining and occasional black speckling and occasional wind occasional black speckling and occasional speckling and occasional speckling wind occasional wind occasional black speckling and occasional wind occasional black speckling and occasional wind occasional wind occasional wind occasional black speckling and occasional wind wind occasional wind occasional wind occasional wind occasional wind occasional wind oc					TCR (%)	SCR (%)	RQD (%)	Sackfill Sackfill Mentatic	Water	Description of Strata	(Thick	Graphic Legend
CLAY.  Drillers description - Red brown silty CLAY.    Drillers description - Weak red brown	_				,	( )	,			Drillers description - Grass over red brown silty	0.10	<u>x                                      </u>
Drillers description - Weak red brown MUDSTONE.    1.20	-									CLAY.	-	× ×
Drillers description - Weak red brown MUDSTONE.    Very weak thickly laminated red brown MUDSTONE.   (0.40)	-									Drillers description - Red brown silty CLAY.		xx
Drillers description - Weak red brown MUDSTONE.    Very weak thickly laminated red brown MUDSTONE.   (0.40)	F										(1.10)	×
Drillers description - Weak red brown MUDSTONE.    2.30	-										(1.10)	× ×
Drillers description - Weak red brown MUDSTONE.    2.30	-										-	<u> </u>
Drillers description - Weak red brown MUDSTONE.    2.30	F										-	x
Very weak thickly laminated red brown (0.40)    Very weak thickly laminated red brown (0.40)	ţ										1.20	<u> </u>
Very weak thickly laminated red brown MUDSTONE. (Weathering Grade II)  (7ARPORLEY SILTSTONE FORMATION)  Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION)  between 2.88m and 2.93m bgl, red brown silty gravelly clay.  between 3.09m and 3.13m bgl, red brown silty gravelly clay.  between 3.09m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface.  between 5.45m and 5.49m bgl, firm clayey gravely.	-										-	
2.30   Very weak thickly laminated red brown (0.40)   (0.	ţ									MUDSTONE.	į	
2.30   Very weak thickly laminated red brown (0.40)   (0.	-										(1.10)	
Very weak thickly laminated red brown MUDSTONE. (Weathering Grade II) (TARPORLEY SILTSTONE FORMATION) Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	ļ										(1.10)	
Very weak thickly laminated red brown MUDSTONE. (Weathering Grade II) (TARPORLEY SILTSTONE FORMATION) Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-										-	
Very weak thickly laminated red brown MUDSTONE. (Weathering Grade II) (TARPORLEY SILTSTONE FORMATION) Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	F										-	
MUDSTONE. (Weathering Grade II) (TARPORLEY SILTSTONE FORMATION)  Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	t										2.30	
Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interhedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with hin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION)  between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	- 2.30-3.80				1 1	1	1			Very weak thickly laminated red brown	(0.40)	
\( \text{\text{CTARPORLEY SILTSTONE FORMATION} \) \( Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	ţ										Γ` ΄	
Weak to strong thickly interlaminated to thinly interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough every closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-										2.70	
interbedded red brown and light grey MUDSTONE and siltstone with occasional thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	ļ									Weak to strong thickly interlaminated to thinly	-	
MODS flowe and sitistone with occasional thinly interlaminated to very thinly interbedded fine grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.09m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-				100	52	0			interbedded red brown and light grey	F	
grained sandstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous.  (Weathering Grade I)  (TARPORLEY SILTSTONE FORMATION)  between 2.88m and 2.93m bgl, red brown silty gravelly clay.  between 3.09m and 3.13m bgl, red brown silty gravelly clay.  between 3.30m and 3.39m bgl, red brown silty gravelly clay.  between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface.  between 5.45m and 5.49m bgl, firm clayey gravel.	-				100	32				MUDSTONE and siltstone with occasional thinly	-	
subhorizontal undulating rough and planar rough very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous.  (Weathering Grade I)  (TARPORLEY SILTSTONE FORMATION)  between 2.88m and 2.93m bgl, red brown silty gravelly clay.  between 3.09m and 3.13m bgl, red brown silty gravelly clay.  between 3.30m and 3.39m bgl, red brown silty gravelly clay.  between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface.  between 5.45m and 5.49m bgl, firm clayey gravel.	t									grained sandstone Discontinuities are	t	
very closely to medium spaced (28/120/290) tight to open with thin clay smearing, with occasional dark brown and orange brown staining and occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-									subhorizontal undulating rough and planar rough	-	
dark brown and orange brown staining and occasional black speckling and occasionally micaceous.  (Weathering Grade I)  (TARPORLEY SILTSTONE FORMATION)  between 2.88m and 2.93m bgl, red brown silty gravelly clay.  between 3.09m and 3.13m bgl, red brown silty gravelly clay.  between 3.30m and 3.39m bgl, red brown silty gravelly clay.  between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface.  between 5.45m and 5.49m bgl, firm clayey gravel.										very closely to medium spaced (28/120/290) tight	Ĺ	
occasional black speckling and occasionally micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	3 80 5 30				$\perp$	lacksquare	lacksquare			to open with thin clay smearing, with occasional	-	
micaceous. (Weathering Grade I) (TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	5.80-5.50						Ï			occasional black speckling and occasionally	_	
(TARPORLEY SILTSTONE FORMATION) between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-									micaceous.	-	
57 13  between 2.88m and 2.93m bgl, red brown silty gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-									(Weathering Grade I)	-	
gravelly clay between 3.09m and 3.13m bgl, red brown silty gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	ţ									hetween 2 88m and 2 93m hal red brown silty	_	
gravelly clay between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-				100	57	13			gravelly clay.	F	
5.30-6.80  between 3.30m and 3.39m bgl, red brown silty gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-										ļ	
gravelly clay between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	Ł									graverry cray.  between 3.30m and 3.39m holered brown silty.	Ł	
5.30-6.80  between 4.60m and 4.95m bgl, subvertical stepped rough fracturing with dark brown staining and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	-									gravelly clay.	F	
and moist surface between 5.45m and 5.49m bgl, firm clayey gravel.	ţ				<b>_</b>	<u> </u>	y			between 4.60m and 4.95m bgl, subvertical	ţ	
between 5.45m and 5.49m bgl, firm clayey gravel.	5.30-6.80				🕴	<b>^</b>	<b>^</b>				-	
	‡									between 5.45m and 5.49m bgl. firm clavev	ļ	
	-									gravel.	<u> </u>	
between 5.55m and 5.62m bgl, firm clayey	F										-	
gravel. 100   53   23   gravel between 5.97m and 6.22m bgl, medium strong	t				100	53	23				t	
light grey brown and red brown fine grained	-				100	ادر	ر کے			light grey brown and red brown fine grained	ŀ	
sandstone.	<u> </u>									sandstone.	ţ	
between 6.39m and 6.43m bgl, firm clayey	-										}	
gravel between 6.60m and 6.73m bgl, several	-									gravei. between 6.60m and 6.73m hol several	ţ	
	6.80-8.30					-	$\perp$				<u> </u>	
6.80-8.30   100   60   21   subvertical stepped rough fractures with dark grey staining.	0.00.00				100	60	21				L	

	Boring Pr	ogress and	Water Ob	servations	
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth
01/10/13 01/10/13 01/10/13	08:00 13:00 17:00	3.80 12.80 24.80	2.30 12.10 12.10	121 121 121	- - -

GINT LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PijVersion: v8 05 - Core+Logs 0002 | Log COMPOSITE LOG | 312494 - EAST MIDLANDS GATEWAY.GPJ - v8 05 | 10/12/13 - 10/41 | KF. RSK Environment Ltd. The Enterprise Centre, Coventry University Technology Park, Coventry, CV1 2TX. Tel: 02476 236816, Fax: 02476 236014, Web: www.rsk.co.uk.

## General Remarks

- Location scanned with GPR and CAT and signal generator prior to breaking ground. Hand dug service pit to 1.20m bgl. No services encountered.
   Rotary open holed to 2.30m bgl.
   Borehole advanced to 24.80m bgl using coring techniques.
   Gas and groundwater monitoring well installed to 24.80m bgl upon completion.
   No groundwater strikes noted.

6 Diamamatan				la a l
<ol><li>Piezometer</li></ol>	mstaneu	at 12.	TOIII	ogi.

					A	All dimens	sions in metre	es	Scale:	1:39
Method Used:	Rotary open hole + Rotary Cored	Plant Used:	Coma	cchio MC4	50-P1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:



												BUKER	JLI	_ L	UG
Contract:								Cl	ient:				Boreho	le:	
ŀ	East	t Mid	lands	Gate	eway	7				Ro	xhil	ll Developments Ltd		CP(I	R)207
Contract Ref	:			Start:	1.10	0.13	Grou	ınd L	evel (r	n AOI	D):	National Grid Co-ordinate:	Sheet:		
3	312	<b>494</b>		End:	1.10	0.13		(	63.04	1		E:447086.9 N:326841.6		2	of <b>4</b>
Depth		Samples	& Test	ing	TCR	Mecha	nical RQD	Log	Backfill & Instru-	Water		Description of Strata		Depth (Thick	Material Graphic
(m)	No	Type	Res	sults	(%)	(%)	(%)	(mm	Back In In	≽		2 computer of Suum		ness)	Legend
- 8.30-9.80					100	60	21				inte MU inte grai subl very to o darl occa mic	aceous.	grey thinly d fine are rough )) tight asional g and	(10.30)	
-					100	81	occasional black speckling and occasionally micaceous.  (Weathering Grade I)  (TARPORLEY SILTSTONE FORMATION)  (stratum copied from 2.70m from previous sheet)  between 7.17m and 7.36m bgl, firm clayey gravel.  between 7.81m and 7.86m bgl, firm clayey gravel.  at 8.20m bgl, 26mm cavity with partial calcite infill.  at 8.97m bgl, 35mm vug with partial calcite infill.								
9.80-11.30					100	87	30				brov freq 45n	between 10.60m and 10.83m bgl, light with fine to medium grained sandstonquent medium to coarse gravel sized nm) vugs with partial calcite infill.	e with (up to	- - - - - - - - - - - - - -	
11.30-12.80					100	85	29	between 10.90m and 11.25m bgl, light grey brown fine to medium grained sandstone with frequent medium to coarse gravel sized (up to 45mm) vugs with partial calcite infill.							
12.80-14.30					100	63	47					scription on next sheet  between 13.70m and 13.86m bgl, day thin cross stratification.	k grey	13.00	

) veill		Boring Pr	ogress and	Water Ob	servations				Ca	norol	Remarks		
inc,	Date	Time	Borehole	U	Borehole Diameter	Water			Ge	nerai	Kemarks		
3			Depth	Depth	(mm)	Depth							
חופווו ביש, זווס בוווטוווי													
5							l A	All dimensi	ions in metre	S	Scale:	1:39	
Non Fun	Method Used:	Rotary o Rotar	pen hole + y Cored	- Plan Use		echio MC4	50-P1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:	AGS



												Вυ	KEH	JLI		.C	
Contract:								Cli	ient:					Boreho	le:		
l I	East	t Mid	lands	Gate	eway	y				Ro	xhil	ll Developments L	ıtd .		CP(	<b>R</b> )2	207
Contract Ref	f:			Start:	1.1	0.13	Grou	ınd L	evel (n	ı AO	D):	National Grid Co-ordinate	e:	Sheet:			
3	312	494		End:	1.1	0.13		(	63.04			E:447086.9 N:3	26841.6		3	of	4
		Sample	s & Test	ting	1	Mech	anical	Log	II & u- tion	er					Depth		ateria
Depth (m)	No	Туре	Res	sults	TCR (%)	SCR (%)	RQD (%)	If (mm)	Backfill Instru- mentation	Water		Description of	Strata		(Thick ness)		aphic egend
					100	63	47				plai	between 13.92m and 14. nar rough fracture with order sandy surface.	05m bgl, subvange brown st	rertical aining	(2.25)		
14.30-15.80	,					1					Me	dium strong to strong the strong the strong the strong to strong the strong t	n and red brov	ted to	[		

				(%)					
				100	63	47		between 13.92m and 14.05m bgl, subvertical planar rough fracture with orange brown staining	1
14.30-15.80				1	1	<b>A</b>		and sandy surface.  Medium strong to strong thickly laminated to	
								thinly bedded light grey brown and red brown fine grained SANDSTONE with occasional thick	
								laminations of mudstone and siltstone.	
								Discontinuities are subhorizontal undulating rough	
				100	89	67		and planar rough very closely to medium spaced (26/150/290) partly open to open with thin clay 15.25	
								(26/150/290) partly open to open with thin clay 15.25 smearing, occasional black speckling and rarely	
								micaceous.	
								(Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION)	
					<u> </u>	•		(stratum copied from 13.00m from previous sheet)	
15.80-17.30				1	↑	1		between 14.44m and 14.65m bgl,	
								subhorizontal undulating rough fracture with dark	
								grey staining.  Medium strong to strong very thinly to thinly	
								bedded light grey brown and red brown fine to	
				95	87	77		medium grained SANDSTONE with occasional	
					L	$\perp$		thickly interlaminated to thinly interbedded mudstone nd siltstone. Discontinuities are	
								mudstone nd siltstone. Discontinuities are subhorizontal undulating rough and planar rough	
							(∴ ∀ 🗄	extremely closely to medium spaced (12/170/300)	
							::::	partly open to open with thin clay smearing,	
7.30-18.80				<b> </b>	<b> </b>		:::  :	occasional black speckling and rarely micaceous.  (Weathering Grade I)	
							::: <u> </u>	(BROMSGROVE SANDSTONE FORMATION)	
							:∵ B:	between 15.32m and 15.40m bgl, coarse [	
							:::H	gravel sized vugs with partial calcite infill between 15.80m and 15.87m bgl, zone of core	
				100	68	45		loss.	
				100	08	43	::: <u> </u>	between 16.44m and 16.48m bgl, coarse	
								gravel sized vugs with partial and some complete calcite infill.	
							:::  :	between 17.57m and 17.64m bgl, firm	
								gravelly clay.	
3.80-20.30				-	I I	+ 🚶		at 18.16m bgl, 45mm clean cavity. between 18.80m and 18.94m bgl, zone of core	
5.00 20.50								loss.	
								_	
							:::H	-	
				91	36	0	:∷ :		
							::::	-	
							:::   :		
							:::: <u> </u>	[(9.75)	'
20.30-21.80				<u> </u>	T.	+ *		-	
20.30-21.80					l T	[	:::甘		
				100	65	37	:::::	between 20.50m and 20.53m bgl, medium to	
				100	05		∷⊹: }	coarse.	
Bo	ring F	rogress a	and Water C					Canaral Damaria	
Date T	ime	Boreho	_	I Dian	nole	Wat	er	General Remarks	
Dute 1		Dept	h Depth	(mı		Dep	h		
		1							
					- 1				
								W.F	
Method R		open ho	ole + Pla					Il dimensions in metres Scale: 1:39 Drilled Logged Checked	

₫.													
200		Boring Pr	ogress and	Water Ob	servations				$C_{\alpha}$	maral	Damarla		
centre, c	Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth			Ge		Remarks		
oeridia o				•		•							
,													
THE PERSON								. 11 1:			a 1	1.20	
Ě								All dimens	ions in metre	es	Scale:	1:39	 
00 TO	Method Used:						50-P1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:	AGS



Contract:				Client:		Boreho	le:		
East Midlands	Gate	eway		Roxhil	l Developments Ltd		CP	(R)	207
Contract Ref:	Start:	1.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	1.10.13		63.04	E:447086.9 N:326841.6		4	of	4

	112	1/1	Ena:		0.13			J.U4		E:44/000.9 IN:320041.0	4	oi <b>4</b>
		Samples	s & Testing		Mecha	anical	Log	% _ uo			Depth	Material
Depth (m)	No	_	Results	TCR (%)	SCR (%)	RQD (%)	If (mm)	Backfill & Instru-	Water	Description of Strata	(Thick ness)	
21.80-23.30				100	65	37				Medium strong to strong very thinly to thinly bedded light grey brown and red brown fine to medium grained SANDSTONE with occasional thickly interlaminated to thinly interbedded mudstone nd siltstone. Discontinuities are subhorizontal undulating rough and planar rough extremely closely to medium spaced (12/170/300) partly open to open with thin clay smearing, occasional black speckling and rarely micaceous. (Weathering Grade I) (BROMSGROVE SANDSTONE FORMATION) (stratum copied from 15.25m from previous sheet) between 21.03m and 21.30m bgl, subvertical undulating rough fracture.		
23.30-24.80				<u> </u>	V V	Y	_			between 22.47 and 22.51m bgl, soft gravelly clay between 22.79 and 22.82m bgl, soft gravelly clay.	- - - - - - - - -	
				100	87	58	-			at 24.53m bgl, 28mm vug with partial calcite infill.	25.00	
-											- - - - - - - -	
_											- - - - - -	
											-	

		Boring Pr	ogress and	Water O	bservations				Ca	noro1	Remarks		
,	Date	Time	Borehole	Casing	Borehole Diameter	Water			Ge	merai	Kemarks		
3	Dute	Time	Depth	Depth	(mm)	Depth							
1													
:													
							A	All dimensi	ions in metre	es	Scale:	1:39	
4	Method Used:					oobio MC4	50 D1	Drilled By:	LS/PC	Logged By:	LAlderman	Checked By:	<b>AGS</b>
3	Oscu.	Rotai	y Corea	US	a. Coma	ccino MC4	3U-F 1	Dy.	LS/FC	Dy.	LAiuerman	Dy.	HILD)



Contract:				Client:		Boreho	le:		
East Midlands	Gate	way		Roxhil	l Developments Ltd		CP	(R)	208
Contract Ref:	Start:	4.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:			
312494	End:	4.10.13		66.58	E:446834.8 N:326895.4		1	of	3

	3124	494	End:	4.10	0.13		66.58	•	E:446834.8 N:326895.4	1	of <b>3</b>
		Sampla	s & Testing		Macha	nical	Log & =				Matamial
Depth (m)	No		Results	TCR (%)	SCR	RQD		Water	Description of Strata	(Thick ness)	Material Graphic Legend
				(, ,,	(, ,	(, ,			Drillers Descriptions - Dark brown silty CLAY.	-	<u>x                                     </u>
E									Difficis Descriptions Bark brown sitty CE111.	0.40	×
t									Drillers Descriptions - Red brown silty CLAY.	0.40	$\frac{\times}{\times}$
ŀ									Dimers Descriptions - Red brown sitty CEATT.	(0.00)	×
										(0.80)	<u>×x</u>
F										F	
F									D.II. D. D. L. L. D. L. L. MUDCTONE	1.20	
F									Drillers Descriptions - Red brown MUDSTONE.	-	
F										(1.00)	
F										F` ′	
F										F	
F									D.II. D	2.20	
-									Drillers Descriptions - Grey MUDSTONE.	2.50	
F									Drillers Descriptions - Red brown MUDSTONE.		
ļ.									1	-	
F										(1.00)	
-										-	
-										3.50	
3.50-5.00				<b>A</b>	<b>—</b>	<b>—</b>			Firm red brown and light grey silty slightly sandy	3.60	
ļ									CLAY. Recovery includes subangular to	-	
F									subrounded fine to coarse mudstone lithorelicts. (TARPORLEY SILTSTONE FORMATION)	4.00	
-				100	60	21			Medium strong to strong light grey brown	(0.65)	
ţ					1	l			SANDSTONE.	1.05	
ļ.									(TARPORLEY SILTSTONE FORMATION) between 3.82m and 3.89m bgl, occasional	4.65	
·					J	↓			medium to coarse gravel sized vugs, some with	-	
5.00-6.50				<b>—</b>	$\rightarrow$		:::		partial calcite infill.	-	
ļ.									Recovered as red brown angular blocks/coarse	-	
ļ									gravel with small amount of clay along fractures. (Weathering Grade II)	-	
				100	0.4	4.7			(TARPORLEY SILTSTONE FORMATION)	-	
				100	84	47			between 4.06 and 4.35m bgl, stepped rough	-	
F									subvertical fracture with dark brown staining.	-	
-									Weak to medium strong thickly laminated to thinly	(3.43)	
6.50.000				<u> </u>	+	<u> </u>			interbedded red brown and light grey MUDSTONE and siltstone, with some very thinly	F	
6.50-8.00				1	1	<b>1</b>			to thinly interbedded red brown and light grey	F	
F									brown fine to medium grained sandstone.	-	
F									Discontinuities are subhorizontal undulating rough	F	
: [				100	87	38			and planar rough extremely closely to medium spaced (18/100/270) tight to open with thin clay	-	
7.40-7.59	1	CS			1				smearing, occasional black speckling and grey	-	
. [									staining and occasionally micaceous.	-	
ļ.						↓			(TARPORLEY SILTSTONE FORMATION)	<b>F</b>	
8.00-9.50				<b>—</b>	<b>—</b>	1	1 <b> </b>		between 4.95m and 5.20m bgl, strong light grey brown fine to medium grained sandstone.	- 8.08	
									between 5.04m and 5.07m bgl, with medium	-	
ļ.				98	89	26			to coarse gravel sized vugs with partial calcite	(1.12)	
` <b> </b>				98	09	_∠0			infill.	(1.12)	
ļ									between 5.20m and 5.60m bgl, clayey gravel.	‡	

Boring Progress and Water Observations														
Date	Time	Borehole	Casing	Borehole Diameter	Water									
Date	Tillic	Depth	Depth	(mm)	Depth									
04/10/13	08:00	3.50	3.50	121	-									
04/10/13	17:00	20.00	3.50	121	-									

Plant

Used:

Comacchio MC450-

Rotary open hole + Rotary Cored

Method

Used:

## General Remarks

Location scanned with GPR and CAT and signal generator prior to breaking ground. Hand dug service pit 10 1.20m bgl. No services encountered.
 Rotary open holed to 3.50m bgl.
 Borehole advanced to 20.00m bgl using coring techniques.
 Gas and groundwater monitoring well installed to 20.00m bgl.

- 5. No groundwater stikes noted.

A	All dimensi	ons in metre	Scale:	1:50	
P1	Drilled By:	SC/JO	Logged By:	LAlderman	Checked By:





Contract:				Client:	Client:						
East Midlands	Gate	eway		Roxhil	<b>Roxhill Developments Ltd</b>						
Contract Ref:	Start:	4.10.13	Groun	d Level (m AOD):	National Grid Co-ordinate:	Sheet:					
312494	End:	4.10.13		66.58	E:446834.8 N:326895.4		2	of	3		

3	3124	494	End:	4.10	0.13		66.58		E:446834.8 N:326895.4	2	of <b>3</b>
		Sample	s & Testing	N	Mecha	nical	Log 💐 🚊 .			Depth	Material
Depth (m)	No		Results	TCR (%)	SCR	RQD		w alc	Description of Strata	(Thick ness)	
				98	89	26		П.	. between 5.31m and 5.37m bgl, clayey gravel . between 5.53m and 5.56m bgl, medium	to 9.20	
9.50-11.00				*	<del>- X</del> -	<b>X</b>		to	parse gravel sized vugs with partial calcite infill between 6.55m and 6.60m bgl, medium stro strong light grey brown fine to medium grain	ng∥[	
9.98-10.15	2	CS		97	90	40		su	ndstone band between 6.64m and 6.90m bgl, stepped rou lbvertical fracture.	~   }	
-						40		lo	between 8.00m and 8.03m bgl, zone of coss at 8.27m bgl, 34mm vug with partial calc	ite  -	
11.00-12.50				<b>X</b>	*	<b>X</b>		M	fill. ledium strong to very strong thickly laminated inly bedded light grey brown and red brown fi	to   -	
11.22-11.42	3	CS						to	medium grained SANDSTONE with occasion edium to coarse gravel sized vugs with part licite infill with occasional thickly interlaminat	ial  - ial  -	
-				100	87 	35		to D	thinly interbedded mudstone and siltstor iscontinuities are subhorizontal undulating rou ad planar rough very closely to medium space	ne.	
				<u> </u>	_ <u>_</u>	<u> </u>		(4	8/100/270) tight to moderately wide with the ay smearing, occasional black speckling a seassionally micaceous.	in [	
12.50-14.00								(E	BROMSGŘOVE SANDSTONE FORMATION tratum copied from 8.08m from previous sheet,	Ĺ⊪F	
- - - - -				100	87 	76 		M in	ledium strong to strong thickly interlaminated bry thinly interbedded red brown and light gray thinly interbedded red brown and light gray. IUDSTONE and siltstone with occasional thick terlaminated to very thinly interbedded light gray.	ey   t ly   t ey   t	
14.00-15.50				<b>X</b>	<del> </del>	X		Dan	own and red brown fine grained sandstoriscontinuities are subhorizontal undulating round planer rough very closely to medium space 6/80/170) partly open to open with thin cl	gh   [ ed   -	
14.15-14.35	4	CS						sn	nearing, occasional orange brown stained a ack speckling and occassionally micaceous. Veathering Grade I)	nd E	
- - -				100	82	47		(E	BROMSGROVE SANDSTONE FORMATION between 9.50m and 9.55m bgl, zone of coss.		
15.50-17.00				<u> </u>	<del>-</del>	<b>X</b>		ve	dedium strong to strong thickly interlaminated by thinly interbedded light green grey fi ained SANDSTONE and red brown and light	ne  [	
-								gr	ey siltstone and mudstone. Discontinuities a abhorizontal undulating rough and planar rou ery closely to medium spaced (25/100/20	gh	
- - - -				90	73	29		pa sn	artly open to moderately open with thin cl nearing, micaceous and with occasional bla beckling and orange brown staining.	ay  [(7.43)	
17.00-18.50				<b>X</b>	+	<b> </b>		(È	BROMŠGROVE ŠANDSTONE FORMATION  between 11.46m and 11.48m bgl, clay avel.	ey -	
-				150	94	45		gr D	between 11.70m and 11.74m bgl, clay avel.  eser horror in heart spring 13.71m bgl, medium	to	
-								co	oarse gravel sized vugs with partial calcite infill escription on next sheet	. [- -	

	Boring P	rogress and	Water Ob	servations		General Remarks							
Date	Time	Borehole Depth	Casing Depth	Borehole Diameter (mm)	Water Depth				ilerai	Kemarks			
	D Option		Бериг	(11111)	Бериі								
Ī													
							All dimens	ions in metre	es	Scale:	1:50		
Method Used:	Rotary	open hole +	- Plan		echio MC4	50_P1	Drilled By:	SC/IO	Logged By:	LAlderman	Checked By:		AGS



Contract:					Client:		Borehole:				
E	ast Midlands	Gate	way		Ro	xhil		CP(	$(\mathbf{R})^2$	208	
Contract Ref:		Start:	4.10.13	Ground	d Level (m AO	D):	National Grid Co-ordinate:	Sheet:			
3	12494	End:	4.10.13		66.58		E:446834.8 N:326895.4		3	of	3
	a 1 0 m				N _						

	114	· / · _	Elia.	7.1	0.13		00.50			L. 110051.0 11.520075.1		01 5
Depth				Mechanical Log SCR RQD If SCR RQD (mm) Bustin Busti				nstru- ntation	Water	Description of Strata	(Thick	Material Graphic
(m)	No	Type	Results	150		45	(mm)	am	^	between 15.04m and 15.11m bgl, coarse gravel sized vugs with partial calcite infill between 15.50m and 15.65m bgl, zone of core loss between 16.00m and 16.25m bgl, undulating rough subvertical fracture.	ness)	Legend
19.10-19.30	5	CS		98	83	23				between 16.48m and 16.50m bgl, firm gravelly clay between 16.77m and 16.78m bgl, clayey gravel.	- - - -	
-				•		•				occasional medium to coarse gravel sized vugs with partial calcite infill.  Medium strong to very strong thickly laminated to thinly bedded light grey brown and red brown fine to medium grained SANDSTONE, with occasional thickly interlaminated and very thinly interbedded	20.00	
										mudstone and siltstone. Discontinuities are subhorizontal undulating rough and planar rough very closely to medium spaced (26/150/300) partly open to moderately open with thin clay smearing. (BROMSGROVE SANDSTONE FORMATION) (stratum copied from 12.55m from previous sheet)  between 19.80m and 19.86m bgl, clayey	- - - - - - -	
										Rotary probehole terminated at 20.00m depth.	- - - - - - -	
-												
-											- - - - - -	
-											- - - - - - -	
-											- - - - -	
- - - - - - -												

	Boring P	rogress and	Water Ob	servations				Ca	noro1	Remarks		
Date	Time	Borehole	Casing	Borehole Diameter	Water			Ge	merai	Kemarks		
Bute	Time	Depth	Depth	(mm)	Depth							
<u> </u>												
i												
:												
3												
						A	All dimensi	ions in metre	es	Scale:	1:50	
Method		Rotary open hole + Rotary Cored		Plant Used: Comacchio MC45			Drilled	00/10	Logged	* ***	Checked	<b>AGS</b>
Used:	Rota						By:	SC/JO	By:	LAlderman	By:	AGS



# APPENDIX E ROTARY CORED BOREHOLE PHOTOGRAPHS

Zone:

1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

5.50 - 7.00m



## Zone:

1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

7.00 - 8.50m











1

Borehole number:


CP(R)203

Date drilled:

02/10/13

Depth range:

11.50 – 13.00m



## Zone:

1

Borehole number:


CP(R)203

Date drilled:

02/10/13

Depth range:

13.00 – 14.50m





1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

14.50 -16.00m



## Zone:

1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

16.00 -17.50m





1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

17.50 – 19.00m



#### Zone:

1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

19.00 – 20.50m





1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

20.50 – 22.00m



## Zone:

1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

22.00 – 23.50m





1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

23.50 – 25.00m



## Zone:

1

Borehole number:


CP(R)203

Date drilled:

02/10/13

Depth range:

25.00 – 26.50m





1

Borehole number:

CP(R)203

Date drilled:

02/10/13

Depth range:

26.50 – 28.00m



## Zone:

1

Borehole number:

CP(R)203

Date drilled:

03/10/13

Depth range:

28.00 – 29.50m





1

Borehole number:

CP(R)203

Date drilled:

03/10/13

Depth range:

29.50 – 30.00m



# Zone:

1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

3.50 - 5.00m





1

Borehole number:


CP(R)204

Date drilled:

03/10/13

Depth range:

5.00 - 6.50m



# Zone:

1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

6.50 - 8.00m





1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

8.00 - 9.50m



# Zone:

1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

9.50 - 11.00m





1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

11.00 – 12.50m



# Zone:

1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

12.50 – 14.00m





1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

14.00 – 15.50m CONTRACT: EAST MIDLANDS GATEWAY
CONTRACT NO 312494
BORE HOLE NO: 1204 CORE BOX NO: 8
DEPTH - FROM: 114-100 TO: 115-50

# Zone:

1

Borehole number:

CP(R)204

Date drilled:

03/10/13

Depth range:

15.50 – 17.00m











1

Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

4.50 - 6.00m



# Zone:

1

# Borehole number:


CP(R)205

Date drilled:

03/10/13

#### Depth range:

6.00 - 7.50m





1

Borehole number:


CP(R)205

Date drilled:

03/10/13

Depth range:

7.50 – 9.00m



# Zone:

1

# Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

9.00 - 10.50m





1

Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

10.50 – 12.00m



# Zone:

1

Borehole number:

CP(R)205

Date drilled:


03/10/13

Depth range:

12.00 – 13.50m











1

Borehole number:


CP(R)205

Date drilled:

03/10/13

Depth range:

16.50 – 18.00m



# Zone:

1

# Borehole number:

CP(R)205

#### Date drilled:

03/10/13

#### Depth range:

18.00 – 19.50m





1

Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

19.50 – 21.00m



# Zone:

1

# Borehole number:

CP(R)205

Date drilled:

03/10/13

#### Depth range:

21.00 – 22.50m





1

Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

22.50 – 24.00m



# Zone:

1

# Borehole number:

CP(R)205

Date drilled:

03/10/13

# Depth range:

24.00 – 25.50m





1

Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

25.50 – 27.00m



#### Zone:

1

Borehole number:

CP(R)205

Date drilled:

03/10/13

Depth range:

27.00 – 28.50m





1

Borehole number:

CP(R)205

Date drilled:

04/10/13

Depth range:

28.50 – 30.00m



# Zone:

1

# Borehole number:


CP(R)206

Date drilled:

04/10/13

#### Depth range:

4.00 - 5.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

5.50 - 7.00m



# Zone:

1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

7.00 – 8.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

8.50 - 10.00m



Zone:

1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

10.00 – 11.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

11.50 – 13.00m



# Zone:

1

Borehole number:


CP(R)206

Date drilled:

04/10/13

Depth range:

13.00 – 14.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

14.50 -

16.00m



# Zone:

1

#### **Borehole** number:

CP(R)206

Date drilled:

04/10/13

#### Depth range:

16.00 -17.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

17.50 – 19.00m



# Zone:

1

# Borehole number:

CP(R)206

Date drilled:

04/10/13

#### Depth range:

19.00 – 20.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

20.50 – 22.00m



# Zone:

1

# Borehole number:

CP(R)206

Date drilled:

04/10/13

#### Depth range:

22.00 – 23.50m





1

Borehole number:

CP(R)206

Date drilled:

04/10/13

Depth range:

23.50 – 25.00m



# Zone:

1

Borehole number:


CP(R)207

Date drilled:

01/10/13

Depth range:

2.30 - 3.80m





1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

3.80 - 5.30m



# Zone:

1

# Borehole number:

CP(R)207

Date drilled:

01/10/13

#### Depth range:

5.30 - 6.80m





1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

6.80 - 8.30m



# Zone:

1

# Borehole number:


CP(R)207

Date drilled:

01/10/13

#### Depth range:

8.30 - 9.80m





1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

9.80 - 11.30m



Zone:

1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

11.30 – 12.80m





1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

12.80 – 14.30m



# Zone:

1

Borehole number:


CP(R)207

Date drilled:

01/10/13

Depth range:

14.30 – 15.80m











1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

18.80 – 20.30m



#### Zone:

1

Borehole number:


CP(R)207

Date drilled:

01/10/13

Depth range:

20.30 – 21.80m





1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

21.80 – 23.30m



# Zone:

1

Borehole number:

CP(R)207

Date drilled:

01/10/13

Depth range:

23.30 – 24.80m





1

Borehole number:

CP(R)208

Date drilled:

04/10/13

Depth range:

3.50 - 5.00m



# Zone:

1

Borehole number:

CP(R)208

Date drilled:

04/10/13

Depth range:

5.00 - 6.50m





1

Borehole number:


CP(R)208

Date drilled:

04/10/13

Depth range:

6.50 - 8.00m



# Zone:

1

# Borehole number:


CP(R)208

Date drilled:

04/10/13

#### Depth range:

8.00 - 9.50m





1

Borehole number:

CP(R)208

Date drilled:

04/10/13

Depth range:

9.50 - 11.00m



# Zone:

1

# Borehole number:

CP(R)208

#### Date drilled:

04/10/13

#### Depth range:

11.00 – 12.50m





1

Borehole number:

CP(R)208

Date drilled:

04/10/13

Depth range:

12.50 – 14.00m



#### Zone:

1

Borehole

number:

CP(R)208

Date drilled:

04/10/13

Depth range:

14.00 – 15.50m





1

Borehole number:

CP(R)208

Date drilled:

04/10/13

Depth range:

15.50 – 17.00m



# Zone:

1

# Borehole number:

CP(R)208

#### Date drilled:

04/10/13

#### Depth range:

17.00 – 20.00m





# APPENDIX F IN-SITU SOAKAWAY TEST RESULTS



# STRUCTURAL SOILS LTD

INSITU TESTING REPORT						
Report No.	744139R.01(02)					
Date	-November-2013	Contract	Field Farm,	Lockington		
Client Address	RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ					
For the Atter	ntion of Gareth Sl	naw				
Order received Testing Started Testing Completed		18-September 01-October-20 11-October-20	013	Client Reference Client Order No. Instruction Type	None P0235653 Written	
	oakaway tests carried out at a	locations specifie	d by client.			
Environment	tal conditions (if relevant)					

The results represent the ground conditions at the specified locations and depths at the time of testing.

Please Note: Remaining samples will be retained for a period of one month from today and will then be disposed of .

Test were undertaken on samples 'as received' unless otherwise stated.

Opinions and interpretations expressed in this report are outside the scope of accreditation for this laboratory.

Page 1 of 8

Structural Soils Ltd 1a Princess Street Bedminster Bristol BS3 4AG


# J002 | Graph I - TP SOAKAWAY - 2 - FINAL REPORT | 744139 GP! - v8 05 | 6 . . ./13 - 11:25 | MS (FINT LIBRARY V8 05 GLB LibVersion: v8 05 - Lib0003 PrjVersion: v8 05 - Core+In Situ Test.

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP301

### PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME





STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol

BS3 4AG

atories. D. Inc white of Introduction					
Compiled By	Date	Checked By	Date		
	07/10/13		5/10/13		
Contract:		Contract Ref:			
Field Farm, Lockin	744139				

# J002 | Graph 1 - TP SOAKAWAY - 2 - FINAL REPORT | 744139 GPJ - v8\_05 | 6 13 - 11:28


# GINT LIBRARY V8 05 GLB LibVersion: v8 05 - Lib0003 PrjVersion: v8 05 - Core+In Situ Testi

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP302

### PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

Date

07/10/13

Contract:

Field Farm, Lockington

Contract Ref:

744139


# J002 | Graph | - TP SOAKAWAY - 2 - FINAL REPORT | 744139 GPJ - v8 05 | 6 - J13 - 11:30 | MS (JINT LIBRARY V8 05 GLB LibVersion: v8 05 - Lib0003 PrjVersion: v8 05 - Core+In Situ Testi

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP303

### PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME





## STRUCTURAL SOILS 1a Princess Street Bedminster Bristol

BS3 4AG

Compiled By	Date	Checked By	Date
	07/10/13		15/10/1
		Contract Ref:	
Field Farm, Locki	ngton	744139	


MS

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP304

# PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME





STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By	Date	Checked By	Date	
	07/10/13		15/10/13	
Contract:		Contract Ref:		
Field Farm, Lockington		744139		


# J002 | Graph I - TP SOAKAWAY - 2 - FINAL REPORT | 744139 GPJ - v8\_05 | C 13 - 11:33

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP305

### PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME



STRUG la I

STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol

**BS3 4AG** 


y Date
15/10/13
-
139
4

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP351

## PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME





# STRUCTURAL SOILS 1a Princess Street Bedminster

Bedminster
Bristol
BS3 4AG

atories. D. TROWBRIDGE	TITINING OIL III	0.01120	
Compiled By	Date	Checked By	Date
	07/10/13		15/10/13
		Contract Ref:	
Field Farm, Lockington		744139	

"13 - 11:40 | MS

J002 | Graph | - TP SOAKAWAY - 2 - FINAL REPORT | 744139 GPJ - v8\_05 | 0,


(iINT LIBRARY V8 05 GLB LibVersion: v8 05 - Lib0003 PrjVersion: v8\_05 - Core+In Situ Testi,

# **FULL SCALE SOAKAWAY TEST**

Non standard test

Soakaway Test - Position ID: TP352

### PLOT OF DEPTH OF WATER BELOW GROUND LEVEL AGAINST TIME



STRUCTURAL SOILS 1a Princess Street **Bedminster Bristol BS3 4AG** 

calculate infiltration rate.

Approved Signatories: D. TROWBRIDGE A. FROST F. HAMILTON M. STOKES Compiled By Date 07/10/13

Contract: Field Farm, Lockington Checked By Date

15/0/13 Contract Ref:



# APPENDIX G GEOTECHNICAL LABORATORY TESTING RESULTS



### STRUCTURAL SOILS LTD

### **TEST REPORT**



Report No. 744186R.01(00) 1774

Date 20-November-2013 Contract East Midlands Gateway - Zone 1

Client RSK Environment Address Abbey Park

> Humber Road Coventry CV3 4AQ

For the Attention of Darren Bench

Samples submitted by client	16-October-2013	Client Reference	312494
Testing Started	18-October-2013	Client Order No.	None
Testing Completed	14-November-2013	Instruction Type	Written

Tests marked 'Not UKAS Accredited' in this report are not included in the UKAS Accreditation Schedule for our Laboratory.

### **UKAS** Accredited Tests

1.01	Moisture Content (oven drying method) BS1377:Part 2:1990:clause 3.2
1.03	Liquid Limit (one point method ) & Plastic Limit BS1377:Part 2:1990,clause 4.4/5.3
1.08	Density linear measurement method BS1377:Part 2:1990, clause 7.2
1.10	Particle Size Distribution wet sieve method BS1377:Part 2:1990,clause 9.2
3.02	Dry density/moisture content relationship 4.5kg rammer method BS1377:Part 4:1990
	clause 3.5
3.04	Dry density/moisture content relationship 4.5kg rammer method BS1377:Part 4:1990
	clause 3.6
3.10	California Bearing Ratio BS1377:Part 4:1990,clause 7.4
3.06	Moisture condition value natural moisture content BS1377:Part 4:1990,clause 5.4
3.07	Moisture condition value/moisture content relationship BS1377:Part 4:1990,clause 5.5
5.05	Undrained shear strength triaxial compression without pore pressure measurement
	(multistage loading) BS1377:Part 7:1990,clause 9.4
10.06	Point Load Index ISRM:1985

### Not UKAS Acredited Tests

1.13	Particle Size Distribution sedimentation hydrometer method BS1377:Part 2:
	1990, clause 9.5
4.01	One-dimensional consolidation BS1377:Part 5:1990,clause 3.5
	Hand Vane

Page 1 of 55

Structural Soils Ltd 1a Princess Street Bedminster Bristol BS3 4AG



## STRUCTURAL SOILS LTD



Report No. 744186R.01(00) 1774

Testing carried out by an external laboratory - Envirolab

2.06	Sulphate content (acid extract) in accordance with BRE Special Digest 1:2005
2.04	Sulphate content (water extract) in accordance with BRE Special Digest 1:2005
2.07	pH value in accordance with BRE Special Digest 1:2005
2.05	Total sulphur in accordance with BRE Special Digest 1:2005

Please Note: Remaining samples will be retained for a period of one month from today and will then be disposed of .

Test were undertaken on samples 'as received' unless otherwise stated.

Opinions and interpretations expressed in this report are outside the scope of accreditation for this laboratory.

Page 1 of 55

Structural Soils Ltd 1a Princess Street Bedminster Bristol BS3 4AG

# GINT\_LIBRARY Vg\_05.GLB LibVersion: v8 05 - Lib0002 PifVersion: v8 05 - Core+Logs+Geotech Lab-Bristol - 0004 | GrfcText L - LAB VERIFICATION REPORT | 744186.GPJ - v8 05 | 16/11/13 - 09:03 | JB. Structural Soils Ltd, Branch Office - Bristol Lab. Famil: ask@soils.co.uk, Email: ask@soils.co.uk.

# TESTING VERIFICATION CERTIFICATE



1774

The test results included in this report are certified as:-

ISSUE STATUS: FINAL

In accordance with Structural Soils Ltd Laboratory Quality Assurance Manual, Issue 6, January 2010 all results sheets and summaries of results issued by the laboratory are checked by an approved signatory. This check will also involve checking of at least 10% of calculations for each test type to ensure that data has been correctly entered into the computer and calculated. The integrity of the test data and results are ensured by control of the computer system employed by the laboratory as part of the Software Verification Program as detailed in the Laboratory Quality Assurance Manual.

This testing verification certificate covers all testing compiled on or before the following datetime: 16/11/2013 09:01:43.

Testing reported after this date is not covered by this Verification Certificate.



Approved Signatory **Justin Barrett (Laboratory Manager)** 



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Contract:

East Midlands Gateway - Zone 1

Job No:



# GINT\_LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PifVersion: v8 05 - Core+Logs+Geotech Lab-Bristol - 0004 | GrfcTbl L - SUMMARY OF STANDALONE MC - A4P | 744186.GPJ - v8 05 | 15/11/13 - 06:32 | AF. Structural Soils Lid, Branch Office - Bristol Lab Fincess Street, Bedminster, Bristol, BS3 4AG. Tel: 0117-947-1000, Fax: 0117-947-1004, Web: www.soils.co.uk, Email: ask@soils.co.uk.

# SUMMARY OF MOISTURE CONTENT TESTS In accordance with clause 3.2 of BS1377:Part 2

Exploratory Position ID	Sample Ref	Depth (m)	Sample Type	Moisture Content (%)
CP203	8	2.20	DSPT	14
CP203	11	3.00	DSPT	12
CP203	12	3.70	D	15
CP204	4	1.20	DSPT	14
CP204	10	3.00	DSPT	12
CP204	13	4.00	DSPT	15
CP205	4	1.20	DSPT	13
CP205	7	2.20	DSPT	14
CP205	9	3.00	DSPT	13
CP205	12	3.80	DSPT	10
CP206	5	2.00	D	23
CP206	8	3.00	D	12
CP210		2.00	D	17
CP210	12	4.00	D	14
CP210		6.00	D	12
CP210	5	8.00	D	14
CP210	24	9.00	D	13
CP211	6	2.00	D	15
CP211	12	4.00	D	13
CP211	18	6.00	D	11
CP211	11	7.00	D	12
CP221	12	4.20	DSPT	32
CP221	14	5.00	DSPT	26
CP222	7	2.20	DSPT	9.4
CP222	12	4.00	DSPT	35


Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



Compiled By			
ALAN FROST			
Contract:		Contract Ref:	

**East Midlands Gateway - Zone 1** 

PLASTICITY CHART - PI Vs LL
In accordance with clause 42.3 of BS5930:1999
Testing in accordance with BS1377-2:1990



	Sample I	dentificat	ion	BS Test	Preparation	MC	LL	PL	PI	<425um	
	Exploratory Position ID	Sample	Depth (m)	Method #	Method +	%	%	%	%	%	
	CP203	5U	1.27	3.2/4.4/5.3/5.4	4.2.3	13	24	17	7	100	
	CP204	7U	2.20	3.2/4.4/5.3/5.4	4.2.3	15	31	16	15	100	
	CP210	3U	1.57	3.2/4.4/5.3/5.4	4.2.3	17	39	17	22	92	
*	CP210	9U	3.06	3.2/4.4/5.3/5.4	4.2.3	19	34	17	17	74	
0	CP210	14U	5.00	3.2/4.4/5.3/5.4	4.2.3	12	31	16	15	69	
0	CP221	9U	3.35	3.2/4.4/5.3/5.4	4.2.3	40	61	26	35	100	
0	CP222	9U	3.42	3.2/4.4/5.3/5.4	4.2.3	32	35	26	9	98	
Δ	TP301	В	0.70	3.2/4.4/5.3/5.4	4.2.3	23	25	15	10	93	
8	TP302	В	1.60	3.2/4.4/5.3/5.4	4.2.4	14	29	15	14	23	
$\oplus$	TP321	В	2.70	3.2/4.4/5.3/5.4	4.2.4	12	31	18	13	17	
	TP322	1LB	2.20	3.2/4.4/5.3/5.4	4.2.4	14	27	16	11	73	
8	TP324	1LB	2.00	3.2/4.4/5.3/5.4	4.2.3	16	32	18	14	78	
•	TP326	1LB	1.50	3.2/4.4/5.3/5.4	4.2.3	15	24	15	9	100	

# Tested in accordance with the following clauses of BS1377-2:1990.

- Moisture Content
- 4.3 Cone Penetrometer Method 4.4 One Point Cone Penetrometer Method
- 4.6 One Point Casagrande Method
- 5.3 Plastic Limit Method 5.4 Plasticity Index

+ Tested in accordance with the following clauses of BS1377-2:1990.

4.2.3 - Natural State 4.2.4 - Wet Sieved

Key: \* = Non standard test, NP = Non plastic.

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol** BS3 4AG


Compi	led By		Date
		ALAN FROST	15/11/13
Contract	C	ontract Ref:	,

East Midlands Gateway - Zone 1



# GINT\_LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PjVersion: v8 05 - Coret-Logs+Geotech Lab-Bristol - 0004 | Graph L - ALINE STANDARD - EC7 | 744186.GPJ - v8 05 | 15/11/13 - 06:34 | AF. Structural Soils Ltd, Branch Office - Bristol Lab: 1a Princess Street, Bedminster, Bristol, BS3 4AG. Tel: 0117-947-1000, Fax: 0117-947-1004, Web: www.soils.co.uk, Email: ask@soils.co.uk.

PLASTICITY CHART - PI Vs LL
In accordance with clause 42.3 of BS5930:1999
Testing in accordance with BS1377-2:1990



	Sample I	dentificat	ion	BS Test	Preparation	MC	LL	PL	PI	<425um	
	Exploratory Position ID	Sample	Depth (m)	Method #	Preparation Method +	%	%	%	%	%	
•	TP327	1LB	1.20	3.2/4.4/5.3/5.4	4.2.4	23	36	21	15	77	
	TP328	1LB	2.10	3.2/4.4/5.3/5.4	4.2.3	14	30	19	11	62	

# Tested in accordance with the following clauses of BS1377-2:1990.

- Moisture Content
- 4.3 Cone Penetrometer Method 4.4 One Point Cone Penetrometer Method
- 4.6 One Point Casagrande Method
- 5.3 Plastic Limit Method 5.4 Plasticity Index

+ Tested in accordance with the following clauses of BS1377-2:1990.

4.2.3 - Natural State 4.2.4 - Wet Sieved

Key: \* = Non standard test, NP = Non plastic.

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol** BS3 4AG

Compiled By Date ALAN FROST 15/11/13 Contract Ref:

East Midlands Gateway - Zone 1



# GINT\_LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PjVersion: v8 05 - Core+Logs+Geotech Lab-Bristol - 0004 | Grêc'Tbl L. SUMMARY OF DENSITY - A4P | 744186.GPJ - v8 05 | 15/11/13 - 06.34 | AF. Structural Soils Lid, Branch Office - Bristol Lab. 1a Princess Street, Bedminster, Bristol, BS3 4AG. Tel: 0117-947-1000, Fax: 0117-947-1004, Web: www.soils.co.uk, Email: ask@soils.co.uk.

# **SUMMARY OF DENSITY TESTS**

In accordance with clause 7.2 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Depth (m)	Sample Type	Moisture Content (%)	Bulk Density (Mg/m³)	Dry Density (Mg/m³)
CP204	7	2.20	U	15	2.08	1.81

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK

STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

Date

ALAN FROST 15/11/13

ontract: Contract Ref:

East Midlands Gateway - Zone 1

In accordance with clauses 3.2,4.3,4.4,5.3,5.4,7.2,8.2,8.3 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content %	Bulk Density Mg/m³	Dry Density Mg/m <sup>3</sup>	Liquid Limit %	Plastic Limit %	Plasticity Index %	% <425um	MCV (%)	% retained on 20 mm sieve	Description of Sample
CP203	5	U	1.27	13			24	17	7	100			Brown slightly sandy silty CLAY
CP203	8	DSPT	2.20	14									Reddish brown slightly sandy CLAY
CP203	11	DSPT	3.00	12									Reddish brown slightly gravelly CLAY
CP203	12	D	3.70	15									Reddish brown CLAY
CP204	4	DSPT	1.20	14									Reddish brown mottled greenish grey CLAY
CP204	7	U	2.20	15	2.08	1.81	31	16	15	100			Reddish brown slightly sandy CLAY
CP204	10	DSPT	3.00	12									Reddish brown mottled greenish grey slightly sandy CLAY
CP204	13	DSPT	4.00	15									Reddish brown slightly sandy CLAY

STRUCTURAL SOILS LTD

Contract: Contract Ref:

**East Midlands Gateway - Zone 1** 



In accordance with clauses 3.2,4.3,4.4,5.3,5.4,7.2,8.2,8.3 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content %	Bulk Density Mg/m³	Dry Density Mg/m <sup>3</sup>	Liquid Limit %	Plastic Limit %	Plasticity Index %	% <425um	MCV (%)	% retained on 20 mm sieve	Description of Sample
CP205	4	DSPT	1.20	13									Reddish brown mottled greenish grey CLAY
CP205	7	DSPT	2.20	14									Reddish brown mottled greenish grey CLAY
CP205	9	DSPT	3.00	13									Reddish brown mottled greenish grey CLAY
CP205	12	DSPT	3.80	10									Greenish grey mottled reddish brown slightly gravelly slightly sandy
													CLAY
CP206	5	D	2.00	23									Reddish brown slightly sandy CLAY
CP206	8	D	3.00	12									Greenish grey mottled reddish brown CLAY
CP207	4	DSPT	1.20	15									Brown mottled grey CLAY
CP207	7	DSPT	2.10	12									Brown CLAY



Contract: Contract Ref:

East Midlands Gateway - Zone 1



In accordance with clauses 3.2,4.3,4.4,5.3,5.4,7.2,8.2,8.3 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content %	Bulk Density Mg/m³	Dry Density Mg/m³	Liquid Limit %	Plastic Limit %	Plasticity Index %	% <425um	MCV (%)	% retained on 20 mm sieve	Description of Sample
CP207	9	DSPT	2.70	12									Brown CLAY
CP210	3	U	1.57	17			39	17	22	92			Reddish brown mottled grey slightly gravelly CLAY
CP210		D	2.00	17									Reddish brown slightly sandy CLAY
CP210	9	U	3.06	19			34	17	17	74			Brown slightly sandy slightly gravelly CLAY
CP210	12	D	4.00	14									Reddish brown CLAY
CP210	14	U	5.00	12			31	16	15	69			Brown slightly sandy slightly gravelly CLAY
CP210		D	6.00	12									Reddish brown CLAY
CP210	5	D	8.00	14									Reddish brown slightly sandy CLAY



Contract: Contract Ref:

East Midlands Gateway - Zone 1



In accordance with clauses 3.2,4.3,4.4,5.3,5.4,7.2,8.2,8.3 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content %	Bulk Density Mg/m³	Dry Density Mg/m <sup>3</sup>	Liquid Limit %	Plastic Limit %	Plasticity Index %	% <425um	MCV (%)	% retained on 20 mm sieve	Description of Sample
CP210	24	D	9.00	13									Reddish brown CLAY
CP211	6	D	2.00	15									Reddish brown CLAY
CP211	12	D	4.00	13									Reddish brown slightly sandy CLAY
CP211	18	D	6.00	11									Reddish brown mottled greenish grey CLAY
CP211	11	D	7.00	12									Reddish brown CLAY
CP221	9	U	3.35	40			61	26	35	100			Reddish brown slightly sandy CLAY
CP221	12	DSPT	4.20	32									Reddish brown CLAY
CP221	14	DSPT	5.00	26									Reddish brown CLAY

_	
	STRUCTURAL SOILS LTD

Contract: Contract Ref:

**East Midlands Gateway - Zone 1** 



In accordance with clauses 3.2,4.3,4.4,5.3,5.4,7.2,8.2,8.3 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content %	Bulk Density Mg/m³	Dry Density Mg/m³	Liquid Limit %	Plastic Limit %	Plasticity Index %	% <425um	MCV (%)	% retained on 20 mm sieve	Description of Sample
CP222	7	DSPT	2.20	9.4									Reddish brown mottled greenish grey silty sandy GRAVEL
CP222	9	U	3.42	32			35	26	9	98			Brown slightly gravelly slightly sandy SILT
CP222	12	DSPT	4.00	35									Reddish brown CLAY
TP301		В	0.70	23			25	15	10	93			Reddish brown slightly gravelly slightly sandy silty CLAY
TP302		В	1.60	14			29	15	14	23			Brown slightly gravelly slightly sandy silty CLAY with high cobble
													content
TP321		В	2.70	12			31	18	13	17			Brown slightly sandy slightly silty very gravelly COBBLES
TP322	1	LB	2.20	14			27	16	11	73	9.8	59	Brown mottled grey slightly sandy gravelly CLAY
TP324	1	LB	2.00	16			32	18	14	78	9.9	0	Brown slightly gravelly slightly sandy silty CLAY



Contract: Contract Ref:

East Midlands Gateway - Zone 1



In accordance with clauses 3.2,4.3,4.4,5.3,5.4,7.2,8.2,8.3 of BS1377:Part 2:1990

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content %	Bulk Density Mg/m³	Dry Density Mg/m <sup>3</sup>	Liquid Limit %	Plastic Limit %	Plasticity Index %	% <425um	MCV (%)	% retained on 20 mm sieve	Description of Sample
TP326	1	LB	1.50	15			24	15	9	100			Brown slightly gravelly sandy silty CLAY
TP327	1	LB	1.20	23			36	21	15	77			Reddish brown slightly gravelly slightly sandy CLAY
TP328	1	LB	2.10	14			30	19	11	62			Reddish brown slightly gravelly slightly sandy silty CLAY




Contract: Contract Ref:

East Midlands Gateway - Zone 1



In accordance with clauses 9.2,9.5 of BS1377:Part 2:1990 NON STANDARD TEST

Sample Ref: Sample Type: **B** Depth (m): **1.60** 



Particle Size (mm	Partic:	le Size	(mm)
-------------------	---------	---------	------

CLAV	fine	medium	coarse	fine	medium	coarse	fine	medium	coarse	COBBLES
CLAT		SILT			SAND			GRAVEI		COBBLES

BS Test	Percentage
Sieve (mm)	Passing
125.0 75.0 63.0 37.5 20.0 10.0 6.30 3.35 2.00 1.18 0.600 0.425 0.212 0.150 0.063	100 77 77 76 74 73 72 71 70 68 66 65 58 54

Trial Pit: TP302

Particle	Percentage	Soil	Sieve
Diameter	Passing	Fraction	n Percentage
0.02	35	COBBL	ES <b>23</b>
0.02	35	GRAVE	EL 7
0.006	21	SAND	23
0.002	14	SILT	33
0.002	14	CLAY	14

Soil Description:

Brown slightly gravelly slightly sandy silty CLAY with high cobble content

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By			
	MATT STOKES	15/11/13	
Contract	Contract Ref:		


East Midlands Gateway - Zone 1



In accordance with clauses 9.2,9.5 of BS1377:Part 2:1990

NON STANDARD TEST





Particle Size (mm)

CLAV	fine	medium	coarse	fine	medium	coarse	fine	medium	coarse	COBBLES
CLAT		SILT			SAND			GRAVEI		COBBLES

BS Test	Percentage
Sieve (mm)	Passing
125.0 75.0 63.0 37.5 20.0 10.0 6.30 3.35 2.00 1.18 0.600 0.425 0.212 0.150 0.063	100 70 37 15 7 6 5 5 5 4 4 4 4 4 4

Particle	Percentage	Soil	Sieve
Diameter	Passing	Fraction	Percentage
0.02	2	COBBLES	63
0.02	3	GRAVEL	32
0.006	1	SAND	1
0.002	.002	SILT	3
0.002	1	CLAY	1

Soil Description:

Brown slightly sandy slightly silty very gravelly COBBLES

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By

MATT STOKES

Date 15/11/13


East Midlands Gateway - Zone 1

Contract Ref:



In accordance with clauses 9.2,9.5 of BS1377:Part 2:1990

Trial Pit: TP324 Sample Ref: 1 Sample Type: LB Depth (m): 2.00



Particle Size (mm)

CLAV	fine	medium	coarse	fine	medium	coarse	fine	medium	coarse	COBBLES
CLAT		SILT			SAND			GRAVEI		COBBLES

BS Test	Percentage
Sieve (mm)	Passing
125.0 75.0 63.0 37.5 20.0 10.0 6.30 3.35 2.00 1.18 0.600 0.425	100 100 100 100 100 100 99 99 99 99 98 98 98 97
0.212 0.150 0.063	95 94 83

Particle	Percentage	Soil	Sieve
Diameter	Passing	Fraction	Percentage
0.02	65	GRAVEL	2
0.006	35	SAND	15
0.000	35	SILT	65
0.002	18	CLAY	18

Soil Description:

Brown slightly gravelly slightly sandy silty CLAY

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster Bristol BS3 4AG Compiled By

MATT STOKES

15/11/13

Contract


Contract Ref:

East Midlands Gateway - Zone 1



In accordance with clauses 9.2,9.5 of BS1377:Part 2:1990

Trial Pit: TP326 Sample Ref: 1 Sample Type: LB Depth (m): 1.50



Particle Size (mm)

CLAV	fine	medium	coarse	fine	medium	coarse	fine	medium	coarse	COBBLES
CLAT		SILT			SAND		(	GRAVEI		COBBLES

BS Test	Percentage
Sieve (mm)	Passing
125.0	100
75.0	100
63.0	100
37.5	100
20.0	100
10.0	99
6.30	98
3.35	97
2.00	96
1.18	96
0.600	94
0.425	92
0.212	78
0.150	72
0.063	59

Particle	Percentage	Soil
Diameter	Passing	Fraction
0.02	36	GRAVEI
		SAND
0.006	19	SILT
0.002	13	CLAY

Soil Description:

Brown slightly gravelly sandy silty CLAY

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

MATT STOKES

Date

MATT STOKES

15/11/13

Contract

Contract Ref:

East Midlands Gateway - Zone 1

744186

Sieve Percentage

4


37


46



In accordance with clauses 9.2,9.5 of BS1377:Part 2:1990

NON STANDARD TEST





Particle Size (mm)

CLAV	fine	medium	coarse	fine	medium	coarse	fine	medium	coarse	COBBLES
CLAT		SILT			SAND			GRAVEI		COBBLES

BS Test	Percentage
Sieve (mm)	Passing
125.0 75.0 63.0 37.5 20.0 10.0 6.30 3.35 2.00 1.18 0.600 0.425 0.212 0.150 0.063	100 74 70 62 54 45 40 37 35 34 33 33 32 32 30

Particle	Percentage
Diameter	Passing
0.02	23
0.006	11
0.002	6

Soil	Sieve
Fraction	Percentage
COBBLES	30
GRAVEL	35
SAND	5
SILT	24
CLAY	6

Soil Description:

Reddish brown sandy very silty GRAVEL with high cobble content

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol** BS3 4AG


Comp	piled By		Date
MATT STOKES			
Contract		Contract Ref:	

East Midlands Gateway - Zone 1



In accordance with clauses 9.2,9.5 of BS1377:Part 2:1990

Trial Pit: TP328 Sample Ref: 1 Sample Type: LB Depth (m): 2.10



Particle Size (mm)

CLAV	fine	medium	coarse	fine	medium	coarse	fine	medium	coarse	COBBLES
CLAT		SILT			SAND		(	GRAVEI		COBBLES

BS Test	Percentage
Sieve (mm)	Passing
125.0 75.0	100 100
63.0	100 100
20.0 10.0 6 30	100 99 97
3.35	95 95
1.18	94 94
0.425 0.212	93 93
0.150 0.063	92 88

Particle	Percentage	Soil	Sieve
Diameter	Passing	Fraction	Percentage
0.02	78	GRAVEL	5
0.006	44	SAND	7
0.000	44	SILT	67
0.002	21	CLAY	21

Soil Description:

Reddish brown slightly gravelly slightly sandy silty CLAY

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By Date

MATT STOKES 15/11/13


East Midlands Gateway - Zone 1

744186

Contract Ref:



Trial Pit: TP324 Sample Ref: 1 Sample Type: LB Depth (m): 2.00



Initial Sample Conditions		Test Details	Test Results
Initial Moisture Content (%)	: 16	Compaction Type : Heavy	Maximum Dry Density (Mg/m³) : <b>1.99</b>
% Retained on 37.5mm BS Sieve	: 0	Mass of Rammer (kg): 4.5	Optimum Moisture Content (%) : 10
% Retained on 20.0mm BS Sieve	: 0	Type of Mould : <b>Proctor</b>	Method Used: Clause 3.5
Particle Density - assumed (Mg/m <sup>3</sup> )	: <b>2.70</b>		Remarks:
Size of Soil Pieces	: <20mm	Separate samples were used.	
Samp	Sample Description		
Brown slightly gravelly slightly sandy silty CLAY			0% 5% 10%

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street **Bedminster Bristol** BS3 4AG

Compiled By


East Midlands Gateway - Zone 1

Date ALAN FROST 15/11/13

Contract Ref:



Trial Pit: TP326 Sample Ref: 1 Sample Type: LB Depth (m): 1.50



Initial Sample Conditions		Test Details	Test Results
Initial Moisture Content (%)	: 15	Compaction Type : Heavy	Maximum Dry Density (Mg/m³) : 2.01
% Retained on 37.5mm BS Sieve	: 0	Mass of Rammer (kg): 4.5	Optimum Moisture Content (%) : 10
% Retained on 20.0mm BS Sieve	: <b>0</b>	Type of Mould : <b>Proctor</b>	Method Used: Clause 3.5
Particle Density - assumed (Mg/m <sup>3</sup> )	: <b>2.65</b>		Remarks:
Size of Soil Pieces	: <20mm	Separate samples were used.	
Sample Description			Key to Air Voids Lines
Brown slightly gravelly sandy silty CLAY			0% 5% 10%

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street **Bedminster Bristol** BS3 4AG

East Midlands Gateway - Zone 1

ALAN FROST


Date 15/11/13

Contract Ref:

Compiled By



Trial Pit: TP327 Sample Ref: 1 Sample Type: LB Depth (m): 1.20



Initial Sample Conditions		Test Details	Test Results
Initial Moisture Content (%)	: 18	Compaction Type : Heavy	Maximum Dry Density (Mg/m³) : 1.96
% Retained on 37.5mm BS Sieve	: 0	Mass of Rammer (kg): 4.5	Optimum Moisture Content (%) : 12
% Retained on 20.0mm BS Sieve	: 3	Type of Mould : <b>Proctor</b>	Method Used: Clause 3.5
Particle Density - assumed (Mg/m <sup>3</sup> )	: <b>2.65</b>		Remarks:
Size of Soil Pieces	: <20mm	Separate samples were used.	
Samp	Sample Description		
Reddish brown slightly gravelly slightly sandy CLAY			0%

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK




STRUCTURAL SOILS 1a Princess Street **Bedminster Bristol** BS3 4AG

Compiled By				
		ALAN FROST	15/11/13	

East Midlands Gateway - Zone 1

Contract Ref:

Trial Pit: TP328 Sample Ref: 1 Sample Type: LB Depth (m): 2.10



Initial Sample Condition	ns	Test Details	Test Results		
Initial Moisture Content (%)	: 15	Compaction Type : Heavy	Maximum Dry Density (Mg/m³) : 1.98		
% Retained on 37.5mm BS Sieve	: 4	Mass of Rammer (kg): 4.5	Optimum Moisture Content (%) : 12		
% Retained on 20.0mm BS Sieve	: 6	Type of Mould : CBR	Method Used: Clause 3.6		
Particle Density - assumed (Mg/m³)	: <b>2.70</b>		Remarks:		
Size of Soil Pieces	: <20mm	Separate samples were used.			
Samp	ole Descripti	on	Key to Air Voids Lines		
Reddish brown slightly gravell	0% 5% 10%				

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street **Bedminster Bristol** BS3 4AG


Compiled By			
		ALAN FROST	15/11/13

East Midlands Gateway - Zone 1

Contract Ref:

# LABORATORY CALIFORNIA BEARING RATIO TEST In accordance with clause 7 of BS1377:Part 4:1990 NON STANDARD TEST

Trial Pit: TP322 Sample Ref: 1 Sample Type: LB Depth (m): 2.20



Initial Sample Condi	tions	Test	Test Details		Тор	Base
Initial Moisture Content (%)	: 15	Compaction Type	: 4.5 kg Dynamic	Moisture Content (%)	15	15
Initial Bulk Density (Mg/m³)	: <b>2.17</b>	Surcharge (kg)	: 4.5	CBR value (%)	4.8	6.1
Initial Dry Density (Mg/m³)	: 1.89	Soaking Time (hrs)	:	Remarks:	•	
% retained on 20mm sieve	: 59	Swelling (mm)	:			
	Sample	Description		Key		
Brown mottled grey slightly sandy gravelly CLAY				<b>●</b> Top <b>X</b>	Base	

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 


Compiled By				
	ALAN FROST	15/11/13		
Contract	Contract Ref:			

East Midlands Gateway - Zone 1



# LABORATORY CALIFORNIA BEARING RATIO TEST In accordance with clause 7 of BS1377:Part 4:1990

Trial Pit: TP324 Sample Ref: 1 Sample Type: LB Depth (m): 2.00



Initial Sample Condi	tions	Test	Test Details		Тор	Base
Initial Moisture Content (%)	: 16	Compaction Type	: 4.5 kg Dynamic	Moisture Content (%)	17	16
Initial Bulk Density (Mg/m³)	: 2.14	Surcharge (kg)	: 4.5	CBR value (%)	3.2	3.2
Initial Dry Density (Mg/m³)	: 1.84	Soaking Time (hrs)	:	Remarks:	•	
% retained on 20mm sieve	: 0	Swelling (mm)	:			
	Sample	Description		Key		
Brown slightly gravelly slightly sandy silty CLAY				● Top <b></b>	Base	

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By				
	MATT STOKES	15/11/13		
a · ·	0			


East Midlands Gateway - Zone 1

Contract Ref:



# LABORATORY CALIFORNIA BEARING RATIO TEST In accordance with clause 7 of BS1377:Part 4:1990

Trial Pit: TP326 Sample Ref: 1 Sample Type: LB Depth (m): 1.50



Initial Sample Condi	itions		Test Details		Test Results	Top	Base	
Initial Moisture Content (%)	:	15	Compaction Type	: <b>4.5 kg Dyna</b>	mic	Moisture Content (%)	15	15
Initial Bulk Density (Mg/m³)	: 2	2.10	Surcharge (kg)	: 4.5		CBR value (%)	2.7	1.9
Initial Dry Density (Mg/m³)	: 1	1.82	Soaking Time (hrs)	:		Remarks:		
% retained on 20mm sieve	:	0	Swelling (mm)	:				
	Sam	ple De	escription			Key		
Brown slightly gravelly sandy silty CLAY				● Top 🗷	Base			

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By					
MATT STOKES	15/11/13				
C + P					


East Midlands Gateway - Zone 1

Contract Ref:

744186 AGS

# LABORATORY CALIFORNIA BEARING RATIO TEST In accordance with clause 7 of BS1377:Part 4:1990

Trial Pit: TP327 Sample Ref: 1 Sample Type: LB Depth (m): 1.20



Initial Sample Condi	tions		Test Details		Test Results	Тор	Base
Initial Moisture Content (%)	: 1	18	Compaction Type	: 4.5 kg Dynamic	Moisture Content (%)	18	17
Initial Bulk Density (Mg/m³)	: <b>2.</b>	.19	Surcharge (kg)	: 4.5	CBR value (%)	3.9	4.9
Initial Dry Density (Mg/m³)	: <b>1.</b>	.86	Soaking Time (hrs)	:	Remarks:		
% retained on 20mm sieve	: 2	2	Swelling (mm)	:			
	Samp	ole De	escription		Key		
Reddish brown slightly gravelly slightly sandy CLAY				<b>●</b> Top <b>X</b>	Base		

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By					
	MATT STOKES	15/11/13			

East Midlands Gateway - Zone 1


Contract Ref:

744186

AGS

# LABORATORY CALIFORNIA BEARING RATIO TEST In accordance with clause 7 of BS1377:Part 4:1990 NON STANDARD TEST

Trial Pit: TP327 Sample Ref: 1 Sample Type: LB Depth (m): 2.60



Initial Sample Condi	tions		Test Details		Test Results	Top	Base
Initial Moisture Content (%)	: 1	15	Compaction Type	: 4.5 kg Dynamic	Moisture Content (%)	15	14
Initial Bulk Density (Mg/m³)	: <b>2.</b>	.21	Surcharge (kg)	: 4.5	CBR value (%)	5.2	4.5
Initial Dry Density (Mg/m³)	: 1.	.92	Soaking Time (hrs)	:	Remarks:		
% retained on 20mm sieve	: 5	57	Swelling (mm)	:			
	Samp	ole De	escription		Key		
Reddish brown sandy very silty GRAVEL with high cobble content				<b>●</b> Top <b>■</b>	Base		

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By			Date
		ALAN FROST	15/11/13
	•	~ ~ ~	


East Midlands Gateway - Zone 1

Contract Ref:



# LABORATORY CALIFORNIA BEARING RATIO TEST In accordance with clause 7 of BS1377:Part 4:1990

Trial Pit: TP328 Sample Ref: 1 Sample Type: LB Depth (m): 2.10



Initial Sample Condi	itions	5	Test Details		Test Results	Тор	Base	
Initial Moisture Content (%)	:	16	Compaction Type	: <b>4.5</b> k	g Dynamic	Moisture Content (%)	16	16
Initial Bulk Density (Mg/m³)	:	2.18	Surcharge (kg)	:	4.5	CBR value (%)	6.8	7.5
Initial Dry Density (Mg/m³)	:	1.89	Soaking Time (hrs)	:		Remarks:	•	
% retained on 20mm sieve	:	10	Swelling (mm)	:				
Sample Description				Key				
Reddish brown slightly gravelly slightly sandy silty CLAY				<ul><li>● Top</li></ul>	Base			

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By				Date	
			MATT STOKES	1	15/11/13
Contract			Contract Ref:		

East Midlands Gateway - Zone 1



# M(

### MOISTURE CONDITION VALUE

In accordance with clause 5 of BS1377:Part 4:1990

Trial Pit: TP322


Sample Ref:

Sample Type:

LB

Depth (m): 2.20

Description: Brown mottled grey slightly sandy gravelly CLAY



Moisture Condition Value

Moisture Content:

= 15

Percentage retained on 20 mm sieve:

= 59 %

%

Moisture Condition Value:

= 9.8

Interpretation of curve:

= Steepest straight line

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK

STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

MATT STOKES

Date 15/11/13

Contract

**East Midlands Gateway - Zone 1** 

Contract Ref:

744186

Change in penetration (mm)

### MOISTURE CONDITION VALUE

In accordance with clause 5 of BS1377:Part 4:1990

Trial Pit: TP324

Sample Ref:


Sample Type:

LB

Depth (m):

2.00

Description: Brown slightly gravelly slightly sandy silty CLAY



Moisture Content:

= 17

%

Percentage retained on 20 mm sieve:

= 0

%

Moisture Condition Value:

= 9.9

Interpretation of curve:

= Steepest straight line

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK

STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By

MATT STOKES

Date 15/11/13

Contract

East Midlands Gateway - Zone 1

Contract Ref:

In accordance with clause 5.5 of BS1377:Part 4:1990


Trial Pit: TP326 Sample Ref: 1 Sample Type: LB Depth (m): 1.50

Percentage retained on 20mm sieve: 0

Description: Brown slightly gravelly sandy silty CLAY

Single/Separate Sample Used: Separate

Test Number	1	2	3	4	5
Moisture Content	15.0	16.3	17.7	13.3	-
MCV	9.0	6.8	4.2	10.8	-



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

MATT STOKES

Date 15/11/13

Contract

East Midlands Gateway - Zone 1

Contract Ref:



In accordance with clause 5.5 of BS1377:Part 4:1990


Trial Pit: TP327 Sample Ref: 1 Sample Type: LB Depth (m): 1.20

Percentage retained on 20mm sieve: 2

Description: Reddish brown slightly gravelly slightly sandy CLAY

Single/Separate Sample Used: Separate

Test Number	1	2	3	4	5
Moisture Content	18.8	20.2	20.9	17.3	-
MCV	9.0	7.3	5.2	11.7	-



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol** BS3 4AG

Contract

Compiled By MATT STOKES

15/11/13

Date

East Midlands Gateway - Zone 1

Contract Ref:



In accordance with clause 5.5 of BS1377:Part 4:1990


Trial Pit: TP327 Sample Ref: 1 Sample Type: LB Depth (m): 2.60

Percentage retained on 20mm sieve: 58

Description: Reddish brown sandy very silty GRAVEL with high cobble content

Single/Separate Sample Used: Separate

Test Number	1	2	3	4	5
Moisture Content	14.0	12.5	16.0	16.5	-
MCV	9.7	11.4	7.2	3.6	-



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

11 0					
Compiled By					
		MATT STOKES	15/11/13		
Contract		Contract Ref:			

East Midlands Gateway - Zone 1 744186



In accordance with clause 5.5 of BS1377:Part 4:1990


Trial Pit: TP328 Sample Ref: 1 Sample Type: LB Depth (m): 2.10

Percentage retained on 20mm sieve: 9

Description: Reddish brown slightly gravelly slightly sandy silty CLAY

Single/Separate Sample Used: Separate

Test Number	1	2	3	4	5
Moisture Content	15.6	16.9	18.2	14.7	-
MCV	10.9	7.9	4.8	12.6	-



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

MATT STOKES

15/11/13

Date

Contract


East Midlands Gateway - Zone 1

Contract Ref:



# ONE DIMENSIONAL CONSOLIDATION TEST In accordance with BS1377:Part 5:1990

Position ID: CP216 3 U Depth (m): Sample Ref: Sample Type: 1.41



Initial Specimen Condition			Final Specimen Condition		
Moisture Content (%) Bulk Density (Mg/m³) Dry Density (Mg/m³) Void Ratio	:	14 2.16 1.89 0.3985	Moisture Content (%) Bulk Density (Mg/m³) Dry Density (Mg/m³) Void Ratio	:	16 2.24 1.93 0.3748

Specimen Details						
Description	Height (mm)	:	20.14			
Reddish brown CLAY	Diameter (mm) Particle Density (Mg/m³) (assumed)	:	75.05 2.65			
	Swelling Pressure (kPa)	:	NA			

Test Results					
Pressure Range (kPa)	Mv (m²/MN)	Cv (m²/yr)			
0 - 50	Sample	Swelling			
50 - 100	0.093	32			
100 - 200	0.081	27			
200 - 400	0.055	43			
400 - 50	NA	NA			

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By	Date
MATT STOKES	15/11/13


East Midlands Gateway - Zone 1

Contract Ref:



# ONE DIMENSIONAL CONSOLIDATION TEST In accordance with BS1377:Part 5:1990

Position ID: CP218 U Depth (m): Sample Ref: 4 Sample Type: 2.02



Moisture Content (%) : 14 Moisture Content (%) : 17 Bulk Density (Mg/m³) : 2.09 Bulk Density (Mg/m³) : 2.20	Initial Specimen Condition			Final Specimen Condition		
Dry Density (Mg/m²)         :         1.83         Dry Density (Mg/m²)         :         1.88           Void Ratio         :         0.4462         Void Ratio         :         0.4042	Bulk Density (Mg/m <sup>3</sup> ) Dry Density (Mg/m <sup>3</sup> )	:	2.09 1.83	Bulk Density (Mg/m <sup>3</sup> ) Dry Density (Mg/m <sup>3</sup> )	:	2.20 1.88

Specimen Details						
Description Height (mm)		:	19.62			
Reddish brown slightly gravelly sandy CLAY	Diameter (mm) Particle Density (Mg/m³) (assumed)	:	75.08 2.65			
	Swelling Pressure (kPa)	:	NA			

Test Results						
Pressure My Cv						
Range (kPa)	(m <sup>2</sup> /MN)	(m²/yr)				
0 - 50	0.32	105				
50 - 100	0.11	22				
100 - 200	0.081	37				
200 - 400	0.052	44				
400 - 50	NA	NA				

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By		
	MATT STOKES	15/11/13

East Midlands Gateway - Zone 1


Contract Ref:



# GINT\_LIBRARY V8 05.GLB LibVersion: v8 05 - Lib0004 PriVersion: v8 05 - Core+Logs+Geotech Lab-Bristol - 0004 | Graph L - 1-D CONSOL DATALOGGED | 744186.GPJ - v8 05 | 15/11/13 - 06:56 | AF. Structural Soils Lid, Branch Office - Bristol Lab. 1a Princess Street, Bedminster, Bristol, BS3 4AG. Tel: 0117-947-1000, Fax: 0117-947-1004, Web: www.soils.co.uk, Email: ask@soils.co.uk.

# ONE DIMENSIONAL CONSOLIDATION TEST In accordance with BS1377:Part 5:1990

Position ID: CP220 5 U Sample Ref: Sample Type: Depth (m): 1.50



Initial Specimen Condition			Final Specime	en Co	ndition
Moisture Content (%)	:	9.9	Moisture Content (%)	:	14
Bulk Density (Mg/m <sup>3</sup> )	:	2.00	Bulk Density (Mg/m <sup>3</sup> )	:	2.11
Dry Density (Mg/m <sup>3</sup> )	:	1.82	Dry Density (Mg/m <sup>3</sup> )	:	1.85
Void Ratio	:	0.4549	Void Ratio	:	0.4307
Spaciman Datails					

void Ratio	. 0.4549	Void Katio .	0.4307				
Specimen Details							
Des	cription	Height (mm)	20.00				
Brown clayey gravelly SAND		Diameter (mm) Particle Density (Mg/m³) (assumed)	75.00 2.65				
		Swelling Pressure (kPa)	: NA				

Test Results					
Pressure	Mv	Cv			
Range (kPa)	$(m^2/MN)$	(m²/yr)			
0 - 25	0.28	23			
25 - 50	0.11	13			
50 - 100	0.097	27			
100 - 200	0.067	15			
200 - 25	NA	NA			

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By			
	MATT STOKES	15/11/13	


East Midlands Gateway - Zone 1

Contract Ref:



# ONE DIMENSIONAL CONSOLIDATION TEST In accordance with BS1377:Part 5:1990

Position ID: CP221 9 U Depth (m): Sample Ref: Sample Type: 3.39



Initial Specimen Condition			Final Specime	n Co	ndition
Moisture Content (%) Bulk Density (Mg/m³) Dry Density (Mg/m³) Void Ratio	: : :	40 1.94 1.38 0.9200	Moisture Content (%) Bulk Density (Mg/m³) Dry Density (Mg/m³) Void Ratio	:	37 2.03 1.48 0.7835

Specimen Details					
Description	:	18.91			
Reddish brown slightly sandy CLAY	Diameter (mm) Particle Density (Mg/m³) (assumed)	:	75.06 2.65		
	Swelling Pressure (kPa)	:	NA		

Test Results						
Pressure Range (kPa)	Mv (m²/MN)	Cv (m²/yr)				
0 - 50 50 - 100	0.48 0.27	1.7 1.0				
100 - 200	0.27	1.0				
200 - 400 400 - 50	0.18 NA	0.62 NA				

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By		
MATT STOKES	15/11/13	


East Midlands Gateway - Zone 1

Contract Ref:



# ONE DIMENSIONAL CONSOLIDATION TEST In accordance with BS1377:Part 5:1990

Position ID: CP222 9 U Sample Ref: Sample Type: Depth (m): 3.40



Initial Specime	en Co	ondition	Final Specime	n Co	ondition
Moisture Content (%) Bulk Density (Mg/m³) Dry Density (Mg/m³) Void Ratio	:	34 1.90 1.42 0.8717	Moisture Content (%) Bulk Density (Mg/m³) Dry Density (Mg/m³) Void Ratio	: : : :	30 1.99 1.53 0.7274
Specimen Details					

Specimen Details					
Description	Height (mm)	:	20.50		
Brown slightly gravelly slightly sandy SILT	Diameter (mm) Particle Density (Mg/m³) (assumed)	:	75.03 2.65		
	Swelling Pressure (kPa)	:	NA		

	Test Results							
	Pressure	Cv						
	Range (kPa)	$(m^2/MN)$	(m²/yr)					
	0 - 50	0.81	37					
	50 - 100	0.24	61					
	100 - 200	0.16	34					
	200 - 400	0.10	31					
	400 - 50	NA	NA					

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol BS3 4AG** 

Compiled By		
	MATT STOKES	15/11/13

East Midlands Gateway - Zone 1

Contract Ref:

# SUMMARY OF LABORATORY HAND PENETROMETER & VANE TEST RESULTS

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Moisture Content (%)	Vane Type	Average Reading (kPa)	Sample Description
CP204	7	U	2.20	15	HVP	134	Reddish brown slightly sandy CLAY

Key: HVP = Hand Vane (Peak), HVR = Hand Vane (Remoulded), PP = Pocket Penetrometer.

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK

744186

n

STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG


FF		
Compiled By		Contract Ref:
ALAN FROST	15.11.13	
Midlands Gateway - Zone 1		
	Compiled By	ALAN FROST 15.11.13

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP203 Sample Ref: 5 Sample Type: U Depth (m): 1.35

Description: Brown slightly sandy silty CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	102.12		
	Height	(mm)	204.45		
	Moisture Content	(%)	23		
	Bulk Density	(Mg/m³)	1.91		
	Dry Density	(Mg/m³)	1.56		
TEST DETAILS	Membrane Thickness	(mm)	0.62	0.62	0.62
	Rate of Axial Displacement	(%/min)	1.22	1.22	1.22
	Cell Pressure	(kPa)	40	80	160
	Membrane Correction	(kPa)	0.73	1.15	1.79
	Corrected Deviator Stress	(kPa)	235	267	313
	Undrained Shear Strength	(kPa)	117	133	156
	Strain at Failure	(%)	4.4	7.8	14.2
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By			
	MATT STOKES		
Contract	Contract Ref:		

East Midlands Gateway - Zone 1

.....




In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP210 Sample Ref: 3 Sample Type: U Depth (m): 1.37

Description: Reddish brown mottled grey slightly gravelly CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.19		
	Height	(mm)	204.38		
	Moisture Content	(%)	18		
	Bulk Density	(Mg/m³)	2.10		
	Dry Density	(Mg/m³)	1.78		
TEST DETAILS	Membrane Thickness	(mm)	0.55	0.55	0.55
	Rate of Axial Displacement	(%/min)	1.22	1.22	1.22
	Cell Pressure	(kPa)	40	80	160
	Membrane Correction	(kPa)	0.91	1.53	1.96
	Corrected Deviator Stress	(kPa)	131	155	183
	Undrained Shear Strength	(kPa)	65	77	91
	Strain at Failure	(%)	6.8	13.7	19.1
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By Date

MATT STOKES 15/11/13

Contract Ref:

East Midlands Gateway - Zone 1

Contract Ref:


744186

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP210 Sample Ref: 9 Sample Type: U Depth (m): 3.15

Description: Brown mottled grey slightly sandy CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.34		
	Height	(mm)	204.08		
	Moisture Content	(%)	21		
	Bulk Density	(Mg/m³)	2.12		
	Dry Density	(Mg/m³)	1.75		
TEST DETAILS	Membrane Thickness	(mm)	0.55	0.55	0.55
	Rate of Axial Displacement	(%/min)	1.22	1.22	1.22
	Cell Pressure	(kPa)	60	120	240
	Membrane Correction	(kPa)	1.33	1.63	1.84
	Corrected Deviator Stress	(kPa)	121	137	152
	Undrained Shear Strength	(kPa)	61	69	76
	Strain at Failure	(%)	11.3	14.9	17.6
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By		
MATT STOKES		
C	C + +D C	

East Midlands Gateway - Zone 1

Contract Ref:


744186

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP210 Sample Ref: 14 Sample Type: U Depth (m): 5.10

Description: Brown slightly sandy slightly gravelly CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.32		
	Height	(mm)	199.08		
	Moisture Content	(%)	15		
	Bulk Density	(Mg/m³)	2.13		
	Dry Density	(Mg/m³)	1.85		
TEST DETAILS	Membrane Thickness	(mm)	0.57	0.57	0.57
	Rate of Axial Displacement	(%/min)	1.26	1.26	1.26
	Cell Pressure	(kPa)	80	160	320
	Membrane Correction	(kPa)	1.36	1.70	2.05
	Corrected Deviator Stress	(kPa)	231	299	380
	Undrained Shear Strength	(kPa)	116	150	190
	Strain at Failure	(%)	11.0	15.1	19.3
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster Bristol BS3 4AG Compiled By Date

MATT STOKES 15/11/13

East Midlands Gateway - Zone 1

Contract Ref:


744186

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP210 Sample Ref: 19 Sample Type: U Depth (m): 7.00

Description: Reddish brown mottled grey CLAY

STAGE NUMBER		1	2	3	
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.40		
	Height	(mm)	193.85		
	Moisture Content	(%)	14		
	Bulk Density	(Mg/m <sup>3</sup> )	2.18		
	Dry Density	(Mg/m <sup>3</sup> )	1.92		
TEST DETAILS	Membrane Thickness	(mm)	0.49	0.49	0.49
	Rate of Axial Displacement	(%/min)	1.29	1.29	1.29
	Cell Pressure	(kPa)	100	200	300
	Membrane Correction	(kPa)	0.98	1.23	1.80
	Corrected Deviator Stress	(kPa)	300	455	619
	Undrained Shear Strength	(kPa)	150	228	309
	Strain at Failure	(%)	8.8	11.9	19.9
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster Bristol BS3 4AG Compiled By Date

MATT STOKES 15/11/13

East Midlands Gateway - Zone 1

Contract Ref:




In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP211 Sample Ref: 9 Sample Type: U Depth (m): 3.00

Description: Reddish brown mottled grey slightly sandy CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.00		
	Height	(mm)	193.57		
	Moisture Content	(%)	13		
	Bulk Density	(Mg/m³)	2.20		
	Dry Density	(Mg/m³)	1.95		
TEST DETAILS	Membrane Thickness	(mm)	0.48	0.48	0.48
	Rate of Axial Displacement	(%/min)	1.29	1.29	1.29
	Cell Pressure	(kPa)	60	120	240
	Membrane Correction	(kPa)	1.12	1.34	1.77
	Corrected Deviator Stress	(kPa)	358	421	518
	Undrained Shear Strength	(kPa)	179	210	259
	Strain at Failure	(%)	10.6	13.7	19.9
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster Bristol BS3 4AG

	Сотр	iled By	Date
		MATT STOKES	15/11/13
<u> </u>		0	

East Midlands Gateway - Zone 1

Contract Ref:


744186

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP211 Sample Ref: 15 Sample Type: U Depth (m): 5.01

Description: Reddish brown mottled grey slightly sandy CLAY

STAGE NUMBER		1	2	3	
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.25		
	Height	(mm)	204.32		
	Moisture Content	(%)	15		
	Bulk Density	(Mg/m³)	2.20		
	Dry Density	(Mg/m <sup>3</sup> )	1.91		
TEST DETAILS	Membrane Thickness	(mm)	0.61	0.61	0.61
	Rate of Axial Displacement	(%/min)	1.22	1.22	1.22
	Cell Pressure	(kPa)	80	160	320
	Membrane Correction	(kPa)	1.17	1.46	1.87
	Corrected Deviator Stress	(kPa)	334	479	715
	Undrained Shear Strength	(kPa)	167	240	358
	Strain at Failure	(%)	8.3	11.0	15.7
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By Date

MATT STOKES 15/11/13

Contract Ref:

East Midlands Gateway - Zone 1

Contract Ref:

744186


In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP216 Sample Ref: 3 Sample Type: U Depth (m): 1.20

Description: Brown mottled grey CLAY

Remarks: Non-standard height

STAGE NUMBER		1	2	3	
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.45		
	Height	(mm)	178.75		
	Moisture Content	(%)	15		
	Bulk Density	(Mg/m³)	2.11		
	Dry Density	(Mg/m <sup>3</sup> )	1.83		
TEST DETAILS	Membrane Thickness	(mm)	0.64	0.64	0.64
	Rate of Axial Displacement	(%/min)	1.40	1.40	1.40
	Cell Pressure	(kPa)	50	100	200
	Membrane Correction	(kPa)	1.49	1.91	2.35
	Corrected Deviator Stress	(kPa)	207	280	401
	Undrained Shear Strength	(kPa)	103	140	200
	Strain at Failure	(%)	10.6	15.1	19.9
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Contract

East Midlands Gateway - Zone 1 Cont




In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP218 Sample Ref: 4 Sample Type: U Depth (m): 2.06

Description: Reddish brown slightly gravelly sandy CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	103.37		
	Height	(mm)	204.50		
	Moisture Content	(%)	13		
	Bulk Density	(Mg/m <sup>3</sup> )	2.17		
	Dry Density	(Mg/m <sup>3</sup> )	1.92		
TEST DETAILS	Membrane Thickness	(mm)	0.49	0.49	0.49
	Rate of Axial Displacement	(%/min)	1.22	1.22	1.22
	Cell Pressure	(kPa)	50	100	200
	Membrane Correction	(kPa)	1.07	1.27	1.50
	Corrected Deviator Stress	(kPa)	250	311	399
	Undrained Shear Strength	(kPa)	125	156	200
	Strain at Failure	(%)	9.8	12.5	15.6
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By

MATT STOKES

Date

MATT STOKES

15/11/13

Contract

Contract Ref:

East Midlands Gateway - Zone 1

744186


In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP220 Sample Ref: 5 Sample Type: U Depth (m): 1.28

Description: Brown mottled grey and light brown slightly gravelly slightly

sandy CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	101.62		
	Height	(mm)	204.19		
	Moisture Content	(%)	27		
	Bulk Density	(Mg/m³)	2.03		
	Dry Density	(Mg/m³)	1.59		
TEST DETAILS	Membrane Thickness	(mm)	0.56	0.56	0.56
	Rate of Axial Displacement (%/min)		1.22	1.22	1.22
	Cell Pressure	(kPa)	40	80	160
	Membrane Correction	(kPa)	0.91	1.34	1.74
	Corrected Deviator Stress	(kPa)	192	235	278
	Undrained Shear Strength	(kPa)	96	118	139
	Strain at Failure	(%)	6.6	10.8	15.7
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster Bristol BS3 4AG Compiled By

MATT STOKES

Date

MATT STOKES

15/11/13

Contract

Contract Ref:

East Midlands Gateway - Zone 1


744186

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP221 Sample Ref: 9 Sample Type: U Depth (m): 3.14

Description: Reddish brown slightly sandy CLAY

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	102.85		
	Height	(mm)	204.21		
	Moisture Content	(%)	27		
	Bulk Density	(Mg/m³)	1.92		
	Dry Density	(Mg/m³)	1.51		
TEST DETAILS	Membrane Thickness	(mm)	0.57	0.57	0.57
	Rate of Axial Displacement	(%/min)	1.22	1.22	1.22
	Cell Pressure	(kPa)	60	120	240
	Membrane Correction	(kPa)	0.95	1.37	1.75
	Corrected Deviator Stress	(kPa)	81	89	92
	Undrained Shear Strength	(kPa)	41	45	46
	Strain at Failure	(%)	6.9	11.0	15.7
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

Compiled By Date

MATT STOKES 15/11/13

Contract Ref:

East Midlands Gateway - Zone 1

Contract Ref:


744186

In accordance with BS1377:Part 7:1990, Clause 9

Position ID: CP222 Sample Ref: 9 Sample Type: U Depth (m): 3.10

Description: Brown slightly gravelly slightly sandy SILT

STAGE NUMBER			1	2	3
SAMPLE DETAILS	Sample Condition		Undisturbed		
	Orientation of sample		Vertical		
	Diameter	(mm)	104.62		
	Height	(mm)	203.46		
	Moisture Content	(%)	14		
	Bulk Density	(Mg/m³)	2.13		
	Dry Density	$(Mg/m^3)$	1.86		
TEST DETAILS	Membrane Thickness	(mm)	0.62	0.62	0.62
	Rate of Axial Displacement	(%/min)	1.23	1.23	1.23
	Cell Pressure	(kPa)	50	100	200
	Membrane Correction	(kPa)	1.07	1.35	2.23
	Corrected Deviator Stress	(kPa)	26	32	47
	Undrained Shear Strength	(kPa)	13	16	24
	Strain at Failure	(%)	7.4	9.8	19.7
	Mode of Failure				Compound



Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK



STRUCTURAL SOILS 1a Princess Street Bedminster Bristol BS3 4AG Compiled By Date

MATT STOKES 15/11/13

Contract Puris

Contract Ref:

East Midlands Gateway - Zone 1

Contract Ref:



(International Society for Rock Mechanics: 1985)


Exploratory Position ID	Depth (m)	Type of Test	Width or Length (W or L) (mm)	Platen Separation (D) (mm)	Failure Load (P) (kN)	Equivalent Diameter (D <sub>e</sub> ) (mm)	Point Load (I <sub>s</sub> ) (MN/m <sup>2</sup> )	Size Factor (F)	Point Load Index (I <sub>s(50)</sub> ) (MN/m <sup>2</sup> )	Moisture Content (%)	Rock Type
CP206	1.50	A	86	50	1.419	74	0.26	1.19	0.31	12	MUDSTONE
CP206	1.50	A	61	18	0.239	37	0.17	0.88	0.15	12	MUDSTONE
CP206	1.50	A	65	15	0.098	35	0.08	0.85	0.07	12	MUDSTONE

Key: A = Axial, D = Diametral, I = Irregular, B = Block, L = Parallel to planes of weakness, P = Perpendicular to planes of weakness. [NS] denotes Non Standard Test.



STRUCTURAL SOILS 1a Princess Street Bedminster **Bristol** 

Contract Ref: Compiled By Date **ALAN FROST** 15.11.13 Contract: East Midlands Gateway - Zone 1



# **SUMMARY OF CHEMICAL ANALYSES**

Exploratory Position ID	Sample Ref	Sample Type	Depth (m)	Acid Soluble Sulphate (% SO <sub>4</sub> )	Aqueous Extract Sulphate (mg/l SO <sub>4</sub> )	рН	Total Sulphur (%)	Description
TP326	1	LB	1.50	< 0.02	19	7.91	< 0.01	Brown slightly gravelly sandy silty CLAY
NOTES:-								

NOTES:- All chemical tests were undertaken by Envirolab.

Approved Signatories: J.BARRETT A.FROST M.STOKES S.HANDCOCK

Up.

STRUCTURAL SOILS
1a Princess Street
Bedminster
Bristol
BS3 4AG

		Approved Signad	ones. J.DAKKETT A.	TROST MISTO
	Compiled By			
		ALAN FROST	15.11.13	
Contract:	East Mi	dlands Gateway - Zone 1		





Edinburgh Road Springhill Shotts ML7 5DT

Tel: 01501 822 244 Fax 01501 825 044

email: info@mattest.org Website: www.mattest.org

# LABORATORY TEST CERTIFICATE MATERIALS LABORATORY

Certificate No 13/889 - 01

Client : Structural Soils Limited
The Potteries

Pottery Street Castleford WF10 1NJ

Mr Mark Athorne

Dear Sirs,

To:

### LABORATORY TESTING OF ROCK

### Introduction

We refer to samples taken from East Midlands Gateway, Zone 1 and delivered to our laboratory on the 18th November 2013.

### **Material & Source**

Sampled By : Client

Test Reference : See Report Plates

Description : N/A

Date Sampled : Not Supplied

Date Tested : 18th November 2013 Onwards

Source : East Midlands Gateway - Zone 1

### Test Results;

As Detailed On Page 2 to Page 4 inclusive.

### Comments;

Opinions and interpretations expressed herein are outside the scope of UKAS accreditation. This report should not be reproduced except in full without the written approval of the laboratory. All remaining samples for this project will be disposed of 28 days after issue of this test certificate.

Date

Remarks;		
Approved for Issue		

29/11/2013

Laboratory Manager



Issue No. 02 Page 1 of 4



BOREHOLE	SAMPLE	DEPTH (m)	MOISTURE CONTENT (%)	BULK DENSITY (Mg/m³)	DRY DENSITY (Mg/m³)
CP(R)203	-	6.40	9.9	2.38	2.17
CP(R)203	-	12.10	6.7	2.41	2.26
CP(R)203	-	18.60	4.4	2.41	2.31
CP(R)203	-	23.83	9.3	2.45	2.24
CP(R)206	-	7.57	10.1	2.25	2.04

Tested in accordance with "ISRM Suggested Methods"


# SUMMARY OF MOISTURE CONTENT AND DENSITY TEST RESULTS



BOREHOLE CORE RUN DEPTH SAMPLE DIAMETER SAMPLE HEIGHT WATER CONTENT TEST CONDITION RATE OF LOADING TEST DURATION DATE OF TESTING LOAD FRAME USED LOAD DIRECTION WITH RESPECT TO LITHOLOGY FAILURE LOAD WN AND AND AND AND AND AND AND AND AND AN	CP(R)203 - 6.40 85.96 136.32 9.9 As received 0.1 4.00 20-Nov-13 50kN Perpendicular 18.8 3.2  SAMPLE FAILURE SHAPES  External Internal
--	---

Test specimen does not meet specified length / diameter ratio requirements

BOREHOLE CORE RUN DEPTH SAMPLE DIAMETER mm SAMPLE HEIGHT mm WATER CONTENT % TEST CONDITION RATE OF LOADING kN/s TEST DURATION min.s DATE OF TESTING LOAD FRAME USED LOAD DIRECTION WITH RESPECT TO LITHOLOGY FAILURE LOAD kN UNCONFINED COMPRESSIVE STRENGTH MPa	192.80 6.7 As received 0.2 4.05 20-Nov-13 50kN Perpendicular 39.0 External Internal
--	---




Tested in accordance with ASTM D7012 - 10



BOREHOLE CORE RUN DEPTH SAMPLE DIAMETER SAMPLE HEIGHT WATER CONTENT TEST CONDITION RATE OF LOADING KN/S TEST DURATION DATE OF TESTING LOAD FRAME USED LOAD DIRECTION WITH RESPECT TO LITHOLOGY FAILURE LOAD WNCONFINED COMPRESSIVE STRENGTH MPa	
---	--

BOREHOLE CORE RUN DEPTH SAMPLE DIAMETER SAMPLE HEIGHT WATER CONTENT TEST CONDITION RATE OF LOADING TEST DURATION DATE OF TESTING LOAD FRAME USED LOAD DIRECTION WITH RESPECT TO LITHOLOGY FAILURE LOAD WNCONFINED COMPRESSIVE STRENGTH MPa	CP(R)206 - 7.57 86.73 149.31 10.1 As received 0.1 14.14 20-Nov-13 2000kN Perpendicular 124.3 21.0  SAMPLE FAILURE SHAPES  Fair Company of the second of the
--	---

Test specimen does not meet specified length / diameter ratio requirements




Tested in accordance with ASTM D7012 - 10

(International Society for Rock Mechanics: 1985)

Exploratory Position ID	Depth (m)	Type of Test	Width or Length (W or L) (mm)	Platen Separation (D) (mm)	Failure Load (P) (kN)	Equivalent Diameter (D <sub>e</sub> ) (mm)	Point Load (I <sub>s</sub> ) (MN/m <sup>2</sup> )	Size Factor (F)	Point Load Index (I <sub>s(50)</sub> ) (MN/m <sup>2</sup> )	Moisture Content (%)	Rock Type
CP(R)203	27.02	D	107.5	85	1.015	85	0.14	1.27	0.18	8.4	SANDSTONE
CP(R)203	27.02	A	85	60	0.565	81	0.09	1.24	0.11	8.4	SANDSTONE
CP(R)203	28.35	D	52.645	86.4	1.870	86	0.25	1.28	0.32	5.7	MUDSTONE
CP(R)203	28.35	A	86.4	40.29	1.170	67	0.26	1.14	0.30	5.7	MUDSTONE
CP(R)204	8.25	D	62.365	85.87	0.240	86	0.03	1.28	0.04	11	MUDSTONE
CP(R)204	8.25	A	85.87	66.22	0.190	85	0.03	1.27	0.03	11	MUDSTONE
CP(R)204	12.90	A	87.41	69.47	1.640	88	0.21	1.29	0.27	8.8	MUDSTONE
CP(R)204	18.87	D	57.475	86.75	2.320	87	0.31	1.28	0.40	7.4	MUDSTONE

 $Key: A = Axial, D = Diametral, I = Irregular, B = Block, L = Parallel \ to \ planes \ of \ weakness, P = Perpendicular \ to \ planes \ of \ weakness.$ 

Approved Signatories: J.BARRETT M.ATHORNE A.FROST M.RANDERSON R.CLARKSON M.FISHER C.COLE M.STOKES



	Compi	iled By	Date
		MAUREEN FISHER	29.11.13
ontract:			

**East Midlands Gateway - Zone 1** 

781044

Contract Ref:




(International Society for Rock Mechanics: 1985)

Exploratory Position ID	Depth (m)	Type of Test	Width or Length (W or L) (mm)	Platen Separation (D) (mm)	Failure Load (P) (kN)	Equivalent Diameter (D <sub>e</sub> ) (mm)	Point Load (I <sub>s</sub> ) (MN/m <sup>2</sup> )	Size Factor (F)	Point Load Index (I <sub>s(50)</sub> ) (MN/m²)	Moisture Content (%)	Rock Type
CP(R)204	18.87	A	86.75	53.79	1.445	77	0.24	1.22	0.30	7.4	MUDSTONE
CP(R)205	8.58	D	60.11	86.31	0.780	86	0.10	1.28	0.13	8.2	MUDSTONE
CP(R)205	8.58	A	86.31	42	1.080	68	0.23	1.15	0.27	8.2	MUDSTONE
CP(R)205	9.70	D	119	85	1.600	85	0.22	1.27	0.28	7.6	MUDSTONE
CP(R)205	9.70	A	85	52.92	1.305	76	0.23	1.21	0.27	7.6	MUDSTONE
CP(R)205	10.92	D	67.72	86.24	2.130	86	0.29	1.28	0.37	8.5	MUDSTONE
CP(R)205	10.92	A	86.24	58.1	2.440	80	0.38	1.23	0.47	8.5	MUDSTONE
CP(R)206	6.61	D	44.22	86.59	2.825	87	0.38	1.28	0.48	9.6	MUDSTONE

 $Key: A = Axial, D = Diametral, I = Irregular, B = Block, L = Parallel \ to \ planes \ of \ weakness, P = Perpendicular \ to \ planes \ of \ weakness.$ 

Approved Signatories: J.BARRETT M.ATHORNE A.FROST M.RANDERSON R.CLARKSON M.FISHER C.COLE M.STOKES



	Compi	iled By	Date
		MAUREEN FISHER	29.11.13
Contract:			

**East Midlands Gateway - Zone 1** 

781044

Contract Ref:




(International Society for Rock Mechanics: 1985)

Exploratory Position ID	Depth (m)	Type of Test	Width or Length (W or L) (mm)	Platen Separation (D) (mm)	Failure Load (P) (kN)	Equivalent Diameter (D <sub>e</sub> ) (mm)	Point Load (I <sub>s</sub> ) (MN/m <sup>2</sup> )	Size Factor (F)	Point Load Index (I <sub>s(50)</sub> ) (MN/m²)	Moisture Content (%)	Rock Type
CP(R)206	6.61	A	86.59	28.16	3.010	56	0.97	1.05	1.02	9.6	MUDSTONE
CP(R)206	12.72	D	65.9	86.57	3.155	87	0.42	1.28	0.54	5.9	MUDSTONE
CP(R)206	12.72	A	86.57	62.92	3.255	83	0.47	1.26	0.59	5.9	MUDSTONE
CP(R)207	9.40	D	52.08	86.4	0.790	86	0.11	1.28	0.14	8.6	MUDSTONE
CP(R)207	9.40	A	86.4	42.65	1.170	68	0.25	1.15	0.29	8.6	MUDSTONE
CP(R)207	16.64	D	63.225	86.3	0.940	86	0.13	1.28	0.16	6.7	MUDSTONE
CP(R)207	16.64	A	86.3	56.13	2.465	79	0.40	1.23	0.49	6.7	MUDSTONE
CP(R)207	24.15	D	43.955	86.1	0.370	86	0.05	1.28	0.06	7.1	MUDSTONE

Key: A = Axial, D = Diametral, I = Irregular, B = Block, L = Parallel to planes of weakness, P = Perpendicular to planes of weakness. [NS] denotes Non Standard Test.

Approved Signatories: J.BARRETT M.ATHORNE A.FROST M.RANDERSON R.CLARKSON M.FISHER C.COLE M.STOKES



Compiled By Date

MAUREEN FISHER 29.11.13

Contract:

East Midlands Gateway - Zone 1

Contract Ref:

781044


/81044

(International Society for Rock Mechanics: 1985)

Exploratory Position ID	Depth (m)	Type of Test	Width or Length (W or L) (mm)	Platen Separation (D) (mm)	Failure Load (P) (kN)	Equivalent Diameter (D <sub>e</sub> ) (mm)	Point Load $(I_s)$ $(MN/m^2)$	Size Factor (F)	Point Load Index (I <sub>s(50)</sub> ) (MN/m <sup>2</sup> )	Moisture Content (%)	Rock Type
CP(R)207	24.15	A	86.1	45.15	0.910	70	0.18	1.17	0.21	7.1	MUDSTONE
CP(R)208	7.40	D	50	85	0.965	85	0.13	1.27	0.17	9.5	MUDSTONE
CP(R)208	7.40	A	85	36	0.630	62	0.16	1.10	0.18	9.5	MUDSTONE
CP(R)208	9.98	D	51.44	86.89	1.955	87	0.26	1.28	0.33	8.0	MUDSTONE
CP(R)208	9.98	A	86.89	45.04	1.115	71	0.22	1.17	0.26	8.0	MUDSTONE
CP(R)208	11.22	D	48.285	86.22	4.625	86	0.62	1.28	0.80	12	MUDSTONE
CP(R)208	11.22	A	86.22	48.13	5.250	73	0.99	1.18	1.18	12	MUDSTONE

 $Key: A = Axial, D = Diametral, I = Irregular, B = Block, L = Parallel \ to \ planes \ of \ weakness, P = Perpendicular \ to \ planes \ of \ weakness.$ 

Approved Signatories: J.BARRETT M.ATHORNE A.FROST M.RANDERSON R.CLARKSON M.FISHER C.COLE M.STOKES



	Compiled By					
			MAUREEN FISHER	29.11.13		
Contract:						

**East Midlands Gateway - Zone 1** 

781044

Contract Ref:





# APPENDIX H CHEMICAL LABORATORY CERTIFICATES FOR SOIL ANALYSIS



## FINAL ANALYTICAL TEST REPORT

**Envirolab Job Number:** 13/04787

**Issue Number:** Date: 24 October, 2013

**Client: RSK Environment Ltd Coventry** 

Humber Road, Abbey Park

Coventry

UK

CV3 4AQ

**Project Manager:** Darren Bench / Mariah Hocking / Marc Dixon

**Project Name:** East Midlands Gateway Zone 1

**Project Ref:** 312494

**Order No:** Not specified **Date Samples Received:** 02/10/13 **Date Instructions Received:** 10/10/13 **Date Analysis Completed:** 24/10/13

Prepared by:

Approved by:

Melanie Marshall

**Laboratory Coordinator** 

Liz Oliver

Client Service Manager





Lab Sample ID	13/04787/1	13/04787/2	13/04787/3	13/04787/4	13/04787/5	13/04787/6	13/04787/7	13/04787/8		
Client Sample No										
Client Sample ID	TP310	TP314	TP323	TP324	TP316	TP319	TP326	TP328		
Depth to Top	0.80	0.60	0.50	0.10	0.10	0.10	0.60	0.15		
Depth To Bottom	0.90	0.70		0.20	0.20	0.20	0.70	0.25		
Date Sampled	25-Sep-13	25-Sep-13	24-Sep-13	24-Sep-13	26-Sep-13	26-Sep-13	24-Sep-13	24-Sep-13		)÷
Sample Type	Soil - ES		Method ref							
Sample Matrix Code	5	5	3	6E	6E	6E	6E	6E	Units	Meth
pH <sub>D</sub> <sup>M#</sup>	6.36	7.46	7.98	4.96	5.66	8.30	7.00	7.08	рН	A-T-031s
Total Organic Carbon <sub>D</sub> <sup>M#</sup>	0.41	0.29	0.19	-	1.64	-	0.36	-	% w/w	A-T-032s
Arsenic <sub>D</sub> #	3	1	2	4	4	3	2	5	mg/kg	A-T-024
Cadmium <sub>D</sub> <sup>M#</sup>	<0.5	0.7	1.0	0.5	0.7	0.7	0.5	0.6	mg/kg	A-T-024
Copper <sub>D</sub> <sup>M#</sup>	10	14	28	19	17	12	16	21	mg/kg	A-T-024
Chromium <sub>D</sub> #	20	45	57	25	30	40	30	26	mg/kg	A-T-024
Chromium (hexavalent) <sub>D</sub>	<1	<1	<1	<1	<1	<1	<1	<1	mg/kg	A-T-040s
Lead <sub>D</sub> <sup>M#</sup>	11	10	8	25	27	54	9	56	mg/kg	A-T-024
Mercury <sub>D</sub>	<0.17	0.22	0.30	0.24	0.21	0.27	<0.17	0.37	mg/kg	A-T-024
Nickel <sub>D</sub> #	12	28	44	15	21	26	19	22	mg/kg	A-T-024
Selenium <sub>D</sub> #	<1	<1	1	<1	<1	<1	<1	<1	mg/kg	A-T-024
Zinc <sub>D</sub> <sup>M#</sup>	52	102	77	64	71	76	52	77	mg/kg	A-T-024
Asbestos in Soil (inc. matrix)										
Asbestos in soil <sub>D</sub> #	-	NAD	-	-	-	NAD	-	-		A-T-045
Asbestos Matrix (visual) <sub>A</sub>	-	N/A	-	-	-	N/A	-	-		Visual
Asbestos Matrix (microscope) <sub>D</sub>	-	N/A	-	-	-	N/A	-	-		A-T-045



						Project Rei				
Lab Sample ID	13/04787/1	13/04787/2	13/04787/3	13/04787/4	13/04787/5	13/04787/6	13/04787/7	13/04787/8		
Client Sample No										
Client Sample ID	TP310	TP314	TP323	TP324	TP316	TP319	TP326	TP328		
Depth to Top	0.80	0.60	0.50	0.10	0.10	0.10	0.60	0.15		
Depth To Bottom	0.90	0.70		0.20	0.20	0.20	0.70	0.25		
Date Sampled	25-Sep-13	25-Sep-13	24-Sep-13	24-Sep-13	26-Sep-13	26-Sep-13	24-Sep-13	24-Sep-13		ef
Sample Type	Soil - ES	Soil - ES	Soil - ES	vo.	Method ref					
Sample Matrix Code	5	5	3	6E	6E	6E	6E	6E	Units	Meth
Pest-c										
Mevinphos	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Dichlorvos	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
alpha-Hexachlorocyclohexane (HCH)	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Diazinon	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
gamma-Hexachlorocyclohexane (HCH / Lindane)	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Heptachlor	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Aldrin	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
beta-Hexachlorocyclohexane (HCH)	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Methyl Parathion	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Malathion	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Fenitrothion	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Heptachlor Epoxide	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Parathion (Ethyl Parathion)	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
p,p-DDE	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
p,p-DDT	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
p,p-Methoxychlor	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
p,p-TDE (DDD)	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
o,p-DDE	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
o,p-DDT	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
o,p-Methoxychlor	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
o,p-TDE (DDD)	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Endosulphan I	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Endosulphan II	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Endosulphan Sulphate	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Endrin	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Ethion	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Dieldrin	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
Azinphos-methyl	-	-	-	<50	-	<50	-	<50	μg/kg	Subcon
	<u> </u>	<u> </u>								



-						i roject nei				
Lab Sample ID	13/04787/1	13/04787/2	13/04787/3	13/04787/4	13/04787/5	13/04787/6	13/04787/7	13/04787/8		
Client Sample No										
Client Sample ID	TP310	TP314	TP323	TP324	TP316	TP319	TP326	TP328		
Depth to Top	0.80	0.60	0.50	0.10	0.10	0.10	0.60	0.15		
Depth To Bottom	0.90	0.70		0.20	0.20	0.20	0.70	0.25		
Date Sampled	25-Sep-13	25-Sep-13	24-Sep-13	24-Sep-13	26-Sep-13	26-Sep-13	24-Sep-13	24-Sep-13		<del>J</del> e
Sample Type	Soil - ES	Soil - ES	Soil - ES	s	Method ref					
Sample Matrix Code	5	5	3	6E	6E	6E	6E	6E	Units	Meth
PAH 16										
Acenaphthene <sub>A</sub> <sup>M#</sup>	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-019s
Acenaphthylene <sub>A</sub> <sup>M#</sup>	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-019s
Anthracene <sub>A</sub> <sup>M#</sup>	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	<0.02	mg/kg	A-T-019s
Benzo(a)anthracene <sub>A</sub> <sup>M#</sup>	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	mg/kg	A-T-019s
Benzo(a)pyrene <sub>A</sub> <sup>M#</sup>	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	0.04	mg/kg	A-T-019s
Benzo(b)fluoranthene <sub>A</sub> M#	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	mg/kg	A-T-019s
Benzo(ghi)perylene <sub>A</sub> <sup>M#</sup>	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	mg/kg	A-T-019s
Benzo(k)fluoranthene <sub>A</sub> M#	<0.07	<0.07	<0.07	<0.07	<0.07	<0.07	<0.07	<0.07	mg/kg	A-T-019s
Chrysene <sub>A</sub> <sup>M#</sup>	<0.06	<0.06	<0.06	<0.06	<0.06	<0.06	<0.06	<0.06	mg/kg	A-T-019s
Dibenzo(ah)anthracene <sub>A</sub> M#	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	<0.04	mg/kg	A-T-019s
Fluoranthene <sub>A</sub> <sup>M#</sup>	<0.08	<0.08	<0.08	<0.08	<0.08	<0.08	<0.08	<0.08	mg/kg	A-T-019s
Fluorene <sub>A</sub> <sup>M#</sup>	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-019s
Indeno(123-cd)pyrene <sub>A</sub> M#	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	mg/kg	A-T-019s
Naphthalene <sub>A</sub> <sup>M#</sup>	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	mg/kg	A-T-019s
Phenanthrene <sub>A</sub> <sup>M#</sup>	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	<0.03	0.04	mg/kg	A-T-019s
Pyrene <sub>A</sub> <sup>M#</sup>	<0.07	<0.07	<0.07	<0.07	<0.07	<0.07	<0.07	<0.07	mg/kg	A-T-019s
PAH (total 16) <sub>A</sub> <sup>M#</sup>	<0.08	<0.08	<0.08	<0.08	<0.08	<0.08	<0.08	0.09	mg/kg	A-T-019s



					••	Project her				
Lab Sample ID	13/04787/1	13/04787/2	13/04787/3	13/04787/4	13/04787/5	13/04787/6	13/04787/7	13/04787/8		
Client Sample No										
Client Sample ID	TP310	TP314	TP323	TP324	TP316	TP319	TP326	TP328		
Depth to Top	0.80	0.60	0.50	0.10	0.10	0.10	0.60	0.15		
Depth To Bottom	0.90	0.70		0.20	0.20	0.20	0.70	0.25		
Date Sampled	25-Sep-13	25-Sep-13	24-Sep-13	24-Sep-13	26-Sep-13	26-Sep-13	24-Sep-13	24-Sep-13		e e
Sample Type	Soil - ES	Soil - ES	Soil - ES	σ.	Method ref					
Sample Matrix Code	5	5	3	6E	6E	6E	6E	6E	Units	Meth
Triazines (x11)										
Ametryne	-	-	-	<0.2	-	<0.2	-	<0.2	mg/kg	Subcon
Atraton	-	-	-	<0.2	-	<0.2	-	<0.2	mg/kg	Subcon
Atrazine	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon
Cyanazine	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon
Prometon	-	-	-	<0.2	-	<0.2	-	<0.2	mg/kg	Subcon
Prometryn	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon
Propazine	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon
Simazine	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon
Simetryn	-	-	-	<0.2	-	<0.2	-	<0.2	mg/kg	Subcon
Terbuthylazine	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon
Terbutryn	-	-	-	<0.02	-	<0.02	-	<0.02	mg/kg	Subcon



						Project nei				
Lab Sample ID	13/04787/1	13/04787/2	13/04787/3	13/04787/4	13/04787/5	13/04787/6	13/04787/7	13/04787/8		
Client Sample No										
Client Sample ID	TP310	TP314	TP323	TP324	TP316	TP319	TP326	TP328		
Depth to Top	0.80	0.60	0.50	0.10	0.10	0.10	0.60	0.15		
Depth To Bottom	0.90	0.70		0.20	0.20	0.20	0.70	0.25		
Date Sampled	25-Sep-13	25-Sep-13	24-Sep-13	24-Sep-13	26-Sep-13	26-Sep-13	24-Sep-13	24-Sep-13		e e
Sample Type	Soil - ES	Soil - ES	Soil - ES	<b>6</b> 0	Method ref					
Sample Matrix Code	5	5	3	6E	6E	6E	6E	6E	Units	Meth
TPH CWG										
% Stones >10mm <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	% w/w	A-T-044
Ali >C5-C6 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Ali >C6-C8 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Ali >C8-C10 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Ali >C10-C12 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Ali >C12-C16 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Ali >C16-C21 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Ali >C21-C35 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Total Aliphatics <sub>A</sub>	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-022+23s
Aro >C5-C7 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Aro >C7-C8 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Aro >C8-C9 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Aro >C9-C10 <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Aro >C10-C12 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Aro >C12-C16 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Aro >C16-C21 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Aro >C21-C35 <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s
Total Aromatics <sub>A</sub>	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-022+23s
TPH (Ali & Aro) <sub>A</sub>	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-022+23s
BTEX - Benzene <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
BTEX - Toluene <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
BTEX - Ethyl Benzene <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
BTEX - m & p Xylene <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
BTEX - o Xylene <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
MTBE <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	<0.01	mg/kg	A-T-022s
Mineral Oil (>C10-C35) <sub>A</sub>	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	mg/kg	A-T-023s



#### **REPORT NOTES**

#### Notes - Soil analysis

All results are reported as dry weight (<40 ℃).

For samples with Matrix Codes 1 - 6 natural stones >10mm are removed or excluded from the sample prior to analysis and reported results corrected to a whole sample basis. For samples with Matrix Code 7 the whole sample is dried and crushed prior to analysis.

#### Notes - General

Subscript "A" indicates analysis performed on the sample as received. "D" indicates analysis performed on the dried sample, crushed to pass a 2mm sieve, unless asbestos is found to be present in which case all analysis is performed on the sample as received.

All analysis is performed on the dried and crushed sample for samples with Matrix Code 7 and this supercedes any "A" subscripts.

Superscript "M" indicates method accredited to MCERTS.

For complex, multi-compound analysis, quality control results do not always fall within chart limits for every compound and we have criteria for reporting in these situations. If results are in italic font they are associated with such quality control failures and may be unreliable.

A deviating samples report is appended and will indicate if samples or tests have been found to be deviating. Any test results affected may not be an accurate record of the concentration at the time of sampling.

#### TPH analysis of water by method A-T-007

Free and visible oils are excluded from the sample used for analysis so that the reported result represents the dissolved phase only.

#### Asbestos in soil

Asbestos in soil analysis is performed on an aliquot of the submitted sample and cannot guarantee to identify asbestos if present at low concentrations or as discrete fibres/fragments.

Quantification of asbestos is a 3 stage process including visual identification, hand picking and weighing and fibre counting by sedimentation/phase contrast optical microscopy if required. If asbestos is identified a being present but is not in a form that is suitable for analysis by hand picking and weighing (normally if the asbestos is present as free fibres) quantification by sedimentation is performed. Where ACMs are found a percentage asbestos is assigned to each with reference to 'HSG264, Asbestos: The survey guide' and the calculated asbestos content is expressed as a percentage of the dried soil sample aliquot used.

#### **Predominant Matrix Codes:**

1 = SAND, 2 = LOAM, 3 = CLAY, 4 = LOAM/SAND, 5 = SAND/CLAY, 6 = CLAY/LOAM, 7 = OTHER. Samples with Matrix Code 7 are not predominantly a SAND/LOAM/CLAY mix and are not covered by our MCERTS accreditation.

#### **Secondary Matrix Codes:**

A = contains stones, B = contains construction rubble, C = contains visible hydrocarbons, D = contains glass/metal, E = contains roots/twigs.

IS indicates Insufficient sample for analysis.

NDP indicates No Determination Possible.

NAD indicates No Asbestos Detected.

N/A indicates Not Applicable.

Superscript # indicates method accredited to ISO 17025.

Analytical results reflect the quality of the sample at the time of analysis only. Opinions and interpretations expressed are outside the scope of our accreditation.

Please contact us if you need any further information.



## FINAL ANALYTICAL TEST REPORT

**Envirolab Job Number:** 13/04851

**Issue Number:** 1 **Date:** 28 October, 2013

Client: RSK Environment Ltd Coventry

Humber Road, Abbey Park

Coventry

UK

CV3 4AQ

Project Manager: Derren Bench / Mariah Hocking / Marc Dixon

**Project Name:** East Midlands Gateway Zone 1

Project Ref: 312494

Order No: Not specified Date Samples Received: 15/10/13 Date Instructions Received: 15/10/13 Date Analysis Completed: 28/10/13

Prepared by: Approved by:

Melanie Marshall

Laboratory Coordinator

Liz Oliver

Client Service Manager





Lab Sample ID	13/04851/1	13/04851/2	13/04851/3				
Client Sample No							
Client Sample ID	TP301	TP303	TP352				
Depth to Top	0.50	0.10	0.50				
Depth To Bottom		0.20	0.70				
Date Sampled	03-Oct-13	03-Oct-13	01-Oct-13				<del>)</del>
Sample Type	Soil - ES	Soil - ES	Soil - ES			,	Method ref
Sample Matrix Code	5E	5AE	5E			Units	Meth
pH <sub>D</sub> <sup>M#</sup>	8.32	6.26	6.06			рН	A-T-031s
Total Organic Carbon <sub>D</sub> <sup>M#</sup>	0.61	0.99	0.46			% w/w	A-T-032s
Arsenic <sub>D</sub> #	8	3	4			mg/kg	A-T-024
Cadmium <sub>D</sub> <sup>M#</sup>	<0.5	<0.5	<0.5			mg/kg	A-T-024
Copper <sub>D</sub> <sup>M#</sup>	28	14	12			mg/kg	A-T-024
Chromium <sub>D</sub> #	30	23	18			mg/kg	A-T-024
Chromium (hexavalent) <sub>D</sub>	<1	<1	<1			mg/kg	A-T-040s
Lead <sub>D</sub> <sup>M#</sup>	11	27	21			mg/kg	A-T-024
Mercury <sub>D</sub>	<0.17	0.17	<0.17			mg/kg	A-T-024
Nickel <sub>D</sub> #	23	14	10			mg/kg	A-T-024
Selenium <sub>D</sub> #	<1	<1	<1			mg/kg	A-T-024
Zinc <sub>D</sub> <sup>M#</sup>	45	57	51			mg/kg	A-T-024
Asbestos in Soil (inc. matrix)							
Asbestos in soil <sub>D</sub> #	-	NAD	-				A-T-045
Asbestos Matrix (visual) <sub>A</sub>	-	N/A	-				Visual
Asbestos Matrix (microscope) <sub>D</sub>	-	N/A	-				A-T-045



		1			Project Rei			
Lab Sample ID	13/04851/1	13/04851/2	13/04851/3					
Client Sample No								
Client Sample ID	TP301	TP303	TP352					
Depth to Top	0.50	0.10	0.50					
Depth To Bottom		0.20	0.70					
Date Sampled	03-Oct-13	03-Oct-13	01-Oct-13					<del>J</del> e
Sample Type	Soil - ES	Soil - ES	Soil - ES				0	Method ref
Sample Matrix Code	5E	5AE	5E				Units	Meth
Pest-c								
Mevinphos	-	<50	-				μg/kg	Subcon
Dichlorvos	-	<50	-				μg/kg	Subcon
alpha-Hexachlorocyclohexane (HCH)	-	<50	-				μg/kg	Subcon
Diazinon	-	<50	-				μg/kg	Subcon
gamma-Hexachlorocyclohexane (HCH / Lindane)	-	<50	-				μg/kg	Subcon
Heptachlor	-	<50	-				μg/kg	Subcon
Aldrin	-	<50	-				μg/kg	Subcon
beta-Hexachlorocyclohexane (HCH)	-	<50	-				μg/kg	Subcon
Methyl Parathion	-	<50	-				μg/kg	Subcon
Malathion	-	<50	-				μg/kg	Subcon
Fenitrothion	-	<50	-				μg/kg	Subcon
Heptachlor Epoxide	•	<50	•				μg/kg	Subcon
Parathion (Ethyl Parathion)	-	<50	•				μg/kg	Subcon
p,p-DDE	-	<50	-				μg/kg	Subcon
p,p-DDT	-	<50	-				μg/kg	Subcon
p,p-Methoxychlor	-	<50	-				μg/kg	Subcon
p,p-TDE (DDD)	-	<50	-				μg/kg	Subcon
o,p-DDE	•	<50	•				μg/kg	Subcon
o,p-DDT	-	<50	-				μg/kg	Subcon
o,p-Methoxychlor	-	<50	-				μg/kg	Subcon
o,p-TDE (DDD)	•	<50	•				μg/kg	Subcon
Endosulphan I	-	<50					μg/kg	Subcon
Endosulphan II	-	<50	-	 		 	μg/kg	Subcon
Endosulphan Sulphate	-	<50	-	 		 	μg/kg	Subcon
Endrin	-	<50	-				μg/kg	Subcon
Ethion	-	<50	-				μg/kg	Subcon
Dieldrin	-	<50	-				μg/kg	Subcon
Azinphos-methyl	-	<50	-				μg/kg	Subcon



B					i roject nei			
Lab Sample ID	13/04851/1	13/04851/2	13/04851/3					
Client Sample No								
Client Sample ID	TP301	TP303	TP352					
Depth to Top	0.50	0.10	0.50					
Depth To Bottom		0.20	0.70					
Date Sampled	03-Oct-13	03-Oct-13	01-Oct-13					<del>]</del>
Sample Type	Soil - ES	Soil - ES	Soil - ES					Method ref
Sample Matrix Code	5E	5AE	5E				Units	Meth
PAH 16								
Acenaphthene <sub>A</sub> <sup>M#</sup>	<0.01	<0.01	<0.01				mg/kg	A-T-019s
Acenaphthylene <sub>A</sub> <sup>M#</sup>	<0.01	<0.01	<0.01				mg/kg	A-T-019s
Anthracene <sub>A</sub> <sup>M#</sup>	<0.02	<0.02	<0.02				mg/kg	A-T-019s
Benzo(a)anthracene <sub>A</sub> <sup>M#</sup>	<0.04	<0.04	<0.04				mg/kg	A-T-019s
Benzo(a)pyrene <sub>A</sub> <sup>M#</sup>	<0.04	<0.04	<0.04				mg/kg	A-T-019s
Benzo(b)fluoranthene <sub>A</sub> <sup>M#</sup>	<0.05	<0.05	<0.05				mg/kg	A-T-019s
Benzo(ghi)perylene <sub>A</sub> <sup>M#</sup>	<0.05	<0.05	<0.05				mg/kg	A-T-019s
Benzo(k)fluoranthene <sub>A</sub> M#	<0.07	<0.07	<0.07				mg/kg	A-T-019s
Chrysene <sub>A</sub> <sup>M#</sup>	<0.06	<0.06	<0.06				mg/kg	A-T-019s
Dibenzo(ah)anthracene <sub>A</sub> M#	<0.04	<0.04	<0.04				mg/kg	A-T-019s
Fluoranthene <sub>A</sub> M#	<0.08	<0.08	<0.08				mg/kg	A-T-019s
Fluorene <sub>A</sub> <sup>M#</sup>	<0.01	<0.01	<0.01				mg/kg	A-T-019s
Indeno(123-cd)pyrene <sub>A</sub> <sup>M#</sup>	<0.03	<0.03	<0.03				mg/kg	A-T-019s
Naphthalene <sub>A</sub> <sup>M#</sup>	<0.03	<0.03	<0.03				mg/kg	A-T-019s
Phenanthrene <sub>A</sub> <sup>M#</sup>	<0.03	<0.03	<0.03				mg/kg	A-T-019s
Pyrene <sub>A</sub> <sup>M#</sup>	<0.07	<0.07	<0.07				mg/kg	A-T-019s
PAH (total 16) <sub>A</sub> <sup>M#</sup>	<0.08	<0.08	<0.08				mg/kg	A-T-019s



					Project nei	 		
Lab Sample ID	13/04851/1	13/04851/2	13/04851/3					
Client Sample No								
Client Sample ID	TP301	TP303	TP352					
Depth to Top	0.50	0.10	0.50					
Depth To Bottom		0.20	0.70					
Date Sampled	03-Oct-13	03-Oct-13	01-Oct-13					ef
Sample Type	Soil - ES	Soil - ES	Soil - ES				v	Method ref
Sample Matrix Code	5E	5AE	5E				Units	Meth
Triazines (x11)								
Ametryne	-	<0.2	-				mg/kg	Subcon
Atraton	-	<0.2	-				mg/kg	Subcon
Atrazine	-	<0.02	-				mg/kg	Subcon
Cyanazine	-	<0.02	-				mg/kg	Subcon
Prometon	-	<0.2	-				mg/kg	Subcon
Prometryn	-	<0.02	-				mg/kg	Subcon
Propazine	-	<0.02	-				mg/kg	Subcon
Simazine	-	<0.02	-				mg/kg	Subcon
Simetryn	-	<0.2	-				mg/kg	Subcon
Terbuthylazine	-	<0.02	-				mg/kg	Subcon
Terbutryn	-	<0.02	-				mg/kg	Subcon



					Project nei			
Lab Sample ID	13/04851/1	13/04851/2	13/04851/3					
Client Sample No								
Client Sample ID	TP301	TP303	TP352					
Depth to Top	0.50	0.10	0.50					
Depth To Bottom		0.20	0.70					
Date Sampled	03-Oct-13	03-Oct-13	01-Oct-13					je
Sample Type	Soil - ES	Soil - ES	Soil - ES					od re
Sample Matrix Code	5E	5AE	5E				Units	Method ref
TPH CWG								
% Stones >10mm <sub>A</sub> #	<0.1	4.5	<0.1				% w/w	A-T-044
Ali >C5-C6 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Ali >C6-C8 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Ali >C8-C10 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Ali >C10-C12 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Ali >C12-C16 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Ali >C16-C21 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Ali >C21-C35 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Total Aliphatics <sub>A</sub>	<0.1	<0.1	<0.1				mg/kg	A-T-022+23s
Aro >C5-C7 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Aro >C7-C8 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Aro >C8-C9 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Aro >C9-C10 <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
Aro >C10-C12 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Aro >C12-C16 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Aro >C16-C21 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Aro >C21-C35 <sub>A</sub> #	<0.1	<0.1	<0.1				mg/kg	A-T-023s
Total Aromatics <sub>A</sub>	<0.1	<0.1	<0.1				mg/kg	A-T-022+23s
TPH (Ali & Aro) <sub>A</sub>	<0.1	<0.1	<0.1				mg/kg	A-T-022+23s
BTEX - Benzene <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
BTEX - Toluene <sub>A</sub> #	<0.01	<0.01	<0.01				mg/kg	A-T-022s
BTEX - Ethyl Benzene <sub>A</sub> #	<0.01	<0.01	<0.01	 			mg/kg	A-T-022s
BTEX - m & p Xylene <sub>A</sub> #	<0.01	<0.01	<0.01	 			mg/kg	A-T-022s
BTEX - o Xylene <sub>A</sub> #	<0.01	<0.01	<0.01	 			mg/kg	A-T-022s
MTBE <sub>A</sub> #	<0.01	<0.01	<0.01	 			mg/kg	A-T-022s
Mineral Oil (>C10-C35) <sub>A</sub>	<0.1	<0.1	<0.1				mg/kg	A-T-023s



#### **REPORT NOTES**

#### Notes - Soil analysis

All results are reported as dry weight (<40 ℃).

For samples with Matrix Codes 1 - 6 natural stones >10mm are removed or excluded from the sample prior to analysis and reported results corrected to a whole sample basis. For samples with Matrix Code 7 the whole sample is dried and crushed prior to analysis.

#### Notes - General

Subscript "A" indicates analysis performed on the sample as received. "D" indicates analysis performed on the dried sample, crushed to pass a 2mm sieve, unless asbestos is found to be present in which case all analysis is performed on the sample as received.

All analysis is performed on the dried and crushed sample for samples with Matrix Code 7 and this supercedes any "A" subscripts.

Superscript "M" indicates method accredited to MCERTS.

For complex, multi-compound analysis, quality control results do not always fall within chart limits for every compound and we have criteria for reporting in these situations. If results are in italic font they are associated with such quality control failures and may be unreliable.

A deviating samples report is appended and will indicate if samples or tests have been found to be deviating. Any test results affected may not be an accurate record of the concentration at the time of sampling.

#### TPH analysis of water by method A-T-007

Free and visible oils are excluded from the sample used for analysis so that the reported result represents the dissolved phase only.

#### Asbestos in soil

Asbestos in soil analysis is performed on an aliquot of the submitted sample and cannot guarantee to identify asbestos if present at low concentrations or as discrete fibres/fragments.

Quantification of asbestos is a 3 stage process including visual identification, hand picking and weighing and fibre counting by sedimentation/phase contrast optical microscopy if required. If asbestos is identified a being present but is not in a form that is suitable for analysis by hand picking and weighing (normally if the asbestos is present as free fibres) quantification by sedimentation is performed. Where ACMs are found a percentage asbestos is assigned to each with reference to 'HSG264, Asbestos: The survey guide' and the calculated asbestos content is expressed as a percentage of the dried soil sample aliquot used.

#### **Predominant Matrix Codes:**

1 = SAND, 2 = LOAM, 3 = CLAY, 4 = LOAM/SAND, 5 = SAND/CLAY, 6 = CLAY/LOAM, 7 = OTHER. Samples with Matrix Code 7 are not predominantly a SAND/LOAM/CLAY mix and are not covered by our MCERTS accreditation.

#### **Secondary Matrix Codes:**

A = contains stones, B = contains construction rubble, C = contains visible hydrocarbons, D = contains glass/metal, E = contains roots/twigs.

IS indicates Insufficient sample for analysis.

NDP indicates No Determination Possible.

NAD indicates No Asbestos Detected.

N/A indicates Not Applicable.

Superscript # indicates method accredited to ISO 17025.

Analytical results reflect the quality of the sample at the time of analysis only. Opinions and interpretations expressed are outside the scope of our accreditation.

Please contact us if you need any further information.



## FINAL ANALYTICAL TEST REPORT

**Envirolab Job Number:** 13/04858

**Issue Number:** 2 **Date:** 19 November, 2013

Client: RSK Environment Ltd Coventry

Humber Road, Abbey Park

Coventry

UK

CV3 4AQ

Project Manager: Darren Bench / Mariah Hocking / Marc Dixon

**Project Name:** East Midlands Gateway Zone 1

Project Ref: 312494

Order No: Not specified
Date Samples Received: 15/10/13
Date Instructions Received: 16/10/13
Date Analysis Completed: 23/10/13

Prepared by: Approved by:

Lynette Toon

Administrative Assistant

Liz Oliver

Client Service Manager





Lab Sample ID	13/04858/1	13/04858/2	13/04858/3	13/04858/4	13/04858/5	13/04858/6	13/04858/7	13/04858/8		
Client Sample No	4	8	20	2	14	2	4	8		
Client Sample ID	CP219	CP219	CP219	CP203	CP203	CP221	CP221	CP221		
Depth to Top	1.70	2.90	6.90	0.50	4.00	0.45	1.20	2.90		
Depth To Bottom										
Date Sampled	26-Sep-13	27-Sep-13	27-Sep-13	25-Sep-13	25-Sep-13	27-Sep-13	27-Sep-13	27-Sep-13		<del>-</del>
Sample Type	Soil - D	<b>6</b> 0	Method ref							
Sample Matrix Code	3	3	3	6E	3	4AE	4AE	3	Units	Meth
% Stones >10mm <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	8.3	11.7	<0.1	% w/w	A-T-044
pH BRE <sub>D</sub> M#	8.71	8.70	8.73	8.10	8.74	7.35	8.22	6.94	рН	A-T-031s
Sulphate BRE (water sol 2:1) <sub>D</sub> <sup>M#</sup>	142	39	25	<10	20	<10	12	32	mg/l	A-T-026s
Sulphate BRE (acid sol) <sub>D</sub> <sup>M#</sup>	0.07	0.05	0.04	0.02	0.02	<0.02	<0.02	<0.02	% w/w	A-T-028
Sulphur BRE (total) <sub>D</sub>	0.03	0.02	0.02	0.01	<0.01	<0.01	<0.01	<0.01	% w/w	A-T-024



Lab Sample ID	13/04858/9	13/04858/10	13/04858/11	13/04858/12	13/04858/13			
Client Sample No				5	9		=	
Client Sample ID	CP210	CP210	CP210	CP217	CP217			
Depth to Top	1.70	5.50	7.50	1.70	3.50			
Depth To Bottom	2.00			2.00				
Date Sampled				27-Sep-13	27-Sep-13			e e
Sample Type	Soil - D	Soil - D	Soil - D	Soil - D	Soil - D		,	Method ref
Sample Matrix Code	6	6	6	6	6		Units	Meth
% Stones >10mm <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1		% w/w	A-T-044
pH BRE <sub>D</sub> <sup>M#</sup>	8.54	8.60	8.74	8.43	8.67		pН	A-T-031s
Sulphate BRE (water sol 2:1) <sub>D</sub> <sup>M#</sup>	13	15	15	22	32		mg/l	A-T-026s
Sulphate BRE (acid sol) <sub>D</sub> <sup>M#</sup>	<0.02	<0.02	0.03	<0.02	0.04		% w/w	A-T-028
Sulphur BRE (total) <sub>D</sub>	<0.01	<0.01	<0.01	<0.01	0.01		% w/w	A-T-024



#### **REPORT NOTES**

#### Notes - Soil chemical analysis

All results are reported as dry weight (<40 °C).
For samples with Matrix Codes 1 - 6 natural stones >10mm are removed or excluded from the sample prior to analysis and reported results corrected to a whole sample basis. For samples with Matrix Code 7 the whole sample is dried and crushed prior to analysis.

#### Notes - General

Subscript "A" indicates analysis performed on the sample as received. "D" indicates analysis performed on the dried sample, crushed to pass a 2mm sieve, unless asbestos is found to be present in which case all analysis is performed on the sample as received.

All analysis is performed on the dried and crushed sample for samples with Matrix Code 7 and this supercedes any "A" subscripts.

All analysis is performed on the sample as received for soil samples from outside the European Union and this supercedes any "D" subscripts

Superscript "M" indicates method accredited to MCERTS.

For complex, multi-compound analysis, quality control results do not always fall within chart limits for every compound and we have criteria for reporting in these situations. If results are in italic font they are associated with such quality control failures and may be unreliable.

A deviating samples report is appended and will indicate if samples or tests have been found to be deviating. Any test results affected may not be an accurate record of the concentration at the time of sampling.

#### TPH analysis of water by method A-T-007

Free and visible oils are excluded from the sample used for analysis so that the reported result represents the dissolved phase only.

#### Asbestos in soil

Asbestos in soil analysis is performed on a dried aliquot of the submitted sample and cannot guarantee to identify asbestos if present as discrete fibres/fragments. Stones etc. are not removed from the sample prior to analysis.

Quantification of asbestos is a 3 stage process including visual identification, hand picking and weighing and fibre counting by sedimentation/phase contrast optical microscopy if required. If asbestos is identified a being present but is not in a form that is suitable for analysis by hand picking and weighing (normally if the asbestos is present as free fibres) quantification by sedimentation is performed. Where ACMs are found a percentage asbestos is assigned to each with reference to 'HSG264, Asbestos: The survey guide' and the calculated asbestos content is expressed as a percentage of the dried soil sample aliquot used.

#### **Predominant Matrix Codes:**

1 = SAND, 2 = LOAM, 3 = CLAY, 4 = LOAM/SAND, 5 = SAND/CLAY, 6 = CLAY/LOAM, 7 = OTHER. Samples with Matrix Code 7 are not predominantly a SAND/LOAM/CLAY mix and are not covered by our MCERTS accreditation.

#### Secondary Matrix Codes:

A = contains stones, B = contains construction rubble, C = contains visible hydrocarbons, D = contains glass/metal, E = contains roots/twigs.

IS indicates Insufficient sample for analysis.

NDP indicates No Determination Possible.

NAD indicates No Asbestos Detected.

N/A indicates Not Applicable.

Superscript # indicates method accredited to ISO 17025.

Analytical results reflect the quality of the sample at the time of analysis only. Opinions and interpretations expressed are outside the scope of our accreditation.

Please contact us if you need any further information.



## FINAL ANALYTICAL TEST REPORT

**Envirolab Job Number:** 13/05397

**Issue Number:** 2a **Date:** 20 November, 2013

Client: Structural Soils Castleford Lab

The Potteries
Pottery Street
Castleford
West Yorkshire

UK

**WF10 1NJ** 

Project Manager: Mark Athorne

**Project Name:** East Midlands Gateway - Zone 1

Project Ref: 781044

Order No: Not specified Date Samples Received: 12/11/13
Date Instructions Received: 13/11/13
Date Analysis Completed: 20/11/13

Prepared by:

Approved by:

Melanie Marshall Laboratory Coordinator Liz Oliver

Client Service Manager



	r				1	1		ı	ı
Lab Sample ID	13/05397/1	13/05397/2	13/05397/3	13/05397/4	13/05397/5	13/05397/6			
Client Sample No									
Client Sample ID	CP(R)203	CP(R)203	CP(R)204	CP(R)205	CP(R)206	CP(R)208			
Depth to Top	18.60	27.02	8.25	9.70	7.57	7.40			
Depth To Bottom	18.94	27.47	8.50	9.92	7.85	7.59			
Date Sampled									e e
Sample Type	Solid	Solid	Soil	Solid	Solid	Solid		y v	Method ref
Sample Matrix Code	7	7	5	7	7	7		Units	Meth
% Stones >10mm <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1		% w/w	A-T-044
pH BRE <sub>D</sub> <sup>M#</sup>	8.98	8.95	8.90	9.08	9.25	9.14		pН	A-T-031s
Sulphate BRE (water sol 2:1) <sub>D</sub> <sup>M#</sup>	15	17	21	<10	<10	<10		mg/l	A-T-026s
Sulphate BRE (acid sol) <sub>D</sub> <sup>M#</sup>	<0.02	0.03	0.03	<0.02	0.02	0.03		% w/w	A-T-028
Sulphur BRE (total) <sub>D</sub>	<0.01	<0.01	0.01	<0.01	<0.01	0.01		% w/w	A-T-024



#### **REPORT NOTES**

#### Notes - Soil chemical analysis

All results are reported as dry weight (<40 ℃).

For samples with Matrix Codes 1 - 6 natural stones >10mm are removed or excluded from the sample prior to analysis and reported results corrected to a whole sample basis. For samples with Matrix Code 7 the whole sample is dried and crushed prior to analysis.

#### Notes - General

Subscript "A" indicates analysis performed on the sample as received. "D" indicates analysis performed on the dried sample, crushed to pass a 2mm sieve, unless asbestos is found to be present in which case all analysis is performed on the sample as received.

All analysis is performed on the dried and crushed sample for samples with Matrix Code 7 and this supercedes any "A" subscripts.

All analysis is performed on the sample as received for soil samples from outside the European Union and this supercedes any "D" subscripts.

Superscript "M" indicates method accredited to MCERTS.

For complex, multi-compound analysis, quality control results do not always fall within chart limits for every compound and we have criteria for reporting in these situations. If results are in italic font they are associated with such quality control failures and may be unreliable.

A deviating samples report is appended and will indicate if samples or tests have been found to be deviating. Any test results affected may not be an accurate record of the concentration at the time of sampling.

#### TPH analysis of water by method A-T-007

Free and visible oils are excluded from the sample used for analysis so that the reported result represents the dissolved phase only.

### Asbestos in soil

Asbestos in soil analysis is performed on a dried aliquot of the submitted sample and cannot guarantee to identify asbestos if present as discrete fibres/fragments. Stones etc. are not removed from the sample prior to analysis.

Quantification of asbestos is a 3 stage process including visual identification, hand picking and weighing and fibre counting by sedimentation/phase contrast optical microscopy if required. If asbestos is identified a being present but is not in a form that is suitable for analysis by hand picking and weighing (normally if the asbestos is present as free fibres) quantification by sedimentation is performed. Where ACMs are found a percentage asbestos is assigned to each with reference to 'HSG264, Asbestos: The survey guide' and the calculated asbestos content is expressed as a percentage of the dried soil sample aliquot used.

#### **Predominant Matrix Codes:**

1 = SAND, 2 = LOAM, 3 = CLAY, 4 = LOAM/SAND, 5 = SAND/CLAY, 6 = CLAY/LOAM, 7 = OTHER. Samples with Matrix Code 7 are not predominantly a SAND/LOAM/CLAY mix and are not covered by our MCERTS accreditation.

#### Secondary Matrix Codes:

A = contains stones, B = contains construction rubble, C = contains visible hydrocarbons, D = contains glass/metal, E = contains roots/twigs.

IS indicates Insufficient sample for analysis.

NDP indicates No Determination Possible.

NAD indicates No Asbestos Detected.

N/A indicates Not Applicable.

Superscript # indicates method accredited to ISO 17025.

Analytical results reflect the quality of the sample at the time of analysis only. Opinions and interpretations expressed are outside the scope of our accreditation.

Please contact us if you need any further information.



# APPENDIX I CHEMICAL LABORATORY CERTIFICATES FOR GROUNDWATER ANALYSIS



## FINAL ANALYTICAL TEST REPORT

**Envirolab Job Number:** 13/05152

**Issue Number:** 2a **Date:** 29 November, 2013

Client: RSK Environment Ltd Coventry

Humber Road, Abbey Park

Coventry

UK

CV3 4AQ

**Project Manager:** Gareth Shaw / Darren Bench / Leon Terrace

**Project Name:** East Midlands RFT

Project Ref: 312494

Order No: Not specified Date Samples Received: 29/10/13 Date Instructions Received: 31/10/13 Date Analysis Completed: 13/11/13

Prepared by:

Melanie Marshall Laboratory Coordinator Approved by:

Gill Scott

Laboratory Manager





					Onone	Project nei	. 0.2.0.			
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		<del>J</del> e
Sample Type	Water - W	Water - W	Water - W	,	Method ref					
Sample Matrix Code									Units	Meth
pH (w) <sub>A</sub> #	8.14	8.03	7.91	7.92	8.05	8.00	7.11	7.20	рН	A-T-031w
Redox Potential (w) <sub>A</sub>	246	263	274	284	287	259	239	232	mV	A-T-048
Electrical conductivity @ 20 ℃ (w) A <sup>#</sup>	1220	1030	868	2690	847	645	1040	675	μs/cm	A-T-037w
Dissolved oxygen <sub>A</sub>	8.6	5.8	7.6	3.7	6.1	8.1	3.7	6.2	mg/l	A-T-048
Hardness <sub>A</sub> #	458	493	522	838	499	383	552	447	mg/l Ca CO3	A-T-049
Ammoniacal nitrogen (w) <sub>A</sub> #	0.21	0.09	0.16	0.31	0.18	0.06	0.09	0.03	mg/l	A-T-033w
Phenois - Total by HPLC (w)A	0.02	0.05	<0.01	<0.01	<0.01	0.01	<0.01	<0.01	mg/l	A-T-050w
Arsenic (dissolved) <sub>A</sub> #	1	1	<1	1	<1	<1	<1	<1	μg/l	A-T-025
Boron (dissolved) <sub>A</sub> #	48	62	52	82	53	22	50	25	μg/l	A-T-025
Cadmium (dissolved) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-025
Copper (dissolved) <sub>A</sub> #	2	2	2	4	2	<1	2	2	μg/l	A-T-025
Chromium (dissolved) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-025
Chromium (hexavalent) (w) <sub>A</sub> #	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	<0.05	mg/l	A-T-040w
Lead (dissolved) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-025
Mercury (dissolved) <sub>A</sub> #	<0.1	<0.1	<0.1	<0.1	<0.1	<0.1	0.1	<0.1	μg/l	A-T-025
Nickel (dissolved) <sub>A</sub> #	3	3	1	3	1	<1	1	<1	μg/l	A-T-025
Selenium (dissolved) <sub>A</sub> #	39	1	<1	4	<1	<1	<1	<1	μg/l	A-T-025
Zinc (dissolved) <sub>A</sub> #	7	9	2	4	6	<1	6	6	μg/l	A-T-025



						Project nei				
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		<del>-</del>
Sample Type	Water - W	Water - W	Water - W	(n	Method ref					
Sample Matrix Code									Units	Meth
PAH 16MS (w)										
Acenaphthene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Acenaphthylene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Anthracene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Benzo(a)anthracene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Benzo(a)pyrene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Benzo(b)fluoranthene (w) <sub>A</sub> #	0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Benzo(ghi)perylene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Benzo(k)fluoranthene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Chrysene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Dibenzo(ah)anthracene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Fluoranthene (w) <sub>A</sub> #	0.02	<0.01	<0.01	0.02	<0.01	-	0.01	<0.01	μg/l	A-T-019w
Fluorene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Indeno(123-cd)pyrene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	0.01	0.01	-	<0.01	<0.01	μg/l	A-T-019w
Naphthalene (w) <sub>A</sub> #	<0.01	<0.01	<0.01	<0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Phenanthrene (w) <sub>A</sub> #	0.02	<0.01	<0.01	0.01	<0.01	-	<0.01	<0.01	μg/l	A-T-019w
Pyrene (w) <sub>A</sub> #	0.03	<0.01	0.01	0.02	0.01	-	<0.01	<0.01	μg/l	A-T-019w
PAH (total 16) (w) <sub>A</sub> #	0.08	<0.01	0.01	0.06	0.02	-	0.01	<0.01	μg/l	A-T-019w



					- Cilioni	Project Rei	. 012101		1	,
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		eŧ
Sample Type	Water - W	Water - W	Water - W	s	Method ref					
Sample Matrix Code									Units	Meth
SVOC (w)										
1,2,4-Trichlorobenzene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
1,2-Dichlorobenzene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
1,3-Dichlorobenzene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
1,4-Dichlorobenzene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,4,5-Trichlorophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,4,6-Trichlorophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,4-Dichlorophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,4-Dimethylphenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,4-Dinitrotoluene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,6-Dinitrotoluene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2-Chloronaphthalene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2-Chlorophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2-Methylnaphthalene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2-Methylphenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2-Nitrophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
4-Bromophenyl phenyl ether <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
4-Chloro-3-methylphenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
4-Methylphenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
4-Nitrophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Acenaphthene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Acenaphthylene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Anthracene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Bis(2-chloroethyl)ether <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Bis(2-chloroethoxy)methane <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Bis(2-ethylhexyl)phthalate <sub>A</sub>	<2	<2	<2	<2	<2	-	<2	<2	μg/l	A-T-052
Benzo(a)anthracene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Butylbenzyl phthalate <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Benzo(b)fluoranthene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Benzo(k)fluoranthene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
		-		-	-	-	-	-		



		1			Ciletit	Project Ref	. 512434			
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		eŧ
Sample Type	Water - W	Water - W	Water - W	s	Method ref					
Sample Matrix Code									Units	Meth
Benzo(a)pyrene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Benzo(ghi)perylene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Carbazole <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Chrysene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Dibenzofuran <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
n-Dibutylphthalate <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
n-Dioctylphthalate <sub>A</sub>	<5	<5	<5	<5	<5	-	<5	<5	μg/l	A-T-052
n-Nitroso-n-dipropylamine₄	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Diethyl phthalate <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Dimethyl phthalate <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Dibenzo(ah)anthracene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Fluorene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Fluoranthene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Hexachlorobutadiene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Hexachlorobenzene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Pentachlorophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Phenol <sub>A</sub>	<1	<1	<1	<1	<1	-	4	<1	μg/l	A-T-052
Hexachloroethane <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Nitrobenzene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Naphthalene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Isophorone <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Hexachlorocyclopentadiene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Phenanthrene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Pyrene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Indeno(1,2,3-cd)pyrene A	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Bis(2-chloroisopropyl)ether <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
2,4-Dinitrophenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
4,6-Dinitro-2-methylphenol <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052
Perylene <sub>A</sub>	<1	<1	<1	<1	<1	-	<1	<1	μg/l	A-T-052



					- Cilioni	Project Rei	. 012101		1	
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		ef
Sample Type	Water - W	Water - W	Water - W	s	Method ref					
Sample Matrix Code									Units	Meth
VOC (w)										
Dichlorodifluoromethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Chloromethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Vinyl Chloride <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Bromomethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Chloroethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Trichlorofluoromethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
trans 1,2-Dichloroethene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Dichloromethane <sub>A</sub>	<100	<100	<100	<100	<100	<100	<100	<100	μg/l	A-T-006
Carbon Disulphide <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,1-Dichloroethene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,1-Dichloroethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
cis 1,2-Dichloroethene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Bromochloromethane <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-006
Chloroform <sub>A</sub> #	<25	<25	<25	<25	<25	<25	<25	<25	μg/l	A-T-006
2,2-Dichloropropane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,2-Dichloroethane <sub>A</sub> #	<2	<2	<2	<2	<2	<2	<2	<2	μg/l	A-T-006
1,1,1-Trichloroethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,1-Dichloropropene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Benzene VOC <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Carbon Tetrachloride <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Dibromomethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,2-Dichloropropane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Bromodichloromethane <sub>A</sub> #	<10	<10	<10	<10	<10	<10	<10	<10	μg/l	A-T-006
Trichloroethene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
cis 1,3-Dichloropropene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
trans 1,3-Dichloropropene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,1,2-Trichloroethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Toluene VOC <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,3-Dichloropropane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
	•	•		•		•		•		



		1	1	1	• · · · · · · · ·	Project Rei	. 0.2.0.	1		
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		ef
Sample Type	Water - W	Water - W	Water - W	Water - W	s	Method ref				
Sample Matrix Code									Units	Meth
Dibromochloromethane <sub>A</sub> #	<3	<3	<3	<3	<3	<3	<3	<3	μg/l	A-T-006
1,2-Dibromoethane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Tetrachloroethene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,1,1,2-Tetrachloroethane <sub>A</sub>	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Chlorobenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Ethylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
m & p Xylene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Bromoform <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Styrene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,1,2,2-Tetrachloroethane <sub>A</sub>	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
o-Xylene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,2,3-Trichloropropane <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Isopropylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
Bromobenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
2-Chlorotoluene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
n-propylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
4-Chlorotoluene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,2,4-Trimethylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
4-Isopropyltoluene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,3,5-Trimethylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,2-Dichlorobenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,4-Dichlorobenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
sec-Butylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
tert-Butylbenzene <sub>A</sub> #	<2	<2	<2	<2	<2	<2	<2	<2	μg/l	A-T-006
1,3-Dichlorobenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
n-butylbenzene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
1,2-Dibromo-3-chloropropane <sub>A</sub> #	<2	<2	<2	<2	<2	<2	<2	<2	μg/l	A-T-006
1,2,4-Trichlorobenzene <sub>A</sub> #	<3	<3	<3	<3	<3	<3	<3	<3	μg/l	A-T-006
1,2,3-Trichlorobenzene <sub>A</sub> #	<3	<3	<3	<3	<3	<3	<3	<3	μg/l	A-T-006
Hexachlorobutadiene <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-006
	•				•					



					Cilent	Project Ref	. 312494			
Lab Sample ID	13/05152/1	13/05152/2	13/05152/3	13/05152/4	13/05152/6	13/05152/7	13/05050/1	13/05050/2		
Client Sample No							Deep			
Client Sample ID	CP220	CP210	CP213	CP217	CP212	CP204	CPR206	CPR204		
Depth to Top							14.68			
Depth To Bottom										
Date Sampled	23-Oct-13	24-Oct-13	24-Oct-13	23-Oct-13	24-Oct-13	22-Oct-13	22-Oct-13	22-Oct-13		<del>-</del>
Sample Type	Water - W	Water - W	Water - W	60	Method ref					
Sample Matrix Code									Units	Meth
TPH CWG										
Ali >C5-C6 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Ali >C6-C8 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Ali >C8-C10 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Ali >C10-C12 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Ali >C12-C16 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Ali >C16-C21 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Ali >C21-C35 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Total Aliphatics (w) <sub>A</sub>	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-022+23w
Aro >C5-C7 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Aro >C7-C8 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Aro >C8-C9 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Aro >C9-C10 (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
Aro >C10-C12 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Aro >C12-C16 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Aro >C16-C21 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Aro >C21-C35 (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
Total Aromatics (w) <sub>A</sub>	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-022+23w
TPH (Ali & Aro) (w) <sub>A</sub>	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-022+23w
Mineral Oil (>C10-C35) (w) <sub>A</sub> #	<5	<5	<5	<5	<5	<5	<5	<5	μg/l	A-T-023w
BTEX - Benzene (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
BTEX - Toluene (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
BTEX - Ethyl Benzene (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
BTEX - m & p Xylene (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
BTEX - o Xylene (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w
MTBE (w) <sub>A</sub> #	<1	<1	<1	<1	<1	<1	<1	<1	μg/l	A-T-022w



#### **REPORT NOTES**

#### Notes - Soil analysis

All results are reported as dry weight (<40 ℃).

For samples with Matrix Codes 1 - 6 natural stones >10mm are removed or excluded from the sample prior to analysis and reported results corrected to a whole sample basis. For samples with Matrix Code 7 the whole sample is dried and crushed prior to analysis.

#### Notes - General

Subscript "A" indicates analysis performed on the sample as received. "D" indicates analysis performed on the dried sample, crushed to pass a 2mm sieve, unless asbestos is found to be present in which case all analysis is performed on the sample as received.

All analysis is performed on the dried and crushed sample for samples with Matrix Code 7 and this supercedes any "A" subscripts.

All analysis is performed on the sample as received for soil samples from outside the European Union and this supercedes any "D" subscripts.

Superscript "M" indicates method accredited to MCERTS.

For complex, multi-compound analysis, quality control results do not always fall within chart limits for every compound and we have criteria for reporting in these situations. If results are in italic font they are associated with such quality control failures and may be unreliable.

A deviating samples report is appended and will indicate if samples or tests have been found to be deviating. Any test results affected may not be an accurate record of the concentration at the time of sampling.

#### TPH analysis of water by method A-T-007

Free and visible oils are excluded from the sample used for analysis so that the reported result represents the dissolved phase only.

#### Asbestos in soil

Asbestos in soil analysis is performed on an aliquot of the submitted sample and cannot guarantee to identify asbestos if present at low concentrations or as discrete fibres/fragments.

Quantification of asbestos is a 3 stage process including visual identification, hand picking and weighing and fibre counting by sedimentation/phase contrast optical microscopy if required. If asbestos is identified a being present but is not in a form that is suitable for analysis by hand picking and weighing (normally if the asbestos is present as free fibres) quantification by sedimentation is performed. Where ACMs are found a percentage asbestos is assigned to each with reference to 'HSG264, Asbestos: The survey guide' and the calculated asbestos content is expressed as a percentage of the dried soil sample aliquot used.

#### **Predominant Matrix Codes:**

1 = SAND, 2 = LOAM, 3 = CLAY, 4 = LOAM/SAND, 5 = SAND/CLAY, 6 = CLAY/LOAM, 7 = OTHER. Samples with Matrix Code 7 are not predominantly a SAND/LOAM/CLAY mix and are not covered by our MCERTS accreditation.

#### Secondary Matrix Codes:

A = contains stones, B = contains construction rubble, C = contains visible hydrocarbons, D = contains glass/metal, E = contains roots/twigs.

IS indicates Insufficient sample for analysis.

NDP indicates No Determination Possible.

NAD indicates No Asbestos Detected.

N/A indicates Not Applicable.

Superscript # indicates method accredited to ISO 17025.

Analytical results reflect the quality of the sample at the time of analysis only. Opinions and interpretations expressed are outside the scope of our accreditation.

Please contact us if you need any further information.



# APPENDIX J GAS AND GROUNDWATER MONITORING RESULTS

[Pressures]	<u>Previous</u>	<u>During</u>	<u>Start</u>	<u>End</u>	Equipment Used & Remarks
Round 1 Round 2 Round 3 Round 4	- - -	Constant Constant Constant Constant	1003 984 1012 1020	1003 984 1012 1020	Dipmeter + GA2000 SN-GA07744 + Weather: Overcast + Ground: Wet + Wind: None + Air Temp: 12DegC Dipmeter + GA2000 SN-GA07744 + Weather: Overcast + Ground: Wet + Wind: None + Air Temp: 15DegC Dipmeter + GA2000 SN-GA07744 + Weather: Sunny + Ground: Wet + Wind: None + Air Temp: 12DegC Dipmeter + GA2000 SN-GA07744 + Weather: Overcast + Ground: Wet + Wind: None + Air Temp: 10DegC

Exploratory Position ID	Monitoring Round	Measured Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP203	1	3.77	16/10/2013 12:33:00	1003	1003	-	DRY	0.1	0.0	20.7	0.0	0.0	0.0	
CP203	1		15 secs	-	-	-	-	1.5	0.0	19.9	0.0	0.0	0.0	
CP203	1		30 secs	-	-	-	-	1.4	0.0	18.8	0.0	0.0	0.0	
CP203	1		60 secs	-	-	-	-	1.4	0.0	19.0	0.0	0.0	0.0	
CP203	1		90 secs	-	-	-	-	1.5	0.0	18.9	0.0	0.0	0.0	
CP203	1		120 secs	-	-	ı	-	1.4	0.0	18.9	0.0	0.0	0.0	
CP203	1		180 secs	-	-	-	-	1.5	0.0	19.0	0.0	0.0	0.0	
CP203	1		240 secs	-	-	-	-	1.5	0.0	19.0	0.0	0.0	0.0	
CP203	1		300 secs	-	-	-	-	1.6	0.0	19.0	0.0	0.0	0.0	
CP203	2	3.78	23/10/2013 13:42:00	987	987	-0.1 <sub>(I)</sub>	DRY	0.0	0.0	20.8	0.0	0.0	0.0	
CP203	2		15 secs	-	-	$0.0_{(SS)}$	-	1.9	0.0	19.9	0.0	0.0	0.0	
CP203	2		30 secs	-	-	-	-	1.8	0.1	19.8	1.0	0.0	0.0	
CP203	2		60 secs	-	-	-	-	2.0	0.0	18.6	0.0	0.0	0.0	
CP203	2		90 secs	-	-	-	-	2.0	0.0	18.5	0.0	0.0	0.0	
CP203	2		120 secs	-	-	-	-	2.0	0.0	18.6	0.0	0.0	0.0	
CP203	2		180 secs	-	-	-	-	2.0	0.0	18.8	0.0	0.0	0.0	
CP203	2		240 secs	-	-	-	-	2.1	0.0	18.7	0.0	0.0	0.0	
CP203	2		300 secs	-	-	-	-	2.0	0.0	18.7	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

1				
Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:				Page:

**East Midlands Gateway** 

1 of **36** 

312494

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP203	3	3.74	30/10/2013 16:50:00	1010	1010	0.0(1)	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP203	3		15 secs	-	-	$0.0_{(SS)}$	-	1.4	0.0	18.1	0.0	0.0	0.0	
CP203	3		30 secs	-	-	-	-	1.7	0.0	17.8	0.0	0.0	0.0	
CP203	3		60 secs	-	-	-	-	1.6	0.1	17.8	1.0	0.0	0.0	
CP203	3		90 secs	-	-	-	-	1.6	0.1	17.8	1.0	0.0	0.0	
CP203	3		120 secs	-	-	-	-	1.7	0.1	17.7	1.0	0.0	0.0	
CP203	3		180 secs	-	-	-	-	1.4	0.1	18.2	1.0	0.0	0.0	
CP203	3		240 secs	-	-	-	-	1.6	0.1	18.1	1.0	0.0	0.0	
CP203	3		300 secs	-	-	-	-	1.5	0.1	18.4	1.0	0.0	0.0	
CP203	4	3.76	12/11/2013 10:22:00	1020	1020	$0.3_{(I)}$	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP203	4		15 secs	-	-	$0.1_{(SS)}$	-	1.4	0.0	18.6	0.0	0.0	0.0	
CP203	4		30 secs	-	-	-	-	1.2	0.0	17.9	0.0	0.0	0.0	
CP203	4		60 secs	-	-	-	-	1.2	0.0	17.8	0.0	13.0	0.0	
CP203	4		90 secs	-	-	-	-	1.3	0.0	17.8	0.0	0.0	0.0	
CP203	4		120 secs	-	-	-	-	1.3	0.0	17.9	0.0	0.0	0.0	
CP203	4		180 secs	-	-	-	-	1.3	0.0	17.8	0.0	2.0	0.0	
CP203	4		240 secs	-	-	-	-	1.3	0.0	18.0	0.0	4.0	0.0	
CP203	4		300 secs	-	-	-	-	1.3	0.0	17.9	0.0	0.0	0.0	
CP204	1	3.90	17/10/2013 16:06:00	1010	1010	-	DRY	0.0	0.0	20.8	0.0	0.0	0.0	
CP204	1		15 secs	-	-	-	-	1.1	0.0	18.9	0.0	0.0	0.0	
CP204	1		30 secs	-	-	-	-	1.1	0.0	16.7	0.0	0.0	0.0	
CP204	1		60 secs	-	-	-	-	1.1	0.0	16.3	0.0	0.0	0.0	
CP204	1		90 secs	-	-	-	-	1.2	0.0	16.4	0.0	0.0	0.0	
CP204	1		120 secs	-	-	-	-	1.2	0.0	16.4	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment** Abbey Park Humber Road Coventry CV3 4AQ

Ltd	
	Cont

Compiled By	Date		Checked By		
	28/11/13				
Contract:					
	<b>East Midlands Gateway</b>				

Contract Ref: Date 28/11/13 Page:

312494

of **36** 



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP204	1		180 secs	-	-	-	-	1.3	0.0	16.3	0.0	0.0	0.0	
CP204	1		240 secs	-	-	-	-	1.4	0.0	15.9	0.0	0.0	0.0	
CP204	1		300 secs	-	-	-	-	1.4	0.0	15.8	0.0	0.0	0.0	
CP204	2	3.91	22/10/2013 15:38:00	983	983	$0.0_{(I)}$	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP204	2		15 secs	-	-	$0.0_{(SS)}$	-	0.7	0.0	20.0	0.0	0.0	0.0	
CP204	2		30 secs	-	-	-	-	1.0	0.0	18.6	0.0	0.0	0.0	
CP204	2		60 secs	-	-	-	-	1.3	0.0	17.4	0.0	0.0	0.0	
CP204	2		90 secs	-	-	-	-	1.4	0.1	16.8	1.0	0.0	0.0	
CP204	2		120 secs	-	-	-	-	1.5	0.0	16.7	0.0	0.0	0.0	
CP204	2		180 secs	-	-	-	-	1.6	0.1	16.6	1.0	0.0	0.0	
CP204	2		240 secs	-	-	-	-	1.7	0.0	16.6	0.0	0.0	0.0	
CP204	2		300 secs	-	-	-	-	1.7	0.0	16.7	0.0	0.0	0.0	
CP204	3	3.95	30/10/2013 16:00:00	1009	1009	$0.0_{(I)}$	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP204	3		15 secs	-	-	$0.0_{(SS)}$	-	0.9	0.0	18.5	0.0	0.0	0.0	
CP204	3		30 secs	-	-	-	-	0.9	0.0	17.6	0.0	0.0	0.0	
CP204	3		60 secs	-	-	-	-	0.9	0.0	17.6	0.0	0.0	0.0	
CP204	3		90 secs	-	-	-	-	0.9	0.0	17.5	0.0	0.0	0.0	
CP204	3		120 secs	-	-	-	-	0.9	0.0	17.5	0.0	0.0	0.0	
CP204	3		180 secs	-	-	-	-	0.9	0.0	17.5	0.0	0.0	0.0	
CP204	3		240 secs	-	-	-	-	0.9	0.0	17.5	0.0	0.0	0.0	
CP204	3		300 secs	-	-	-	-	0.9	0.0	17.5	0.0	0.0	0.0	
CP204	4	3.88	12/11/2013 11:36:00	1020	1020	-0.4 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP204	4		15 secs	-	-	0.0 <sub>(SS)</sub>	-	0.1	0.0	20.1	0.0	0.0	0.0	
CP204	4		30 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP204	4		60 secs	-	-	-	-	0.1	0.0	20.4	0.0	3.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	Date
	28/11/13		28/11/13
Contract:			•
	East Midlan	ds Gateway	

Contract Ref:

312494

Page:

**3** of **36** 



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP204	4		90 secs	-	-	-	-	0.1	0.0	20.5	0.0	9.0	0.0	
CP204	4		120 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP204	4		180 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP204	4		240 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP204	4		300 secs	-	-	-	-	0.1	0.0	20.5	0.0	1.0	0.0	
CP205	1	4.37	16/10/2013 12:43:00	1003	1003		4.13	0.1	0.0	20.7	0.0	0.0	0.0	
	1		15 secs			-		0.1	0.0	20.7		0.0	0.0	
CP205 CP205	1		30 secs	-	-	-	-	1.1	0.0	19.8	0.0	0.0	0.0	
	1		60 secs	-	-	-	-	1.1	0.0	19.8	0.0	0.0	0.0	
CP205 CP205	1		90 secs	-	-	-	-	1.2	0.0	19.7	0.0	0.0	0.0	
	_		120 secs	-	-	-	-			-,,,,				
CP205 CP205	1		120 secs	-	-	-	-	1.2	0.0	19.8 19.7	0.0	0.0	0.0	
	1		240 secs	-	-	-	-			19.7				
CP205 CP205	1		300 secs	-	-	-	-	1.2	0.0	19.7	0.0	0.0	0.0	
CP205	-	4.37	23/10/2013 14:06:00	987	987	-	4.12	0.1	0.0	20.8	0.0	0.0	0.0	
CP205	2 2		15 secs	987	987	0.0 <sub>(I)</sub>	4.12	1.3	0.0	19.6	0.0	0.0	0.0	
CP205	2		30 secs			0.0 <sub>(SS)</sub>		1.3	0.0	18.8	0.0	0.0	0.0	
CP205	2		60 secs	-	-		-	1.3	0.0	18.5	0.0	0.0	0.0	
CP205	2		90 secs					1.4	0.0	18.6	0.0	0.0	0.0	
CP205	2		120 secs	-	-	-		1.4	0.0	18.6	0.0	0.0	0.0	
CP205	2		180 secs	-	-	-	-	1.4	0.0	18.6	0.0	0.0	0.0	
CP205	2		240 secs	_	_		-	1.4	0.0	18.6	0.0	0.0	0.0	
CP205	2		300 secs		_		_	1.4	0.0	18.6	0.0	0.0	0.0	
							4 10							
CP205	3	4.37	30/10/2013 09:25:00	1010	1012	-2.5 <sub>(I)</sub>	4.19	0.1	0.0	20.8	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Ch	ecked By	Date						
	28/11/13			28/11/13						
Contract:										
	East Midlands Gateway									

Page:

Contract Ref:

312494

4 of **36** 

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP205	3		15 secs	-	-	-2.5 <sub>(SS)</sub>	-	0.9	0.0	20.5	0.0	0.0	0.0	
CP205	3		30 secs	-	-	-	-	1.1	0.0	19.2	0.0	0.0	0.0	
CP205	3		60 secs	-	-	-	-	1.1	0.0	18.8	0.0	0.0	0.0	
CP205	3		90 secs	-	-	-	-	1.1	0.0	18.9	0.0	0.0	0.0	
CP205	3		120 secs	-	-	-	-	1.1	0.0	18.8	0.0	0.0	0.0	
CP205	3		180 secs	-	-	-	-	1.1	0.0	18.9	0.0	0.0	0.0	
CP205	3		240 secs	-	-	-	-	1.1	0.0	18.8	0.0	0.0	0.0	
CP205	3		300 secs	-	-	-	-	1.1	0.0	18.8	0.0	0.0	0.0	
CP205	4	4.37	12/11/2013 09:45:00	1020	1020	1.0 <sub>(I)</sub>	4.20	0.1	0.0	20.8	0.0	0.0	0.0	
CP205	4		15 secs	-	-	$0.4_{(SS)}$	-	0.6	0.0	20.3	0.0	0.0	0.0	
CP205	4		30 secs	-	-	-	-	1.1	0.0	18.9	0.0	0.0	0.0	
CP205	4		60 secs	-	-	-	-	1.2	0.0	18.9	0.0	0.0	0.0	
CP205	4		90 secs	-	-	-	-	1.2	0.0	18.8	0.0	0.0	0.0	
CP205	4		120 secs	-	-	-	-	1.2	0.0	18.9	0.0	0.0	0.0	
CP205	4		180 secs	-	-	-	-	1.2	0.0	18.8	0.0	0.0	0.0	
CP205	4		240 secs	-	-	-	-	1.2	0.0	19.0	0.0	0.0	0.0	
CP205	4		300 secs	-	-	-	-	1.2	0.0	19.0	0.0	0.0	0.0	
CP206	1	3.22	16/10/2013 13:37:00	1003	1003	-	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP206	1		15 secs	-	-	-	-	2.5	0.0	18.8	0.0	0.0	0.0	
CP206	1		30 secs	-	-	-	-	2.6	0.0	16.0	0.0	0.0	0.0	
CP206	1		60 secs	-	-	-	-	2.6	0.0	15.6	0.0	0.0	0.0	
CP206	1		90 secs	-	-	-	-	2.6	0.0	15.5	0.0	0.0	0.0	
CP206	1		120 secs	-	-	-	-	2.7	0.0	15.5	0.0	0.0	0.0	
CP206	1		180 secs	-	-	-	-	2.7	0.0	15.5	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK KS.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By
	28/11/13	
Contract:	E4 M: 11	d. C.
	East Midlar	rds (-a

Date Contract Ref:

28/11/13 312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP206	1		240 secs	-	-	-	-	2.7	0.0	15.6	0.0	0.0	0.0	
CP206	1		300 secs	-	-	-	-	2.8	0.0	15.7	0.0	0.0	0.0	
CP206	2	3.23	22/10/2013 14:26:30	988	988	0.4 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP206	2		15 secs	-	-	0.3 <sub>(SS)</sub>	-	2.5	0.0	15.4	0.0	0.0	0.0	
CP206	2		30 secs	-	-	-	-	3.4	0.0	12.6	0.0	0.0	0.0	
CP206	2		60 secs	-	-	-	-	3.5	0.0	12.4	0.0	0.0	0.0	
CP206	2		90 secs	-	-	-	-	3.5	0.0	12.6	0.0	0.0	0.0	
CP206	2		120 secs	-	-	-	-	3.5	0.0	12.5	0.0	0.0	0.0	
CP206	2		180 secs	-	-	-	-	3.5	0.0	12.6	0.0	0.0	0.0	
CP206	2		240 secs	-	-	-	-	3.5	0.0	12.6	0.0	0.0	0.0	
CP206	2		300 secs	-	-	-	-	3.5	0.0	12.7	0.0	0.0	0.0	
CP206	3	3.29	30/10/2013 09:43:00	1012	1012	-0.7 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP206	3		15 secs	-	-	-0.5 <sub>(SS)</sub>	-	2.7	0.0	19.3	0.0	0.0	0.0	
CP206	3		30 secs	1	-	•	-	2.9	0.0	14.9	0.0	0.0	0.0	
CP206	3		60 secs	-	-	-	-	2.9	0.0	14.7	0.0	0.0	0.0	
CP206	3		90 secs	ı	-	ı	-	2.9	0.0	14.7	0.0	0.0	0.0	
CP206	3		120 secs	-	-	-	-	2.9	0.0	14.7	0.0	0.0	0.0	
CP206	3		180 secs	-	-	-	-	2.9	0.0	14.9	0.0	0.0	0.0	
CP206	3		240 secs	-	-	-	-	2.9	0.0	14.9	0.0	0.0	0.0	
CP206	3		300 secs	-	-	-	-	2.9	0.0	14.9	0.0	0.0	0.0	
CP206	4	3.21	11/11/2013 16:44:00	1017	1017	$0.0_{(I)}$	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP206	4		15 secs	-	-	0.0 <sub>(SS)</sub>	-	3.3	0.0	12.9	0.0	0.0	0.0	
CP206	4		30 secs	-	-	-	-	3.5	0.0	12.2	0.0	7.0	0.0	
CP206	4		60 secs	-	-	-	-	3.5	0.0	12.1	0.0	0.0	0.0	
CP206	4		90 secs	-	-	-	-	3.5	0.0	12.0	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment** Abbey Park Humber Road Coventry CV3 4AQ

t Ltd	L
[	ŀ
-	

Ltd	
200	
	Cc

Compiled By ontract:

Date 28/11/13

**East Midlands Gateway** 

Checked By

Date 28/11/13 Contract Ref:

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP206	4		120 secs	-	-	-	-	3.5	0.0	12.1	0.0	2.0	0.0	
CP206	4		180 secs	-	-	-	-	3.5	0.0	12.1	0.0	0.0	0.0	
CP206	4		240 secs	-	-	-	-	3.4	0.0	12.2	0.0	7.0	0.0	
CP206	4		300 secs	-	-	-	-	3.4	0.0	12.3	0.0	0.0	0.0	
CP207	1	2.68	16/10/2013 15:32:00	1003	1003	-	DRY	0.1	0.0	20.7	0.0	0.0	0.0	
CP207	1		15 secs	-	-	-	-	1.4	0.0	19.6	0.0	0.0	0.0	
CP207	1		30 secs	1	-	-	-	1.5	0.0	13.4	0.0	0.0	0.0	
CP207	1		60 secs	-	-	-	-	1.5	0.0	13.2	0.0	0.0	0.0	
CP207	1		90 secs	-	-	-	-	1.5	0.0	13.0	0.0	0.0	0.0	
CP207	1		120 secs	-	-	-	-	1.5	0.0	17.9	0.0	0.0	0.0	
CP207	1		180 secs	-	-	-	-	1.5	0.0	17.8	0.0	0.0	0.0	
CP207	1		240 secs	-	-	-	-	1.5	0.0	17.8	0.0	0.0	0.0	
CP207	1		300 secs	1	-	-	-	1.5	0.0	17.8	0.0	0.0	0.0	
CP207	2	2.70	23/10/2013 14:40:00	987	987	$0.0_{(I)}$	DRY	0.0	0.0	20.8	0.0	0.0	0.0	
CP207	2		15 secs	1	-	$0.0_{(SS)}$	-	1.7	0.0	19.0	0.0	0.0	0.0	
CP207	2		30 secs	-	-	-	-	1.8	0.1	18.5	1.0	0.0	0.0	
CP207	2		60 secs	-	-	-	-	1.7	0.1	18.4	1.0	0.0	0.0	
CP207	2		90 secs	-	-	-	-	1.8	0.1	18.4	1.0	0.0	0.0	
CP207	2		120 secs	-	-	-	-	1.8	0.0	18.5	0.0	0.0	0.0	
CP207	2		180 secs	-	-	-	-	1.8	0.0	18.4	0.0	0.0	0.0	
CP207	2		240 secs	-	-	-	-	1.8	0.0	18.5	0.0	0.0	0.0	
CP207	2		300 secs	-	-	-	-	1.9	0.0	18.5	0.0	0.0	0.0	
CP207	3	2.69	30/10/2013 16:42:00	1010	1010	0.0 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP207	3		15 secs	-	-	$0.0_{(SS)}$	-	1.8	0.0	19.2	0.0	0.0	0.0	

**East Midlands Gateway** 

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment Lt** Abbey Park Humber Road Coventry CV3 4AQ

td		Compiled 1
rta		
	Contract:	

Compiled By	Date	Checked By
	28/11/13	
Contract:	•	

Date 28/11/13

Contract Ref:

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP207	3		30 secs	-	-	-	-	1.8	0.0	18.6	0.0	0.0	0.0	
CP207	3		60 secs	-	-	-	-	1.8	0.0	18.4	0.0	0.0	0.0	
CP207	3		90 secs	-	-	-	-	1.8	0.0	18.4	0.0	0.0	0.0	
CP207	3		120 secs	-	-	-	-	1.8	0.0	18.3	0.0	0.0	0.0	
CP207	3		180 secs	-	-	-	-	1.9	0.0	18.2	0.0	0.0	0.0	
CP207	3		240 secs	-	-	-	-	1.9	0.0	18.1	0.0	0.0	0.0	
CP207	3		300 secs	-	-	-	-	1.9	0.0	18.0	0.0	0.0	0.0	
CP207	4	2.67	11/11/2013 16:08:00	1017	1017	0.1 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP207	4		15 secs	-	-	$0.0_{(SS)}$	-	0.7	0.0	19.9	0.0	0.0	0.0	
CP207	4		30 secs	-	-	-	-	1.4	0.0	18.2	0.0	24.0	0.0	
CP207	4		60 secs	-	-	-	-	1.8	0.0	17.5	0.0	0.0	0.0	
CP207	4		90 secs	-	-	-	-	1.8	0.0	17.6	0.0	5.0	0.0	
CP207	4		120 secs	-	-	-	-	1.9	0.0	17.6	0.0	0.0	0.0	
CP207	4		180 secs	-	-	-	-	1.9	0.0	17.5	0.0	9.0	0.0	
CP207	4		240 secs	-	-	-	-	1.9	0.0	17.5	0.0	0.0	0.0	
CP207	4		300 secs	-	-	-	-	1.9	0.0	17.5	0.0	4.0	0.0	
CP208	1	1.90	16/10/2013 15:16:41	1003	1003	-	DRY	0.0	0.0	20.7	0.0	0.0	0.0	
CP208	1		15 secs	-	-	-	-	1.2	0.1	19.5	1.0	0.0	0.0	
CP208	1		30 secs	-	-	-	-	1.2	0.1	17.4	1.0	0.0	0.0	
CP208	1		60 secs	-	-	-	-	1.2	0.1	17.4	1.0	0.0	0.0	
CP208	1		90 secs	-	-	-	-	1.2	0.1	17.4	1.0	0.0	0.0	
CP208	1		120 secs	-	-	-	-	1.2	0.0	17.4	0.0	0.0	0.0	
CP208	1		180 secs	-	-	-	-	1.2	0.0	17.4	0.0	0.0	0.0	
CP208	1		240 secs	-	-	-	-	1.2	0.0	17.5	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry

CV3 4AQ

Compiled By Date Checked By 28/11/13 Contract: **East Midlands Gateway** 

28/11/13

Date

312494

Page:

Contract Ref:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP208	1		300 secs	-	-	-	-	1.2	0.0	17.3	0.0	0.0	0.0	
CP208	2	1.88	24/10/2013 13:00:00	1005	1005	-0.1 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP208	2		15 secs	-	-	0.0 <sub>(SS)</sub>	-	1.2	0.0	19.0	0.0	0.0	0.0	
CP208	2		30 secs	-	-	-	-	1.3	0.0	16.0	0.0	0.0	0.0	
CP208	2		60 secs	-	-	-	-	1.3	0.0	15.7	0.0	0.0	0.0	
CP208	2		90 secs	-	-	-	-	1.3	0.0	15.7	0.0	0.0	0.0	
CP208	2		120 secs	-	-	-	-	1.3	0.0	15.7	0.0	0.0	0.0	
CP208	2		180 secs	-	-	-	-	1.3	0.0	15.6	0.0	0.0	0.0	
CP208	2		240 secs	-	-	-	-	1.3	0.0	15.6	0.0	0.0	0.0	
CP208	2		300 secs	-	-	-	-	1.3	0.0	15.6	0.0	0.0	0.0	
CP208	3	1.90	30/10/2013 16:10:00	1009	1009	-0.1 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP208	3		15 secs	-	-	$0.0_{(SS)}$	-	1.0	0.0	17.7	0.0	0.0	0.0	
CP208	3		30 secs	-	-	-	-	1.0	0.0	16.5	0.0	0.0	0.0	
CP208	3		60 secs	-	-	-	-	1.0	0.0	16.3	0.0	0.0	0.0	
CP208	3		90 secs	-	-	-	-	1.0	0.0	16.3	0.0	0.0	0.0	
CP208	3		120 secs	-	-	-	-	1.0	0.0	16.3	0.0	0.0	0.0	
CP208	3		180 secs	-	-	-	-	1.0	0.0	16.2	0.0	0.0	0.0	
CP208	3		240 secs	ı	-	-	-	1.1	0.0	16.2	0.0	0.0	0.0	
CP208	3		300 secs	-	-	-	-	1.1	0.0	16.0	0.0	0.0	0.0	
CP208	4	1.86	11/11/2013 15:36:00	1016	1017	0.9 <sub>(I)</sub>	1.85	0.1	0.0	20.8	0.0	0.0	0.0	
CP208	4		15 secs	-	-	$0.2_{(SS)}$	-	0.8	0.0	18.2	0.0	0.0	0.0	
CP208	4		30 secs	-	-	-	-	0.9	0.0	16.4	0.0	0.0	0.0	
CP208	4		60 secs	-	-	-	-	1.0	0.0	15.9	0.0	0.0	0.0	
CP208	4		90 secs	-	-	-	-	1.0	0.0	15.6	0.0	0.0	0.0	
CP208	4		120 secs	-	-	-	-	1.0	0.0	15.5	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd

Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date		Checked By	Date	Contract Ref:
	28/11/13			28/11/13	
Contract:		!			Page:

**East Midlands Gateway** 

9 of **36** 



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP208	4		180 secs	-	-	-	-	1.0	0.0	15.5	0.0	0.0	0.0	
CP208	4		240 secs	-	-	-	-	1.0	0.0	15.6	0.0	0.0	0.0	
CP208	4		300 secs	-	-	-	-	1.0	0.0	15.5	0.0	0.0	0.0	
CP210	1	9.05	17/10/2013 16:31:11	1012	1010	-	5.47	0.0	0.0	20.8	0.0	0.0	0.0	
CP210	1		15 secs	-	-	-	-	0.5	0.0	19.0	0.0	0.0	0.0	
CP210	1		30 secs	-	-	-	-	0.5	0.0	18.1	0.0	0.0	0.0	
CP210	1		60 secs	-	-	-	-	0.5	0.0	18.1	0.0	0.0	0.0	
CP210	1		90 secs	-	-	-	-	0.5	0.0	18.3	0.0	0.0	0.0	
CP210	1		120 secs	-	-	-	-	0.5	0.0	18.3	0.0	0.0	0.0	
CP210	1		180 secs	-	-	-	-	0.5	0.0	18.3	0.0	0.0	0.0	
CP210	1		240 secs	-	-	-	-	0.5	0.0	18.3	0.0	0.0	0.0	
CP210	1		300 secs	-	-	-	-	0.5	0.0	18.3	0.0	0.0	0.0	
CP210	2	9.05	23/10/2013 09:44:00	984	984	$0.0_{(I)}$	4.77	0.0	0.0	20.8	0.0	0.0	0.0	
CP210	2		15 secs	-	-	0.1 <sub>(SS)</sub>	-	0.5	0.0	19.2	0.0	0.0	0.0	
CP210	2		30 secs	-	-	-	-	0.5	0.0	19.1	0.0	0.0	0.0	
CP210	2		60 secs	-	-	-	-	0.4	0.0	19.4	0.0	0.0	0.0	
CP210	2		90 secs	-	-	-	-	0.4	0.0	19.5	0.0	0.0	0.0	
CP210	2		120 secs	-	1	-	-	0.4	0.0	19.5	0.0	0.0	0.0	
CP210	2		180 secs	-	-	-	-	0.4	0.0	19.6	0.0	0.0	0.0	
CP210	2		240 secs	-	-	-	-	0.4	0.0	19.7	0.0	0.0	0.0	
CP210	2		300 secs	-	-	-	-	0.4	0.0	19.7	0.0	0.0	0.0	
CP210	3	9.03	30/10/2013 14:35:00	1009	1009	0.0 <sub>(I)</sub>	3.88	0.1	0.0	20.8	0.0	0.0	0.0	
CP210	3		15 secs	-	-	$0.0_{(SS)}$	-	1.7	0.0	19.5	0.0	0.0	0.0	
CP210	3		30 secs	-	-	-	-	1.7	0.0	18.6	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK** 

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By
	28/11/13	
Contract:		
	East Midlar	nds Gateway

Date Contract Ref: **28/11/13** 

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP210	3		60 secs	-	-	-	-	1.4	0.0	18.7	0.0	0.0	0.0	
CP210	3		90 secs	-	-	-	-	1.4	0.0	18.9	0.0	0.0	0.0	
CP210	3		120 secs	-	-	-	-	1.4	0.0	18.8	0.0	0.0	0.0	
CP210	3		180 secs	-	-	-	-	0.8	0.0	19.5	0.0	0.0	0.0	
CP210	3		240 secs	-	-	-	-	0.9	0.0	19.3	0.0	0.0	0.0	
CP210	3		300 secs	-	-	-	-	0.8	0.0	19.3	0.0	0.0	0.0	
CP210	4	9.04	12/11/2013 12:22:00	1019	1020	0.0(1)	3.27	0.1	0.0	20.8	0.0	0.0	0.0	
CP210	4		15 secs	-	-	1.6 <sub>(SS)</sub>	-	1.5	0.0	18.3	0.0	0.0	0.0	
CP210	4		30 secs	-	-	-	-	2.4	0.0	15.1	0.0	5.0	0.0	
CP210	4		60 secs	-	-	-	-	2.4	0.0	15.0	0.0	0.0	0.0	
CP210	4		90 secs	-	-	-	-	2.1	0.0	15.4	0.0	0.0	0.0	
CP210	4		120 secs	-	-	-	-	2.1	0.0	15.5	0.0	0.0	0.0	
CP210	4		180 secs	-	-	-	-	2.1	0.0	15.5	0.0	0.0	0.0	
CP210	4		240 secs	-	-	-	-	2.0	0.0	15.7	0.0	0.0	0.0	
CP210	4		300 secs	-	-	-	-	2.0	0.0	15.9	0.0	0.0	0.0	
CP211	1	6.68	17/10/2013 16:43:18	1010	1010	-	DRY	0.0	0.0	20.8	0.0	0.0	0.0	
CP211	1		15 secs	-	-	-	-	1.9	0.0	16.0	0.0	0.0	0.0	
CP211	1		30 secs	-	-	-	-	2.0	0.0	12.2	0.0	0.0	0.0	
CP211	1		60 secs	-	-	-	-	2.0	0.0	11.9	0.0	0.0	0.0	
CP211	1		90 secs	-	-	-	-	2.0	0.0	11.8	0.0	0.0	0.0	
CP211	1		120 secs	-	-	-	-	2.0	0.0	11.7	0.0	0.0	0.0	
CP211	1		180 secs	-	-	-	-	2.0	0.0	11.8	0.0	0.0	0.0	
CP211	1		240 secs	-	-	-	-	2.0	0.0	11.6	0.0	0.0	0.0	
CP211	1		300 secs	-	-	-	-	2.0	0.0	11.8	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK En Ab Hun

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By
	28/11/13	
Contract:		
	East Midlan	ds Gateway

Contract Ref:

312494

Page:

Date

28/11/13



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP211	2	6.67	24/10/2013 10:40:00	1005	1005	-0.1 <sub>(I)</sub>	6.14	0.0	0.0	20.8	0.0	0.0	0.0	
CP211	2		15 secs	-	-	0.0 <sub>(SS)</sub>	-	2.5	0.0	17.4	0.0	0.0	0.0	
CP211	2		30 secs	-	-	-	-	2.6	0.0	10.9	0.0	0.0	0.0	
CP211	2		60 secs	-	-	-	-	2.6	0.0	10.8	0.0	0.0	0.0	
CP211	2		90 secs	-	-	-	-	2.6	0.0	10.8	0.0	0.0	0.0	
CP211	2		120 secs	-	-	-	-	2.6	0.0	10.8	0.0	0.0	0.0	
CP211	2		180 secs	-	-	-	-	2.6	0.0	10.9	0.0	0.0	0.0	
CP211	2		240 secs	ı	-	-	-	2.6	0.0	10.9	0.0	0.0	0.0	
CP211	2		300 secs	1	-	-	-	2.6	0.0	10.9	0.0	0.0	0.0	
CP211	3	6.67	30/10/2013 14:00:00	1008	1009	$-0.1_{(I)}$	6.14	0.1	0.0	20.8	0.0	0.0	0.0	
CP211	3		15 secs	-	-	$0.0_{(SS)}$	-	2.1	0.0	15.1	0.0	0.0	0.0	
CP211	3		30 secs	-	-	-	-	2.1	0.0	13.6	0.0	0.0	0.0	
CP211	3		60 secs	-	-	-	-	1.9	0.0	13.9	0.0	0.0	0.0	
CP211	3		90 secs	-	-	-	-	2.0	0.0	13.7	0.0	0.0	0.0	
CP211	3		120 secs	-	-	-	-	1.9	0.0	14.0	0.0	0.0	0.0	
CP211	3		180 secs	-	-	-	-	1.8	0.0	14.3	0.0	0.0	0.0	
CP211	3		240 secs	-	-	-	-	1.9	0.0	14.1	0.0	0.0	0.0	
CP211	3		300 secs	-	-	-	-	1.8	0.0	14.5	0.0	0.0	0.0	
CP211	4	6.65	12/11/2013 12:53:00	1018	1020	$0.1_{(I)}$	5.96	0.1	0.0	20.8	0.0	0.0	0.0	
CP211	4		15 secs	-	-	$0.1_{(SS)}$	-	0.3	0.0	20.1	0.0	0.0	0.0	
CP211	4		30 secs	-	-	-	-	2.3	0.0	9.6	0.0	7.0	0.0	
CP211	4		60 secs	-	-	-	-	2.3	0.0	9.2	0.0	0.0	0.0	
CP211	4		90 secs	-	-	-	-	2.2	0.0	9.3	0.0	0.0	0.0	
CP211	4		120 secs	-	-	-	-	1.0	0.0	17.0	0.0	0.0	0.0	
CP211	4		180 secs	-	-	-	-	0.8	0.0	17.1	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

Compiled By	Date	Checked By
	28/11/13	
Contract:		
	East Midlan	ds Gateway

 Date
 Contract Ref:

 28/11/13
 312494

Page:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP211	4		240 secs	-	-	-	-	0.8	0.0	17.4	0.0	0.0	0.0	
CP211	4		300 secs	-	-	-	-	0.8	0.0	17.3	0.0	0.0	0.0	
CP212	1	3.39	17/10/2013 16:56:18	1010	1010	-	2.22	0.0	0.0	20.8	0.0	0.0	0.0	
CP212	1		15 secs	-	-	-	-	2.3	0.0	19.4	0.0	0.0	0.0	
CP212	1		30 secs	-	1	-	-	2.4	0.0	18.5	0.0	0.0	0.0	
CP212	1		60 secs	-	-	-	-	2.4	0.0	18.2	0.0	0.0	0.0	
CP212	1		90 secs	-	-	-	-	2.4	0.0	18.3	0.0	0.0	0.0	
CP212	1		120 secs	-	-	-	-	2.5	0.0	18.3	0.0	0.0	0.0	
CP212	1		180 secs	-	-	-	-	2.5	0.0	18.1	0.0	0.0	0.0	
CP212	1		240 secs	-	-	-	-	2.4	0.0	18.3	0.0	0.0	0.0	
CP212	1		300 secs	-	-	-	-	2.3	0.0	18.4	0.0	0.0	0.0	
CP212	2	3.39	23/10/2013 10:45:00	984	984	$0.1_{(I)}$	1.48	0.0	0.0	20.8	0.0	0.0	0.0	
CP212	2		15 secs	-	-	$0.0_{(SS)}$	-	3.6	0.0	20.0	0.0	0.0	0.0	
CP212	2		30 secs	-	-	-	-	3.8	0.0	15.0	0.0	0.0	0.0	
CP212	2		60 secs	-	-	-	-	3.8	0.0	15.5	0.0	0.0	0.0	
CP212	2		90 secs	-	-	-	-	3.8	0.0	15.5	0.0	0.0	0.0	
CP212	2		120 secs	-	-	-	-	3.8	0.0	15.5	0.0	0.0	0.0	
CP212	2		180 secs	-	-	-	-	3.6	0.0	15.9	0.0	0.0	0.0	
CP212	2		240 secs	-	-	-	-	3.4	0.0	16.4	0.0	0.0	0.0	
CP212	2		300 secs	-	-	-	-	3.2	0.0	16.8	0.0	0.0	0.0	
CP212	3	3.38	30/10/2013 13:55:00	1007	1009	0.3 <sub>(I)</sub>	1.22	0.1	0.0	20.8	0.0	0.0	0.0	
CP212	3		15 secs	-	-	$0.4_{(SS)}$	-	2.3	0.0	19.5	0.0	0.0	0.0	
CP212	3		30 secs	-	-	-	-	2.4	0.0	18.5	0.0	0.0	0.0	
CP212	3		60 secs	-	-	-	-	2.4	0.0	18.3	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By
	28/11/13	
Contract:	•	
	East Midlar	ds Gateway

Contract Ref: Date 312494 28/11/13

Page:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP212	3		90 secs	-	-	-	-	2.4	0.0	18.3	0.0	0.0	0.0	
CP212	3		120 secs	-	-	-	-	2.3	0.0	18.4	0.0	0.0	0.0	
CP212	3		180 secs	-	-	-	-	2.2	0.0	18.6	0.0	0.0	0.0	
CP212	3		240 secs	-	-	-	-	2.0	0.0	18.9	0.0	0.0	0.0	
CP212	3		300 secs	-	-	-	-	1.8	0.0	19.1	0.0	0.0	0.0	
CP212	4	3.37	12/11/2013 13:12:00	1020	1020	-1.6 <sub>(I)</sub>	1.04	0.1	0.0	20.8	0.0	0.0	0.0	
CP212	4		15 secs	-	-	0.1 <sub>(SS)</sub>	-	3.3	0.0	17.0	0.0	0.0	0.0	
CP212	4		30 secs	-	-	-	-	3.4	0.0	16.9	0.0	0.0	0.0	
CP212	4		60 secs	-	-	-	-	3.4	0.0	16.9	0.0	11.0	0.0	
CP212	4		90 secs	-	-	-	-	3.4	0.0	16.8	0.0	0.0	0.0	
CP212	4		120 secs	-	1	-	-	3.3	0.0	16.8	0.0	0.0	0.0	
CP212	4		180 secs	-	-	-	-	2.9	0.0	17.5	0.0	0.0	0.0	
CP212	4		240 secs	-	-	-	-	2.8	0.0	17.6	0.0	0.0	0.0	
CP212	4		300 secs	-	1	•	-	2.8	0.0	17.5	0.0	0.0	0.0	
CP213	1	4.08	17/10/2013 18:00:00	1010	1010	•	2.39	0.0	0.0	20.8	0.0	0.0	0.0	
CP213	1		15 secs	-	-	-	-	1.2	0.0	18.5	0.0	3.0	0.0	
CP213	1		30 secs	-	1	ı	-	1.5	0.0	18.3	0.0	2.0	0.0	
CP213	1		60 secs	-	-	-	-	1.3	0.0	18.4	0.0	6.0	0.0	
CP213	1		90 secs	-	-	•	-	1.4	0.0	18.1	0.0	0.0	0.0	
CP213	1		120 secs	-	-	-	-	1.4	0.0	18.1	0.0	0.0	0.0	
CP213	1		180 secs	-	-	-	-	1.5	0.0	18.0	0.0	0.0	0.0	
CP213	1		240 secs	-	-	-	-	1.6	0.0	18.1	0.0	0.0	0.0	
CP213	1		300 secs	-	-	-	-	1.6	0.0	18.1	0.0	0.0	0.0	
CP213	2	4.08	23/10/2013 10:16:00	983	983	0.2 <sub>(I)</sub>	2.24	0.0	0.0	20.8	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK E A Hu

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

d		Compiled
	Contract	•
	Contract	•

<u> </u>			
Compiled By	Date	Checked By	
	28/11/13		

**East Midlands Gateway** 

Date Con 28/11/13

Contract Ref:

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP213	2		15 secs	-	-	0.1 <sub>(SS)</sub>	-	1.6	0.0	19.9	0.0	0.0	0.0	
CP213	2		30 secs	-	-	-	-	1.7	0.0	18.0	0.0	0.0	0.0	
CP213	2		60 secs	-	-	-	-	1.7	0.0	17.8	0.0	0.0	0.0	
CP213	2		90 secs	-	-	-	-	1.8	0.0	17.8	0.0	0.0	0.0	
CP213	2		120 secs	-	-	-	-	1.8	0.0	17.6	0.0	0.0	0.0	
CP213	2		180 secs	-	-	-	-	2.0	0.0	17.6	0.0	0.0	0.0	
CP213	2		240 secs	-	-	-	-	2.1	0.0	17.6	0.0	0.0	0.0	
CP213	2		300 secs	-	-	-	-	2.1	0.0	17.6	0.0	0.0	0.0	
CP213	3	4.08	30/10/2013 12:00:00	1012	1012	2.4 <sub>(I)</sub>	2.18	0.1	0.0	20.8	0.0	0.0	0.0	
CP213	3		15 secs	-	-	2.5 <sub>(SS)</sub>	-	2.1	0.0	20.0	0.0	0.0	0.0	
CP213	3		30 secs	-	-	-	-	2.4	0.0	17.2	0.0	0.0	0.0	
CP213	3		60 secs	-	-	-	-	2.4	0.0	17.0	0.0	0.0	0.0	
CP213	3		90 secs	-	-	-	-	2.4	0.0	16.9	0.0	0.0	0.0	
CP213	3		120 secs	-	-	-	-	2.4	0.0	17.0	0.0	0.0	0.0	
CP213	3		180 secs	-	-	-	-	2.4	0.0	17.0	0.0	0.0	0.0	
CP213	3		240 secs	-	-	-	-	2.4	0.0	17.0	0.0	0.0	0.0	
CP213	3		300 secs	-	-	-	-	2.4	0.0	17.0	0.0	0.0	0.0	
CP213	4	4.07	12/11/2013 15:46:00	1020	1020	0.3 <sub>(I)</sub>	1.78	0.1	0.0	20.8	0.0	0.0	0.0	
CP213	4		15 secs	-	-	$0.1_{(SS)}$	-	1.5	0.0	19.3	0.0	0.0	0.0	
CP213	4		30 secs	-	-	-	-	1.6	0.0	18.5	0.0	0.0	0.0	
CP213	4		60 secs	-	-	-	-	1.9	0.0	17.8	0.0	21.0	0.0	
CP213	4		90 secs	-	-	-	-	2.0	0.0	17.6	0.0	4.0	0.0	
CP213	4		120 secs	-	-	-	-	2.0	0.0	17.7	0.0	0.0	0.0	
CP213	4		180 secs	-	-	-	-	2.0	0.0	17.6	0.0	0.0	0.0	
CP213	4		240 secs	-	-	-	-	2.0	0.0	17.6	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	
	28/11/13		
Contract:			
	East Midlan	nds Gateway	

Contract Ref:

Date

28/11/13

312494

Page:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP213	4		300 secs	-	-	-	-	2.0	0.0	17.5	0.0	0.0	0.0	
CP214	1	4.08	17/10/2013 18:20:18	1011	1010	-	3.49	0.0	0.0	20.8	0.0	0.0	0.0	
CP214	1		15 secs	-	-	-	-	3.4	0.0	18.6	0.0	0.0	0.0	
CP214	1		30 secs	-	-	-	-	3.6	0.0	16.1	0.0	0.0	0.0	
CP214	1		60 secs	-	-	-	-	3.6	0.0	15.9	0.0	0.0	0.0	
CP214	1		90 secs	-	-	-	-	3.6	0.0	15.9	0.0	0.0	0.0	
CP214	1		120 secs	-	-	-	-	3.6	0.0	18.8	0.0	0.0	0.0	
CP214	1		180 secs	-	-	-	-	3.6	0.0	18.6	0.0	0.0	0.0	
CP214	1		240 secs	-	-	-	-	3.6	0.0	16.0	0.0	0.0	0.0	
CP214	1		300 secs	-	-	-	-	3.5	0.0	16.0	0.0	0.0	0.0	
CP214	2	4.10	24/10/2013 13:20:00	1005	1005	0.1 <sub>(I)</sub>	3.38	0.1	0.0	20.7	0.0	0.0	0.0	
CP214	2		15 secs	-	1	$0.0_{(SS)}$	-	3.7	0.0	17.8	0.0	0.0	0.0	
CP214	2		30 secs	-	-	-	-	3.8	0.0	14.5	0.0	0.0	0.0	
CP214	2		60 secs	-	-	-	-	3.7	0.0	14.3	0.0	0.0	0.0	
CP214	2		90 secs	-	-	-	-	3.7	0.0	14.3	0.0	0.0	0.0	
CP214	2		120 secs	-	-	-	-	3.7	0.0	14.3	0.0	0.0	0.0	
CP214	2		180 secs	-	-	-	-	3.7	0.0	14.3	0.0	0.0	0.0	
CP214	2		240 secs	-	-	-	-	3.7	0.0	14.3	0.0	0.0	0.0	
CP214	2		300 secs	-	-	-	-	3.7	0.0	14.3	0.0	0.0	0.0	
CP214	3	4.08	30/10/2013 10:35:00	1012	1012	-1.5 <sub>(I)</sub>	3.00	0.1	0.0	20.8	0.0	0.0	0.0	
CP214	3		15 secs	-	-	-1.0 <sub>(SS)</sub>	-	3.6	0.0	17.9	0.0	0.0	0.0	
CP214	3		30 secs	-	-	-	-	3.8	0.0	13.4	0.0	0.0	0.0	
CP214	3		60 secs	-	-	-	-	3.8	0.0	12.9	0.0	0.0	0.0	
CP214	3		90 secs	-	-	-	-	3.8	0.0	12.8	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment** Abbey Park Humber Road Coventry CV3 4AQ

t Ltd	L
l	

Compiled By Contract:

Date 28/11/13

Checked By

**East Midlands Gateway** 

Contract Ref: Date 28/11/13

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP214	3		120 secs	-	-	-	-	3.8	0.0	12.9	0.0	0.0	0.0	
CP214	3		180 secs	-	-	-	-	3.8	0.0	12.9	0.0	0.0	0.0	
CP214	3		240 secs	-	-	-	-	3.8	0.0	13.0	0.0	0.0	0.0	
CP214	3		300 secs	-	-	-	-	3.8	0.0	13.0	0.0	0.0	0.0	
CP214	4	4.07	12/11/2013 15:49:00	1020	1020	0.3 <sub>(I)</sub>	2.13	0.1	0.0	20.8	0.0	0.0	0.0	
CP214	4		15 secs	-	-	0.1 <sub>(SS)</sub>	-	4.0	0.0	14.2	0.0	0.0	0.0	
CP214	4		30 secs	-	-	-	-	4.1	0.0	13.1	0.0	0.0	0.0	
CP214	4		60 secs	-	-	-	-	4.1	0.0	12.6	0.0	0.0	0.0	
CP214	4		90 secs	-	-	-	-	4.1	0.0	12.6	0.0	16.0	0.0	
CP214	4		120 secs	-	-	-	-	4.1	0.0	12.6	0.0	0.0	0.0	
CP214	4		180 secs	-	-	-	-	4.1	0.0	12.5	0.0	0.0	0.0	
CP214	4		240 secs	-	-	-	-	4.1	0.0	12.6	0.0	0.0	0.0	
CP214	4		300 secs	-	-	-	-	4.1	0.0	12.5	0.0	0.0	0.0	
CP215	1	4.98	17/10/2013 17:15:00	1010	1010	-	1.72	0.0	0.0	20.8	0.0	0.0	0.0	
CP215	1		15 secs	-	-	•	-	2.5	0.0	18.1	0.0	0.0	0.0	
CP215	1		30 secs	-	-	-	-	1.9	0.0	16.4	0.0	0.0	0.0	
CP215	1		60 secs	-	-	ı	-	1.4	0.0	17.8	0.0	0.0	0.0	
CP215	1		90 secs	-	-	-	-	1.2	0.0	18.2	0.0	0.0	0.0	
CP215	1		120 secs	-	-	•	-	1.0	0.0	18.6	0.0	0.0	0.0	
CP215	1		180 secs	-	-	-	-	0.8	0.0	19.3	0.0	0.0	0.0	
CP215	1		240 secs	-	-	-	-	0.6	0.0	19.6	0.0	0.0	0.0	
CP215	1		300 secs	-	-	-	-	0.5	0.0	19.7	0.0	0.0	0.0	
CP215	2	4.98	24/10/2013 11:15:00	1005	1005	0.1 <sub>(I)</sub>	1.07	0.1	0.0	20.8	0.0	0.0	0.0	
CP215	2		15 secs	-	-	$0.0_{(SS)}$	-	3.1	0.0	18.6	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment** Abbey Park Humber Road Coventry CV3 4AQ

Ltd	
	Сс

ontract:

Compiled By Date Checked By 28/11/13

East Midlands Gateway

28/11/13

Contract Ref: Date

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP215	2		30 secs	-	-	-	-	2.4	0.0	15.2	0.0	0.0	0.0	
CP215	2		60 secs	-	-	-	-	1.9	0.0	16.3	0.0	0.0	0.0	
CP215	2		90 secs	-	-	-	-	1.5	0.0	17.1	0.0	0.0	0.0	
CP215	2		120 secs	-	-	-	-	1.3	0.0	17.6	0.0	0.0	0.0	
CP215	2		180 secs	-	-	-	-	1.0	0.0	18.3	0.0	0.0	0.0	
CP215	2		240 secs	-	-	-	-	0.9	0.0	18.5	0.0	0.0	0.0	
CP215	2		300 secs	-	-	-	-	0.8	0.0	18.7	0.0	0.0	0.0	
CP215	3	4.98	30/10/2013 13:20:00	1012	1012	-2.3 <sub>(I)</sub>	0.88	0.1	0.0	20.8	0.0	0.0	0.0	
CP215	3		15 secs	-	-	-1.8 <sub>(SS)</sub>	-	2.5	0.0	20.0	0.0	0.0	0.0	
CP215	3		30 secs	-	-	-	-	2.0	0.0	16.5	0.0	0.0	0.0	
CP215	3		60 secs	-	-	-	-	1.2	0.0	18.1	0.0	0.0	0.0	
CP215	3		90 secs	-	-	-	-	1.1	0.0	18.6	0.0	0.0	0.0	
CP215	3		120 secs	-	-	-	-	1.0	0.0	18.9	0.0	0.0	0.0	
CP215	3		180 secs	-	-	-	-	1.1	0.0	18.8	0.0	0.0	0.0	
CP215	3		240 secs	-	-	-	-	1.0	0.0	18.9	0.0	0.0	0.0	
CP215	3		300 secs	-	-	-	-	1.0	0.0	19.0	0.0	0.0	0.0	
CP215	4	4.96	12/11/2013 13:30:00	1019	1020	$0.0_{(I)}$	0.55	0.1	0.0	20.8	0.0	0.0	0.0	
CP215	4		15 secs	-	-	0.0 <sub>(SS)</sub>	-	3.8	0.0	15.0	0.0	0.0	0.0	
CP215	4		30 secs	-	-	-	-	3.8	0.0	13.6	0.0	0.0	0.0	
CP215	4		60 secs	-	-	-	-	3.8	0.0	13.4	0.0	4.0	0.0	
CP215	4		90 secs	-	-	-	-	3.4	0.0	13.9	0.0	0.0	0.0	
CP215	4		120 secs	-	-	-	-	3.4	0.0	13.9	0.0	0.0	0.0	
CP215	4		180 secs	-	-	-	-	3.4	0.0	14.1	0.0	0.0	0.0	
CP215	4		240 secs	-	-	-	-	3.2	0.0	14.4	0.0	0.0	0.0	
CP215	4		300 secs	-	-	-	-	3.2	0.0	14.4	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment** Abbey Park Humber Road Coventry CV3 4AQ

. L	-	Ltd	t
l			l

Compiled By Contract:

Date 28/11/13

**East Midlands Gateway** 

Checked By

Date 28/11/13 Contract Ref:

312494

Page:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CD216		2.55	40/04/0000	1011	1011	2.4	DDI	0.1	0.0	20.0	0.0	0.0	0.0	
CP216	3	2.55	18/01/2000	1011	1011	2.4 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
		Borehole co	ould not be located o	n the first i	wo visits o									
CP216	3		15 secs	-	-	2.4 <sub>(SS)</sub>	-	1.4	0.0	19.1	0.0	6.0	0.0	
CP216	3		30 secs	-	-	-	-	1.4	0.0	17.2	0.0	3.0	0.0	
CP216	3		60 secs	-	-	-	-	1.3	0.0	17.4	0.0	0.0	0.0	
CP216	3		90 secs	-	-	-	-	1.2	0.1	17.5	1.0	0.0	0.0	
CP216	3		120 secs	-	-	-	-	1.2	0.1	17.7	1.0	0.0	0.0	
CP216	3		180 secs	-	-	-	-	1.1	0.0	18.0	0.0	0.0	0.0	
CP216	3		240 secs	-	-	-	-	1.0	0.0	18.1	0.0	0.0	0.0	
CP216	3		300 secs	-	-	-	-	1.0	0.0	18.3	0.0	0.0	0.0	
CP216	4	2.55	12/11/2013 14:35:00	1020	1020	2.2 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP216	4		15 secs	-	-	2.0 <sub>(SS)</sub>	-	1.4	0.0	19.4	0.0	1.0	0.0	
CP216	4		30 secs	-	-	-	-	1.3	0.0	17.0	0.0	0.0	0.0	
CP216	4		60 secs	-	-	-	-	1.1	0.0	17.7	0.0	0.0	0.0	
CP216	4		90 secs	-	-	-	-	1.0	0.0	17.8	0.0	0.0	0.0	
CP216	4		120 secs	-	-	-	-	1.0	0.0	18.1	0.0	0.0	0.0	
CP216	4		180 secs	-	-	-	-	0.9	0.0	18.3	0.0	12.0	0.0	
CP216	4		240 secs	-	-	-	-	0.9	0.0	18.2	0.0	0.0	0.0	
CP216	4		300 secs	-	-	-	-	0.9	0.0	18.3	0.0	0.0	0.0	
CP217	1	4.64	17/10/2013 17:42:00	1010	1010	-	2.25	0.0	0.0	20.8	0.0	0.0	0.0	
CP217	1		15 secs	-	-	-	-	0.8	0.0	18.1	0.0	0.0	0.0	
CP217	1		30 secs	-	-	-	-	0.6	0.0	17.9	0.0	0.0	0.0	
CP217	1		60 secs	-	-	-	-	0.5	0.0	18.4	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

| Compiled By | Date | Checked By | Date | Contract: | Page:

East Midlands Gateway

**19** of **36** 

312494

Contract Ref:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP217	1		90 secs	-	-	-	-	0.5	0.0	18.5	0.0	0.0	0.0	
CP217	1		120 secs	-	-	-	-	0.4	0.0	18.7	0.0	0.0	0.0	
CP217	1		180 secs	-	1	-	-	0.4	0.0	18.8	0.0	0.0	0.0	
CP217	1		240 secs	-	-	-	-	0.4	0.0	18.8	0.0	0.0	0.0	
CP217	1		300 secs	-	-	-	-	0.3	0.0	18.8	0.0	0.0	0.0	
CP217	2	4.64	23/10/2013 11:20:00	984	984	-	1.70	0.1	0.0	20.7	0.0	0.0	0.0	
CP217	2		15 secs	-	-	-	-	1.6	0.0	19.6	0.0	0.0	0.0	
CP217	2		30 secs	-	-	-	-	1.7	0.0	16.2	0.0	0.0	0.0	
CP217	2		60 secs	-	-	-	-	1.1	0.0	17.3	0.0	0.0	0.0	
CP217	2		90 secs	-	-	-	-	0.8	0.0	18.4	0.0	0.0	0.0	
CP217	2		120 secs	-	-	-	-	0.6	0.0	19.1	0.0	0.0	0.0	
CP217	2		180 secs	-	-	-	-	0.4	0.0	20.0	0.0	0.0	0.0	
CP217	2		240 secs	-	-	-	-	0.3	0.0	20.4	0.0	0.0	0.0	
CP217	2		300 secs	-	-	-	-	0.2	0.0	20.6	0.0	0.0	0.0	
CP217	3	4.64	30/10/2013 12:56:00	1011	1012	1.6 <sub>(I)</sub>	1.60	0.1	0.0	20.8	0.0	0.0	0.0	
CP217	3		15 secs	-	-	1.3 <sub>(SS)</sub>	-	2.1	0.0	17.6	0.0	0.0	0.0	
CP217	3		30 secs	-	-	-	-	2.0	0.0	16.8	0.0	0.0	0.0	
CP217	3		60 secs	-	-	-	-	1.3	0.0	17.9	0.0	0.0	0.0	
CP217	3		90 secs	-	-	-	-	1.0	0.0	18.6	0.0	0.0	0.0	
CP217	3		120 secs	-	-	-	-	0.7	0.0	19.3	0.0	0.0	0.0	
CP217	3		180 secs	-	-	-	-	0.6	0.0	19.6	0.0	0.0	0.0	
CP217	3		240 secs	-	-	-	-	0.4	0.0	20.0	0.0	0.0	0.0	
CP217	3		300 secs	-	-	-	-	0.2	0.0	20.2	0.0	0.0	0.0	
CP217	4	4.62	12/11/2013 14:06:00	1020	1020	0.4 <sub>(I)</sub>	1.43	0.1	0.0	20.8	0.0	0.0	0.0	
CP217	4		15 secs	1	-	$0.2_{(SS)}$	-	2.2	0.0	17.9	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By Contract:

Date Checked By 28/11/13

East Midlands Gateway

Date 28/11/13

Contract Ref:

312494

Page:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP217	4		30 secs	-	-	-	-	1.8	0.0	17.7	0.0	0.0	0.0	
CP217	4		60 secs	-	-	-	-	0.8	0.0	19.5	0.0	2.0	0.0	
CP217	4		90 secs	-	-	-	-	0.7	0.0	19.6	0.0	10.0	0.0	
CP217	4		120 secs	-	-	-	-	0.6	0.0	19.9	0.0	0.0	0.0	
CP217	4		180 secs	-	-	-	-	0.5	0.0	19.9	0.0	3.0	0.0	
CP217	4		240 secs	-	-	-	-	0.4	0.0	20.0	0.0	0.0	0.0	
CP217	4		300 secs	-	-	-	-	0.4	0.0	20.0	0.0	0.0	0.0	
CP218	1	4.77	17/10/2013 17:47:19	1011	1010	-	DRY	0.0	0.0	20.8	0.0	0.0	0.0	
CP218	1		15 secs	-	-	-	-	2.0	0.0	18.3	0.0	0.0	0.0	
CP218	1		30 secs	-	-	-	-	2.1	0.0	16.6	0.0	0.0	0.0	
CP218	1		60 secs	-	-	-	-	2.1	0.0	16.7	0.0	0.0	0.0	
CP218	1		90 secs	-	-	-	-	2.1	0.0	16.6	0.0	0.0	0.0	
CP218	1		120 secs	-	-	-	-	2.1	0.0	16.5	0.0	0.0	0.0	
CP218	1		180 secs	-	-	-	-	2.1	0.0	16.6	0.0	0.0	0.0	
CP218	1		240 secs	-	-	-	-	2.1	0.0	16.7	0.0	0.0	0.0	
CP218	1		300 secs	-	-	-	-	2.1	0.0	16.7	0.0	0.0	0.0	
CP218	2	4.77	24/10/2013 11:40:00	1005	1005	0.1 <sub>(I)</sub>	DRY	0.0	0.0	20.7	0.0	0.0	0.0	
CP218	2		15 secs	-	-	$0.0_{(SS)}$	-	1.4	0.0	19.0	0.0	0.0	0.0	
CP218	2		30 secs	-	-	-	-	1.4	0.0	18.3	0.0	0.0	0.0	
CP218	2		60 secs	-	-	-	-	1.4	0.0	18.1	0.0	0.0	0.0	
CP218	2		90 secs	-	-	-	-	1.4	0.0	18.1	0.0	0.0	0.0	
CP218	2		120 secs	-	-	-	-	1.4	0.0	18.2	0.0	0.0	0.0	
CP218	2		180 secs	-	-	-	-	1.4	0.0	18.2	0.0	0.0	0.0	
CP218	2		240 secs	-	-	-	-	1.4	0.0	18.2	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK** 

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

*				
Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:				Page:

East Midlands Gateway

**21** of **36** 

312494

36 A(

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP218	2		300 secs	-	-	-	-	1.4	0.0	18.3	0.0	0.0	0.0	
CP218	3	4.78	30/10/2013 13:30:00	1013	1012	0.9 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP218	3		15 secs	-	-	0.8 <sub>(SS)</sub>	-	1.0	0.0	20.5	0.0	0.0	0.0	
CP218	3		30 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	3		60 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	3		90 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	3		120 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	3		180 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	3		240 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	3		300 secs	-	-	-	-	1.1	0.0	19.9	0.0	0.0	0.0	
CP218	4	4.76	12/11/2013 14:58:00	1020	1020	0.1 <sub>(I)</sub>	4.63	0.1	0.0	20.8	0.0	0.0	0.0	
CP218	4		15 secs	-	-	0.0 <sub>(SS)</sub>	-	1.6	0.0	18.8	0.0	0.0	0.0	
CP218	4		30 secs	-	-	-	-	2.2	0.0	15.8	0.0	0.0	0.0	
CP218	4		60 secs	-	-	-	-	2.5	0.0	15.1	0.0	0.0	0.0	
CP218	4		90 secs	-	-	-	-	2.7	0.0	14.1	0.0	0.0	0.0	
CP218	4		120 secs	-	-	-	-	2.7	0.0	14.0	0.0	0.0	0.0	
CP218	4		180 secs	-	-	-	-	2.7	0.0	14.1	0.0	0.0	0.0	
CP218	4		240 secs	ı	-	-	-	2.7	0.0	14.1	0.0	0.0	0.0	
CP218	4		300 secs	-	-	-	-	2.7	0.0	14.0	0.0	0.0	0.0	
CP219	1	7.43	16/10/2013 14:47:23	1003	1003	-	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP219	1		15 secs	-	-	-	-	1.5	0.0	18.4	0.0	0.0	0.0	
CP219	1		30 secs	-	-	-	-	1.5	0.0	16.4	0.0	0.0	0.0	
CP219	1		60 secs	-	-	-	-	1.5	0.0	16.0	0.0	0.0	0.0	
CP219	1		90 secs	-	-	-	-	1.5	0.1	15.9	1.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:	•			Page:

**East Midlands Gateway** 

312494



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP219	1		120 secs	-	-	-	-	1.5	0.1	15.9	1.0	0.0	0.0	
CP219	1		180 secs	-	-	-	-	1.6	0.1	15.3	1.0	0.0	0.0	
CP219	1		240 secs	-	-	-	-	1.6	0.1	14.8	1.0	0.0	0.0	
CP219	1		300 secs	-	-	-	-	1.6	0.0	14.6	0.0	0.0	0.0	
CP219	2	7.44	24/10/2013 13:40:00	1006	1006	0.1 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP219	2		15 secs	-	-	$0.0_{(SS)}$	-	0.2	0.0	20.2	0.0	0.0	0.0	
CP219	2		30 secs	-	-	-	-	0.2	0.0	20.1	0.0	0.0	0.0	
CP219	2		60 secs	-	-	-	-	0.1	0.0	20.2	0.0	0.0	0.0	
CP219	2		90 secs	-	-	-	-	0.1	0.0	20.1	0.0	0.0	0.0	
CP219	2		120 secs	-	-	-	-	0.1	0.0	20.2	0.0	0.0	0.0	
CP219	2		180 secs	-	-	-	-	0.1	0.0	20.2	0.0	0.0	0.0	
CP219	2		240 secs	-	-	-	-	0.1	0.0	20.2	0.0	0.0	0.0	
CP219	2		300 secs	-	-	-	-	0.1	0.0	20.2	0.0	0.0	0.0	
CP219	3	7.41	30/10/2013 13:10:13	1009	1009	0.2 <sub>(I)</sub>	7.32	0.1	0.0	20.8	0.0	0.0	0.0	
CP219	3		15 secs	-	-	0.1 <sub>(SS)</sub>	-	1.4	0.0	16.0	0.0	0.0	0.0	
CP219	3		30 secs	-	-	-	-	1.2	0.0	12.3	0.0	0.0	0.0	
CP219	3		60 secs	-	-	-	-	0.9	0.0	14.1	0.0	0.0	0.0	
CP219	3		90 secs	-	-	-	-	0.8	0.0	15.5	0.0	0.0	0.0	
CP219	3		120 secs	-	-	-	-	0.7	0.0	16.1	0.0	0.0	0.0	
CP219	3		180 secs	-	-	-	-	0.6	0.0	17.0	0.0	0.0	0.0	
CP219	3		240 secs	-	-	-	-	0.5	0.0	17.5	0.0	0.0	0.0	
CP219	3		300 secs	-	-	-	-	0.5	0.0	17.8	0.0	0.0	0.0	
CP219	4	7.43	11/11/2013 14:58:00	1017	1017	-3.0 <sub>(I)</sub>	7.34	0.1	0.0	20.8	0.0	0.0	0.0	
CP219	4		15 secs	-	-	1.5 <sub>(SS)</sub>	-	0.9	0.0	19.5	0.0	0.0	0.0	
CP219	4		30 secs	-	-	-	-	0.9	0.0	18.6	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

	RSK Environment Ltd		Compiled By	Date		Checked By	Date	Contract Ref:				
DCK	Abbey Park			28/11/13			28/11/13		3	12494	ļ	
	Humber Road	Contra	act:					Page:				
	Coventry CV3 4AO			East Midlar	ids (	Sateway			23	of	36	AGS

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP219	4		60 secs	-	-	-	-	0.9	0.0	18.8	0.0	0.0	0.0	
CP219	4		90 secs	-	-	-	-	0.8	0.0	18.9	0.0	3.0	0.0	
CP219	4		120 secs	-	-	-	-	0.4	0.0	19.8	0.0	0.0	0.0	
CP219	4		180 secs	-	-	-	-	0.4	0.0	19.9	0.0	0.0	0.0	
CP219	4		240 secs	-	-	-	-	0.3	0.0	20.0	0.0	0.0	0.0	
CP219	4		300 secs	-	-	-	-	0.3	0.0	20.0	0.0	1.0	0.0	
CP220	1	5.79	16/10/2013 13:54:18	1003	1003	-	3.04	0.0	0.0	20.7	0.0	0.0	0.0	
CP220	1		15 secs	-	-	-	-	0.8	0.0	20.4	0.0	0.0	0.0	
CP220	1		30 secs	-	-	-	-	0.8	0.0	19.6	0.0	0.0	0.0	
CP220	1		60 secs	-	-	-	-	0.8	0.0	19.6	0.0	0.0	0.0	
CP220	1		90 secs	-	-	-	-	0.8	0.0	19.6	0.0	0.0	0.0	
CP220	1		120 secs	-	-	-	-	0.8	0.0	19.6	0.0	0.0	0.0	
CP220	1		180 secs	-	-	-	-	0.8	0.0	19.6	0.0	0.0	0.0	
CP220	1		240 secs	-	-	-	-	0.9	0.0	19.5	0.0	0.0	0.0	
CP220	1		300 secs	-	-	-	-	0.9	0.0	19.6	0.0	0.0	0.0	
CP220	2	5.79	22/10/2013 13:28:00	988	988	$0.4_{(I)}$	3.04	0.1	0.0	20.8	0.0	0.0	0.0	
CP220	2		15 secs	-	-	$0.8_{(SS)}$	-	0.3	0.0	19.4	0.0	0.0	0.0	
CP220	2		30 secs	-	-	-	-	0.3	0.0	19.5	0.0	0.0	0.0	
CP220	2		60 secs	-	-	-	-	0.3	0.0	19.5	0.0	0.0	0.0	
CP220	2		90 secs	-	-	-	-	0.3	0.0	19.4	0.0	0.0	0.0	
CP220	2		120 secs	-	-	-	-	0.4	0.0	19.4	0.0	0.0	0.0	
CP220	2		180 secs	-	-	-	-	0.4	0.0	19.4	0.0	0.0	0.0	
CP220	2		240 secs	-	-	-	-	0.4	0.0	19.4	0.0	0.0	0.0	
CP220	2		300 secs	-	-	-	-	0.4	0.0	19.4	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	Date
	28/11/13		28/11/13
Contract:	East Midlar	da Catarrar	·
	East Mildian	ids Gateway	

Contract Ref:

Page:

**24** of **36** 

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP220	3	5.80	30/10/2013 14:40:00	1013	1012	-1.3 <sub>(I)</sub>	2.99	0.1	0.0	20.8	0.0	0.0	0.0	
CP220	3		15 secs	-	-	-1.0 <sub>(SS)</sub>	-	0.5	0.0	20.5	0.0	0.0	0.0	
CP220	3		30 secs	-	-	-	-	0.6	0.0	20.0	0.0	0.0	0.0	
CP220	3		60 secs	-	-	-	-	0.4	0.0	20.2	0.0	0.0	0.0	
CP220	3		90 secs	-	-	-	-	0.4	0.0	20.2	0.0	0.0	0.0	
CP220	3		120 secs	-	-	-	-	0.5	0.0	20.2	0.0	0.0	0.0	
CP220	3		180 secs	-	-	-	-	0.5	0.0	20.0	0.0	0.0	0.0	
CP220	3		240 secs	-	-	-	-	0.5	0.0	20.1	0.0	0.0	0.0	
CP220	3		300 secs	-	-	-	-	0.4	0.0	20.2	0.0	0.0	0.0	
CP220	4	5.77	11/11/2013 14:39:00	1017	1017	1.5 <sub>(I)</sub>	2.08	0.1	0.0	20.8	0.0	0.0	0.0	
CP220	4		15 secs	-	-	1.6 <sub>(SS)</sub>	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP220	4		30 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP220	4		60 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP220	4		90 secs	-	-	-	-	0.1	0.0	20.5	0.0	3.0	0.0	
CP220	4		120 secs	-	-	-	-	0.1	0.0	20.7	0.0	4.0	0.0	
CP220	4		180 secs	-	-	-	-	0.1	0.0	20.7	0.0	5.0	0.0	
CP220	4		240 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP220	4		300 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP221	1	10.00	16/10/2013 14:30:00	1003	1003	-	5.43	0.1	0.0	20.7	0.0	0.0	0.0	
CP221	1		15 secs	-	-	-	-	1.3	0.0	19.7	0.0	0.0	0.0	
CP221	1		30 secs	-	-	-	-	1.2	0.0	18.8	0.0	0.0	0.0	
CP221	1		60 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	1		90 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	1		120 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry

CV3 4AQ

Compiled By Date 28/11/13 Contract: **East Midlands Gateway** 

Date 28/11/13

Checked By

Contract Ref:

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP221	1		180 secs	-	-	-	-	1.2	0.0	18.9	0.0	0.0	0.0	
CP221	1		240 secs	-	-	-	-	1.2	0.0	18.6	0.0	0.0	0.0	
CP221	1		300 secs	-	-	-	-	1.2	0.0	18.9	0.0	0.0	0.0	
CP221	2	10.10	24/10/2013 14:00:00	1006	1006	$0.0_{(I)}$	5.50	0.0	0.0	20.8	0.0	0.0	0.0	
CP221	2		15 secs	-	-	$0.0_{(SS)}$	-	1.4	0.0	19.6	0.0	0.0	0.0	
CP221	2		30 secs	-	-	-	-	1.3	0.0	18.6	0.0	0.0	0.0	
CP221	2		60 secs	-	-	-	-	1.2	0.0	18.6	0.0	0.0	0.0	
CP221	2		90 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	2		120 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	2		180 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	2		240 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	2		300 secs	-	-	-	-	1.2	0.0	18.7	0.0	0.0	0.0	
CP221	3	10.08	30/10/2013 13:10:00	1008	1009	$0.1_{(I)}$	5.48	0.1	0.0	20.8	0.0	0.0	0.0	
CP221	3		15 secs	-	-	$0.0_{(SS)}$	-	1.0	0.0	19.6	0.0	0.0	0.0	
CP221	3		30 secs	ı	-	-	-	1.1	0.0	18.6	0.0	0.0	0.0	
CP221	3		60 secs	-	-	-	-	1.3	0.0	18.0	0.0	0.0	0.0	
CP221	3		90 secs	-	-	-	-	1.3	0.0	18.1	0.0	0.0	0.0	
CP221	3		120 secs	ı	-	-	-	1.3	0.0	17.4	0.0	0.0	0.0	
CP221	3		180 secs	-	-	-	-	1.3	0.0	18.0	0.0	0.0	0.0	
CP221	3		240 secs	-	-	-	-	1.3	0.0	18.0	0.0	0.0	0.0	
CP221	3		300 secs	-	-	-	-	1.3	0.0	18.1	0.0	0.0	0.0	
CP221	4	10.07	11/11/2013 14:20:00	1017	1017	-	5.36	0.1	0.0	20.8	0.0	0.0	0.0	
CP221	4		15 secs	-	-	-	-	0.6	0.0	20.0	0.0	0.0	0.0	
CP221	4		30 secs	-	-	-	-	1.4	0.0	18.3	0.0	0.0	0.0	
CP221	4		60 secs	-	-	-	-	1.6	0.0	17.7	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK** 

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

	Compiled By	Date		Checked By	Date
		28/11/13		-	28/11/1
Contract:		•		-	
		East Midlar	ıds G	ateway	

Date Contract Ref: 28/11/13

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP221	4		90 secs	-	-	-	-	1.6	0.0	17.7	0.0	0.0	0.0	
CP221	4		120 secs	-	-	-	-	1.6	0.0	17.7	0.0	0.0	0.0	
CP221	4		180 secs	-	-	-	-	1.6	0.0	17.6	0.0	0.0	0.0	
CP221	4		240 secs	-	-	-	-	1.7	0.0	17.7	0.0	0.0	0.0	
CP221	4		300 secs	-	-	-	-	1.7	0.0	17.6	0.0	0.0	0.0	
CP222	1	5.68	16/10/2013 14:12:16	1003	1004	-	2.93	0.1	0.0	20.7	0.0	0.0	0.0	
CP222	1		15 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP222	1		30 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP222	1		60 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	1		90 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	1		120 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	1		180 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	1		240 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP222	1		300 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP222	2	5.95	22/10/2013 12:48:00	988	988	0.4(1)	2.82	0.1	0.0	20.8	0.0	0.0	0.0	
CP222	2		15 secs	-	-	0.4 <sub>(SS)</sub>	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	2		30 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP222	2		60 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	2		90 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	2		120 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP222	2		180 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP222	2		240 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP222	2		300 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP222	3	5.64	30/10/2013 15:10:00	-	-	-	2.44	-	-	-	-	-	-	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By Date Checked By  28/11/13	
Compiled By Date Checked By	Compiled By Date Checked I

Contract Ref: 312494 28/11/13

Page:

Date

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP222	4	5.69	11/11/2013 14:10:00	-	-	-	2.42	-	-	-	-	-	-	
CP(R)203	1	24.78	16/10/2013 12:05:00	1003	1003	-	24.47	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)203	1		15 secs	-	-	-	-	2.2	0.0	18.9	0.0	0.0	0.0	
CP(R)203	1		30 secs	-	-	-	-	2.3	0.1	16.6	1.0	0.0	0.0	
CP(R)203	1		60 secs	-	-	-	-	2.3	0.0	16.2	0.0	0.0	0.0	
CP(R)203	1		90 secs	-	-	-	-	2.3	0.0	16.2	0.0	0.0	0.0	
CP(R)203	1		120 secs	-	-	-	-	2.3	0.0	16.0	0.0	0.0	0.0	
CP(R)203	1		180 secs	-	-	-	-	2.3	0.0	16.0	0.0	0.0	0.0	
CP(R)203	1		240 secs	-	-	-	-	2.3	0.0	16.0	0.0	0.0	0.0	
CP(R)203	1		300 secs	-	-	-	-	2.4	0.0	15.8	0.0	0.0	0.0	
CP(R)203	2	24.81	23/10/2013 13:34:00	987	987	-0.2 <sub>(I)</sub>	24.56	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)203	2		15 secs	-	-	-0.2 <sub>(SS)</sub>	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)203	2		30 secs	-	-	-	-	2.2	0.1	18.8	1.0	0.0	0.0	
CP(R)203	2		60 secs	-	-	-	-	2.5	0.1	15.6	1.0	0.0	0.0	
CP(R)203	2		90 secs	-	-	-	-	2.5	0.1	15.0	1.0	0.0	0.0	
CP(R)203	2		120 secs	-	-	-	-	2.6	0.1	15.0	1.0	0.0	0.0	
CP(R)203	2		180 secs	-	-	-	-	2.6	0.0	15.0	0.0	0.0	0.0	
CP(R)203	2		240 secs	-	-	-	-	2.6	0.0	15.0	0.0	0.0	0.0	
CP(R)203	2		300 secs	-	-	-	-	2.6	0.0	15.0	0.0	0.0	0.0	
CP(R)203	2		330 secs	-	-	-	-	2.6	0.0	15.0	0.0	0.0	0.0	
CP(R)203	3	24.79	30/10/2013 16:50:00	1010	1010	-0.3 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)203	3		15 secs	-	-	-0.2 <sub>(SS)</sub>	-	1.4	0.1	19.4	1.0	0.0	0.0	
CP(R)203	3		30 secs	-	-	-	-	1.4	0.1	19.0	1.0	0.0	0.0	
CP(R)203	3		60 secs	-	-	-	-	1.4	0.1	18.9	1.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK E

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

•	EEE EOWEI Emploorive Emilie 670	, ,, ,,			
	Compiled By	Date	Checked By	Date	Contract Ref:
		28/11/13		28/11/13	
	Contract:				Page:

East Midlands Gateway

**28** of **36** 

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)203	3		90 secs	-	-	-	-	1.4	0.1	18.9	1.0	0.0	0.0	
CP(R)203	3		120 secs	-	-	-	-	1.4	0.1	18.9	1.0	0.0	0.0	
CP(R)203	3		180 secs	-	-	-	-	1.5	0.1	18.9	1.0	0.0	0.0	
CP(R)203	3		240 secs	-	-	-	-	1.5	0.1	18.9	1.0	0.0	0.0	
CP(R)203	3		300 secs	-	-	-	-	1.5	0.1	18.8	1.0	0.0	0.0	
CP(R)203	4	24.77	12/11/2013 10:31:00	1027	1027	-1.3 <sub>(I)</sub>	24.51	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)203	4		15 secs	-	-	-1.6 <sub>(SS)</sub>	-	0.9	0.0	19.5	0.0	0.0	0.0	
CP(R)203	4		30 secs	-	-	-	-	1.4	0.0	18.4	0.0	0.0	0.0	
CP(R)203	4		60 secs	-	-	-	-	1.6	0.0	17.9	0.0	0.0	0.0	
CP(R)203	4		90 secs	-	-	-	-	1.7	0.0	17.7	0.0	0.0	0.0	
CP(R)203	4		120 secs	-	-	-	-	1.8	0.0	17.5	0.0	0.0	0.0	
CP(R)203	4		180 secs	-	-	-	-	1.9	0.0	17.2	0.0	0.0	0.0	
CP(R)203	4		240 secs	-	-	-	-	1.9	0.0	17.2	0.0	0.0	0.0	
CP(R)203	4		300 secs	-	-	-	-	1.9	0.0	17.2	0.0	0.0	0.0	
CP(R)204	1	19.80	17/10/2013 15:50:00	1010	1010	-	15.90	0.0	0.0	20.8	0.0	0.0	0.0	
CP(R)204	1		15 secs	-	-	-	-	0.9	0.0	19.2	0.0	0.0	0.0	
CP(R)204	1		30 secs	-	-	-	-	0.9	0.0	18.3	0.0	0.0	0.0	
CP(R)204	1		60 secs	-	-	-	-	0.9	0.0	18.2	0.0	0.0	0.0	
CP(R)204	1		90 secs	-	-	-	-	0.9	0.0	18.1	0.0	0.0	0.0	
CP(R)204	1		120 secs	-	-	-	-	0.9	0.0	18.2	0.0	0.0	0.0	
CP(R)204	1		180 secs	-	-	-	-	0.9	0.0	18.3	0.0	0.0	0.0	
CP(R)204	1		240 secs	-	-	-	-	0.9	0.0	18.5	0.0	0.0	0.0	
CP(R)204	1		300 secs	-	-	-	-	0.9	0.0	18.5	0.0	0.0	0.0	
CP(R)204	2	19.80	22/10/2013 15:50:00	985	986	$0.0_{(I)}$	15.80	0.0	0.0	20.8	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK RS

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By
	28/11/13	
Contract:	•	
	East Midlar	ds Gateway

Date | Contract Ref: |

312494

Page:

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)204	2		15 secs	-	-	0.0 <sub>(SS)</sub>	-	0.6	0.0	20.3	0.0	0.0	0.0	
CP(R)204	2		30 secs	-	-	-	-	0.6	0.0	19.5	0.0	0.0	0.0	
CP(R)204	2		60 secs	-	-	-	-	0.6	0.0	19.7	0.0	0.0	0.0	
CP(R)204	2		90 secs	-	-	-	-	0.6	0.0	19.7	0.0	0.0	0.0	
CP(R)204	2		120 secs	-	-	-	-	0.6	0.0	19.7	0.0	0.0	0.0	
CP(R)204	2		180 secs	-	-	-	-	0.6	0.0	19.6	0.0	0.0	0.0	
CP(R)204	2		240 secs	-	-	-	-	0.6	0.0	19.6	0.0	0.0	0.0	
CP(R)204	2		300 secs	-	-	-	-	0.6	0.0	19.6	0.0	0.0	0.0	
CP(R)204	3	19.72	30/10/2013 15:36:00	1008	1009	0.0(1)	15.51	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)204	3		15 secs	-	-	$0.0_{(SS)}$	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)204	3		30 secs	-	-	-	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)204	3		60 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)204	3		90 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)204	3		120 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)204	3		180 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)204	3		240 secs	-	-	-	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)204	3		300 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)204	4	19.81	12/11/2013 11:44:00	1020	1020	-14.1 <sub>(I)</sub>	14.93	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)204	4		15 secs	-	-	-13.1 <sub>(SS)</sub>	-	0.6	0.0	19.7	0.0	0.0	0.0	
CP(R)204	4		30 secs	-	-	-	-	0.6	0.0	18.8	0.0	0.0	0.0	
CP(R)204	4		60 secs	-	-	-	-	1.2	0.0	16.6	0.0	13.0	0.0	
CP(R)204	4		90 secs	-	-	-	-	1.6	0.0	15.1	0.0	1.0	0.0	
CP(R)204	4		120 secs	-	-	-	-	1.7	0.0	14.6	0.0	14.0	0.0	
CP(R)204	4		180 secs	-	-	-	-	1.8	0.0	14.0	0.0	0.0	0.0	
CP(R)204	4		240 secs	-	-	-	-	1.8	0.0	13.8	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Env

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:				Page:

**East Midlands Gateway** 

**30** of **36** 

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)204	4		300 secs	-	-	-	-	1.8	0.0	14.0	0.0	0.0	0.0	
CP(R)205	1	18.41	16/10/2013 12:50:15	1002	1003	-	18.27	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)205	1		15 secs	-	-	-	-	1.8	0.0	19.7	0.0	0.0	0.0	
CP(R)205	1		30 secs	-	-	-	-	1.9	0.0	17.3	0.0	0.0	0.0	
CP(R)205	1		60 secs	-	-	-	-	1.9	0.0	16.9	0.0	0.0	0.0	
CP(R)205	1		90 secs	-	-	-	-	1.9	0.0	16.7	0.0	0.0	0.0	
CP(R)205	1		120 secs	-	-	-	-	2.0	0.0	16.6	0.0	0.0	0.0	
CP(R)205	1		180 secs	-	-	-	-	2.0	0.0	16.6	0.0	0.0	0.0	
CP(R)205	1		240 secs	-	-	-	-	2.0	0.0	16.5	0.0	0.0	0.0	
CP(R)205	1		300 secs	-	-	-	-	2.0	0.0	16.6	0.0	0.0	0.0	
CP(R)205	2	18.41	23/10/2013 14:14:00	989	987	-3.1 <sub>(I)</sub>	18.28	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)205	2		15 secs	-	-	-3.0 <sub>(SS)</sub>	-	0.1	0.0	20.3	0.0	0.0	0.0	
CP(R)205	2		30 secs	1	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	2		60 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	2		90 secs	ı	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	2		120 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	2		180 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	2		240 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	2		300 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	3	18.40	30/10/2013 16:55:00	1011	1010	-0.1 <sub>(I)</sub>	18.26	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)205	3		15 secs	-	-	0.0 <sub>(SS)</sub>	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)205	3		30 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)205	3		60 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)205	3		90 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

**RSK Environment** Abbey Park Humber Road Coventry CV3 4AQ

t	Ltd	
d		•

Compiled By Date Contract:

Checked By 28/11/13

**East Midlands Gateway** 

Date 28/11/13 Contract Ref:

312494

Page:



Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)205	3		120 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)205	3		180 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)205	3		240 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)205	3		300 secs	-	1	ı	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)205	4	18.40	12/11/2013 09:55:00	1021	1020	-12.6 <sub>(I)</sub>	18.27	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)205	4		15 secs	-	-	-18.6 <sub>(SS)</sub>	-	0.1	0.0	20.8	0.0	4.0	0.0	
CP(R)205	4		30 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)205	4		60 secs	-	-	•	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)205	4		90 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)205	4		120 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)205	4		180 secs	-	-	-	-	0.1	0.0	20.9	0.0	0.0	0.0	
CP(R)205	4		240 secs	-	1	ı	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)205	4		300 secs	-	-	-	-	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)206	1	21.17	16/10/2013 13:37:00	1003	1003	-	14.72	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)206	1		15 secs	-	-	-	-	2.3	0.0	18.7	0.0	0.0	0.0	
CP(R)206	1		30 secs	-	-	-	-	2.4	0.0	16.9	0.0	0.0	0.0	
CP(R)206	1		60 secs	-	-	-	-	2.4	0.0	16.5	0.0	0.0	0.0	
CP(R)206	1		90 secs	-	-	-	-	2.4	0.0	16.4	0.0	0.0	0.0	
CP(R)206	1		120 secs	-	-	-	-	2.6	0.0	16.6	0.0	0.0	0.0	
CP(R)206	1		180 secs	-	-	-	-	2.6	0.0	16.6	0.0	0.0	0.0	
CP(R)206	1		240 secs	-	-	-	-	2.6	0.0	16.4	0.0	0.0	0.0	
CP(R)206	1		300 secs	-	-	-	-	2.6	0.0	16.5	0.0	0.0	0.0	
CP(R)206	2	21.18	22/10/2013 14:45:00	988	988	1.2 <sub>(I)</sub>	14.68	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)206	2		15 secs	-	-	1.6 <sub>(SS)</sub>	-	2.4	0.0	16.5	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:				Page:
	East Midlar	ıds Gateway		

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)206	2		30 secs	-	-	-	-	2.4	0.0	16.4	0.0	0.0	0.0	
CP(R)206	2		60 secs	-	-	-	-	2.4	0.0	16.2	0.0	0.0	0.0	
CP(R)206	2		90 secs	-	-	-	-	2.4	0.0	16.2	0.0	0.0	0.0	
CP(R)206	2		120 secs	-	-	-	-	2.4	0.0	16.2	0.0	0.0	0.0	
CP(R)206	2		180 secs	-	-	-	-	2.4	0.0	16.3	0.0	0.0	0.0	
CP(R)206	2		240 secs	-	-	-	-	2.4	0.0	16.2	0.0	0.0	0.0	
CP(R)206	2		300 secs	-	-	-	-	2.4	0.0	16.1	0.0	0.0	0.0	
CP(R)206	3	21.11	30/10/2013 10:23:00	1011	1012	-4.6 <sub>(I)</sub>	14.63	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)206	3		15 secs	-	-	-4.5 <sub>(SS)</sub>	-	0.3	0.0	20.2	0.0	0.0	0.0	
CP(R)206	3		30 secs	-	-	-	-	0.4	0.0	20.0	0.0	0.0	0.0	
CP(R)206	3		60 secs	-	-	-	-	0.5	0.0	19.9	0.0	0.0	0.0	
CP(R)206	3		90 secs	-	-	-	-	0.5	0.0	19.8	0.0	0.0	0.0	
CP(R)206	3		120 secs	-	-	-	-	0.6	0.0	19.7	0.0	0.0	0.0	
CP(R)206	3		180 secs	-	-	-	-	0.8	0.0	19.6	0.0	0.0	0.0	
CP(R)206	3		240 secs	-	-	-	-	1.8	0.0	18.3	0.0	0.0	0.0	
CP(R)206	3		300 secs	-	-	-	-	2.1	0.0	17.7	0.0	0.0	0.0	
CP(R)206	4	21.15	11/11/2013 16:54:00	1017	1017	0.1 <sub>(I)</sub>	14.65	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)206	4		15 secs	-	-	-5.6 <sub>(SS)</sub>	-	0.1	0.0	20.1	0.0	0.0	0.0	
CP(R)206	4		30 secs	-	-	-	-	0.1	0.0	20.4	0.0	6.0	0.0	
CP(R)206	4		60 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)206	4		90 secs	-	-	-	-	0.1	0.0	20.4	0.0	2.0	0.0	
CP(R)206	4		120 secs	-	-	-	-	0.1	0.0	20.6	0.0	6.0	0.0	
CP(R)206	4		180 secs	-	-	-	-	0.1	0.0	20.4	0.0	2.0	0.0	
CP(R)206	4		240 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)206	4		300 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Envir
Abbe
Humbo

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

_	r				
	Compiled By	Date	Checked By	Date	Contract Re
		28/11/13		28/11/13	
	Contract:	•			Page:

East Midlands Gateway

**33** of **36** 

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)207	1	24.66	16/10/2013 15:40:00	1001	1003	-	24.25	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)207	1		15 secs	-	-	-	-	2.4	0.0	19.1	0.0	0.0	0.0	
CP(R)207	1		30 secs	-	-	-	-	2.5	0.0	15.5	0.0	0.0	0.0	
CP(R)207	1		60 secs	-	-	-	-	2.5	0.0	14.8	0.0	0.0	0.0	
CP(R)207	1		90 secs	-	-	-	-	2.5	0.0	14.7	0.0	0.0	0.0	
CP(R)207	1		120 secs	-	-	-	-	2.5	0.0	14.6	0.0	0.0	0.0	
CP(R)207	1		180 secs	-	-	-	-	2.5	0.0	14.9	0.0	0.0	0.0	
CP(R)207	1		240 secs	-	-	-	-	2.5	0.0	14.8	0.0	0.0	0.0	
CP(R)207	1		300 secs	-	-	-	-	2.5	0.0	14.9	0.0	0.0	0.0	
CP(R)207	2	24.67	23/10/2013 15:00:00	989	987	-3.4 <sub>(I)</sub>	24.24	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)207	2		15 secs	-	-	-3.3 <sub>(SS)</sub>	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)207	2		30 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)207	2		60 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)207	2		90 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)207	2		120 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)207	2		180 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)207	2		240 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)207	2		300 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)207	3	24.64	30/10/2013 10:07:00	-	1012	-3.5 <sub>(I)</sub>	24.48	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)207	3		15 secs	-	-	-3.3 <sub>(SS)</sub>	-	0.3	0.0	19.8	0.0	0.0	0.0	
CP(R)207	3		30 secs	-	-	-	-	0.3	0.0	19.8	0.0	0.0	0.0	
CP(R)207	3		60 secs	-	-	-	-	0.3	0.0	19.7	0.0	0.0	0.0	
CP(R)207	3		90 secs	-	-	-	-	0.6	0.0	19.5	0.0	0.0	0.0	
CP(R)207	3		120 secs	-	-	-	-	0.6	0.0	19.5	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

 			_	
Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:				Page:

**East Midlands Gateway** 

**34** of **36** 

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)207	3		180 secs	-	-	-	-	0.7	0.0	19.4	0.0	0.0	0.0	
CP(R)207	3		240 secs	-	-	-	-	0.7	0.0	19.2	0.0	0.0	0.0	
CP(R)207	3		300 secs	-	-	-	-	0.7	0.0	19.3	0.0	0.0	0.0	
CP(R)207	4	24.65	11/11/2013 16:14:00	1017	1017	-12.2 <sub>(I)</sub>	24.54	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)207	4		15 secs	-	-	-13.5 <sub>(SS)</sub>	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)207	4		30 secs	-	-	-	-	0.1	0.0	20.5	0.0	22.0	0.0	
CP(R)207	4		60 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)207	4		90 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)207	4		120 secs	-	-	-	-	0.2	0.0	20.5	0.0	0.0	0.0	
CP(R)207	4		180 secs	-	-	-	-	0.4	0.0	20.3	0.0	3.0	0.0	
CP(R)207	4		240 secs	-	-	-	-	0.5	0.0	20.1	0.0	0.0	0.0	
CP(R)207	4		300 secs	-	-	-	-	0.6	0.0	19.9	0.0	0.0	0.0	
CP(R)208	1	20.20	16/10/2013 14:59:01	1002	1003	-	DRY	0.0	0.1	20.7	1.0	0.0	0.0	
CP(R)208	1		15 secs	-	-	-	-	1.4	0.1	19.8	1.0	0.0	0.0	
CP(R)208	1		30 secs	-	-	-	-	1.4	0.1	17.4	1.0	0.0	0.0	
CP(R)208	1		60 secs	-	-	-	-	1.4	0.1	17.1	1.0	0.0	0.0	
CP(R)208	1		90 secs	-	-	-	-	1.4	0.1	17.2	1.0	0.0	0.0	
CP(R)208	1		120 secs	-	-	-	-	1.4	0.1	17.0	1.0	0.0	0.0	
CP(R)208	1		180 secs	-	-	-	-	1.4	0.1	17.3	1.0	0.0	0.0	
CP(R)208	1		240 secs	-	-	-	-	1.4	0.0	17.5	0.0	0.0	0.0	
CP(R)208	1		300 secs	-	-	-	-	1.4	0.0	17.2	0.0	0.0	0.0	
CP(R)208	2	20.20	24/10/2013 13:08:00	1006	1005	-1.8 <sub>(I)</sub>	DRY	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)208	2		15 secs	-	-	-1.9 <sub>(SS)</sub>	-	0.1	0.0	20.3	0.0	0.0	0.0	
CP(R)208	2		30 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date		Checked By	Date	Contract Ref:
	28/11/13			28/11/13	
Contract:			-		Page:
	East Midlar	ids G	ateway		

312494

Exploratory Position ID	Monitoring Round	Installation Depth (mbgl)	Date & Time of Monitoring (elapsed time)	Borehole Pressure (mb)	Atmos Pressure (mb)	Gas Flow (l/hr)	Water Depth (mbgl)	Carbon Dioxide (% / vol)	Methane (% / vol)	Oxygen (% / vol)	LEL (%)	Carbon Monoxide (ppm)	Hydrogen Sulphide (ppm)	
CP(R)208	2		60 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)208	2		90 secs	-	-	-	-	0.1	0.0	20.4	0.0	0.0	0.0	
CP(R)208	2		120 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	2		180 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	2		240 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	2		300 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	3	20.19	30/10/2013 16:35:00	1011	1010	-0.1 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)208	3		15 secs	-	-	$0.0_{(SS)}$	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)208	3		30 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)208	3		60 secs	-	-	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)208	3		90 secs	-	1	-	-	0.1	0.0	20.7	0.0	0.0	0.0	
CP(R)208	3		120 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)208	3		180 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)208	3		240 secs	1	1	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	3		300 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	4	20.19	11/11/2013 15:26:00	1017	1017	1.3 <sub>(I)</sub>	DRY	0.1	0.0	20.8	0.0	0.0	0.0	
CP(R)208	4		15 secs	-	-	1.3 <sub>(SS)</sub>	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	4		30 secs	ı	1	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)208	4		60 secs	-	-	-	-	0.1	0.0	20.5	0.0	0.0	0.0	
CP(R)208	4		90 secs	1	-	-	-	0.1	0.0	20.6	0.0	4.0	0.0	
CP(R)208	4		120 secs	1	-	-	-	0.1	0.0	20.5	0.0	4.0	0.0	
CP(R)208	4		180 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)208	4		240 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	
CP(R)208	4		300 secs	-	-	-	-	0.1	0.0	20.6	0.0	0.0	0.0	

Key: I = Initial, P = Peak, SS = Steady State. Note: LEL = Lower Explosive Limit = 5% v/v.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	Date	Contract Ref:
	28/11/13		28/11/13	
Contract:	•			Page:

**East Midlands Gateway** 

**36** of **36** 

	Weather	Ground Conditions	Wind Conditions	Air Temperature (°C)	Equipment Used & Remarks
Round 1	Overcast	Wet	None	12	Dipmeter + GA2000 SN-GA07744
Round 2	Overcast	Wet	None	15	Dipmeter + GA2000 SN-GA07744
Round 3	Sunny	Wet	None	12	Dipmeter + GA2000 SN-GA07744
Round 4	Overcast	Wet	None	10	Dipmeter + GA2000 SN-GA07744

Exploratory Position ID	Pipe Ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (mbgl)	Response Zone	Date & Time of Monitoring	Water Depth (mbgl)	Remarks
CP203	1	50	1 / 1	4.00	3.78	1.00 to 4.00	16/10/2013 12:05	DRY	
CP203	1	50	2 / 1	4.00	3.78	1.00 to 4.00	23/10/2013 13:42	DRY	
CP203	1	50	3 / 1	4.00	3.83	1.00 to 4.00	30/10/2013 16:50	DRY	
CP203	1	50	4 / 1	4.00	3.76	1.00 to 4.00	12/11/2013 10:22	DRY	
CP204	1	50	1 / 1	4.00	3.91	1.00 to 4.00	17/10/2013 15:50	DRY	
CP204	1	50	2 / 1	4.00	3.91	1.00 to 4.00	22/10/2013 15:38	DRY	
CP204	1	50	3 / 1	4.00	3.95	1.00 to 4.00	30/10/2013 16:00	DRY	
CP204	1	50	4 / 1	4.00	3.88	1.00 to 4.00	12/11/2013 11:36	DRY	
CP205	1	50	1 / 1	4.30	4.37	1.00 to 4.30	16/10/2013 12:13	4.13	
CP205	1	50	2 / 1	4.30	4.37	1.00 to 4.30	23/10/2013 14:06	4.12	
CP205	1	50	3 / 1	4.30	4.37	1.00 to 4.30	30/10/2013 09:25	4.19	
CP205	1	50	4 / 1	4.30	4.37	1.00 to 4.30	12/11/2013 09:45	4.20	
CP206	1	50	1 / 1	3.30	3.23	0.50 to 3.30	16/10/2013 13:37	DRY	
CP206	1	50	2 / 1	3.30	3.23	0.50 to 3.30	22/10/2013 14:26	DRY	
CP206	1	50	3 / 1	3.30	3.29	0.50 to 3.30	30/10/2013 09:43	DRY	

Key: NDA denotes 'no data available'.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date		Checked By	Date
	3/12/13			28/11/13
Contract:				
	East Midlan	ids (	Gateway	

Contract Ref: 312494

Page:



Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP206	1	50	4 / 1	3.30	3.21	0.50 to 3.30	11/11/2013 16:44	DRY	
CP207	1	50	1 / 1	2.70	2.68	1.00 to 2.70	16/10/2013 15:32	DRY	
CP207	1	50	2 / 1	2.70	2.70	1.00 to 2.70	23/10/2013 14:40	DRY	
CP207	1	50	3 / 1	2.70	2.69	1.00 to 2.70	30/10/2013 16:42	DRY	
CP207	1	50	4 / 1	2.70	2.67	1.00 to 2.70	11/11/2013 16:08	DRY	
CP208	1	50	1 / 1	2.00	1.90	1.00 to 2.00	16/10/2013 15:41	DRY	
CP208	1	50	2 / 1	2.00	1.88	1.00 to 2.00	24/10/2013 13:00	DRY	
CP208	1	50	3 / 1	2.00	1.90	1.00 to 2.00	30/10/2013 16:10	DRY	
CP208	1	50	4 / 1	2.00	1.85	1.00 to 2.00	11/11/2013 15:36	DRY	
CP210	1	50	1 / 1	9.50	9.05	8.50 to 9.50	17/10/2013 16:31	5.47	
CP210	1	50	2 / 1	9.50	9.05	8.50 to 9.50	23/10/2013 09:00	4.77	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3x well volume purged - full sample obtained.
CP210	1	50	3 / 1	9.50	9.03	8.50 to 9.50	30/10/2013 14:35	3.88	
CP210	1	50	4 / 1	9.50	9.04	8.50 to 9.50	12/11/2013 12:22	3.27	
CP211	1	50	1 / 1	7.00	6.68	1.00 to 7.00	17/10/2013 16:43	DRY	
CP211	1	50	2 / 1	7.00	6.67	1.00 to 7.00	24/10/2013 10:40	6.14	
CP211	1	50	3 / 1	7.00	6.67	1.00 to 7.00	30/10/2013 14:00	6.14	
CP211	1	50	4 / 1	7.00	6.65	1.00 to 7.00	12/11/2013 12:53	5.96	
CP212	1	50	1 / 1	3.30	3.39	1.00 to 3.30	17/10/2013 16:56	2.22	
CP212	1	50	2 / 1	3.30	3.39	1.00 to 3.30	22/10/2013 10:20	2.22	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3x well volume purged - full sample obtained.
CP212	1	50	2/2	3.30	3.39	1.00 to 3.30	23/10/2013 10:45	1.48	

Key: NDA denotes 'no data available'.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

Compiled By
Date
Checked By
Date
Contract Ref:

28/11/13
Page:

Page:

2 of 8

Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP212	1	50	3 / 2	3.30	3.38	1.00 to 3.30	30/10/2013 13:55	1.22	
CP212	1	50	4 / 2	3.30	3.37	1.00 to 3.30	12/11/2013 13:12	1.04	
CP213	1	50	1 / 1	4.20	4.08	1.00 to 4.20	17/10/2013 18:00	2.39	
CP213	1	50	2 / 1	4.20	4.08	1.00 to 4.20	22/10/2013 18:00	2.39	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3x well volume purged - full sample obtained.
CP213	1	50	2/2	4.20	4.08	1.00 to 4.20	23/10/2013 10:16	2.24	
CP213	1	50	3 / 1	4.20	4.08	1.00 to 4.20	30/10/2013 12:00	2.18	
CP213	1	50	4 / 1	4.20	4.07	1.00 to 4.20	12/11/2013 15:46	1.78	
CP214	1	50	1 / 1	4.20	4.08	1.00 to 4.20	17/10/2013 18:20	3.49	
CP214	1	50	2 / 1	4.20	4.10	1.00 to 4.20	24/10/2013 13:30	3.38	
CP214	1	50	3 / 1	4.20	4.08	1.00 to 4.20	30/10/2013 10:35	3.00	
CP214	1	50	4 / 1	4.20	4.07	1.00 to 4.20	12/11/2013 15:49	2.13	
CP215	1	50	1 / 1	4.80	4.85	1.00 to 4.80	17/10/2013 17:15	1.72	
CP215	1	50	2 / 1	4.80	4.85	1.00 to 4.80	24/10/2013 11:15	1.07	
CP215	1	50	3 / 1	4.80	4.85	1.00 to 4.80	30/10/2013 13:20	0.88	
CP215	1	50	4 / 1	4.80	4.85	1.00 to 4.80	12/11/2013 13:30	0.55	
CP216	1	50	3 / 1	2.40	2.45	0.50 to 2.40	30/10/2013 12:40	DRY	
CP216	1	50	4 / 1	2.40	2.45	0.50 to 2.40	12/11/2013 14:35	DRY	
CP217	1	50	1 / 1	4.60	4.64	1.00 to 4.60	17/10/2013 17:42	2.25	
CP217	1	50	2 / 1	4.60	4.64	1.00 to 4.60	23/10/2013 11:20	1.70	
CP217	1	50	2/2	4.60	4.64	1.00 to 4.60	23/10/2013 12:05	1.70	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample obtained

Key: NDA denotes 'no data available'.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

Compiled By	Date	Checked By	Date	Contract Ref:	
	3/12/13		28/11/13	312494	
Contract:			•	Page:	
	3 of 8				

Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP217	1	50	3 / 1	4.60	4.64	1.00 to 4.60	30/10/2013 12:56	1.60	
CP217	1	50	4 / 1	4.60	4.62	1.00 to 4.60	12/11/2013 14:06	1.43	
CP218	1	50	1 / 1	4.60	4.65	1.00 to 4.60	17/10/2013 17:47	DRY	
CP218	1	50	2 / 1	4.60	4.65	1.00 to 4.60	24/10/2013 11:40	DRY	
CP218	1	50	3 / 1	4.60	4.65	1.00 to 4.60	30/10/2013 13:30	DRY	
CP218	1	50	4 / 1	4.60	4.65	1.00 to 4.60	12/11/2013 14:58	4.63	
CP219	1	50	1 / 1	7.50	7.43	1.00 to 7.50	16/10/2013 14:47	DRY	
CP219	1	50	2 / 1	7.50	7.44	1.00 to 7.50	24/10/2013 13:45	DRY	
CP219	1	50	3 / 1	7.50	7.41	1.00 to 7.50	30/10/2013 13:10	7.32	
CP219	1	50	4 / 1	7.50	7.43	1.00 to 7.50	11/11/2013 14:58	7.34	
CP220	1	50	1 / 1	5.70	5.79	0.00 to 5.70	16/10/2013 13:54	3.04	
CP220	1	50	2 / 1	5.70	5.79	0.00 to 5.70	22/10/2013 13:28	3.04	
CP220	1	50	2/2	5.70	5.80	0.00 to 5.70	23/10/2013 09:00	4.40	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample obtained
CP220	1	50	3 / 1	5.70	5.80	0.00 to 5.70	30/10/2013 14:40	2.99	
CP220	1	50	4 / 1	5.70	5.77	0.00 to 5.70	11/11/2013 14:39	2.08	
CP221	1	50	1 / 1	10.70	10.00	1.00 to 10.70	16/10/2013 14:30	5.43	
CP221	1	50	2 / 1	10.70	10.10	1.00 to 10.70	24/10/2013 14:00	5.50	
CP221	1	50	3 / 1	10.70	10.08	1.00 to 10.70	30/10/2013 13:10	5.48	
CP221	1	50	4 / 1	10.70	10.07	1.00 to 10.70	11/11/2013 14:20	5.36	
									Weather: Overgoot Surface Conditions: Wet
CP222	1	19	1 / 1	6.00	5.68	5.70 to 6.00	17/10/2013 12:45	2.93	Weather: Overcast, Surface Conditions: Wet

Key: NDA denotes 'no data available'.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

/10			
/13			
Midlands	Cateway		
	/13   : Midlands	: Midlands Gateway	

Contract Ref: 312494

Page:

Date

28/11/13

Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP222	1	19	2 / 1	6.00	5.65	5.70 to 6.00	22/10/2013 12:48	2.82	Weather: Overcast, Surface Conditions: Wet
CP222	1	19	3 / 1	6.00	5.64	5.70 to 6.00	30/10/2013 15:10	2.44	Weather: Overcast, Surface Conditions: Wet
CP222	1	19	4 / 1	6.00	5.69	5.70 to 6.00	11/11/2013 14:10	2.42	Weather: Overcast, Surface Conditions: Wet
CP(R)203	1	50	1 / 1	25.00	24.78	7.00 to 25.00	16/10/2013 12:05	24.47	
CP(R)203	2	19	1 / 1	29.00	29.41	0.00 to 29.00	16/10/2013 12:10	DRY	
CP(R)203	1	50	2 / 1	25.00	24.81	7.00 to 25.00	23/10/2013 13:43	24.56	
CP(R)203	2	19	2 / 1	29.00	29.43	0.00 to 29.00	23/10/2013 13:48	DRY	
CP(R)203	1	50	3 / 1	25.00	24.79	7.00 to 25.00	30/10/2013 16:50	DRY	
CP(R)203	2	19	3 / 1	29.00	29.55	0.00 to 29.00	30/10/2013 16:55	DRY	
CP(R)203	1	50	4 / 1	25.00	24.77	7.00 to 25.00	12/11/2013 10:31	24.51	
CP(R)203	2	19	4 / 1	29.00	29.43	0.00 to 29.00	12/11/2013 10:40	DRY	
CP(R)204	1	50	1 / 1	20.00	19.80	14.00 to 20.00	17/10/2013 16:06	15.90	
CP(R)204	1	50	2 / 1	20.00	19.80	14.00 to 20.00	22/10/2013 15:10	15.80	
CP(R)204	1	50	2/2	20.00	19.80	14.00 to 20.00	22/10/2013 16:30	15.80	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample obtained
CP(R)204	1	50	3 / 1	20.00	19.72	14.00 to 20.00	30/10/2013 15:36	15.51	
CP(R)204	1	50	4 / 1	20.00	19.81	14.00 to 20.00	12/11/2013 11:36	14.93	
CP(R)205	1	50	1 / 1	19.00	18.41	4.00 to 19.00	16/10/2013 12:13	18.27	
CP(R)205	1	50	2 / 1	19.00	18.41	4.00 to 19.00	23/10/2013 14:14	18.28	
CP(R)205	1	50	3 / 1	19.00	18.40	4.00 to 19.00	30/10/2013 16:55	18.26	
CP(R)205	1	50	4 / 1	19.00	18.40	4.00 to 19.00	11/11/2013 09:55	18.27	
CP(R)206	1	50	1 / 1	21.00	21.17	9.00 to 21.00	16/10/2013 13:37	14.72	

Key: NDA denotes 'no data available'.

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ

Compiled By	Date	Checked By	Date	Contract Ref:	
	3/12/13		28/11/13		312494
Contract:				Page:	

**East Midlands Gateway** 

Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP(R)206	2	19	1 / 1	24.00	24.04	23.70 to 24.00	16/10/2013 13:42	14.65	
CP(R)206	2	19	2 / 1	24.00	24.08	23.70 to 24.00	22/10/2013 13:14	14.69	
CP(R)206	1	50	2 / 1	21.00	21.18	9.00 to 21.00	22/10/2013 14:45	14.68	
CP(R)206	1	50	2/2	21.00	21.18	9.00 to 21.00	22/10/2013 14:55	14.68	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample obtained
CP(R)206	1	50	3 / 1	21.00	21.11	9.00 to 21.00	30/10/2013 09:53	14.63	
CP(R)206	2	19	3 / 1	24.00	23.91	23.70 to 24.00	30/10/2013 10:28	14.57	
CP(R)206	1	50	4 / 1	21.00	21.15	9.00 to 21.00	11/11/2013 16:45	14.65	
CP(R)206	2	19	4 / 1	24.00	24.06	23.70 to 24.00	11/11/2013 17:02	14.78	
CP(R)207	1	50	1 / 1	25.00	24.66	17.00 to 25.00	16/10/2013 15:40	24.25	
CP(R)207	2	19	1 / 1	12.10	12.18	11.80 to 12.10	16/10/2013 15:45	10.85	
CP(R)207	1	50	2 / 1	25.00	24.67	17.00 to 25.00	23/10/2013 15:00	24.24	
CP(R)207	2	19	2 / 1	12.10	12.17	11.80 to 12.10	23/10/2013 15:05	10.90	
CP(R)207	1	50	3 / 1	25.00	24.64	17.00 to 25.00	30/10/2013 10:07	24.48	
CP(R)207	2	19	3 / 1	12.10	12.16	11.80 to 12.10	30/10/2013 10:12	10.82	
CP(R)207	1	50	4 / 1	25.00	24.65	17.00 to 25.00	11/11/2013 16:14	24.54	
CP(R)207	2	19	4 / 1	12.10	12.17	11.80 to 12.10	11/11/2013 16:19	10.81	
CP(R)208	1	50	1 / 1	20.00	20.00	5.00 to 15.00	16/10/2013 14:59	DRY	
CP(R)208	1	50	2 / 1	20.00	20.00	5.00 to 15.00	24/10/2013 13:08	DRY	
CP(R)208	1	50	3 / 1	20.00	20.00	5.00 to 15.00	30/10/2013 16:35	DRY	
CP(R)208	1	50	4 / 1	20.00	20.00	5.00 to 15.00	11/11/2013 15:26	DRY	
CP/RC 101	1	19	1 / 1	27.60	27.59	14.00 to 27.60	16/10/2013 08:56	26.20	
CP/RC 101	1	19	2 / 1	27.60	27.57	14.00 to 27.60	23/10/2013 13:55	26.16	

Key: NDA denotes 'no data available'.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

Contract:

Compiled By
Date
Checked By
Date
Checked By
Date
Checked By
Date
Checked By
Date
Contract Ref:

28/11/13

Page:
6 of 8

Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP/RC 101	1	19	3 / 1	27.60	27.57	14.00 to 27.60	30/10/2013 08:56	26.18	
CP/RC 101	1	19	4 / 1	27.60	27.56	14.00 to 27.60	11/11/2013 10:09	26.07	
CP/RC 102	1	19	1 / 1	17.20	4.32	4.00 to 17.20	16/10/2013 11:10	DRY	
CP/RC 102	1	19	2 / 1	17.20	4.32	4.00 to 17.20	23/10/2013 14:27	DRY	
CP/RC 102	1	19	3 / 1	17.20	4.32	4.00 to 17.20	30/10/2013 16:50	DRY	
CP/RC 102	1	19	4 / 1	17.20	4.36	4.00 to 17.20	11/11/2013 16:31	4.34	
CP/RC 103	1	19	1 / 1	15.00	14.87	12.00 to 15.00	16/10/2013 10:30	DRY	
CP/RC 103	2	19	1 / 1	5.00	4.10	1.00 to 5.00	16/10/2013 10:33	DRY	
CP/RC 103	1	19	2 / 1	15.00	14.81	12.00 to 15.00	23/10/2013 13:08	14.56	
CP/RC 103	2	19	2 / 1	5.00	4.12	1.00 to 5.00	23/10/2013 13:11	DRY	
CP/RC 103	1	19	3 / 1	15.00	14.75	12.00 to 15.00	30/10/2013 08:15	DRY	
CP/RC 103	2	19	3 / 1	5.00	4.13	1.00 to 5.00	30/10/2013 08:18	DRY	
CP/RC 103	1	19	4 / 1	15.00	14.88	12.00 to 15.00	12/11/2013 10:59	14.83	
CP/RC 103	2	19	4 / 1	5.00	4.13	1.00 to 5.00	12/11/2013 11:03	3.83	
CP/RC 104	1	19	1 / 1	18.00	17.92	16.00 to 18.00	16/10/2013 10:28	DRY	
CP/RC 104	2	19	1 / 1	12.00	12.96	7.00 to 14.00	16/10/2013 10:29	DRY	
CP/RC 104	1	19	2 / 1	18.00	17.92	16.00 to 18.00	24/10/2013 10:58	DRY	
CP/RC 104	2	19	2 / 1	12.00	12.96	7.00 to 14.00	24/10/2013 10:59	DRY	
CP/RC 104	1	19	3 / 1	18.00	17.91	16.00 to 18.00	31/10/2013 11:50	DRY	
CP/RC 104	2	19	3 / 1	12.00	12.96	7.00 to 14.00	31/10/2013 11:51	DRY	
CP/RC 104	1	19	4 / 1	18.00	17.90	16.00 to 18.00	12/11/2013 12:38	DRY	
CP/RC 104	2	19	4 / 1	12.00	11.95	7.00 to 14.00	12/11/2013 12:39	DRY	

Key: NDA denotes 'no data available'.

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

RSK Environment Ltd
Abbey Park
Humber Road
Coventry
CV3 4AQ

Compiled By
Date
Checked By
Date
Contract Ref:

28/11/13
Page:
7 of 8

Exploratory Position ID	Pipe ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (m)	Response Zone	Date & Time of Monitoring	Water Depth (m)	Remarks
CP/RC 105	1	19	1 / 1	14.70	14.47	1.00 to 14.70	16/10/2013 10:10	DRY	
CP/RC 105	1	19	2 / 1	14.70	14.52	1.00 to 14.70	24/10/2013 11:35	DRY	
CP/RC 105	1	19	3 / 1	14.70	14.48	1.00 to 14.70	30/10/2013 13:10	DRY	
CP/RC 105	1	19	4 / 1	14.70	14.50	1.00 to 14.70	12/11/2013 15:11	14.44	
CP/RC 106	1	19	2 / 1	16.40	16.10	8.00 to 16.50	24/10/2013 08:30	11.84	General Remarks: Borehole not been located on 1st round of monitoring.
CP/RC 106	1	19	3 / 1	16.40	16.09	8.00 to 16.50	30/10/2013 12:00	11.78	
CP/RC 106	1	19	4 / 1	16.40	16.09	8.00 to 16.50	12/11/2013 12:06	11.32	

Key: NDA denotes 'no data available'.

RSK

RSK Environment Ltd Abbey Park Humber Road Coventry CV3 4AQ Compiled By

Date
Checked By

3/12/13

Contract

East Midlands Gateway

Contract Ref:

312494

Page:

Date

28/11/13



**Ground Conditions** Wind Conditions <u>Air Temperature</u> (°C) Equipment Used & Remarks Weather Wet 15 Dipmeter + GA2000 SN-GA07744 Round 2 Overcast None

Exploratory Position ID	Pipe Ref	Pipe Diameter	Monitoring Round / Test Number	Reported Installation Depth (m)	Measured Installation Depth (mbgl)	Response Zone	Date & Time of Monitoring	Water Depth (mbgl)	pН	Conductivity (uS/cm)	Temp- erature (°C)	Remarks
CP210	1	50	2 / 1	9.50	9.05	8.50 to 9.50	23/10/2013 09:00	4.77	6.43	1830	10.2	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3x well volume purged - full sample
												obtained.
CP212	1	50	2 / 1	3.30	3.39	1.00 to 3.30	22/10/2013 10:20	2.22	6.24	1837	12.7	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3x well volume purged - full sample
												obtained.
CP213	1	50	2 / 1	4.20	4.08	1.00 to 4.20	22/10/2013 18:00	2.39	6.27	1500	10.9	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3x well volume purged - full sample
												obtained.
CP217	1	50	2/2	4.60	4.64	1.00 to 4.60	23/10/2013 12:05	1.70	5.48	444	11.9	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample
												obtained
CP220	1	50	2/2	5.70	5.80	0.00 to 5.70	23/10/2013 09:00	4.40	6.51	256	10.9	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample
												obtained
CP(R)204	1	50	2/2	20.00	19.80	14.00 to 20.00	22/10/2013 16:30	15.80	6.18	1530	11.0	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample
												obtained
CP(R)206	1	50	2/2	21.00	21.18	9.00 to 21.00	22/10/2013 14:55	14.68	7.54	940	15.1	Operator: GShaw, Weather: Overcast, Surface Conditions: Wet, General Remarks: 3xwell volume purged - full sample
												obtained

Key: NDA denotes 'no data available'.

RSK Environment Ltd Abbey Park Humber Road Coventry

CV3 4AQ

Contract:

Compiled By Date Checked By 29/11/13 **East Midlands Gateway** 

Contract Ref: Date 28/11/13

312494

Page: